**itc · DIGITAL CONFERENCE SYSTEMS**

# T-30DXT

Directional speaker

The itc T-30DXT is a directional speaker from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: soundbox frequency range 14 3 Hz - 2 1.5kHz; infrared sensing distance of the sound-focusing cover 3 meters.






## Key features

- The sound-concentrating cover is made of acrylic material — The sound-concentrating cover is made of acrylic material, balancing strength and weight .
- The acoustic enclosure consists of one 4 " woofer and two... — The acoustic enclosure consists of one 4 " woofer and two 1" dome tweeters, providing full-frequency radiation range .
- The patented Double Parabola dome technology maximizes... — The patented Double Parabola dome technology maximizes sound focusing by creating a sound-concentrating shield .
- The sound-focusing dome ensures that the sound played in... — The sound-focusing dome ensures that the sound played in each zone does not interfere with each other, and the sound quality is clearest inside the double parabolic
- The sound-focusing cover features an infrared... — The sound-focusing cover features an infrared sensor-controlled audio player that automatically senses and plays audio , stopping playback after a 30-second delay once a person

## Technical specifications

| | |
|---|---|
| Soundproof enclosure rated power | 30W |
| Soundproof enclosure nominal impedance | 8Ω |
| Total Harmonic Distortion of Directional | 0.8 % |
| Maximum sound pressure level of the soun | 95 dB |
| Soundbox frequency range | 14 3 Hz - 2 1.5kHz |
| Sound-concentrating shield pointing angl | 40° |
| Infrared sensing distance of the sound-f | 3 meters |
| Sound trap dimensions (Φ×H) | 300×600mm |
| Net weight of sound-concentrating cover | 3.5 kg |
| drive rated power | 40W |
| peak power of the driver | 160W |
| Total Harmonic Distortion of Driver | ≤0.8% |
| Driver power input | DC12V / 3A |
| Driver dimensions (H×W×D) | 45×175×119mm |
| Drive rnet weight | 0.7 kg |