itc · DIGITAL CONFERENCE SYSTEMS

# TF-A03305

Conference Microphone

The itc TF-A03305 is a conference Microphone from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz ~ 16kHz; sensitivity - 40 ±1dB (0dB=1V/Pa,at 1KHz). Highlights include supports sign-in function, supports voting function and supports web page firmware upgrade function.



## Key features

- Supports sign-in function — Supports sign-in function, and can also prohibit unit sign-in, control unit sign-in and other functions through PC software.
- Support conference logistics service functions. The… — Support conference logistics service functions. The microphone unit can send requests for tea, paper and pen, manual service, etc. to the conference host.
- Supports voting function — Supports voting function, with multiple voting modes to choose from, and the options can be customized and sent to the unit for display.
- Supports web page firmware upgrade function
- Support IP address sniffing function — Support IP address sniffing function, through PC tools can find unknown unit's ID number, IP address, MAC address and other parameters.

## Technical specifications

| | |
|---|---|
| Frequency response | 80Hz ~ 16kHz |
| Microphone input impedance | 1KΩ |
| Sensitivity | - 40 ±1dB (0dB=1V/Pa,at 1KHz) |
| Max SPL | 120dB (THD < 3%) |
| SNR | >80dB(A) |
| Crosstalk | >70dB |
| THD | <0.3% |
| Dynamic Range | >80dB |
| Maximum power consumption | 3.0W |
| Microphone Type | Electret Condenser Microphone |
| Mic rod length | 240mm |
| Microphone directivity | Heart |
| Power supply | Conference host power supply |
| Color | Oxidized fine sand black |
| Dimensions (LxWxH) | 154.9×99×60.5mm (excluding microphone rod length) |
| Weight | 1.01kg |
| Installation | Desktop |