**itc · DIGITAL CONFERENCE SYSTEMS**

# TS-0309

Conference Chairman Unit

The itc TS-0309 is a conference Chairman Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity -41±1.5dB(0dB=1V/Pa,at1KHz). Highlights include uncompressed audio transmission technology, adopt 100M network transmission and adopt standard TCP/IP communication protocol.

## Key features

- The capacitive touch buttons can effectively eliminate the... — The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- Uncompressed audio transmission technology — Uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- Adopt 100M network transmission — Adopt 100M network transmission, adopt network cable hand-in-hand connection, convenient for wiring.
- Adopt standard TCP/IP communication protocol — Adopt standard TCP/IP communication protocol, support ping packet function.
- Adopt a 3.5-inch full color touch screen

## Technical specifications

| | |
|---|---|
| Microphone type | Cardioid Electret |
| Microphone directivity | Cardioid |
| Frequency response | 80Hz~16KHz |
| Microphone input impedance | 680Ω |
| Sensitivity | -41±1.5dB(0dB=1V/Pa,at1KHz) |
| Maximum SPL | 120dB |
| SNR | >80dB(A) |
| Crosstalk | >70dB |
| Dynamic range | >80dB |
| THD | <0.1% |
| Maximum power consumption | 4.5W |
| Power supply | Conference server power supply |