**itc · WIRELESS CONFERENCE SYSTEMS**

# TS-0310A

Conference Delegate Unit

The itc TS-0310A is a conference Delegate Unit from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 41 ±1.5dB (0dB=1V/Pa,at 1KHz). Highlights include uncompressed audio transmission technology, adopt 100M network transmission and adopt standard TCP/IP communication protocol.



## Key features

- The capacitive touch buttons can effectively eliminate the... — The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- Uncompressed audio transmission technology — Uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- Adopt 100M network transmission — Adopt 100M network transmission, adopt network cable hand-in-hand connection, convenient for wiring.
- Adopt standard TCP/IP communication protocol — Adopt standard TCP/IP communication protocol, support ping packet function.
- Adopt a 4.3-inch full color touch screen

## Technical specifications

| | |
|---|---|
| Model | TS-0310A |
| Microphone type | Electret condenser microphone |
| Microphone directivity | Cardioid |
| Frequency response | 80Hz~16KHz |
| Microphone input impedance | 680 Ω |
| Sensitivity | - 41 ±1.5dB (0dB=1V/Pa,at 1KHz) |
| Maximum SPL | 120dB(THD>3%) |
| S NR | >80dB(A) |
| Crosstalk | >70dB |
| Dynamic range | >80dB |
| THD | <0.1% |
| Maximum power consumption | 3W |
| Power supply | Conference server power supply |
| Color | Fine sand graphite gray |
| Sign-in method | Key sign in |
| Dimension | 140*136*49mm (L*W*H) |
| Microphone pole | 380mm |

Continued specifications on request.