itc · DIGITAL CONFERENCE SYSTEMS

TS-0311D

Conference Microphone

The itc TS-0311D is a conference Microphone from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40 ± 2 dB (0dB=1V/Pa,at 1KHz). Highlights include digital transmission link and the chairman unit has a priority function.



Key features

- All core components of the microphone use domestically… — All core components of the microphone use domestically produced chips, which are safe, confidential and controllable.
- Digital transmission link — Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling
- Physical silicone buttons are used to retain the feel of… — Physical silicone buttons are used to retain the feel of physical buttons while eliminating the clicking sound of physical buttons, ensuring a good venue environment.
- The chairman unit has a priority function — The chairman unit has a priority function, which can turn off the microphones of all delegate unit who are speaking.
- The conference PC software supports the function of timing… — The conference PC software supports the function of timing and scheduled speech for the delegate unit. The conference PC software supports the function of timing speech

Technical specifications

Microphone Type	Cardioid electret
Frequency response	80Hz~16KHz
Microphone input impedance	1000 Ω
Sensitivity	- 40 ± 2 dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	1 20dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic Range	>80dB
THD	< 0.1 %
Maximum power consumption	2W
Power supply	Host power supply
Network port	2, hand-in-hand cascade ports
Color	Graphite Gray
Installation	Desktop
Microphone rod length and color	240mm integrated square short microphone rod (light black)
Dimensions (L×W×H)	133.8 × 104.6 × 37.2mm (excluding microphone rod dimension)

Continued specifications on request.