itc · DIGITAL CONFERENCE SYSTEMS

TS-0319/TS-0319A

Conference Chairman Unit

The itc TS-0319/TS-0319A is a conference Chairman Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40 ±1dB (0dB=1V/Pa,at 1KHz); front display + touch screen 7 inch capacitive touch screen. Highlights include using dual-mic and equipped with 6 function keys.



Key features

- The use of capacitive touch buttons can effectively... — The use of capacitive touch buttons can effectively eliminate the noise of button knocking and ensure a good venue environment.
- Using dual-mic — Using dual-mic, dual-speaker and dual-screen design, integrating functions such as conference speech, conference sound reinforcement, electronic nameplate display, camera tracking, conference service.
- Designed wit a 7-inch capacitive touch screen and a... — Designed wit a 7-inch capacitive touch screen and a 6.86-inch electronic nameplate; support the electronic nameplate function, which can display the information of the
- Equipped with 6 function keys — Equipped with 6 function keys, including voting keys, Mic switch, built-in speaker volume up/down keys.
- Using uncompressed audio transmission technology — Using uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth and perfect sound quality.

Technical specifications

Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Input impedance	1KΩ
Sensitivity	- 40 ±1dB (0dB=1V/Pa,at 1KHz)
Max SPL	1 20dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0. 3 %
Max power consumption	10 W
Standard	IEC60914
Headphone load	>16Ω
Headphone jack	3.5mm binaural headset,used for recording and headphones
Front display + touch screen	7 inch capacitive touch screen
Back screen size	6.86 inch

Continued specifications on request.