itc · PAPERLESS CONFERENCE SYSTEMS

TS-F173ZMT3

Motorized Paperless Interactive Monitor Lift

The itc TS-F173ZMT3 is a motorized Paperless Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: screen Touch control ·; screen size 17.3 inches ·; screen ratio 16 □ 9 ·. Highlights include the machine adopts an all-aluminum structure.

Key features

- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum
- The surface of the machine is anodized and looks bright
- The panel is space-saving with 3mm in thickness only. It is… — The panel is space-saving with 3mm in thickness only. It is only one-third weight of the conventional lift, which reduces transportation cost and the pressure of conference
- The transmission structure is specially treated to minimize… — The transmission structure is specially treated to minimize the noise; it adopts high-quality stretch-resistant belts, high-precision sliding guide rail and linear bearings,
- Support HDMI and VGA two-channel signal input. When there… — Support HDMI and VGA two-channel signal input. When there is only one signal input, the screen will automatically recognize the signal. When two signals are input at the

Technical specifications

Screen	Touch control ·
Power supply	AC 220V 50-60/HZ ·
Lifting time	30S ·
Elevation angle	30 ·
Product size	476*130*565 mm ·
Cabinet size	461*126*562mm ·
Panel size	476*130*3mm ·
Desktop opening size	463*127mm (recommended to open hole according to the actual product) ·
Panel sinking size	477*131*3mm □ L*W*T □ (recommended to open hole according to the actual product) ·
Environment conditions	-20℃ □ 50℃ humidity≤70% ·
Screen size	17.3 inches ·
Screen ratio	16 □ 9 ·
Screen resolution	1920*1080 P ·
Video port	VGA □ HDMI ·
Video switching	VGA □ HDMI (switch manually) ·
Screen contrast	700:1 (Typ.) (TM) ·
Screen brightness	300 cd/m² (Typ.) ·

Continued specifications on request.