itc · PAPERLESS CONFERENCE SYSTEMS

TS-F215T

Motorized Paperless Interactive Monitor Lift

The itc TS-F215T is a motorized Paperless Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Touch control; screen size 21.5 inches; screen ratio 16:9. Highlights include the machine adopts an all-aluminum structure.

Key features

- The integration of the ultra-thin HD touch screen and the… — The integration of the ultra-thin HD touch screen and the lift, no exposed wires and screws, no back boards; the lifting touch screen is neat and beautiful.
- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum
- The surface of the machine is anodized and looks bright
- The panel is space-saving with 3mm in thickness and 77mm in… — The panel is space-saving with 3mm in thickness and 77mm in width only.
- The transmission structure is specially treated to minimize… — The transmission structure is specially treated to minimize the noise; it adopts high-quality stretch-resistant belts, high-precision sliding guide rail and linear bearings,

Technical specifications

Touch screen	Touch control
Lifting time	36S
Elevation angle	0-30º , completely accord with ergonomic principle, without blocking the view and face
Total weight	12Kg
Cabinet size	560*66*647
Panel size	582*77*3mm
Desk top opening size	562*68mm(recommended to open hole according to the actual product)
Panel sinking size	583*7 8 *3mm(recommended to open hole according to the actual product)
Working environment	-20 ° C ~ 50 ° C ; humidity ≤ 70%
Screen size	21.5 inches
Screen ratio	16:9
Screen resolution	1920*1080
Video port	VGA, HDMI
Video switch ing	VGA, HDMI (manually signal switching by buttons)
Back light type	WLED, 15K hours, with LED driver
Contrast	1000 □ 1
Brightness	250cd/ □

Continued specifications on request.