itc · WIRELESS CONFERENCE SYSTEMS

# TS-W303DA

Conference microphone

The itc TS-W303DA is a conference microphone from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16 k Hz; sensitivity -40 ± 1dB (0dB=1V/Pa,at 1KHz); display screen IPS screen. Highlights include the microphone utilizes a 48kHz sampling rate and support intelligent detection of faults.

## Key features

- The microphone'score components all utilize domestically… — The microphone'score components all utilize domestically produced chips, ensuring security, confidentiality, and complete control.
- The microphone utilizes a 48kHz sampling rate — The microphone utilizes a 48kHz sampling rate, resulting in clear, crisp sound quality exceeding CD quality.
- Using advanced processing chip architecture and unique… — Using advanced processing chip architecture and unique processing algorithm, the microphone power-on connection time only takes 5 seconds.
- Support intelligent detection of faults — Support intelligent detection of faults, prompting users of AP faults, host communication faults, and low signal strength.
- Support charging through Type-Cport — Support charging through Type-Cport, with smart indicator status.

## Technical specifications

| | |
|---|---|
| Microphone type | Cardioid directional electret microphone |
| Frequency response | 80Hz~16 k Hz |
| Sensitivity | -40 ± 1dB (0dB=1V/Pa,at 1KHz) |
| Max SPL | 1 20dB(THD □ 3%) |
| S NR | >80dB(A) |
| Crosstalk | >70dB |
| Dynamic range | >80dB |
| THD | <0.1% |
| Maximum power consumption | 3W |
| Power supply | 18650 lithium battery |
| Charging method | Connect the charging box through the Type-Cinterface |
| Colour | Graphite gr ay |
| Sign-in function | Touch screen sign in |
| Display screen | IPS screen |
| Dimension | 150×144.8×60.2mm(excluding microphone rod length) |
| Installation method | Desktop |
| Wireless frequency range | 5.15~5.85GHz |

Continued specifications on request.