itc · WIRELESS CONFERENCE SYSTEMS

TS-3421

Converter Box

The itc TS-3421 is a converter Box from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: xlr channel balanced input 1 XLR female plug; xlr channel balanced input 2 XLR female plug; channel 1 control line 485 control line. Highlights include the network interface supports IEEE802.3, support network extension function, support Edit ID function and support web page firmware upgrade function.



Key features

- The network interface supports IEEE802.3 — The network interface supports IEEE802.3, IEEE802.3u, IEEE802.3x standards, with strong anti-interference ability.
- Support network extension function — Support network extension function: using 100M network transmission, network cable hand in hand cascading, easy wiring.
- Support Edit ID function
- Support web page firmware upgrade function
- Support analog-to-digital conversion function — Support analog-to-digital conversion function; analog audio is converted into digital signal and transmitted to the controller to realize long-distance network communication function.

Technical specifications

Maximum power consumption	4.5W
Power voltage	Power ed by conference controller
XLR channel balanced input 1	XLR female plug
XLR channel balanced input 2	XLR female plug
Channel 1 control line	485 control line
Channel 2 control line	485 control line
Network interface	Connect ed to the conference controller
Frequency response	80Hz ~16kHz
Color	Fine sand graphite gray
Edit ID function	ID code button
Installation method	Bottom of the conference table
Dimension (L * W * H)	200*90*44.2mm
Weight	0.49kg