Krinda

LASER PROJECTOR Krinda C-WU2000L

The function is comprehensive and intelligent



DLP Chip Technology
20,600 Lumens Brightness
Active/Passive 3D
720° Omnidirectional Installation
20,000 Hours Light Source Lifespan

Exhibitions/Enterprise Application and Meeting Rooms/Theme Parks/Attractions/Education and Researches/Live Events and Conferences/Staging Applications and Rental/Hotels

Technical specifications

Image	brightness (lumens)	· 20,600 ISO · 18,500 ANSI
	color wheel	· 4 segment (RGBY) – 2X or 3X speed
	contrast (nominal)	· Full on/off (Christie RealBlack™ enabled): 2,000,000:1 · Dynamic contrast: 6000:1 · Full on/off (Christie RealBlack disabled): 1200:1 · ANSI 250:1
Display technology	type	· 1 x 0.96" DMD
	native resolution	· 1920 x 1200 (2,304,000 pixels) (16:10)
Illumination	type	· Laser phosphor with Christie BoldColor™ Technology
	performance	· 20,000 hrs to 50% brightness
Signal Inputs	standard	· HDMI x 2 (HDCP 2.2) (one on side panel, one on bottom) · 3GSDI x 1 (BNC) · DVI-D x 1 (digital only) · VGA x 1 · USB x 1 (Type A) · Wi-Fi® dongle (optional) · HDBaseT (RJ45) x 1
	signals	· HDTV formats VGA through to WUXGA (1920 x 1200) · Horizontal and vertical scaling while maintaining aspect ratio (all inputs)
	3D	· HDMI 1.4, HDBaseT – frame packed, top/bottom, side-by-side (up to 120Hz output); frame sequential @ 1080P up to 120Hz. · 3D sync in (BNC) – for genlocking projectors · 3D sync out (BNC) – for genlocking projectors, or controlling emitter or polarizer
	pixel clock	· 162MHz
	scan rates	· Horizontal: 15-91kHz · Vertical: 24-120Hz
Signal outputs	monitor out (loop-through)	· 3GSDI x 1 (BNC) · HDMI x 1 (HDMI out)
Control and networking		· HDBaseT (RJ45 x 1) · RS232 x 1 · Built-in backlit keypad · DC JACK 12VDC, 200 mA · RJ45 x 1 (Ethernet Control over wired network connection) · Loop out available for daisy chaining · Remote in: 3.5mm stereo female (provides serial communications and power) · IR Remote
Warping and blending	mount type	· Twist ™
	optional	· Twist Premium and Twist Pro · Mystique® automated camera-based alignment
Lenses	mount type	· Boresight adjustable · Motorized horizontal and vertical lens offset (memory available) · Motorized zoom and focus adjustment (memory available for full ILS lenses)
	lens options	· 0.38:1 UST lens · 0.84-1.02:1 zoom lens (no zoom/focus memory) · 1.02-1.36:1 zoom lens (no zoom/focus memory) · 1.2-1.5:1 zoom lens (full ILS) · 1.5-2.0:1 zoom lens (full ILS) · 2.0-4.0:1 zoom lens (full ILS) · 4.0-7.0:1 zoom lens (full ILS)
	offsets for 0.38:1	· +100/-55% Vertical · +4/-28% Horizontal
	offsets for 0.84-1.02:1	· +108/-74% Vertical · +29/-42% Horizontal
	offsets for 1.02:1-1.36:1	· +124/-98% Vertical · +40/-49% Horizontal
	offsets for full ILS Lenses	· ±140% Vertical · ±50% Horizontal
Accessories	standard	· IR remote with wired remote jack (wire not included) · AC line cord for projector · Product Safety Guide
	optional	· One Mount Plus · One Mount Extender Rod · One Rigging Frame · One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) · WiFi Dongle · Fog Filter with Frame · Fog Filter module
Power requirements	operating voltage	· Normal mode: 200-240 VAC @ 50/60Hz with 15A fuse
	power consumption	· Normal mode: 1710W · Eco1 mode: 1380W · Eco2 mode: 830W
	operating current	· Normal mode: 9A (200-240 VAC)
	dissipation	· Normal mode: 5835 BTU/hr · Eco1 mode: 4709 BTU/hr · Eco2 mode: 2832 BTU/hr
Audible noise		2x wheel speed · Standard mode: 44dB(A) · Eco2 mode: 36dB(A) 3x wheel speed · Standard mode: 45dB(A) · Eco2 mode: 39dB(A)
Physical	size	· (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet
	shipping size	· (L xWxH) 37.99 x 31.30 x 14.37" (965 x 795 x365mm)
	weight	· 91.52lb (41.6kg)
	shipping weight	· 117.7lb (53.3kg)
Operating environment	temperature	· 32-104°F (0-40°C)
	humidity	· 10-85% non-condensing
Warranty		· Three years parts and labor on the projector · Three years or 15,000 hours parts and labor on the illumination system

BEIJING WINCOMN TECHNOLOGY CO.,LTD

86-10-6785 6868
info@wincomn.com
www.wincomn.com
Bldg.7,No.11 Kangding Street,Economic-Technological Development Area,BeiJing,P.R.China

Wincomn