Krinda T20

Training Simulation: Flight Simulation | Sailing Simulation | Driving Simulation | Night Flight Training

Virtual Reality: Intelligent Manufacturing | Equipment Development | Exhibition & Display | Scientific Research

1DLP WUXGA 8,000 ANSI lumens Professional Projector for Simulation

High	High	No blending film required
Brightness	Contrast	During night flight training

Designed and manufactured for high-end simulation and virtual reality applications, the T20 is a professional single-chip DLP projector that provides the key features necessary for professional simulation applications.

The T20 features 7 lens options, offering a wide range of mounting positions and options.

The T20 delivers flawless display of multi-channel systems in a range of brightness modes without an optical blending film. While offering better display quality, the T20 avoids the pitfalls of using a blending film in which case the display quality gradually loses in system operation, as well as eliminates the hassle of regular replacement and frequent maintenance.



Krinda

Key Features

- Featuring the latest projector platform, providing multiple simulation-specific functions optimized for application
- Up to 9,200 ISO lumens brightness
- Ultra-low black level output, no optical blending film required for night flight training scenes
- Brightness balancing for blended areas based on pixel parameters
- Laser light source, up to 20,000 hours operational lifetime (Brightness drops to 50% of maximum)
- 0.67-inch single DMD chip
- Native resolution 1920 x 1200 (WUXGA)
- Supports all 3D file formats
- Built-in hardware warping and blending capabilities (Up to 33 x 33 dot-matrix adjustment)
- All-metal construction and body, supports 24/7 operation









Specifications

Function Items	Specifications			
Display Technology	• 0.67" DMD			
Resolution	• Native resolution: 1920 x 1200 (WUXGA)			
Light Source	• Laser modules			
Light Source Lifetime	• 20,000 hours (Brightness drops to 50% maximum time when running at full power)			
Maximum Output Brightness	• 8,000 ANSI lumens	• 9,200 ISO lumens		
Contrast Ratio	• Full White/Full Black 2,000 : 1	• ANSI 250 : 1	• 1,000,000 : 1 (Extreme Black mode on)	
Color Support	• 1073.4 Billion (10 bit)			
Lens	• 0.36 : 1	• 0.65–0.75 : 1	• 0.75–0.95 : 1	• 0.95–1.22 : 1
	• 1.22–1.52 : 1	• 1.52–2.92 : 1	• 2.9–6.5 : 1	
Geometry Alignment	• Built-in, by hardware, up to 33 x 33 control points for complex curved applications			
Lens Offsets Range	• With 1.22-1.52:1 lens: Vertical: ±100% image height, Horizontal: ± 30 % image width			
Aspect Ratio	• 16 : 10 (Native) Compatible with other aspect ratios			
Scan Rates	• Horizontal: 15.7 ~ 91.1 KHz			
Computer Compatible Formats	• WUXGA, 1080P, UXGA, SXGA+, SXGA etc.			
Video Compatible Formats	• HDTV（720 p, 1080 i/p）, SDTV（480 i/p, 576 i/p）, NTSC, PAL, SECAM			
3D Compatibility	• Frame sequential active 3D, up to 1920 x 1200 @ 60 Hz, 120 Hz after frequency multiplication. Compatible with other commonly used stereoscopic formats.			
Signal I/O	• Input: 2 x HDMI, 1 x DVI-D, 1 x HDBaseT, 1 x 3D Sync in, 1 x 3G-SDI in • Output: D-sub 15pins1, 1 x 3D Sync out • Control: 1 x RS232(D-sub 9 pin) (PC Control) 2 x IR, 1 x RJ45(LAN)			
Brightness Uniformity	• 90 %（1.22–1.52 : 1 Lens）			
Operating Noise	• Maximum 38 db			
Overall Power Consumption	• 625 W ± 15 % @ 220 VAC, 659 W ± 15% @ 100 VAC, Bright Mode (Stand-by < 0.5 W)			
Voltage Range	• AC 100 ~ 240V ± 10%、50 / 60 Hz			
Body Volume (W x D x H)	• 480 x 536 x 234 mm			
Body Weight	• 26.5 kg			
Motion Compatibility	• 3g（Optional）			
Black Level	• Lower than 0.25 lumens			
Image Maximum Thermal Drift	• ≤ 1 pixel			
Warranty	• 3 years（Limited warranty）			
Certification	• Motion compatibility, electromagnetic radiation and laser safety certified by internationally recognized third-party agencies.			

BEIJING WINCOMN TECHNOLOGY CO.,LTD

86-10-6785 6868
info@wincomn.com
www.wincomn.com
Bldg.7,No.11 Kangding Street,Economic-Technological Development Area,Beijing,P.R.China

Wincomn