Krinda T50

Training Simulation: Flight Simulation | Sailing Simulation | Driving Simulation | Night Flight Training

Next-generation projector featuring high-resolution infrared night vision training (Indigenously produced in China)

Parallel output
IR and visible light

Ultra-low
Black level output

No blending film required
During night flight training

Designed and manufactured for professional-grade visual simulation applications, the T50 is a high performance single-chip DLP projector featuring system-level functional enhancements essential for professional-grade simulation applications.

The T50 features a dual-image processor that provides parallel input, processing and output of infrared night vision and visible light images.

Image Mode	I/O Signal Resolution	
Visible Light Image	Input: up to 3840 x 2160@60 Hz	Output: 3840 x 2160@60 Hz
Infrared Image	Input: up to 3840 x 2160@60 Hz	Output: 3840 x 2160@60 Hz
Dual Mode Image (IR and Visible Light)	Input 1: Up to 2712 x 1526@60 Hz Output: 2712 x 1526@120 Hz (IR and visible light images alternately displayed)	Input 2: Up to 2712 x 1526@60 Hz
Active Stereo Image	Input 1: Up to 2712 x 1526@60 Hz Output: 2712 x 1526@120 Hz	Input 2: Up to 2712 x 1526@60 Hz
	Input: Up to 2712 x 1526@120 Hz	Output: Up to 2712 x 1526@120 Hz

The T50 delivers flawless display of multi-channel systems in a range of brightness modes without an optical blending film. While offering high quality display, the T50 avoids the pitfalls of using a blending film in which case the display quality gradually loses in system operation, as well as eliminates the hassle of regular replacement and frequent maintenance.

The IR image output function of T50 is compatible with a wide range of domestic professional night vision goggles with high resolution and high IR intensity (partially simulating the effect of exhaust plume).

The T50 is a professional-grade projector owned by Krinda - a Chinese brand. The R&D team has the capacity to customise and expand the hardware and software features to suit the application.




Krinda









Specifications / Function Items

Function Items	Specifications		
Display Technology	• 0.66" TRP 9010 DMD - UHD		
Image Resolution	• 3840 x 2160		
Chip Native resolution	• 2712 x 1528		
Image Processor	• Dual processing (Parallel Serial)		
Light Source	• BLDA&RLD visible light and infrared laser modules		
Luminous Flux Max Output	• 6,150 ANSI lumens (F#2.0 lens)	• 7,050 ISO lumens	
Brightness Uniformity	• 90%		
IR Light Source	• 200 mw (F#4.3 IR lens), wave length 808nm		
Light Source Lifetime	• 25,000 hours (Brightness drops to 50% maximum time when running at full power)		
Contrast Ratio	• 1,000,000 : 1 (Extreme Black mode on)	• Full White/Full Black 4,000 : 1	• ANSI 250 : 1
Visible Light Color Gamut	• 110% of Rec. 709		
Black Level	• ≤ 0.12 lumens		
Brightness Gradient	• ≥ 100		
Lens	• 0.65~1.02 : 1 and 1.2~1.73 : 1, each lens has three types to choose. a. Standard lens with F#2.0 aperture. b. High contrast lens with F#4.0 aperture. c. Specialized IR lens with F#4.0 aperture.		
Lens offsets	• Vertical ± 100 %	• Horizontal ± 30 %	
Lens Control	• Motorized Zoom, Focus and Pan		
Geometry Alignment	• Built-in, by hardware, up to 33 x 33 grid control points, all grid control points (including edge points) can be moved and adjusted in all directions.		
Blending	• Built-in, by hardware, offering blending adjustment with ultra-high-precision based on pixel level.		
Image Signal Input	• HDMI x 2, DP x 1		
Communication & Control Signals	• RJ45 x 1, RS232 (D-sub 9pin) x 1, 3D SYNC Out x 1/ 3D SYNC In x, IR remote, USB type A x 1 (WIFI dongle)		
Compatible Image Formats	• Supports input and output up to UHD (3840 x 2160), compatible with other conventional image formats.		
3D Compatibility	• Frame sequential active 3D, multi-channel synchronization.	• Single input 2712 x 1528 @ 120 Hz, output 2712 x 1528 @ 120 Hz • Dual input, each 2712 x 1528 @ 60 Hz, output 2712 x 1528 @ 120 Hz	
Operating Noise	• Maximum 39 dB(A)		
Overall Power Consumption	• 1080 W ± 10 % @ 220 VAC		
Standby Power Consumption	• Wake-on-LAN on: 2 W	• Wake-on-LAN off: ≤0.5W	
Dissipation	• When running at full power: 945 W[3224.5 BTU/hr]		
Voltage	• AC 100 ~ 240 V ± 10 %, 50 / 60 Hz		
Body Volume (W x D x H)	• 562 x 513 x 242 mm		
Body Weight	• 45.1 kg		
Motion Compatibility	• 3g (Optional)		
Overall Processing Delay	• ≤ 2.5 frames (when warping and blending is on)	• ≤ 1 frame (when warping and blending is off)	
State Parameter Storage	• ≥ 5 groups		
Mounting Angle	• Fully omnidirectional with unrestricted installation flexibility		
Operating Environment	• Temperature: 5 to 35 °C	• Humidity: 10 to 85 % RH (non-condensing)	
Warranty	• 3 years (Limited warranty)		
Certification	• Motion compatibility, electromagnetic radiation and laser safety certified by internationally recognized third-party agencies.		

BEIJING WINCOMN TECHNOLOGY CO.,LTD

86-10-6785 6868

info@wincomn.com

www.wincomn.com

Bldg.7,No.11 Kangding Street,Economic-Technological Development Area,BeiJing,P.R.China

Wincomn