Wincomm

LASER PROJECTOR C-4K1200

4K Spectacle, Unmatched Immersion



DLP Chip Technology

11,000 Lumens Brightness

4K HDR

720° Omnidirectional Installation

20,000 Hours Light Source Life

Exhibitions / Dark Rides / Night Tours / Hotels / Meeting Rooms / Medium-sized Auditoriums / Outdoor Projection Mapping / Water Screens / Outdoor Performances

Wincomn C-4K1200

Wincomn C-4K1200 Engineering Projector meets the demands of various engineering applications, supporting both automatic and manual calibration for geometry, brightness, white balance, and color. Designed with multiple calibration modes to ensure natural image blending for different application environments. With 720° omnidirectional installation and an efficient liquid and air cooling system, it operates continuously 24/7, maintaining consistent performance and stability. The IP5X dust-proof design ensures reliability in harsh conditions, making it ideal for a wide range of applications including cultural tourism, night tours, exhibitions, large and medium-sized conference rooms, medium-sized auditoriums, outdoor projection mapping, water screens, and outdoor performances.



C-4K1200 delivers exceptional performance and rock-solid reliability, offering a stunning 4K visual experience. It is the ideal choice for a wide range of applications, including exhibitions, dark rides, night tours, hotels, meeting rooms, medium-sized auditoriums, outdoor projection mapping, water screens, and outdoor performances.

Specification

Image	Brightness (lumens)	• Center brightness of 11,000
	Brightness Uniformity	• 90 %
	Contrast (Dynamic)	• 3,000,000:1
Display	Type	• 1 x 0.65 DMD
	Resolution	• 3840 x 2160 (4K)
	Refresh Rate	• 4K 60Hz • 1080P 120Hz/240Hz
	Color Support	• > 110 % BT.709
	Color Control	• Advanced color calibration feature for RGBCYM and skin tone adjustments.
Light Source	Type	• Laser light source
	Light Source Lifetime	• ≥ 20,000 hrs
	Adjustable Light Source Mode	• Offers a range of brightness modes for linear adjustment: Bright, Standard, Soft, High Dynamic, and Low Dynamic.
Signal Inputs	Standard	• HDMI 2.0 x 1 • HDMI 2.1 (ARC) x 1 • VGA x 1 • DVI x 1 • USB x 2 (Type A) • RS-232 Input/Output • RJ45 x 1 • Audio Output x 1 • Fiber Optic Output x 1 • HDBaseT x 1 (Optional) • REMOTE IN x 1 • REMOTE OUT x 1
	Signal	• Resolution ranging from VGA to 4K
Signal Outputs	Monitor Out	• HDMI output x 1
Control & Networking	Control & Networking	• RS-232 (In/Out x 1) and RJ45 for projector device management, control, maintenance, and status monitoring.
Warping & Blending	Warping & Blending	• Built - in manual calibration, camera - based auto calibration, and multi - point calibration. Optional features include curve correction, custom shape correction, and edge blending.
Lenses	Motorized Control	• Motorized zoom and focus adjustment
	Throw Ratio	• 1.4 - 2.5:1 • Fixed lens 0.63:1
	Zoom Ratio	• Motorized focus and zoom 1.7x
	Lens offsets	• ± 50 % Horizontal • ± 100 % Vertical
	Optional Lenses	• Available lenses: 0.3:1, 0.48:1, 0.53-0.65:1, 0.63:1, 0.65-0.76:1, 0.74-1.15:1, 3.1-5.0:1, 5.0-8.0:1
Flexibility	Ease-of-operation	• Supports USB playback (images, audio, video) and includes a multifunctional remote control.
Accessories	Standard	• Remote control, User manual, Power cord, Batteries
Power Requirements	Operating Voltage	• 100 - 240 VAC @ 50/60 Hz
	Power Consumption	• 1080 W ± 10 %
	Standby Mode	• < 0.5 W
	Operating Current	• 4.5 A
Audible Noise	Audible Noise	• 40 dB
Physical	Size (mm)	• 566 W x 203 H x 572 D (lens not included)
	Shipping Size (mm)	• 714 W x 405 H x 732 D
	Weight	• 32 kg
	Shipping Weight	• 37.3 kg
Operating Environment	Temperature	• 5-40 °C
	Humidity	• 10-85 % (non-condensing)
Warranty	Warranty	• Three years on the projector
Certification	Certification	• CCC Certification • Energy Conservation Certification • Environmental Certification

BEIJING WINCOMN TECHNOLOGY CO.,LTD

86-10-6785 6868
info@wincomn.com
www.wincomn.com
Bldg.7,No.11 Kangding Street,Economic-Technological Development Area,Beijing,P.R.China

Wincomn




PRODUCT ADVANTAGES

4K Display Technology

4K HDR (3840*2160 60Hz) display technology, offering four times the resolution of Full HD. With improved color accuracy and expanded color gamut, HDR (High Dynamic Range) enhances the color contrast and brightness details of the image. It' s not just about the increase in pixel count—it' s a leap forward in color performance.







Color Control

Wincomn C-4K1200 delivers true-to-life color reproduction with HSG color fine-tuning and advanced color temperature adjustment, ensuring better image consistency in a multiple projector configuration. Featuring seven-color calibration, it further enhances brightness and color uniformity across multiple projectors.









Geometry Alignment

Supports flexible image aspect ratio adjustments, with built-in 8-point geometric correction and multiple curved surface modes. No matter the display environment, it ensures precise image alignment and projection with ease.









MEMC.HDR

Dynamic range enhancement elevates color saturation and sharpness. Colors appear deeper and more natural, bright areas are more vivid, and the overall depth of the image is enhanced. Additionally, motion blur and trailing effects are eliminated, ensuring smoother and more detailed images in high-speed scenes.



Multiple Display Aspect Ratios

Supports a variety of display aspect ratios to meet different screen requirements (16:9/16:10/2.35:1/1.88:1).



Multiple Interfaces

Equipped with a wide range of professional interfaces, the projector supports multiple signal sources for input and output. It also features automatic power-on functionality, allowing the projector to intelligently recognize and power on when an external signal source is connected, which offers great convenience.





Dust-proof Design

Wincomn C-4K1200 is designed with an IP5X dust-proof rating, and the light source has an IP6X dust-proof rating, ensuring reliable and safe operation even in harsh environments.



7×24 Operation

Engineered for 7×24 continuous operation, ensuring long-term stability and reliability. This guarantees high system availability and stable performance over extended use.





720° Omnidirectional Installation

Supports 720° omnidirectional installation without compromising brightness. It also supports portrait projection, offering diverse applications and ensuring that your design is not limited by installation angles.



Unique Heat Dissipation Structure

The unique airflow cooling design is ideal for close-range multi-unit installations, ensuring efficient heat dissipation.

