TRIOLION LCD Display Screen Specifications (B Series)

Model			TRD1046B7	TRD1046B8	TRD1046BA	TRD1049B7	TRD1055B7	TRD1055B8	TRD1055B9	TRD1055BA	TRD1055BB
Panel Parameter	Diagonal Size		46"			49"	55"				
	Panel Type		TFT (LCD)								
	Backlight Type		Direct LED Backlight								
	Pixel Pitch	H	0.53mm			0.5595mm	0.63mm				
		V	0.53mm			0.5595mm	0.63mm				
	Image Area	Width	1018.08mm			1074.24mm	1209.6mm				
		Height	572.67mm			604.26mm	680.4mm				
	Physical Resolution		1920*1080								
	Luminance of White		500cd/㎡			500cd/㎡	500cd/㎡	700cd/㎡	500cd/㎡		700cd/㎡
	Contrast Ratio		1200:1								
	Response Time		8ms								
	Display Colors		8bit								
	Display Ratio		16:9								
	Viewing Angle		178°(H)/178°(V)								
Power Supply	Working Power Consumption		150W			150W	200W				
	Standby Power Consumption		0.5W								
	Power Supply		AC 100-240V, 50/60Hz								
Physical Parameter	Dimensions (Without Mounts)	Width	1021.68mm	1020.68mm	1018.96mm	1078.34mm	1213.5mm		1211.3mm	1210.48mm	
		Height	576.27mm	575.27mm	573.55mm	608.36mm	684.5mm		682.1mm	681.28mm	
		Depth	120mm								
	Bezel Width		3.5mm	2.6mm	0.88mm	3.5mm	3.5mm		1.7mm	0.88mm	
	Bezel Color		Black								
	Weight		18kg			20kg	22kg				
Operation Condition	Operating Temperature		0-50℃								
	Operating Humidity		20%-90% (Non-condensing)								
	MTBF		50000 hours								
I/O Interface	Signal Input		Solution 1: VGA, DVI, HDMI, CVBS Solution 2: VGA, DVI, HDMI, CVBS, RJ45 (Signal Loop In) Solution 3: VGA, DVI, HDMI MHL, HDMI 4K, DP 4K Solution 4: VGA, DVI, HDMI 4K, DP 4K, USB (Optional)								
	Signal Output		Solution 1:CVBS (Signal Loop Out) Solution 2: RJ45 (Signal Loop Out for VGA/DVI/HDMI/CVBS) Solution 3: DP (Signal Loop Out for VGA/DVI/HDMI MHL/HDMI 4K/DP 4K) Solution 4: HDMI (Signal Loop Out for HDMI 4K), Audio								
	Control Input		Solution 1: RS232 IN (RJ45 Port), DEBUG ISP (RJ45 Port), IR Remote (Optional) Solution 2: RS232 IN, RJ45 IN (Loop In), USB, IR Remote (Optional) Solution 3: RS232 IN (RJ45 Port), IR Remote (Optional) Solution 4: RS232 IN (RJ45 Port), USB, IR Remote (Optional)								
	Control Output		Solution 1: RS232 OUT*2 (RJ45 Port) Solution 2: RJ45*1 (Loop Out) Solution 3: RS232 OUT (RJ45 Port) Solution 4: RS232 Out*2 (RJ45 Port)								

Version: 2023-12-01