TRIOLION

DLP/LCD/LED Video Wall Controller Specifications

Product Model	TMC6000		Version	G2
Product Description	TMC6000-G2 adopts pure hardware system structure, which processes images with the use of fast internal bus, high band width and FPGA. It is integrated with the functions of distributed and centralized controller, leading to quick start, stable function, mass IP streams processing and real-time display of images. It supports signal overlapping, cutting and roaming. Different display layouts can be saved and retrieved. All kinds of signal sources can be previewed and redisplayed. Moreover, it supports 8K & 4K HDMI/DP input, 4K IP stream inputs and 4K HDMI/DP output. TMC6000-G2 can be widely applied to control centers, such as Traffic, Electric Power, Telecom, Monitoring, Conference, Public Security, Military, etc.			
Product Features	1. Support IP Stream Decoding Function, such as IP Cameras (**IP Decoding Card Needed**)		2. Support 4K Resolution Base Image on Whole Video Wall	
	3. Support Signal Preview & Redisplay on Control PC, iPAD and Mobile Phone (**Signal Preview & Redisplay Card Needed**)		4. Support Customized Output Resolution under Different Groups	
	5. Support Redundant Power Supply		6. Support Hot-swappable Graphic Card, Fan and Power Supply	
	7. Support Automatic Temperature Detecting of Graphic Card		8. Support Virtual Mouse, Including Movement & Zoom of Signal Windows and Making Marks on Video Wall	
	9. Support Signal Cutting of Major Signal Window and Subsidiary Signal Window can be Operated		10. Support Highlight Cursor or Spotlight Function Based On Virtual Mouse	
	11. Support 8K & 4K HDMI/DP Inputs, 4K IP Stream Inputs and 4K HDMI Outputs (**8K/4K Input/Output Card Needed**)		12. Support Output Cards Devided into Different Groups for Management of Different Video Walls	
	13. Support Anti-burining Function for LCD Panels, with a Timing Cycle Scanning Black Line		14. Support Central Control Device, such as Crestron and AMX	
	15. Support C/S Client, Web Browser (iOS and Android) and APP Control		16. Support Multi-webpage Signal Sources (One Web Server) Displayed on Video Wall	
	17. Support Bezel Compensation Function for LCD Panel		18. Support Brightness/Darkness Adjustmen of Output Signals	
	19. Support Rolling Caption		20. Support Signal Cutting Function (4, 9, 16 Sub-signal Windows)	
	21. Support Audio Output		22. Support Touchable LCD Screen	
DVI-D Output Graphic Card	Port Type	**DVI-D**		
	Output Resolution	1024×768@60Hz, 1366×768@60Hz, 1280×720@60Hz; 1280×1024@60Hz, 1400×1050@60Hz, 1600×1200@60Hz; 1920×1080@60Hz, 1920×1200@60Hz, Customized Output Resolution		
	Output Quantity (Single Card)	**8-ch** **(2 signal slots needed for 8-channel card in chassis)**		
	Signal Source Processing Capability	Single Card Supports up to 40-channel 2K Signal Windows Single Screen Supports up to 16-channel 2K Signal Windows		
HDMI Output Graphic Card	Port Type	**HDMI1.3**		
	Output Quantity (Single Card)	**8-ch or 4-ch**		
	Maximum Resolution	1920×1200@60Hz		
	Signal Source Processing Capability	Single Card Supports up to 40-channel 2K Signal Windows Single Screen Supports up to 16-channel 2K Signal Windows		
4K Output Graphic Card	Port Type	**HDMI2.0 or DP1.2**		
	Output Quantity (Single Card)	**2-ch**		
	Maximum Resolution	3840×2160@60Hz or 7680×4320@30Hz		
	Signal Source Processing Capability	Single Card Supports up to 40-channel 2K Signal Windows Single Screen Supports up to 16-channel 2K Signal Windows		
LED Sending Card	Port Type	**RJ-45 1G (Work with Novastar or Colorlight LED Receiving Card)**		
	Output Quantity (Single Card)	**16-ch or 24-ch** **(2 signal slots needed for 16-channel card in chassis, (3 signal slots needed for 24-channel card in chassis)**		
	Customized Resolution	10,400,000 pixels maximum for each LED Sending Card, including 32,768 pixels maximum for width or height 650,000 pixels maximum for each RJ-45 Port, including 2500 pixels maximum for width & 3200 pixels maximum for height		
	Signal Source Processing Capability	Single Card Supports up to 32-channel 2K Signal Windows		
Fiber Output Graphic Card	Port Type	**LC (Work with Output Node, Support Redundant Output)**		
	Output Quantity (Single Card)	**8-ch**		
	Maximum Resolution	3840×2160@30Hz, 2560×1600@60Hz		
	Data Exchane Capability	80Gbps		
	Maximum Transmission Distance	10KM		
DVI Input Graphic Card	Port Type	**DVI-D or DVI-I**		
	Input Quantity (Single Card)	**8-ch or 4-ch** **(2 signal slots needed for 8-channel card in chassis, 1 signal slot needed for 4-channel card in chassis)**		
	Maximum Resolution	1920×1200@60Hz		
	Supported Signal Source Type	VGA, DVI, HDMI		
	Digital Protection	Support HDCP		
IP Decoding Graphic Card	Port Type	**RJ-45 1G**		
	Decoding Ability	1 Channel of 4K signal or 4 Channels of Pixel-to-Pixel FHD signal (16 Channels of Compressed FHD signal) or 9 Channels of Pixel-to-Pixel 720P signal (36 Channels of Compressed 720P signal)		
	Maximum Resolution	3840×2160@30Hz		
	Supported Protocol	Onvif, RTSP		
	Decoding Format	H.264, H.265		
8K Input Graphic Card	Port Type	**HDMI2.1** or **DP1.4**		
	Input Quantity (Single Card)	**1-ch for HDMI 2.1, 1-ch for DP1.4**		
	Maximum Resolution	7680×4320@60Hz		
	EDID	Supported		
4K Input Graphic Card	Port Type	**HDMI1.4** or **HDMI2.0** or **DP1.2**		
	Input Quantity (Single Card)	**4-ch for HDMI1.4, 4-ch or 2-ch for HDMI2.0, 2-ch for DP1.2**		
	Maximum Resolution	3840×2160@30Hz or 2560×1600@60Hz for HDMI1.4, 3840×2160@60Hz or 7680×4320@30Hz for HDMI 2.0 & DP1.2		
	EDID	Supported		
HDMI Input Graphic Card	Port Type	**HDMI1.3**		
	Input Quantity (Single Card)	**8-ch or 4-ch**		
	Maximum Resolution	1920×1200@60Hz		
	Digital Protection	Support HDCP		
Video Input Graphic Card	Port Type	**BNC**		
	Input Quantity (Single Card)	**4-ch**		
	Format	PAL, NTSC		
	Maximum Resolution	PAL: 720×576@25FPS NTSC: 720×478@30FPS		
	Color Depth	24Bit		
Fiber Input Graphic Card	Port Type	**LC (Work with Input Node, Support VGA/DVI/HDMI Input, Support Redundant Input)**		
	Output Quantity (Single Card)	**4-ch**		
	Maximum Resolution	3840×2160@30Hz, 2560×1600@60Hz		
	Data Exchane Capability	40Gbps		
	Maximum Transmission Distance	10KM		
Signal Preview & Redisplay Card	Port Type	RJ-45 1G		

Control Method	Control Mode	Windows Client Software, Web Browser, APP		
	Operating System	Windows Platform, iOS, Android		
	Port Type	RJ-45, RS232		
	Network Protocol	TCP/IP		
	Software Language	Simplified Chinese, Traditional Chinese, English, Korean.		
Hardware Component	Chassis Dimension (Standard 19"-W×H×D)	2.5U: 482(W)×111(H)×310(D)(mm)	Weight	4kg (Full Card)
		4U: 482(W)×178(H)×310(D)(mm)		11kg (Full Card)
		6.5U: 482(W)×289(H)×310(D)(mm)		20kg (Full Card)
		12U: 482(W)×533(H)×310(D)(mm)		38kg (Full Card)
	Chassis Card Slot	2.5U: 5 (1 Control Card Slot, 5 or 3 Signal Card Slot)		
		4U: 10 (1 Control Card Slot, 9 or 7 or 5 Signal Card Slot)		
		6.5U: 20 (1 Control Card Slot, 19 or 13 Signal Card Slot)		
		12U: 28 (1 Control Card Slot, 27 or 39 Signal Card Slot)		
	Power Supply	2.5U: Standard 250W Power Supply	Optional: 460W Power Supply	
		4U/6.5U: Standard 250W Power Supply	Optional: 460W Power Supply, Redundant, Hot-swappable	
		12U: Standard 460W Power Supply	Optional: Redundant, Hot-swappable	
Electric Requirement	Input Voltage	100~240V AC 50/60Hz		
Operating Environment	Working Temperature	0℃- 40℃		
	Working Humidity	10%-90%(No-Condensing)		
	Working Altitude	≤5000m		

TMC6000-G2 Video Wall Controller-Configuration Code Description

	Configuration Code: TMC60XXHXXDXXVXXAXXPXXUXXFXXY-G2	
	60XX	Indicates XX-channel Output
	HXX	Indicates XX-channel HDMI1.4 Input
	DXX	Indicates XX-channel DVI Input
	VXX	Indicates XX-channel VGA Input
	AXX	Indicates XX-channel Video Input
	PXX	Indicates XX-channel Decoding IP Stream Simultaneously, including IP Camera
	Y	Indicates the Function of Signal Preview & Redisplay
	FXX	Indicates XX-channel Fiber Input
	UXX	Indicates XX-channel 8K/4K HDMI/DP Input
	G2	Version

Version: V2026-07-29