**itc · AUDIO PERIPHERALS**

# TS-224DX

Suppressor

The itc TS-224DX is a suppressor from itc's Audio Peripherals range, built for system integration — processing, feedback control, connectivity and wireless microphone distribution.

Key figures: frequency response 20Hz-20kHz□±0.5dB□; frequency resolution 1Hz; input channels and plugs 2 XLR and TRS multi-use plug analog inputs. Highlights include high-performance 40-bit DPS processor, dual methods for feedback suppression, noise gate function and equalizer function.



## Key features

- High-performance 40-bit DPS processor — Provide 32-bit/48kHz excellent high-quality sound
- Dual methods for feedback suppression. — Notch filter provides 12 fixed points + 12 dynamic points High-precision frequency shift ranges from -10Hz to 10Hz
- Noise gate function — Eliminate noise Limit the output size Provide multiple parameter settings at the same time
- Equalizer function — 8-band parametric equalizer 31-band graphic equalizer Support overhead, bottom shelf, and parametric filters Support single-point bandwidth mode configuration
- Crossover function — Support Bessel, Linkwich-Rayleigh, and Butterworth Adjustable filter in the entire frequency range

## Technical specifications

| | |
|---|---|
| Input channels and plugs | 2 XLR and TRS multi-use plug analog inputs |
| Output channels and plugs | 2 XLR male plug + 2 TRS male plug analog outputs |
| Digital channel | Balance: 20KΩ |
| Input impedance | Balance: 100Ω |
| Output impedance | 2 XLR and TRS multi-use plug analog inputs |
| Input range | ≤+20dBu |
| Frequency response | 20Hz-20kHz□±0.5dB□ |
| SNR | ≥103dB@1kHz 20dBu□A□□□ |
| THD | <0.012% OUTPUT=0dBu/1kHz |
| Channel separation | >82dB(1kHz) |
| Howling search and suppression | Fully automatic notch |
| Filter | 24/CH |
| Q value range | 10-50 |
| Frequency resolution | 1Hz |
| Howling search time | 0.1—0.5S |
| FFT length | 1024 |
| Acoustic gain | 4—10dB |
| System gain | 0dB |

Continued specifications on request.