itc · WIRELESS MICROPHONES

TS-316M

Small Diaphragm Microphone

The itc TS-316M is a small Diaphragm Microphone from itc's Wireless Microphones range, built for speech, vocal and instrument pickup for conferences, lectures, worship and live performance.

Key figures: phantom power +48V; power consumption 3mA; frequency response 80Hz-20kHz. Highlights include electret condenser microphone design, can be used for stereo recording, single or multiple microphones can be used at the same time and suitable for group pickups such as chorus and musical instruments.

Key features

- Electret condenser microphone design — Feature excellent bunch directivity
- Can be used for stereo recording — Achieve outstanding spatial effects Support multiple audio sources recording
- Single or multiple microphones can be used at the same time
- Suitable for group pickups such as chorus and musical instruments

Technical specifications

Directivity	Bunch
Interface	Balanced XLR interface
Sensitivity (at 1kHz)	-29dBV(0 dBV=0.775V/Pa)
Frequency response	80Hz-20kHz
Attenuation	-10dB(-12dB Butwrth)
SPL limit (1% THD@1 kHz)	130 dB(0 dB), 140 dB(-10 dB)
Equivalent SPL (according to IEC 651)	19 dB-A
SNR	78 dB
Rated impedance	680Ω
Rated terminal impedance	>1 kΩ
Phantom power	+48V
Power consumption	3mA
Dimension (diameter × length)	22mm×148mm
Weight	205g