itc · CONFERENCE & COLUMN LOUDSPEAKERS

TS-403HW

Column Speaker

The itc TS-403HW is a column Speaker from itc's Conference & Column Loudspeakers range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues.

Key figures: rated power 100W; frequency range 150Hz-14KHz@-6dB / 80Hz-20KHz@-10dB; coverage angle Vertical >20°, horizontal >120°@ (-6db). Highlights include four 3-inch high performance ferrite driver unit, constant beam technology, unique low-frequency cardioid diffusion and strong and durable cabinet.



Key features

- Four 3-inch high performance ferrite driver unit
- Constant beam technology — Solve the problems of projection and interference of traditional speakers
- Unique low-frequency cardioid diffusion — Provide clear treble, natural timbre, and powerful bass
- Strong and durable cabinet — ABS plastic mixed glass fiber reinforced cabinet Aluminum mesh cover, anti-rust cabinet OptionalUV waterproof dip coating for IPx4 waterproof degree OptionalUL94V-0 flame retardant material Optional smart

Technical specifications

Rated power	100W
Nominal resistance	8 Ω
Frequency range	150Hz-14KHz@-6dB / 80Hz-20KHz@-10dB
Sensitivity	95dB(1M/1W)
Coverage angle	Vertical >20°, horizontal >120°@ (-6db)
Speaker	3″ full-range speaker ×4
Housing material	ABS plastic + fiberglass
Net weight	5.08kg
Dimension	530×100×150mm