itc · STAGE MONITORS

TS-612TW

Professional Speaker

The itc TS-612TW is a professional Speaker from itc's Stage Monitors range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues.

Key figures: rated power 400W; peak power 1600W; frequency response 50Hz-20KHz. Highlights include one mid-woofer, one annular polyethylene diaphragm compressed tweeter, strong and wear-resistant cabinet and frequency divider in precise design.



Key features

- One mid-woofer
- One annular polyethylene diaphragm compressed tweeter
- Strong and wear-resistant cabinet — 15mm plywood housing Spray paint treatment surface External hard hexagonal iron mesh Dust-proof cotton inside
- Frequency divider in precise design — Optimize the vocal MF performance
- Polygonal structure for monitoring angle adjustment

Technical specifications

Impedance	8Ω
Frequency response	50Hz-20KHz
Rated power	400W
Peak power	1600W
Sensitivity	99dB/W/M
Maximum SPL (nominal/peak)	125dB/131dB
Coverage angle	(H)80°(V)60°
Tweeter	1.7″ compressed tweeter×1
Woofer	12″ woofer×1
Protection class	IP55
Dimension	380×585×440mm (H×W×D)
Weight	20.5Kg