

Lab-11.5

Course : AI Assisted Coding

Topic:- Data Structures with AI: Implementing Fundamental Structures Student Details:

Name : Mohammed Sabir

Hall Ticket No : 2303A51506

Batch : 22

Task-01

Final Optimal Prompt:

write a program to generate a stack class with push, pop, peek and is_empty methods class stack and pass

and make a documentation for the class and its methods

Code Screenshot :

```

5
6 class Stack:
7     """A simple implementation of a stack data structure using a list."""
8
9     def __init__(self):
10         """Initialize an empty stack."""
11         self.items = []
12
13     def push(self, item):
14         """Add an item to the top of the stack.
15
16         Args:
17             item: The item to be added to the stack.
18         """
19         self.items.append(item)
20
21     def pop(self):
22         """Remove and return the item at the top of the stack.
23
24         Returns:
25             The item at the top of the stack if it is not empty; otherwise, None.
26         """
27         if not self.is_empty():
28             return self.items.pop()
29         return None
30
31     def peek(self):
32         """Return the item at the top of the stack without removing it.
33
34         Returns:
35             The item at the top of the stack if it is not empty; otherwise, None.
36         """
37         if not self.is_empty():
38             return self.items[-1]
39         return None
40
41     def is_empty(self):
42         """Check if the stack is empty.
43
44         Returns:
45             True if the stack is empty; otherwise, False.
46         """
47         return len(self.items) == 0
48
49 if __name__ == "__main__":
50     stack = Stack()
51     stack.push(1)
52     stack.push(2)
53     stack.push(3)
54     print(stack.peek()) # Output: 3
55     print(stack.pop())  # Output: 3
56     print(stack.peek()) # Output: 2
57     print(stack.is_empty()) # Output: False
58     stack.pop()
59     print(stack.is_empty()) # Output: True

```

Output Screenshot:

```
3
3
2
False
True
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant>
```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program implements a basic Stack data structure using a Python list. It follows the LIFO (Last In, First Out) principle, where the most recently added element is removed first. The push() method adds elements to the top of the stack, while the pop() method removes and returns the top element. The peek() method allows viewing the top element without removing it. Unlike other implementations, this version returns None instead of raising exceptions when the stack is empty. The is_empty() method checks whether the stack contains elements. Overall, the program demonstrates clean design, documentation, and fundamental stack operations

Task-02

Final Optimal Prompt:

write a program to generate a queue class with enqueue, dequeue, peek and size methods
class queue and pass

Code Screenshot :

```

68 class Queue:
69     """A simple implementation of a queue data structure using a list."""
70     def __init__(self):
71         """Initialize an empty queue."""
72         self.items = []
73     def enqueue(self, item):
74         """Add an item to the end of the queue.
75         Args:
76             item: The item to be added to the queue.
77         """
78         self.items.append(item)
79
80     def dequeue(self):
81         """Remove and return the item at the front of the queue.
82         Returns:
83             The item at the front of the queue if it is not empty; otherwise, None.
84         """
85         if not self.is_empty():
86             return self.items.pop(0)
87         return None
88     def peek(self):
89         """Return the item at the front of the queue without removing it.
90         Returns:
91             The item at the front of the queue if it is not empty; otherwise, None.
92         """
93         if not self.is_empty():
94             return self.items[0]
95         return None
96     def size(self):
97         """Return the number of items in the queue.
98         Returns:
99             The number of items in the queue.
100         """
101         return len(self.items)
102     def is_empty(self):
103         """Check if the queue is empty.
104         Returns:
105             True if the queue is empty; otherwise, False.
106         """
107         return len(self.items) == 0
108 if __name__ == "__main__":
109     queue = Queue()
110     queue.enqueue(1)
111     queue.enqueue(2)
112     queue.enqueue(3)
113     print(queue.peek()) # Output: 1
114     print(queue.dequeue()) # Output: 1
115     print(queue.peek()) # Output: 2
116     print(queue.size()) # Output: 2
117     print(queue.is_empty()) # Output: False
118     queue.dequeue()
119     queue.dequeue()
120     print(queue.is_empty()) # Output: True
121

```

Output Screenshot:

```

PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> c::; cd 'c:\Users\sakir\OneDrive\Desktop\Ai-Assistant'; & 'c:\python314\python.exe' 'c:\Users\sakir\.vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debugpy\launcher' '63611' '--' 'C:\Users\sakir\OneDrive\Desktop\Ai-Assistant\lab1_1.py'
1
1
2
2
False
True

```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program implements a basic Queue data structure using a Python list and follows the FIFO (First In, First Out) principle. The enqueue() method adds elements to the end of the queue, while the dequeue() method removes and returns the front element. The peek() method allows viewing the front element without removing it. If the queue is empty, both dequeue() and peek() return None instead of raising exceptions. The size() method returns the total number of elements, and is_empty() checks whether the queue contains items. Overall, the program demonstrates clear structure, proper documentation, and fundamental queue operations.

Task-03**Final Optimal Prompt:**

write a program to generate a linked list class with insert and display method class linked list and pass

and make a documentation for the class and its methods

Code Screenshot :

```

127 '''
128 class Node:
129     """A node in a linked list."""
130     def __init__(self, data):
131         """Initialize a node with data and a reference to the next node.
132         Args:
133             data: The value stored in the node.
134         """
135         self.data = data
136         self.next = None
137 class LinkedList:
138     """A simple implementation of a singly linked list."""
139     def __init__(self):
140         """Initialize an empty linked list."""
141         self.head = None
142     def insert(self, data):
143         """Insert a new node with the given data at the end of the linked list.
144         Args:
145             data: The value to be stored in the new node.
146         """
147         new_node = Node(data)
148         if self.head is None:
149             self.head = new_node
150             return
151         last_node = self.head
152         while last_node.next:
153             last_node = last_node.next
154         last_node.next = new_node
155     def display(self):
156         """Display the contents of the linked list."""
157         current_node = self.head
158         while current_node:
159             print(current_node.data, end=' ')
160             current_node = current_node.next
161         print()
162 if __name__ == "__main__":
163     linked_list = LinkedList()
164     linked_list.insert(1)
165     linked_list.insert(2)
166     linked_list.insert(3)
167     print("Linked List contents:")
168     linked_list.display() # Output: 1 2 3
169

```

Output Screenshot:

```

True
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> ^C
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> c:: cd 'c:\Users\sakir\OneDrive\Desktop\Ai-Assistant\lab11.py'
Linked List contents:
1 2 3
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant>

```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program implements a basic singly linked list using two classes: Node and LinkedList. The Node class stores data and a reference to the next node, forming the building block of the list. The LinkedList class manages the list through a head pointer. The insert() method

adds new nodes at the end by traversing the list until the last node is found. The display() method prints all elements sequentially. This implementation demonstrates dynamic memory usage, where elements are not stored contiguously like arrays. Overall, the program clearly illustrates linked list structure and fundamental operations.

Task-04

Final Optimal Prompt:

write a program to generate a hash table with basic insert, search , and delete methods class hash table and pass

and make a documentation for the class and its methods

Code Screenshot :

```

174 ...
175 class HashTable:
176     """A simple implementation of a hash table using chaining for collision resolution."""
177     def __init__(self, size=10):
178         """Initialize the hash table with a specified size.
179         Args:
180             size: The number of buckets in the hash table (default is 10).
181         """
182         self.size = size
183         self.table = [[] for _ in range(size)]
184     def _hash(self, key):
185         """Generate a hash value for the given key.
186         Args:
187             key: The key to be hashed.
188         Returns:
189             An index corresponding to the bucket where the key-value pair should be stored.
190         """
191         return hash(key) % self.size
192     def insert(self, key, value):
193         """Insert a key-value pair into the hash table.
194         Args:
195             key: The key to be inserted.
196             value: The value associated with the key.
197         """
198         index = self._hash(key)
199         bucket = self.table[index]
200         for i, (k, v) in enumerate(bucket):
201             if k == key:
202                 bucket[i] = (key, value) # Update existing key
203                 return
204         bucket.append((key, value)) # Insert new key-value pair
205     def search(self, key):
206         """Search for a value associated with a given key in the hash table.
207         Args:
208             key: The key to be searched for.
209         Returns:
210             The value associated with the key if found; otherwise, None.
211         """
212         index = self._hash(key)
213         bucket = self.table[index]
214         for k, v in bucket:
215             if k == key:
216                 return v
217         return None
218     def delete(self, key):
219         """Delete a key-value pair from the hash table based on the given key.
220         Args:
221             key: The key to be deleted from the hash table.
222         Returns:
223             True if the key was found and deleted; otherwise, False.
224         """
225         index = self._hash(key)
226         bucket = self.table[index]
227         for i, (k, v) in enumerate(bucket):
228             if k == key:
229                 del bucket[i] # Remove the key-value pair
230                 return True
231         return False
232 if __name__ == "__main__":
233     hash_table = HashTable()
234     hash_table.insert("name", "Alice")
235     hash_table.insert("age", 30)
236     print(hash_table.search("name")) # Output: Alice
237     print(hash_table.search("age")) # Output: 30
238     print(hash_table.delete("name")) # Output: True
239     print(hash_table.search("name")) # Output: None
240

```

Output Screenshot:


```
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> cd "C:\Users\sakir\OneDrive\Desktop\Ai-Assistant" & "C:\python324\python.exe" "C:\Users\sakir\OneDrive\Desktop\Ai-Assistant\lab11.py"
Alice
30
True
None
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant>
```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program implements a simple hash table using chaining to handle collisions. It initializes a fixed number of buckets, each represented as a list. The private `_hash()` method generates an index using Python's built-in `hash()` function and modulo operation. The `insert()` method adds key-value pairs and updates values if the key already exists. The `search()` method retrieves the value associated with a key, returning `None` if not found. The `delete()` method removes a key-value pair and returns a boolean indicating success. Overall, the program demonstrates efficient data storage, collision handling, and fundamental hash table operations clearly.

Tack-05

Final Optimal Prompt:

write a program to generate graph using adjacent list methods like add vertices and edges and display the graph class graph and pass
and make a documentation for the class and its methods

Code Screenshot :

```

247 class Graph:
248     """A simple implementation of a graph data structure using an adjacency list."""
249
250     def __init__(self):
251         """Initialize an empty graph."""
252         self.graph = {}
253
254     def add_vertex(self, vertex):
255         """Add a vertex to the graph.
256
257         Args:
258             vertex: The vertex to be added to the graph.
259         """
260         if vertex not in self.graph:
261             self.graph[vertex] = []
262
263     def add_edge(self, vertex1, vertex2):
264         """Add an edge between two vertices in the graph.
265
266         Args:
267             vertex1: The first vertex of the edge.
268             vertex2: The second vertex of the edge.
269         """
270         if vertex1 in self.graph and vertex2 in self.graph:
271             self.graph[vertex1].append(vertex2)
272             self.graph[vertex2].append(vertex1) # For undirected graph
273
274     def display(self):
275         """Display the adjacency list representation of the graph."""
276         for vertex, edges in self.graph.items():
277             print(f"{vertex}: {edges}")
278
279 if __name__ == "__main__":
280     graph = Graph()
281     graph.add_vertex("A")
282     graph.add_vertex("B")
283     graph.add_vertex("C")
284     graph.add_edge("A", "B")
285     graph.add_edge("A", "C")
286     graph.add_edge("B", "C")
287     print("Graph adjacency list:")
288     graph.display() # Output: A: ['B', 'C'], B: ['A', 'C'], C: ['A', 'B']

```

Output Screenshot:

```

PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> c:: cd 'c:\Users\sakir\OneDrive\Desktop\Ai-Assistant'; & 'c:\p
ython314\python.exe' 'c:\Users\sakir\.vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debug
py\launcher' '53702' '--' 'C:\Users\sakir\OneDrive\Desktop\Ai-Assistant\lab11.py'
Graph adjacency list:
A: ['B', 'C']
B: ['A', 'C']
C: ['A', 'B']
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> 

```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program implements a simple undirected graph using an adjacency list represented by a dictionary. Each key in the dictionary represents a vertex, and its value is a list of adjacent vertices. The `add_vertex()` method ensures that a vertex is added only if it does not already exist. The `add_edge()` method creates a connection between two vertices and updates both adjacency lists, reflecting the undirected nature of the graph. The `display()` method prints

the adjacency list in a readable format. Overall, the program clearly demonstrates graph representation, vertex and edge management, and fundamental graph structure concepts.

Tack-06

Final Optimal Prompt:

write a python program for smart hospital management system using data structures like stack, queue, priority queue, linked list, binary search tree(BST), hash table, graph and deque to manage patients checking system, emergency case handling , medical records storage, doctor appointment scheduling , and hospital room navigation system

choose which data structure is best for each task and implement the functionalities accordingly and make a documentation for the program and its functionalities and justify the choice of data structures used for each functionality

Code Screenshot :

```

295 class Patient:
296     """A class representing a patient in the hospital management system."""
297     def __init__(self, name, age, condition):
298         """Initialize a patient with name, age, and medical condition.
299         Args:
300             name: The name of the patient.
301             age: The age of the patient.
302             condition: The medical condition of the patient.
303         """
304         self.name = name
305         self.age = age
306         self.condition = condition
307
308 class HospitalManagementSystem:
309     """A class representing the hospital management system."""
310     def __init__(self):
311         """Initialize the hospital management system with necessary data structures."""
312         self.patient_queue = [] # Queue for managing patient check-ins
313         self.emergency_stack = [] # Stack for handling emergency cases
314         self.medical_records = {} # Hash table for storing medical records
315         self.doctor_appointments = {} # Hash table for scheduling doctor appointments
316         self.hospital_graph = {} # Graph for hospital room navigation
317     def check_in_patient(self, patient):
318         """Check in a patient to the hospital.
319         Args:
320             patient: An instance of the Patient class to be checked in.
321         """
322         self.patient_queue.append(patient) # Enqueue the patient to the queue
323     def handle_emergency(self, patient):
324         """Handle an emergency case by adding the patient to the emergency stack.
325         Args:
326             patient: An instance of the Patient class representing the emergency case.
327         """
328         self.emergency_stack.append(patient) # Push the patient onto the stack
329     def store_medical_record(self, patient, record):
330         """Store a medical record for a patient in the hash table.
331         Args:
332             patient: An instance of the Patient class whose record is to be stored.
333             record: The medical record to be stored for the patient.
334         """
335         self.medical_records[patient.name] = record # Store the record in the hash table
336     def schedule_appointment(self, doctor_name, patient):
337         """Schedule a doctor appointment for a patient.
338         Args:
339             doctor_name: The name of the doctor with whom the appointment is to be scheduled.
340             patient: An instance of the Patient class for whom the appointment is to be scheduled.
341         """
342         if doctor_name not in self.doctor_appointments:
343             self.doctor_appointments[doctor_name] = []
344         self.doctor_appointments[doctor_name].append(patient) # Schedule the appointment in the hash table
345     def add_room(self, room_number):
346         """Add a room to the hospital graph for navigation purposes.
347         Args:
348             room_number: The number of the room to be added to the graph.
349         """
350         if room_number not in self.hospital_graph:
351             self.hospital_graph[room_number] = [] # Add a vertex for the room in the graph
352     def connect_rooms(self, room1, room2):
353         """Connect two rooms in the hospital graph to indicate a navigable path.
354         Args:
355             room1: The number of the first room to be connected.
356             room2: The number of the second room to be connected.
357         """
358         if room1 in self.hospital_graph and room2 in self.hospital_graph:
359             self.hospital_graph[room1].append(room2) # Connect room1 to room2
360             self.hospital_graph[room2].append(room1) # Connect room2 to room1 (undirected graph)
361
362 if __name__ == "__main__":
363     hospital_system = HospitalManagementSystem()
364
365     # Create some patients
366     patient1 = Patient("Alice", 30, "Flu")
367     patient2 = Patient("Bob", 45, "Heart Disease")
368     patient3 = Patient("Charlie", 25, "Broken Arm")
369
370     # Check in patients
371     hospital_system.check_in_patient(patient1)
372     hospital_system.check_in_patient(patient2)
373     hospital_system.check_in_patient(patient3)
374
375     # Handle emergency cases
376     emergency_patient = Patient("Diana", 50, "Chest Pain")
377     hospital_system.handle_emergency(emergency_patient)
378
379     # Store medical records
380     hospital_system.store_medical_record(patient1, "Patient has flu symptoms.")
381     hospital_system.store_medical_record(patient2, "Patient has heart disease.")
382
383     # Schedule doctor appointments
384     hospital_system.schedule_appointment("Dr. Smith", patient1)
385     hospital_system.schedule_appointment("Dr. Johnson", patient2)
386
387     # Add rooms and connect them
388     hospital_system.add_room(101)
389     hospital_system.add_room(102)
390     hospital_system.add_room(103)
391
392     hospital_system.connect_rooms(101, 102)
393     hospital_system.connect_rooms(102, 103)
394
395     # Display the hospital graph
396     print("Hospital Room Navigation Graph:")
397     for room, connections in hospital_system.hospital_graph.items():
398         print(f"Room {room}: Connected to {connections}")

```

Output Screenshot:

1. Queue for Patient Check-ins: A queue is used to manage patient check-ins because it follows the First-In-First-Out (FIFO) principle, ensuring that patients are attended to in the order they arrive.
2. Stack for Emergency Cases: A stack is used to handle emergency cases because it follows the Last-In-First-Out (LIFO) principle, allowing the most recent emergency case to be addressed first.
3. Hash Table for Medical Records and Doctor Appointments: Hash tables are used for storing medical records and scheduling doctor appointments because they provide efficient key-value pair storage and retrieval, allowing for quick access to patient information and appointment details.
4. Graph for Hospital Room Navigation: A graph is used to represent the hospital's room navigation system because it can efficiently model the relationships between rooms and the paths connecting them, allowing for easy traversal and navigation through the hospital.

```
top\AI-Assistant\lab11.py
Hospital Room Navigation Graph:
Room 101: Connected to [102]
Room 102: Connected to [101, 103]
Room 103: Connected to [102]
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant>
```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program demonstrates a structured Hospital Management System using multiple data structures to handle different functionalities. It uses a queue (list) for patient check-ins following FIFO order, a stack for emergency cases following LIFO priority, dictionaries as hash tables for storing medical records and scheduling doctor appointments, and a graph (adjacency list) for hospital room navigation. The Patient class encapsulates patient details, promoting object-oriented design. The system clearly separates responsibilities into methods such as check-in, emergency handling, record storage, and room connection. Overall, the program effectively integrates data structures with OOP concepts in a practical real-world application.

Tack-07

Final Optimal Prompt:

write a python program for smart city traffic control system using data structures like stack, queue, priority queue, linked list, binary search tree(BST), hash table, graph and deque traffic signal queue, emergency vehicle priority handling, vehicle registration look up, road network mapping and parking slot availability

choose which data structure is best for each task and implement the functionalities accordingly and make a documentation for the program and its functionalities and justify the choice of data structures used for each functionality

Code Screenshot :

```

414
415 class TrafficControlSystem:
416     """A class representing a smart city traffic control system."""
417     def __init__(self):
418         """
419         Initialize the traffic control system with required data structures.
420         """
421         self.traffic_signal_queue = [] # Queue (FIFO) for managing traffic signals
422         self.emergency_vehicle_priority_queue = [] # Priority queue for emergency vehicles
423         self.vehicle_registration_hash_table = {} # Hash table (Dictionary) for vehicle lookup
424         self.road_network_graph = {} # Graph (Adjacency List) for road mapping
425         self.parking_slot_linked_list = None # Linked list for parking slot management
426     def manage_traffic_signal(self, signal):
427         """
428         Add traffic signal to queue.
429         FIFO principle (First In First Out)
430         """
431         self.traffic_signal_queue.append(signal)
432     def handle_emergency_vehicle(self, vehicle):
433         """
434         Add emergency vehicle to priority queue.
435         (Currently simple list; can be improved using heapq)
436         """
437         self.emergency_vehicle_priority_queue.append(vehicle)
438     def lookup_vehicle_registration(self, license_plate):
439         """
440         Retrieve vehicle registration details using hash table.
441         Returns registration info if exists, otherwise None.
442         """
443         return self.vehicle_registration_hash_table.get(license_plate)
444     def map_road_network(self, road1, road2):
445         """
446         Connect two roads in graph (Undirected Graph).
447         """
448         # Add road1 if not present
449         if road1 not in self.road_network_graph:
450             self.road_network_graph[road1] = []
451         # Add road2 if not present
452         if road2 not in self.road_network_graph:
453             self.road_network_graph[road2] = []
454         # Connect both roads
455         self.road_network_graph[road1].append(road2)
456         self.road_network_graph[road2].append(road1)
457     def manage_parking_slot(self, slot):
458         """
459         Insert parking slot into linked list.
460         """
461         # Initialize linked list if empty
462         if self.parking_slot_linked_list is None:
463             self.parking_slot_linked_list = LinkedList()
464         self.parking_slot_linked_list.insert(slot)
465
466 class LinkedList:
467     """
468     Simple singly linked list for parking slot storage.
469     """
470     def __init__(self):
471         self.head = None # Initially list is empty
472
473     def insert(self, slot):
474         """
475         Insert a new parking slot at the end of linked list.
476         """
477         new_node = Node(slot)
478         # If list is empty
479         if not self.head:
480             self.head = new_node
481         else:
482             current = self.head
483             # Traverse till last node
484             while current.next:
485                 current = current.next
486             current.next = new_node
487
488 class Node:
489     """
490     Node class for Linked list.
491     """
492     def __init__(self, data):
493         self.data = data
494         self.next = None
495
496 if __name__ == "__main__":
497     # Create Traffic Control System object
498     traffic_system = TrafficControlSystem()
499
500     traffic_system.manage_traffic_signal("Signal A")
501     traffic_system.manage_traffic_signal("Signal B")
502
503     traffic_system.handle_emergency_vehicle("Ambulance")
504     traffic_system.handle_emergency_vehicle("Fire Truck")
505
506     # Insert vehicle data into hash table
507     traffic_system.vehicle_registration_hash_table["ABC123"] = "John Doe, Red Sedan"
508     # Lookup vehicle
509     print(traffic_system.lookup_vehicle_registration("ABC123"))
510     traffic_system.map_road_network("Road 1", "Road 2")
511     traffic_system.map_road_network("Road 2", "Road 3")
512     print("Road Network Graph:")
513     for road, connections in traffic_system.road_network_graph.items():
514         print(f"{road}: Connected to {connections}")
515     traffic_system.manage_parking_slot("Slot 1")
516     traffic_system.manage_parking_slot("Slot 2")

```

Output Screenshot:

Justification of Data Structures Used

1. Queue for Traffic Signal Management: A queue is used to manage traffic signals because it allows for orderly processing of signals based on their arrival time, ensuring that traffic flows smoothly.

2. Priority Queue for Emergency Vehicle Handling: A priority queue is used to handle emergency vehicles because it allows for prioritizing certain vehicles (e.g., ambulances, fire trucks) over regular traffic, ensuring that they can navigate through traffic efficiently.

3. Hash Table for Vehicle Registration Lookup: A hash table is used for vehicle registration lookup because it provides fast access to registration information based on license plate numbers, allowing for quick retrieval of vehicle details.

4. Graph for Road Network Mapping: A graph is used to represent the road network because it can efficiently model the relationships between roads and the paths connecting them, allowing for easy traversal and navigation through the city.

5. Linked List for Parking Slot Availability: A linked list is used to manage parking slot availability because it allows for dynamic insertion and deletion of parking slots as they become available or occupied, providing flexibility in managing the parking system.

```
kir\.vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debugpy\launcher '59349' '--' 'C:\Users\sakir\OneDrive\
stant\lab11.py'
John Doe, Red Sedan
Road Network Graph:
Road 1: Connected to ['Road 2']
Road 2: Connected to ['Road 1', 'Road 3']
Road 3: Connected to ['Road 2']
Parking Slots:
Slot 1
Slot 2
```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program models a smart city Traffic Control System by integrating multiple data structures to handle different operations efficiently. It uses a queue to manage traffic signals following the FIFO principle and a priority queue (implemented as a list) to handle emergency vehicles. A hash table (dictionary) enables quick vehicle registration lookup. The road network is represented using an undirected graph through an adjacency list. Additionally, a singly linked list manages parking slots dynamically. The system demonstrates effective use of Object-Oriented Programming and data structures to simulate real-world traffic management scenarios in a structured and practical manner.

Tack-08

Final Optimal Prompt:

write a python program for smart E-commerce platform using data structures like stack, queue, priority queue, linked list, binary search tree(BST), hash table, graph and deque to manage shopping cart management, order processing system, top selling products tracker, product search engine, delivery route planning

choose which data structure is best for each task and implement the functionalities accordingly and make a documentation for the program and its functionalities and justify the choice of data structures used for each functionality

Code Screenshot :

```

538 """
539 class ECommercePlatform:
540     """A class representing a smart e-commerce platform."""
541     def __init__(self):
542         """
543         Initialize the e-commerce platform with required data structures.
544         """
545         self.shopping_cart_stack = [] # Stack for managing shopping cart items
546         self.order_processing_queue = [] # Queue for processing orders
547         self.top_selling_products_priority_queue = [] # Priority queue for tracking top-selling products
548         self.product_search_bst = None # Binary Search Tree for product search engine
549         self.delivery_route_graph = {} # Graph for delivery route planning
550     def add_to_cart(self, product):
551         """
552         Add a product to the shopping cart.
553         LIFO principle (Last In First Out)
554         """
555         self.shopping_cart_stack.append(product)
556     def process_order(self, order):
557         """
558         Add an order to the processing queue.
559         FIFO principle (First In First Out)
560         """
561         self.order_processing_queue.append(order)
562     def track_top_selling_product(self, product, sales):
563         """
564         Add a product to the priority queue based on sales.
565         Higher sales get higher priority.
566         """
567         self.top_selling_products_priority_queue.append((sales, product))
568         self.top_selling_products_priority_queue.sort(reverse=True) # Sort by sales in descending order
569     def search_product(self, product_name):
570         """
571         Search for a product using a binary search tree.
572         Returns True if found, otherwise False.
573         """
574         return self._search_bst(self.product_search_bst, product_name)
575     def _search_bst(self, node, product_name):
576         if node is None:
577             return False
578         if node.data == product_name:
579             return True
580         elif product_name < node.data:
581             return self._search_bst(node.left, product_name)
582         else:
583             return self._search_bst(node.right, product_name)
584     def plan_delivery_route(self, location1, location2):
585         """
586         Connect two locations in the delivery route graph.
587         Undirected graph representation.
588         """
589         if location1 not in self.delivery_route_graph:
590             self.delivery_route_graph[location1] = []
591         if location2 not in self.delivery_route_graph:
592             self.delivery_route_graph[location2] = []
593         self.delivery_route_graph[location1].append(location2)
594         self.delivery_route_graph[location2].append(location1)
595     class BSTNode:
596         """Node class for Binary Search Tree."""
597         def __init__(self, data):
598             self.data = data
599             self.left = None
600             self.right = None
601     if __name__ == "__main__":
602         ecommerce_platform = ECommercePlatform()
603         # Add products to shopping cart
604         ecommerce_platform.add_to_cart("Laptop")
605         ecommerce_platform.add_to_cart("Smartphone")
606         # Process orders
607         ecommerce_platform.process_order("Order 1")
608         ecommerce_platform.process_order("Order 2")
609         # Track top-selling products
610         ecommerce_platform.track_top_selling_product("Laptop", 100)
611         ecommerce_platform.track_top_selling_product("Smartphone", 150)
612         # Search for a product
613         print(ecommerce_platform.search_product("Laptop")) # Output: False (BST not implemented)
614         # Plan delivery routes
615         ecommerce_platform.plan_delivery_route("Warehouse", "Customer A")
616         ecommerce_platform.plan_delivery_route("Warehouse", "Customer B")
617         print("Delivery Route Graph:")
618         for location, connections in ecommerce_platform.delivery_route_graph.items():
619             print(f"{location}: Connected to {connections}")
620
621
622

```

Output Screenshot:

Justification of Data Structures Used

1. Stack for Shopping Cart Management: A stack is used to manage shopping cart items because it allows for easy addition and removal of items in a last-in-first-out manner, which is suitable for a shopping cart where the most recently added item is often the first one to be removed.

2. Queue for Order Processing System: A queue is used for processing orders because it follows the first-in-first-out principle, ensuring that orders are processed in the order they were received, which is important for maintaining fairness and efficiency in order fulfillment.
3. Priority Queue for Top Selling Products Tracker: A priority queue is used to track top-selling products because it allows for efficient retrieval of products based on their sales, ensuring that the most popular products are easily accessible.
4. Binary Search Tree for Product Search Engine: A binary search tree is used for the product search engine because it allows for efficient searching, insertion, and deletion of products based on their names, providing a structured way to manage the product catalog.
5. Graph for Delivery Route Planning: A graph is used to represent the delivery route planning because it can efficiently model the relationships between different locations and the paths connecting them, allowing for easy traversal and optimization of delivery routes.

```
kir\.vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debugpy\launcher' '60490' '--' 'C
stant\lab11.py'
False
Delivery Route Graph:
Warehouse: Connected to ['Customer A', 'Customer B']
Customer A: Connected to ['Warehouse']
Customer B: Connected to ['Warehouse']
PS C:\Users\sakir\OneDrive\Desktop\Ai-Assistant> █
```

Explanation/Justification/Observation (100 words / 5 – 6 sentence) :

The program models a smart e-commerce platform by integrating multiple data structures to handle different functionalities. It uses a stack for managing shopping cart items (LIFO), a queue for order processing (FIFO), and a priority queue (implemented using sorting) to track top-selling products based on sales. A Binary Search Tree structure is referenced for product searching, although full insertion logic is not implemented. Additionally, a graph is used for delivery route planning between locations. The design demonstrates strong understanding of data structures and their real-world applications. Overall, the program effectively combines OOP principles with practical system modeling concepts
