
Amazon MQ

REST API Reference

Amazon MQ: REST API Reference

Copyright © 2018 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Example REST Request	1
Example REST Response	1
Resources	3
Broker	3
URI	3
HTTP Methods	3
Errors	5
Schemas	5
Attributes	7
Broker Reboot	13
URI	13
HTTP Methods	13
Errors	13
Schemas	14
Attributes	14
Brokers	14
URI	14
HTTP Methods	14
Errors	16
Schemas	16
Attributes	18
Configuration	23
URI	23
HTTP Methods	23
Errors	24
Schemas	24
Attributes	25
Configurations	28
URI	28
HTTP Methods	28
Errors	29
Schemas	30
Attributes	31
Configuration Revision	34
URI	34
HTTP Methods	34
Errors	34
Schemas	35
Attributes	35
Configuration Revisions	36
URI	36
HTTP Methods	36
Errors	37
Schemas	37
Attributes	38
User	39
URI	39
HTTP Methods	39
Errors	41
Schemas	42
Attributes	43
Users	45
URI	45

HTTP Methods	45
Errors	46
Schemas	46
Attributes	46

Welcome

Welcome to the Amazon MQ REST API reference. In this guide, you can find descriptions of REST resources, example requests, HTTP methods, schemas, parameters, and the errors that the service returns.

Amazon MQ is a managed message broker service for [Apache ActiveMQ](#) that makes it easy to set up and operate message brokers in the cloud. Amazon MQ works with your existing applications and services without the need to manage, operate, or maintain your own messaging system.

You can access your brokers by using [any programming language that ActiveMQ supports](#) and by enabling TLS explicitly for the following protocols:

- [AMQP](#)
- [MQTT](#)
- MQTT over [WebSocket](#)
- [OpenWire](#)
- [STOMP](#)
- STOMP over WebSocket

Topics

- [Example REST Request \(p. 1\)](#)
- [Example REST Response \(p. 1\)](#)

Additional Information

- [Amazon MQ Product Page](#)
- [Amazon MQ Developer Guide](#)
- [Amazon MQ in the AWS CLI Command Reference](#)
- [Regions and Endpoints](#)

Last documentation update: September 27, 2018

Example REST Request

The following is an example of an Amazon MQ REST request (and its headers) which creates a new broker:

```
POST /v1/brokers HTTP/1.1
Content-Type: application/json
X-Amz-Date: 20171123T214525Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20171128/us-east-2/mq/aws4_request, SignedHeaders=content-length;content-type;host;x-amz-date, Signature=a12bc34567defg89h0ij1234kl56m789no01p2q345r6s789tu01v2w3x4567890
Host: mq.us-east-2.amazonaws.com
Cache-Control: no-cache

{
  "brokerName": "MyBroker",
```

```
"hostInstanceType": "mq.m5.large",
"engineType": "ActiveMQ",
"engineVersion": "5.15.6",
"logs": {
  "general": true,
  "audit": false
},
"deploymentMode": "ACTIVE_STANDBY_MULTI_AZ",
"publiclyAccessible": true,
"subnetIds": [
  "subnet-12a3b45c",
  "subnet-67d8e90f"
],
"securityGroups": [
  "sg-a1b234cd",
  "sg-e5f678gh"
],
"autoMinorVersionUpgrade": true,
"users": [{
  "password": "MyPassword456",
  "groups": [
    "admins"
  ],
  "consoleAccess": true,
  "username": "jane.doe"
}]
}
```

Example REST Response

The following is an example of an Amazon MQ REST response (and its headers) which acknowledges the creation of the new broker:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 250
Connection: keep-alive
Date: Wed, 28 Nov 2017 12:00:00 GMT
X-Amzn-RequestId: a12bc345-67de-89f0-g12h-345ij6k7l89m
X-Amzn-Trace-Id: sampled=1;root=1-2345a67b-c8defg901hijk2lf3m4nopqr
X-Cache: Miss from cloudfront
Via: 1.1 ab123456cd789ef012g34567890h1i23.cloudfront.net (CloudFront)
X-Amz-Cf-Id: ABCa1D6b2-EcF3dG7e456_fGIgh7JKLMijNO_PQ8RSTUVWX-Y9k0ZA==

{
  "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
  "brokerArn" : "arn:aws:mq:us-east-2:123456789012:broker:MyBroker:b-1234a5b6-78cd-901e-2fgh-3i45j6k17819"
}
```

Resources

The Amazon MQ REST API includes the following resources.

Topics

- [Broker](#) (p. 3)
- [Broker Reboot](#) (p. 13)
- [Brokers](#) (p. 14)
- [Configuration](#) (p. 23)
- [Configurations](#) (p. 28)
- [Configuration Revision](#) (p. 34)
- [Configuration Revisions](#) (p. 36)
- [User](#) (p. 39)
- [Users](#) (p. 45)

Broker

A *broker* is a message broker environment running on Amazon MQ. It is the basic building block of Amazon MQ. For more information, see [Broker](#) in the *Amazon MQ Developer Guide*.

URI

`/v1/brokers/broker-id`

HTTP Methods

DELETE

Deletes a broker.

Note

This API is asynchronous.

Path

Name	Type	Description
<i>broker-id</i>	string	The name of the broker. This value must be unique in your AWS account, 1-50 characters long, must contain only letters, numbers, dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.

Response

Status Code	Schema	Description
200	DeleteBrokerOutput (p. 12)	HTTP Status Code 200: OK.

GET

Returns information about the specified broker.

Path

Name	Type	Description
<i>broker-id</i>	string	The name of the broker. This value must be unique in your AWS account, 1-50 characters long, must contain only letters, numbers, dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.

Response

Status Code	Schema	Description
200	DescribeBrokerOutput (p. 8)	HTTP Status Code 200: OK.

PUT

Adds a pending configuration change to a broker.

Body

Name	Type	Description
UpdateBrokerInput	UpdateBrokerInput (p. 7)	Updates the broker using the specified properties.

Path

Name	Type	Description
<i>broker-id</i>	string	The name of the broker. This value must be unique in your AWS account, 1-50 characters long, must contain only letters, numbers, dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.

Response

Status Code	Schema	Description
200	UpdateBrokerOutput (p. 12)	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 12)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 12)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 12)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
409	Error (p. 12)	HTTP Status Code 409: Conflict. Concurrent broker update detected. Retrying your request might resolve the issue.
500	Error (p. 12)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Request Schemas

Example UpdateBrokerInput

```
{
  "logs": {
    "general": true,
    "audit": false
  },
  "configuration": {
    "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
    "revision": 3
  }
}
```

Response Schemas

Example DescribeBrokerOutput

```
{
  "brokerArn": "arn:aws:mq:us-east-2:123456789012:broker:MyBroker:b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "brokerId": "b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "brokerName": "MyBroker",
  "brokerState": "CREATION_IN_PROGRESS",
  "engineType": "ActiveMQ",
  "engineVersion": "5.15.0",
  "pendingEngineVersion": "5.15.6",
}
```

```

    "hostInstanceType": "mq.m5.large",
    "publiclyAccessible": true,
    "autoMinorVersionUpgrade": false,
    "deploymentMode": "ACTIVE_STANDBY_MULTI_AZ",
    "subnetIds": [
        "subnet-12a3b45c",
        "subnet-67d8e90f"
    ],
    "securityGroups": [
        "sg-a1b234cd",
        "sg-e5f678gh"
    ],
    "brokerInstances": [{
        "consoleURL": "https://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:8162",
        "endpoints": [
            "ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:61617",
            "amqp+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:5671",
            "stomp+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:61614",
            "mqtt+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:8883",
            "wss://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-1.mq.us-east-2.amazonaws.com:61619"
        ]
    }, {
        "consoleURL": "https://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:8162",
        "endpoints": [
            "ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:61617",
            "amqp+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:5671",
            "stomp+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:61614",
            "mqtt+ssl://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:8883",
            "wss://b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2.mq.us-east-2.amazonaws.com:61619"
        ]
    }],
    "maintenanceWindowStartTime": {
        "timeOfDay": "13:00",
        "dayOfWeek": "SUNDAY",
        "timeZone": "UTC"
    },
    "logs": {
        "general": true,
        "generalLogGroup": "/aws/amazonmq/broker/b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2/general",
        "audit": true,
        "auditLogGroup": "/aws/amazonmq/broker/b-1234a5b6-78cd-901e-2fgh-3i45j6k178l9-2/audit",
        "pending": {
            "general": true,
            "audit": false
        }
    },
    "configurations": {
        "pending": {
            "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
            "revision": 3
        },
        "history": [{

```

```
        "id": "c-1987k6j5-48ih-321g-0fed-9c87b6a54512",
        "revision": 2
      }, {
        "id": "c-9876a5b4-32cd-101e-2fgh-3i45j6k17819",
        "revision": 1
      }
    ],
    "users": [{
      "username": "jane.doe"
    }, {
      "username": "paolo.santos"
    }],
    "created": "2017-11-28T01:23:45.678Z"
  }
}
```

Example UpdateBrokerOutput

```
{
  "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
  "logs": {
    "general": true,
    "audit": false
  },
  "configuration": {
    "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
    "revision": 3
  }
}
```

Example DeleteBrokerOutput

```
{
  "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819"
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

UpdateBrokerInput

Attribute	Type	Description
autoMinorVersionUpgrade	Boolean	Enables automatic upgrades to new minor versions for brokers, as Apache releases the versions. The automatic upgrades occur during the maintenance window of the broker or after a manual broker reboot.
configuration	ConfigurationId (p. 8)	A list of information about the configuration.

Attribute	Type	Description
engineVersion	enum	The version of the broker engine. Possible values: 5.15.6, 5.15.0.
logs	Logs (p. 20)	Enables Amazon CloudWatch logging for brokers.

ConfigurationId

Attribute	Type	Description
id	string	Required The unique ID that Amazon MQ generates for the configuration.
revision	integer	The revision number of the configuration.

Logs

Attribute	Type	Description
audit	Boolean	Enables audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged.
general	Boolean	Enables general logging.

DescribeBrokerOutput

Attribute	Type	Description
autoMinorVersionUpgrade	Boolean	Required Enables automatic upgrades to new minor versions for brokers, as Apache releases the versions. The automatic upgrades occur during the maintenance window of the broker or after a manual broker reboot.
brokerArn	string	The Amazon Resource Name (ARN) of the broker.
brokerId	string	The unique ID that Amazon MQ generates for the broker.
brokerInstances	array	A list of information about allocated brokers.
brokerName	string	The name of the broker. This value must be unique in your AWS

Attribute	Type	Description
		account, 1-50 characters long, must contain only letters, numbers, dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.
brokerState	enum	The status of the broker. Possible values: CREATION_IN_PROGRESS, CREATION_FAILED, DELETION_IN_PROGRESS, RUNNING, REBOOT_IN_PROGRESS
configurations	Configurations (p. 10)	The list of all revisions for the specified configuration.
created	string (date-time)	The time when the broker was created.
deploymentMode	enum	Required The deployment mode of the broker. Possible values: SINGLE_INSTANCE, ACTIVE_STANDBY_MULTI_AZ SINGLE_INSTANCE creates a single-instance broker in a single Availability Zone. ACTIVE_STANDBY_MULTI_AZ creates an active/standby broker for high availability.
engineType	enum	Required The type of broker engine. Note Currently, Amazon MQ supports only ACTIVEMQ.
engineVersion	enum	The version of the broker engine. Possible values: 5.15.6, 5.15.0.
hostInstanceType	enum	The broker's instance type. Possible values: mq.t2.micro, mq.m5.large, mq.m5.xlarge, mq.m5.2xlarge, mq.m5.4xlarge, mq.m4.large
logs	LogsSummary (p. 11)	The list of information about logs currently enabled and pending to be deployed for the specified broker.

Attribute	Type	Description
<code>maintenanceWindowStartTime</code>	WeeklyStartTime (p. 11)	The parameters that determine the <code>WeeklyStartTime</code> .
<code>pendingEngineVersion</code>	string	The version of the broker engine to upgrade to.
<code>publiclyAccessible</code>	Boolean	Required Enables connections from applications outside of the VPC that hosts the broker's subnets.
<code>securityGroups</code>	array	Required The list of rules (1 minimum, 125 maximum) that authorize connections to brokers.
<code>subnetIds</code>	array	The list of groups (2 maximum) that define which subnets and IP ranges the broker can use from different Availability Zones. A <code>SINGLE_INSTANCE</code> deployment requires one subnet (for example, the default subnet). An <code>ACTIVE_STANDBY_MULTI_AZ</code> deployment requires two subnets.
<code>users</code>	array	The list of all ActiveMQ usernames for the specified broker.

BrokerInstance

Attribute	Type	Description
<code>consoleURL</code>	string	The URL of the broker's ActiveMQ Web Console .
<code>endpoints</code>	array	The broker's wire-level protocol endpoints.
<code>ipAddress</code>	string	The IP address of the Elastic Network Interface (ENI) attached to the broker.

Configurations

Attribute	Type	Description
<code>current</code>	ConfigurationId (p. 8)	The current configuration of the broker.
<code>history</code>	array	The history of configurations applied to the broker.

Attribute	Type	Description
pending	ConfigurationId (p. 8)	The pending configuration of the broker.

LogsSummary

Attribute	Type	Description
audit	Boolean	Enables audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged.
auditLogGroup	string	The location of the CloudWatch Logs log group where audit logs are sent.
general	Boolean	Enables general logging.
generalLogGroup	string	The location of the CloudWatch Logs log group where general logs are sent.
pending	PendingLogs (p. 11)	The list of information about logs pending to be deployed for the specified broker.

PendingLogs

Attribute	Type	Description
audit	Boolean	Enables audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged.
general	Boolean	Enables general logging.

WeeklyStartTime

Attribute	Type	Description
dayOfWeek	string	Required The day of the week.
timeOfDay	string	Required The time, in 24-hour format.
timeZone	string	The time zone, UTC by default, in either the Country/City format, or the UTC offset format.

UserSummary

Attribute	Type	Description
pendingChange	enum	The type of change pending for the ActiveMQ user. Possible values: CREATE, UPDATE, DELETE
username	string	Required The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

UpdateBrokerOutput

Attribute	Type	Description
autoMinorVersionUpgrade	Boolean	The new value of automatic upgrades to new minor version for brokers.
brokerId	string	Required The unique ID that Amazon MQ generates for the broker.
configuration	ConfigurationId (p. 8)	The ID of the updated configuration.
engineVersion	enum	The version of the broker engine to upgrade to.
logs	Logs (p. 20)	The list of information about logs to be enabled for the specified broker.

DeleteBrokerOutput

Attribute	Type	Description
brokerId	string	The unique ID that Amazon MQ generates for the broker.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Broker Reboot

To apply a new configuration to a broker, you can *reboot* the broker. In addition, if your broker becomes unresponsive, you can reboot it to recover from a faulty state.

Note

You can reboot only a broker with the `RUNNING` status.

URI

`/v1/brokers/broker-id/reboot`

HTTP Methods

POST

Reboots a broker.

Note

This API is asynchronous.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.

Response

Status Code	Schema	Description
200	None	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 14)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 14)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 14)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
500	Error (p. 14)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Response Schemas

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Brokers

This is a collection of brokers. A *broker* is a message broker environment running on Amazon MQ. It is the basic building block of Amazon MQ. For more information, see [Broker](#) in the *Amazon MQ Developer Guide*.

URI

/v1/brokers

HTTP Methods

GET

Returns a list of all brokers.

Query

Name	Type	Description
maxResults	integer	The maximum number of brokers that Amazon MQ can return per page (20 by default). This value must be an integer from 5 to 100.
nextToken	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave nextToken empty.

Response

Status Code	Schema	Description
200	ListBrokersOutput (p. 21)	HTTP Status Code 200: OK.

POST

Creates a broker.

Note

This API is asynchronous.

To create a broker, you must either use the `AmazonMQFullAccess` IAM policy or include the following EC2 permissions in your IAM policy.

- `ec2:CreateNetworkInterface`

This permission is required to allow Amazon MQ to create an elastic network interface (ENI) on behalf of your account.

- `ec2:CreateNetworkInterfacePermission`

This permission is required to attach the ENI to the broker instance.

- `ec2:DeleteNetworkInterface`
- `ec2:DeleteNetworkInterfacePermission`
- `ec2:DetachNetworkInterface`
- `ec2:DescribeInternetGateways`
- `ec2:DescribeNetworkInterfaces`
- `ec2:DescribeNetworkInterfacePermissions`
- `ec2:DescribeRouteTables`
- `ec2:DescribeSecurityGroups`
- `ec2:DescribeSubnets`
- `ec2:DescribeVpcs`

For more information, see [Create an IAM User and Get Your AWS Credentials](#) and [Never Modify or Delete the Amazon MQ Elastic Network Interface](#) in the *Amazon MQ Developer Guide*.

Body

Name	Type	Description
<code>CreateBrokerInput</code>	CreateBrokerInput (p. 18)	Creates a broker using the specified properties.

Response

Status Code	Schema	Description
200	CreateBrokerOutput (p. 22)	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 22)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
401	Error (p. 22)	HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.
403	Error (p. 22)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
409	Error (p. 22)	HTTP Status Code 409: Conflict. This broker name already exists. Retry your request with another name.
500	Error (p. 22)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Request Schemas

Example CreateBrokerInput

```
{
  "brokerName": "MyBroker",
  "hostInstanceType": "mq.m5.large",
  "engineType": "ActiveMQ",
  "engineVersion": "5.15.6",
  "logs": {
    "general": true,
    "audit": false
  },
  "configuration": {
    "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
    "revision": 3
  },
  "creatorRequestId": "kji10h98-76g5-43f2-10ed-9cb8a7654321",
  "deploymentMode": "ACTIVE_STANDBY_MULTI_AZ",
  "publiclyAccessible": true,
  "subnetIds": [
    "subnet-12a3b45c",
    "subnet-67d8e90f"
  ],
  "securityGroups": [
    "sg-a1b234cd",
    "sg-e5f678gh"
  ],
  "autoMinorVersionUpgrade": true,
  "maintenanceWindowStartTime": {
    "timeOfDay": "13:00",
```

```

        "dayOfWeek": "SUNDAY",
        "timeZone": "UTC"
    },
    "users": [{
        "password": "MyPassword456",
        "groups": [
            "admins"
        ],
        "consoleAccess": true,
        "username": "jane.doe"
    }, {
        "password": "MyPassword654",
        "groups": [
            "support"
        ],
        "consoleAccess": true,
        "username": "paolo.santos"
    }
    ]
}

```

Response Schemas

Example ListBrokersOutput

```

{
    "nextToken":
    "eyJEXAMPLEW9uIjojdjEiLCJzZXJpYWxpemVkUGFnZW5hdGlvblRva2VuIjoiaXZlKMGiYdGxialJoZEdFaU9uc2liROZ6ZEMxelpXV",
    "brokerSummaries": [
        {
            "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
            "brokerArn": "arn:aws:mq:us-east-2:123456789012:broker:MyBroker1:b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
            "brokerState": "RUNNING",
            "brokerName": "MyBroker1",
            "deploymentMode": "SINGLE_INSTANCE",
            "hostInstanceType": "mq.t2.micro",
            "created": "2017-11-28T01:23:45.678Z"
        },
        {
            "brokerId" : "b-9876l5k4-32ji-109h-8gfe-7d65c4b132a1",
            "brokerArn": "arn:aws:mq:us-east-2:123456789012:broker:MyBroker2:b-9876l5k4-32ji-109h-8gfe-7d65c4b132a1",
            "brokerState": "DELETION_IN_PROGRESS",
            "brokerName": "MyBroker2",
            "deploymentMode": "ACTIVE_STANDBY_MULTI_AZ",
            "hostInstanceType": "mq.m5.large",
            "created": "2017-11-29T01:23:45.678Z"
        }
    ]
}

```

Example CreateBrokerOutput

```

{
    "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
    "brokerArn": "arn:aws:mq:us-east-2:123456789012:broker:MyBroker:b-1234a5b6-78cd-901e-2fgh-3i45j6k17819"
}

```

Example Error

```

{

```

```
"errorAttribute": "TheAttributeWhichCausedTheError",
"message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

CreateBrokerInput

Attribute	Type	Description
autoMinorVersionUpgrade	Boolean	Required Enables automatic upgrades to new minor versions for brokers, as Apache releases the versions. The automatic upgrades occur during the maintenance window of the broker or after a manual broker reboot.
brokerName	string	Required The name of the broker. This value must be unique in your AWS account, 1-50 characters long, must contain only letters, numbers, dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.
configuration	ConfigurationId (p. 20)	A list of information about the configuration.
creatorRequestId	string	The unique ID that the requester receives for the created broker. Amazon MQ passes your ID with the API action. Note We recommend using a Universally Unique Identifier (UUID) for the <code>creatorRequestId</code> . You may omit the <code>creatorRequestId</code> if your application doesn't require idempotency.
deploymentMode	enum	Required The deployment mode of the broker. Possible values: SINGLE_INSTANCE, ACTIVE_STANDBY_MULTI_AZ SINGLE_INSTANCE creates a single-instance broker in

Attribute	Type	Description
		a single Availability Zone. <code>ACTIVE_STANDBY_MULTI_AZ</code> creates an active/standby broker for high availability.
<code>engineType</code>	enum	Required The type of broker engine. Note Currently, Amazon MQ supports only <code>ACTIVEMQ</code> .
<code>engineVersion</code>	enum	Required The version of the broker engine. Possible values: 5.15.6, 5.15.0.
<code>hostInstanceType</code>	enum	Required The broker's instance type. Possible values: <code>mq.t2.micro</code> , <code>mq.m5.large</code> , <code>mq.m5.xlarge</code> , <code>mq.m5.2xlarge</code> , <code>mq.m5.4xlarge</code> , <code>mq.m4.large</code>
<code>logs</code>	Logs (p. 20)	Enables Amazon CloudWatch logging for brokers.
<code>maintenanceWindowStartTime</code>	WeeklyStartTime (p. 20)	The parameters that determine the <code>WeeklyStartTime</code> .
<code>publiclyAccessible</code>	Boolean	Required Enables connections from applications outside of the VPC that hosts the broker's subnets.
<code>securityGroups</code>	array	The list of rules (1 minimum, 125 maximum) that authorize connections to brokers.
<code>subnetIds</code>	array	The list of groups (2 maximum) that define which subnets and IP ranges the broker can use from different Availability Zones. A <code>SINGLE_INSTANCE</code> deployment requires one subnet (for example, the default subnet). An <code>ACTIVE_STANDBY_MULTI_AZ</code> deployment requires two subnets.

Attribute	Type	Description
users	array	Required The list of ActiveMQ users (persons or applications) who can access queues and topics. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

ConfigurationId

Attribute	Type	Description
id	string	Required The unique ID that Amazon MQ generates for the configuration.
revision	integer	The revision number of the configuration.

Logs

Attribute	Type	Description
audit	Boolean	Enables audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged.
general	Boolean	Enables general logging.

WeeklyStartTime

Attribute	Type	Description
dayOfWeek	string	Required The day of the week.
timeOfDay	string	Required The time, in 24-hour format.
timeZone	string	The time zone, UTC by default, in either the Country/City format, or the UTC offset format.

User

Attribute	Type	Description
consoleAccess	Boolean	Enables access to the the ActiveMQ Web Console for the ActiveMQ user.
groups	array	The list of groups (20 maximum) to which the ActiveMQ user belongs. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.
password	string (password)	Required The password of the ActiveMQ user. This value must be at least 12 characters long, must contain at least 4 unique characters, and must not contain commas.
username	string	Required The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

ListBrokersOutput

Attribute	Type	Description
brokerSummaries	array	A list of information about all brokers.
nextToken	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave nextToken empty.

BrokerSummary

Attribute	Type	Description
brokerArn	string	The Amazon Resource Name (ARN) of the broker.
brokerId	string	The unique ID that Amazon MQ generates for the broker.
brokerName	string	The name of the broker. This value must be unique in your AWS account, 1-50 characters long, must contain only letters, numbers,

Attribute	Type	Description
		dashes, and underscores, and must not contain whitespaces, brackets, wildcard characters, or special characters.
brokerState	enum	The status of the broker. Possible values: CREATION_IN_PROGRESS, CREATION_FAILED, DELETION_IN_PROGRESS, RUNNING, REBOOT_IN_PROGRESS
created	string (date-time)	The time when the broker was created.
deploymentMode	enum	Required The deployment mode of the broker. Possible values: SINGLE_INSTANCE, ACTIVE_STANDBY_MULTI_AZ SINGLE_INSTANCE creates a single-instance broker in a single Availability Zone. ACTIVE_STANDBY_MULTI_AZ creates an active/standby broker for high availability.
hostInstanceType	enum	The broker's instance type. Possible values: mq.t2.micro, mq.m5.large, mq.m5.xlarge, mq.m5.2xlarge, mq.m5.4xlarge, mq.m4.large

CreateBrokerOutput

Attribute	Type	Description
brokerArn	string	The Amazon Resource Name (ARN) of the broker.
brokerId	string	The unique ID that Amazon MQ generates for the broker.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Configuration

A *configuration* contains all of the settings for your ActiveMQ broker, in XML format. For more information, see [Configuration](#) and [Amazon MQ Broker Configuration Parameters](#) in the *Amazon MQ Developer Guide*.

You can create a configuration before creating any brokers. You can then apply the configuration to one or more brokers.

Important

Making changes to a configuration does not apply the changes to the broker immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/configurations/*configuration-id*

HTTP Methods

GET

Returns information about the specified configuration.

Path

Name	Type	Description
<i>configuration-id</i>	string	The unique ID that Amazon MQ generates for the configuration.

Response

Status Code	Schema	Description
200	Configuration (p. 26)	HTTP Status Code 200: OK.

PUT

Updates the specified configuration.

Body

Name	Type	Description
UpdateConfigurationInput	UpdateConfigurationInput (p. 26)	Updates the specified configuration.

Path

Name	Type	Description
<i>configuration-id</i>	string	The unique ID that Amazon MQ generates for the configuration.

Status Code	Schema	Description
200	<code>UpdateConfigurationOutput</code> (p. 177)	HTTP Status Code 200: OK.

Errors

Status Code	Schema	Description
400	Error (p. 28)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 28)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 28)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
409	Error (p. 28)	HTTP Status Code 409: Conflict. Concurrent update to configuration. Retry to create a new revision.
500	Error (p. 28)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Request Schemas

```
{
  "description": "My basic configuration for working with an ActiveMQ broker.",
  "data":
  "lciEXAMPLEB4bWxucz0iaHR0cDovL2FjdGl2ZW1xLmFwYWNoZS5vcmcvc2NoZW1hL2NvcmljaGICAgICAgICAgHNPo"
}
```

```
{
  "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "name": "MyConfiguration",
  "arn": "arn:aws:mq:us-east-2:123456789012:configuration:MyConfiguration:c-987615k4-32ji-109h-8gfe-7d65c4b132a1",

```

```
{
  "engineType": "ActiveMQ",
  "engineVersion": "5.15.6",
  "description": "My basic configuration for working with an ActiveMQ broker.",
  "created": "2017-11-28T01:23:45.678Z",
  "latestRevision": {
    "revision": 3,
    "description": "This is the third revision of the configuration. It improves application functionality.",
    "created": "2017-11-28T01:23:45.678Z"
  }
}
```

Example UpdateConfigurationOutput

```
{
  "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "name": "MyConfiguration",
  "arn": "arn:aws:mq:us-east-2:123456789012:configuration:MyConfiguration:c-9876l5k4-32ji-109h-8gfe-7d65c4b132a1",
  "created": "2017-11-28T01:23:45.678Z",
  "latestRevision": {
    "revision": 4,
    "description": "This is the fourth revision of the configuration. It improves application functionality.",
    "created": "2017-11-29T01:23:45.678Z"
  },
  "warnings": [{
    "elementName": "broker",
    "attributeName": "attrib",
    "reason": "DISALLOWED_ATTRIBUTE_REMOVED"
  }, {
    "elementName": "broker",
    "attributeName": "schemaLocation",
    "reason": "DISALLOWED_ATTRIBUTE_REMOVED"
  }, {
    "elementName": "element",
    "reason": "DISALLOWED_ELEMENT_REMOVED"
  }]
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

UpdateConfigurationInput

Attribute	Type	Description
data	string (byte)	Required The base64-encoded XML configuration.
description	string	The description of the configuration.

Configuration

Attribute	Type	Description
arn	string	Required The ARN of the configuration.
created	string (date-time)	Required The date and time of the configuration revision.
description	string	Required The description of the configuration.
engineType	enum	Required The type of broker engine. Note Currently, Amazon MQ supports only <code>ACTIVEMQ</code> .
engineVersion	enum	Required The version of the broker engine.
id	string	Required The unique ID that Amazon MQ generates for the configuration.
latestRevision	ConfigurationRevision (p. 26)	Required The latest revision of the configuration.
name	string	Required The name of the configuration. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (<code>- . _ ~</code>). This value must be 1-150 characters long.

ConfigurationRevision

Attribute	Type	Description
created	string (date-time)	Required The date and time of the configuration revision.
description	string	The description of the configuration revision.
revision	integer	Required

Attribute	Type	Description
		The revision number of the configuration.

UpdateConfigurationOutput

Attribute	Type	Description
arn	string	Required The Amazon Resource Name (ARN) of the configuration.
created	string (date-time)	Required The date and time of the configuration.
id	string	Required The unique ID that Amazon MQ generates for the configuration.
latestRevision	ConfigurationRevision (p. 26)	The latest revision of the configuration.
name	string	Required The name of the configuration. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 1-150 characters long.
warnings	array	The list of the first 20 warnings about the configuration XML elements or attributes that were sanitized.

SanitizationWarning

Attribute	Type	Description
attributeName	string	The name of the XML attribute that has been sanitized.
elementName	string	The name of the XML element that has been sanitized.
reason	enum	Required The reason for which the XML elements or attributes were sanitized.

Attribute	Type	Description
		Possible values: DISALLOWED_ELEMENT_REMOVED, DISALLOWED_ATTRIBUTE_REMOVED, INVALID_ATTRIBUTE_VALUE_REMOVED DISALLOWED_ELEMENT_REMOVED shows that the provided element isn't allowed and has been removed. DISALLOWED_ATTRIBUTE_REMOVED shows that the provided attribute isn't allowed and has been removed. INVALID_ATTRIBUTE_VALUE_REMOVED shows that the provided value for the attribute isn't allowed and has been removed.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Configurations

This is a collection of configurations. A *configuration* contains all of the settings for your ActiveMQ broker, in XML format. For more information, see [Configuration](#) and [Amazon MQ Broker Configuration Parameters](#) in the *Amazon MQ Developer Guide*.

You can create a configuration before creating any brokers. You can then apply the configuration to one or more brokers.

Important

Making changes to a configuration does not apply the changes to the broker immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/configurations

HTTP Methods

GET

Returns a list of all configurations.

Query

Name	Type	Description
maxResults	integer	The maximum number of configurations that Amazon MQ can

Name	Type	Description
		return per page (20 by default). This value must be an integer from 5 to 100.
nextToken	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave nextToken empty.

Response

Status Code	Schema	Description
200	ListConfigurationsOutput (p. 34)	HTTP Status Code 200: OK.

POST

Creates a new configuration for the specified configuration name. Amazon MQ uses the default configuration (the engine type and version).

Body

Name	Type	Description
CreateConfigurationInput	CreateConfigurationInput (p. 34)	Creates a new configuration for the specified configuration name. Amazon MQ uses the default configuration (the engine type and version).

Response

Status Code	Schema	Description
200	CreateConfigurationOutput (p. 34)	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 34)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 34)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
409	Error (p. 34)	HTTP Status Code 409: Conflict. This configuration name already exists.

Status Code	Schema	Description
		Retry your request with another configuration name.
500	Error (p. 34)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Request Schemas

Example CreateConfigurationInput

```
{
  "name": "MyConfiguration",
  "engineType": "ActiveMQ",
  "engineVersion": "5.15.6"
}
```

Response Schemas

Example ListConfigurationsOutput

```
{
  "configurations": [{
    "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
    "name": "MyConfigurationDevelopment",
    "arn": "arn:aws:mq:us-east-2:123456789012:configuration:MyConfigurationDevelopment:c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
    "engineType": "ActiveMQ",
    "engineVersion": "5.15.6",
    "description": "My configuration for programming for an ActiveMQ broker.",
    "created": "2017-11-28T01:23:45.678Z",
    "latestRevision": {
      "revision": 1,
      "description": "Auto-generated default for MyConfiguration on ActiveMQ 5.15.6.",
      "created": "2017-11-27T01:23:45.678Z"
    }
  }, {
    "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
    "name": "MyConfigurationTesting",
    "arn": "arn:aws:mq:us-east-2:123456789012:configuration:MyConfigurationTesting:c-9876l5k4-32ji-109h-8gfe-7d65c4b132a1",
    "engineType": "ActiveMQ",
    "engineVersion": "5.15.6",
    "description": "My configuration for testing with an ActiveMQ broker.",
    "created": "2017-11-29T01:23:45.678Z",
    "latestRevision": {
      "revision": 3,
      "description": "This is the third revision of a configuration for application testing. It improves application functionality.",
      "created": "2017-11-28T01:23:45.678Z"
    }
  }
],
  "maxResults": 20,
```

```
{
  "nextToken":
    "eyJEXAMPLEW9uIjoidjEiLCJzZXJpYWxpemVhUGFnZW5hdGlvb1Rva2VuIjoiaXZlKMGIydGxialJoZEdFaU9uc2liROZ6ZEMxelpXV"
}
```

Example CreateConfigurationOutput

```
{
  "id": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "name": "MyConfiguration",
  "arn": "arn:aws:mq:us-east-2:123456789012:configuration:MyConfiguration:c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "created": "2017-11-27T01:23:45.678Z",
  "latestRevision": {
    "revision": 3,
    "description": "This is the third revision of the configuration. It improves application functionality.",
    "created": "2017-11-27T01:23:45.678Z"
  }
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

CreateConfigurationInput

Attribute	Type	Description
engineType	enum	Required The type of broker engine. Note Currently, Amazon MQ supports only <code>ACTIVEMQ</code> .
engineVersion	enum	Required The version of the broker engine. Possible values: 5.15.6, 5.15.0.
name	string	Required The name of the configuration. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 1-150 characters long.

ListConfigurationsOutput

Attribute	Type	Description
<code>configurations</code>	array	The list of all revisions for the specified configuration.
<code>maxResults</code>	integer	The maximum number of configurations that Amazon MQ can return per page (20 by default). This value must be an integer from 5 to 100.
<code>nextToken</code>	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave <code>nextToken</code> empty.

Configuration

Attribute	Type	Description
<code>arn</code>	string	Required The ARN of the configuration.
<code>created</code>	string (date-time)	Required The date and time of the configuration revision.
<code>description</code>	string	Required The description of the configuration.
<code>engineType</code>	enum	Required The type of broker engine. Note Currently, Amazon MQ supports only <code>ACTIVEMQ</code> .
<code>engineVersion</code>	enum	Required The version of the broker engine.
<code>id</code>	string	Required The unique ID that Amazon MQ generates for the configuration.
<code>latestRevision</code>	ConfigurationRevision (p. 33)	Required The latest revision of the configuration.
<code>name</code>	string	Required The name of the configuration. This value can contain only alphanumeric

Attribute	Type	Description
		characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 1-150 characters long.

ConfigurationRevision

Attribute	Type	Description
created	string (date-time)	Required The date and time of the configuration revision.
description	string	The description of the configuration revision.
revision	integer	Required The revision number of the configuration.

CreateConfigurationOutput

Attribute	Type	Description
arn	string	Required The Amazon Resource Name (ARN) of the configuration.
created	string (date-time)	Required The date and time of the configuration.
id	string	Required The unique ID that Amazon MQ generates for the configuration.
latestRevision	ConfigurationRevision (p. 33)	The latest revision of the configuration.
name	string	Required The name of the configuration. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 1-150 characters long.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Configuration Revision

To keep track of the changes you make to your configuration, you can create *configuration revisions*. For more information, see [Configuration](#) in the *Amazon MQ Developer Guide*.

Important

Making changes to a configuration does not apply the changes to the broker immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/configurations/*configuration-id*/revisions/*configuration-revision*

HTTP Methods

GET

Returns the specified configuration revision for the specified configuration.

Path

Name	Type	Description
<i>configuration-id</i>	string	The unique ID that Amazon MQ generates for the configuration.
<i>configuration-revision</i>	string	The revision of the configuration.

Response

Status Code	Schema	Description
200	DescribeConfigurationRevision	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 36)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

Status Code	Schema	Description
403	Error (p. 36)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 36)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
500	Error (p. 36)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Response Schemas

Example DescribeConfigurationRevisionOutput

```
{
  "configurationId": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "revision": 1,
  "description": "Auto-generated default for MyConfiguration on ActiveMQ 5.15.6.",
  "data":
  "lc1EEXAMPLEB4bWxucz0iaHR0cDovL2FjdG12ZW1xLmFwYWN0ZS5vcmcvc2NoZW1hL2NvcmluICAgICAgICAgHnOnNjaGVtYUxvYy"
  "created": "2017-11-27T01:23:45.678Z"
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

DescribeConfigurationRevisionOutput

Attribute	Type	Description
configurationId	string	Required The unique ID that Amazon MQ generates for the configuration.
created	string (date-time)	Required The date and time of the configuration.
data	string (byte)	Required The base64-encoded XML configuration.

Attribute	Type	Description
description	string	The description of the configuration.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Configuration Revisions

This is a collection of configuration revisions. To keep track of the changes you make to your configuration, you can create *configuration revisions*. For more information, see [Configuration](#) in the *Amazon MQ Developer Guide*.

Important

Making changes to a configuration does not apply the changes to the broker immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/configurations/*configuration-id*/revisions

HTTP Methods

GET

Returns a list of all revisions for the specified configuration.

Path

Name	Type	Description
<i>configuration-id</i>	string	The unique ID that Amazon MQ generates for the configuration.

Query

Name	Type	Description
maxResults	integer	The maximum number of configurations that Amazon MQ can return per page (20 by default). This value must be an integer from 5 to 100.
nextToken	string	The token that specifies the next page of results Amazon MQ should

Name	Type	Description
		return. To request the first page, leave <code>nextToken</code> empty.

Response

Status Code	Schema	Description
200	ListConfigurationRevisionsOutput (HTTP Status)	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 38)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 38)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 38)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
500	Error (p. 38)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Response Schemas

Example `ListConfigurationRevisionsOutput`

```
{
  "configurationId": "c-1234a5b6-78cd-901e-2fgh-3i45j6k178l9",
  "revisions": [{
    "revision": 1,
    "description": "Auto-generated default for MyConfiguration on ActiveMQ 5.15.6.",
    "created": "2017-11-28T01:23:45.678Z"
  }, {
    "revision": 2,
    "description": "This is the second revision of a configuration for application development. It improves application functionality.",
    "created": "2017-11-29T01:23:45.678Z"
  }],
  "maxResults": 20,
  "nextToken": "eyJEXAMPLEW9uIjoidjEiLCJzZXJpYWxpemVkUGFnZW5hdGlvb1Rva2VuIjoizXlKMGIydGxia1JoZEdFaU9uc2liR0Z6ZEMxelpXV"
}
```

```
}

```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

ListConfigurationRevisionsOutput

Attribute	Type	Description
configurationId	string	The unique ID that Amazon MQ generates for the configuration.
maxResults	integer	The maximum number of configuration revisions that can be returned per page (20 by default). This value must be an integer from 5 to 100.
nextToken	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave nextToken empty.
revisions	array	The list of all revisions for the specified configuration.

ConfigurationRevision

Attribute	Type	Description
created	string (date-time)	Required The date and time of the configuration revision.
description	string	The description of the configuration revision.
revision	integer	Required The revision number of the configuration.

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.

Attribute	Type	Description
message	string	The explanation of the error.

User

An ActiveMQ *user* is a person or an application that can access the queues and topics of an ActiveMQ broker. For more information, see [User](#) in the *Amazon MQ Developer Guide*.

You can configure to have specific permissions. For example, you can allow some users to access the [ActiveMQ Web Console](#).

A user can belong to a *group*. You can configure which users belong to which groups and which groups have permission to send to, receive from, and administer specific queues and topics.

Important

Making changes to a user does not apply the changes to the user immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/brokers/*broker-id*/users/*username*

HTTP Methods

DELETE

Deletes an ActiveMQ user.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.
<i>username</i>	string	The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

Response

Status Code	Schema	Description
200	None	HTTP Status Code 200: OK.

GET

Returns information about an ActiveMQ user.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.
<i>username</i>	string	The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

Response

Status Code	Schema	Description
200	DescribeUserOutput (p. 43)	HTTP Status Code 200: OK.

POST

Creates an ActiveMQ user.

Body

Name	Type	Description
CreateUserInput	CreateUserInput (p. 43)	Creates a new ActiveMQ user.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.
<i>username</i>	string	The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

Response

Status Code	Schema	Description
200	None	HTTP Status Code 200: OK.

PUT

Updates the information for an ActiveMQ user.

Body

Name	Type	Description
UpdateUserInput	UpdateUserInput (p. 43)	Updates the information for an ActiveMQ user.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.
<i>username</i>	string	Required The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

Response

Status Code	Schema	Description
200	None	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 44)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 44)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 44)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
409	Error (p. 44)	HTTP Status Code 409: Conflict. Retrying your request might resolve the issue.
500	Error (p. 44)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Request Schemas

Example UpdateUserInput

```
{
  "password": "MyPassword789",
  "consoleAccess": false,
  "groups": [
    "support"
  ]
}
```

Example CreateUserInput

```
{
  "password": "MyPassword456",
  "consoleAccess": true,
  "groups": [
    "admins"
  ]
}
```

Response Schemas

Example DescribeUserOutput

```
{
  "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
  "username": "jane.doe",
  "consoleAccess": true,
  "groups": [
    "support"
  ],
  "pending": {
    "pendingChange": "CREATE",
    "consoleAccess": true,
    "groups": [
      "admins"
    ]
  }
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

UpdateUserInput

Attribute	Type	Description
consoleAccess	Boolean	Enables access to the the ActiveMQ Web Console for the ActiveMQ user.
groups	array	The list of groups (20 maximum) to which the ActiveMQ user belongs. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.
password	string (password)	The password of the user. This value must be at least 12 characters long, must contain at least 4 unique characters, and must not contain commas.

CreateUserInput

Attribute	Type	Description
consoleAccess	Boolean	Enables access to the the ActiveMQ Web Console for the ActiveMQ user.
groups	array	The list of groups (20 maximum) to which the ActiveMQ user belongs. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.
password	string (password)	Required The password of the user. This value must be at least 12 characters long, must contain at least 4 unique characters, and must not contain commas.

DescribeUserOutput

Attribute	Type	Description
brokerId	string	Required The unique ID that Amazon MQ generates for the broker.

Attribute	Type	Description
consoleAccess	Boolean	Enables access to the the ActiveMQ Web Console for the ActiveMQ user.
groups	array	The list of groups (20 maximum) to which the ActiveMQ user belongs. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.
pending	UserPendingChanges (p. 44)	The status of the changes pending for the ActiveMQ user.
username	string	Required The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

UserPendingChanges

Attribute	Type	Description
consoleAccess	Boolean	Enables access to the the ActiveMQ Web Console for the ActiveMQ user.
groups	array	The list of groups (20 maximum) to which the ActiveMQ user belongs. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.
pendingChange	enum	Required The type of change pending for the ActiveMQ user. Possible values: CREATE, UPDATE, DELETE

Error

Attribute	Type	Description
errorAttribute	string	The attribute which caused the error.
message	string	The explanation of the error.

Users

This is a collection of ActiveMQ users for the specified broker. An ActiveMQ *user* is a person or an application that can access the queues and topics of an ActiveMQ broker. For more information, see [User](#) in the *Amazon MQ Developer Guide*.

You can configure to have specific permissions. For example, you can allow some users to access the [ActiveMQ Web Console](#).

A user can belong to a *group*. You can configure which users belong to which groups and which groups have permission to send to, receive from, and administer specific queues and topics.

Important

Making changes to a user does not apply the changes to the user immediately. To apply your changes, you must wait for the next maintenance window or reboot the broker.

URI

/v1/brokers/*broker-id*/users

HTTP Methods

GET

Returns a list of all ActiveMQ users.

Path

Name	Type	Description
<i>broker-id</i>	string	The unique ID that Amazon MQ generates for the broker.

Query

Name	Type	Description
maxResults	integer	The maximum number of ActiveMQ users that can be returned per page (20 by default). This value must be an integer from 5 to 100.
nextToken	string	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave nextToken empty.

Response

Status Code	Schema	Description
200	ListUsersOutput (p. 46)	HTTP Status Code 200: OK.

Errors

Errors

Status Code	Schema	Description
400	Error (p. 47)	HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.
403	Error (p. 47)	HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.
404	Error (p. 47)	HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.
500	Error (p. 47)	HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

Schemas

Response Schemas

Example ListUsersOutput

```
{
  "brokerId" : "b-1234a5b6-78cd-901e-2fgh-3i45j6k17819",
  "users": [{
    "username": "jane.doe",
    "pendingChange": "CREATE"
  }, {
    "username": "paolo.santos"
  }],
  "maxResults": 20,
  "nextToken":
    "eyJEXAMPLEW9uIjoidjEiLCJzZXJpYWxpemVkUGFnZW5hdGlvblRva2VuIjoiaXZlKMGiYdGxia1JoZEdFaU9uc2liROZ6ZEMxelpXV"
}
```

Example Error

```
{
  "errorAttribute": "TheAttributeWhichCausedTheError",
  "message": "This is the description of the error and the steps to resolve the issue."
}
```

Attributes

ListUsersOutput

Attribute	Type	Description
brokerId	string	Required

Attribute	Type	Description
		The unique ID that Amazon MQ generates for the broker.
<code>maxResults</code>	<code>integer</code>	Required The maximum number of ActiveMQ users that can be returned per page (20 by default). This value must be an integer from 5 to 100.
<code>nextToken</code>	<code>string</code>	The token that specifies the next page of results Amazon MQ should return. To request the first page, leave <code>nextToken</code> empty.
<code>users</code>	<code>array</code>	Required The list of all ActiveMQ usernames for the specified broker.

UserSummary

Attribute	Type	Description
<code>pendingChange</code>	<code>enum</code>	The type of change pending for the ActiveMQ user. Possible values: CREATE, UPDATE, DELETE
<code>username</code>	<code>string</code>	Required The username of the ActiveMQ user. This value can contain only alphanumeric characters, dashes, periods, underscores, and tildes (- . _ ~). This value must be 2-100 characters long.

Error

Attribute	Type	Description
<code>errorAttribute</code>	<code>string</code>	The attribute which caused the error.
<code>message</code>	<code>string</code>	The explanation of the error.