Exercise Two

1) SELECT COUNT (*) As total_employees
FROM employees;

Outcome 1

Total_Employees
10

2. SUM () Function
SELECT sum (salary) As total_IT salary
FROM employees
WHERE department = 'IT';

3 SELECT AVG (salary) As average_hr_salary
FROM employees
WHERE department = 'HR';

2

~~total_IT_salary~~
~~220000~~

Outcome 3

average_hr_salary
49 500

Powered by CamScanner

4) SELECT MAX (salary) As highest_salary,
MIN (salary) As lowest_salary
FROM employees;

Outcome 3 4

Highest_salary	lowest_salary
62 000	48 000

5) SELECT department, SUM (salary) As
total_department_salary
FROM employees
GROUP BY department;

6) SELECT city, COUNT (*) As employee_c
FROM employees GROUP BY CITY

Outcome 5

department	total_departmen_salary
IT	22 0000
HR	99 000
Finance	119 000
Marketing	105000

Powered by CamScanner

Outcome 6

City	employee_count
New York	2
Chicago	3
Los Angel	2
San Francisco	2
Houston	1

7) SELECT department, AVG (salary) As avg_salary
FROM employees
GROUP BY department
ORDER BY avg_salary DESC;

Outcome 7

department	avg_salary
Finance	59 500
IT	55 000
Marketing	52 5000
HR	49 500

Powered by CamScanner

8) SELECT department, SUM (salary) As total_salary
FROM employees
GROUP BY department
HAVING SUM (salary) > 10 000

Outcome 8.

department	total_salary
IT	22 000
Finance	119 000
Marketing	10 5000

9) SELECT city, COUNT(*) As employee_count
FROM employees
GROUP BY city HAVING COUNT(*) >
ORDER BY employees_count DESC;

Outcome 9

City	employee_count
Chicago	3
New York	2
Los Angeles	2
San Francisco	2

Powered by CamScanner

10) SELECT department, Avg (salary) As highest_avg_salary
FROM employees
GROUP BY department
ORDER BY highest_avg_salary DESC
LIMIT 1;

Outcome 10

department	highest_avg_salary
Finance	59 500

Powered by CamScanner