

學號:A106260082

姓名:姜品君

(請依照規定)貼上執行程式碼及執行結果。

詳見: R 程式作業繳交方式

<http://www.hmwu.idv.tw/web/teaching/doc/R-how-homework.pdf>

```
> #ex2.30(a)
```

```
> ans.1 <- read.delim("answer.txt")
```

```
> first5.records <- head(ans.1,5)
```

```
> first5.records
```

	Student	V1	V2	V3	V4	V5	V6	V7	V8	V9	V10
1	s1	C	D	D	A	D	A	B	C	C	B
2	s2	B	D	B	D	D	A	C	D	B	B
3	s3	B	A	A	B	D	A	C	B	C	B
4	s4	B	D	B	A	B	C	C	D	C	B
5	s5	B	D	D	D	A	C	C	D	A	B

```
> #ex2.30(b)
```

```
> cans <- c('B', 'D', 'B', 'D', 'D', 'A', 'C', 'D', 'C', 'B')
```

```
> pans <- c('A', 'D', 'B', 'D', 'B', 'A', 'B', 'D', 'C', 'B')
```

```
> correct.item <- which(pans == cans)
```

```
> n.correct <- 10*length(correct.item)
```

```
> n.correct
```

```
[1] 70
```

```
> #ex2.30(c)
```

```
> v1.1 <-ifelse(ans.1$V1 == cans[1],1,0)
```

```
> v2.1 <-ifelse(ans.1$V2 == cans[2],1,0)
```

```
> v3.1 <-ifelse(ans.1$V3 == cans[3],1,0)
```

```
> v4.1 <-ifelse(ans.1$V4 == cans[4],1,0)
```

```
> v5.1 <-ifelse(ans.1$V5 == cans[5],1,0)
```

```
> v6.1 <-ifelse(ans.1$V6 == cans[6],1,0)
```

```
> v7.1 <-ifelse(ans.1$V7 == cans[7],1,0)
```

```
> v8.1 <-ifelse(ans.1$V8 == cans[8],1,0)
```

```
> v9.1 <-ifelse(ans.1$V9 == cans[9],1,0)
```

```

> v10.1 <-ifelse(ans.1$V10 == cans[10],1,0)
> ans.3 <-
data.frame(ans.1$Student,v1.1,v2.1,v3.1,v4.1,v5.1,v6.1,v7.1,v8.1,v9.1,v10.1)
> sans <-
10*(ans.3$v1.1+ans.3$v2.1+ans.3$v3.1+ans.3$v4.1+ans.3$v5.1+ans.3$v6.1+ans.3$v
7.1+ans.3$v8.1+ans.3$v9.1+ans.3$v10.1)
> ans.4 <- data.frame(ans.3,sans)
> table(ans.4$sans)

```

```

  0  10  20  30  40  50  60  70  80  90 100
3  10   9  11  19  23  28  40  30  12   7

```

```

>

```

```

> #ex2.30(d)
> top <- ans.4$ans.1.Student[which(ans.4$sans > 100*0.75)]
> top
[1] "s2"   "s12"  "s16"  "s19"  "s20"  "s21"  "s24"  "s25"  "s27"  "s31"
"s41"  "s43"  "s44"
[14] "s47"  "s50"  "s52"  "s54"  "s55"  "s66"  "s69"  "s73"  "s79"  "s80"
"s81"  "s86"  "s95"
[27] "s96"  "s108" "s110" "s112" "s123" "s125" "s128" "s129" "s131" "s135" "s136"
"s139" "s143"
[40] "s146" "s152" "s157" "s159" "s165" "s171" "s187" "s189" "s190" "s192"
> low <- ans.4$ans.1.Student[which(ans.4$sans < 100*0.25)]
> low
[1] "s17"  "s32"  "s65"  "s71"  "s74"  "s82"  "s87"  "s90"  "s97"  "s105"
"s107" "s120" "s132"
[14] "s142" "s160" "s161" "s163" "s168" "s169" "s174" "s177" "s178"
> n.top <- length(top)
> n.top
[1] 49
> n.low <- length(low)
> n.low
[1] 22
> #library(dplyr)
> #arans <- arrange(ans.4,sans)
>

```

```

> #ex2.30(e)
> #試計算高分組及低分組在每題答對的人數百分比, 記為 PH 及 PL。
>
> #高分組
> top1 <- round(sum(ans.4$v1.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top2 <- round(sum(ans.4$v2.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top3 <- round(sum(ans.4$v3.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top4 <- round(sum(ans.4$v4.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top5 <- round(sum(ans.4$v5.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top6 <- round(sum(ans.4$v6.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top7 <- round(sum(ans.4$v7.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top8 <- round(sum(ans.4$v8.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top9 <- round(sum(ans.4$v9.1[which(ans.4$sans > 100*0.75)])/n.top,2)
> top10 <- round(sum(ans.4$v10.1[which(ans.4$sans > 100*0.75)])/n.top,2)
>
> PH <- c(top1,top2,top3,top4,top5,top6,top7,top8,top9,top10)
> PH
[1] 0.88 0.88 0.78 0.80 0.88 0.82 0.96 0.76 0.86 0.94
> #低分組
> low1 <- round(sum(ans.4$v1.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low2 <- round(sum(ans.4$v2.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low3 <- round(sum(ans.4$v3.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low4 <- round(sum(ans.4$v4.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low5 <- round(sum(ans.4$v5.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low6 <- round(sum(ans.4$v6.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low7 <- round(sum(ans.4$v7.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low8 <- round(sum(ans.4$v8.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low9 <- round(sum(ans.4$v9.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> low10 <- round(sum(ans.4$v10.1[which(ans.4$sans < 100*0.25)])/n.low,2)
> PL <- c(low1,low2,low3,low4,low5,low6,low7,low8,low9,low10)
> PL
[1] 0.14 0.14 0.27 0.18 0.09 0.14 0.14 0.09 0.00 0.09

> #ex2.30(f)
> #難度
> P <- round((PH+PL)/2,2)
> P
[1] 0.51 0.51 0.52 0.49 0.48 0.48 0.55 0.42 0.43 0.52

```

```
> #鑑別度
> D <-(PH-PL)
> D
[1] 0.74 0.74 0.51 0.62 0.79 0.68 0.82 0.67 0.86 0.85
```

```
> #ex2.51(a)
> #(a) 資料壓縮: 將字串"AAABBBCCCC" 表示成"3A3B4C"。(提示: gregexpr,
cat。)
> x1 <- c("AAABBBCCCC")
> t1 <- length(gregexpr('A',x1)[[1]])
> t2 <- length(gregexpr('B',x1)[[1]])
> t3 <- length(gregexpr('C',x1)[[1]])
> a <- cat(t1,"A",t2,"B",t3,"C")
3 A 3 B 4 C
```

```
> #ex2.51(b)
> #(b) 資料解壓縮: 將字串"3A3B4C" 表示"AAABBBCCCC"。(提示: substr, cat,
rep)
> #help(substr)
> x2 <- c("3A3B4C")
> t4 <- substr(rep(x2,3),c(1,3,5),c(1,3,5))
> a1 <- rep(LETTERS[1:3],times=t4)
> a1
[1] "A" "A" "A" "B" "B" "B" "C" "C" "C" "C"
```

```
> #ex2.52
> #輸入為 ABC 三個字?組成之字串, 例如: 字串"ABAABBAABCCCAC", 輸出為每
個字?出現之次數"6A4B4C"
> compress <- function(x){
+   c1 <-LETTERS[1:3]
+   for(i in c1){
+     c2 <- length(gregexpr(i,x)[[1]])
+     cat(c(c2,i,""))
+   }
+ }
> compress("ABAABBAABCCCAC")
6 A 4 B 4 C
```

```

> #ex5.2(a)
> #白球:w <- 0
> #紅球:R <- 1
> ball <- rep(c(0,1),c(6,4))
> ball
[1] 0 0 0 0 0 1 1 1 1
> play <- sample(ball,3,replace = FALSE)
> set.seed(123456)
> cat('紅球:',sum(play),'白球:',(length(play)-sum(play)))
紅球: 2 白球: 1>

```

```

> #ex5.2(b)
> set.seed(123456)
> play1 <- replicate(10, sample(ball, 3, replace = FALSE))
> R <- colSums(play1)
> W <- rep(3,times=10)-R
> cbind(R,W)
      R W
[1,] 1 2
[2,] 1 2
[3,] 1 2
[4,] 2 1
[5,] 1 2
[6,] 1 2
[7,] 2 1
[8,] 1 2
[9,] 1 2
[10,] 2 1

```

```

> #ex5.2(c)
> #重覆上述實驗 100 次，計算抽中 2 顆白球及 1 顆紅球的機率
> set.seed(123456)
> play2 <- replicate(100, sample(ball, 3, replace = FALSE))
> R1 <- colSums(play2)
> sum(R1==1)/100
[1] 0.51

```