

Entity Linking - Part II

Pawan Goyal

CSE, IIT Kharagpur

Week 10, Lecture 2

Keyphraseness and Commonness: Always the best decision?

Depth-first search

From Wikipedia, the free encyclopedia

Depth-first search (DFS) is an **algorithm** for traversing or searching a **tree** **tree structure** or **graph**. One starts at the root (selecting some node as the root in the graph case) and explores as far as possible along each branch before **backtracking**.

Formally, DFS is an **uninformed search** that progresses by expanding the first child node of the search **tree** that appears and thus going deeper and deeper until a goal node is found, or until it hits a node that has no children. Then the search **backtracks**, returning to the most recent node it hadn't finished exploring. In a non-recursive implementation, all freshly expanded nodes are added to a **LIFO stack** for exploration.

sense	commonness	relatedness
Tree	92.82%	15.97%
Tree (graph theory)	2.94%	59.91%
Tree (data structure)	2.57%	63.26%
Tree (set theory)	0.15%	34.04%
Phylogenetic tree	0.07%	20.33%
Christmas tree	0.07%	0.0%
Binary tree	0.04%	62.43%
Family tree	0.04%	16.31%
...		

Keyphraseness and Commonness: Always the best decision?

Depth-first search

From Wikipedia, the free encyclopedia

Depth-first search (DFS) is an **algorithm** for traversing or searching a **tree** **tree structure** or **graph**. One starts at the root (selecting some node as the root in the graph case) and explores as far as possible along each branch before **backtracking**.

Formally, DFS is an **uninformed search** that progresses by expanding the first child node of the search **tree** that appears and thus going deeper and deeper until a goal node is found, or until it hits a node that has no children. Then the search **backtracks**, returning to the most recent node it hadn't finished exploring. In a non-recursive implementation, all freshly expanded nodes are added to a **LIFO stack** for exploration.

sense	commonness	relatedness
Tree	92.82%	15.97%
Tree (graph theory)	2.94%	59.91%
Tree (data structure)	2.57%	63.26%
Tree (set theory)	0.15%	34.04%
Phylogenetic tree	0.07%	20.33%
Christmas tree	0.07%	0.0%
Binary tree	0.04%	62.43%
Family tree	0.04%	16.31%
...		

Using Relatedness: Basic Idea

- In a sufficiently long text, one finds terms that do not require disambiguation at all.
- Use every unambiguous link in the document as context to disambiguate ambiguous ones.

- Each candidate sense and context term is represented by a single Wikipedia article.

- Each candidate sense and context term is represented by a single Wikipedia article.
- Thus the problem is reduced to selecting the sense article that has most in common with all of the context articles.

- Each candidate sense and context term is represented by a single Wikipedia article.
- Thus the problem is reduced to selecting the sense article that has most in common with all of the context articles.
- Comparison of articles is facilitated by the Wikipedia Link-based measure, which measures the semantic similarity of two Wikipedia pages by comparing their incoming and outgoing links.

- Each candidate sense and context term is represented by a single Wikipedia article.
- Thus the problem is reduced to selecting the sense article that has most in common with all of the context articles.
- Comparison of articles is facilitated by the Wikipedia Link-based measure, which measures the semantic similarity of two Wikipedia pages by comparing their incoming and outgoing links.
- The relatedness of a candidate sense is the weighted average of its relatedness to each context article.

- Each candidate sense and context term is represented by a single Wikipedia article.
- Thus the problem is reduced to selecting the sense article that has most in common with all of the context articles.
- Comparison of articles is facilitated by the Wikipedia Link-based measure, which measures the semantic similarity of two Wikipedia pages by comparing their incoming and outgoing links.
- The relatedness of a candidate sense is the weighted average of its relatedness to each context article.

How to give different weights to the context terms?

Weighting the Context Terms

Weighting the Context Terms

- **link probability:** Use the ones that are almost always used as a link within the articles where they are found, and always link to the same destination

Weighting the Context Terms

- **link probability:** Use the ones that are almost always used as a link within the articles where they are found, and always link to the same destination
- **relatedness:** We can determine how closely a term relates to the central document by calculating its average semantic relatedness to all other context terms

Weighting the Context Terms

- **link probability:** Use the ones that are almost always used as a link within the articles where they are found, and always link to the same destination
- **relatedness:** We can determine how closely a term relates to the central document by calculating its average semantic relatedness to all other context terms

These two variables - link probability and relatedness - are averaged to provide a weight for each context.

Can we improve mention detection with this approach?

- The link detection process starts by gathering all n-grams in the document, and retaining those whose probability exceeds a very low threshold.

Can we improve mention detection with this approach?

- The link detection process starts by gathering all n-grams in the document, and retaining those whose probability exceeds a very low threshold. *Is it the best method?*

Can we improve mention detection with this approach?

- The link detection process starts by gathering all n-grams in the document, and retaining those whose probability exceeds a very low threshold. *Is it the best method?*
- All the remaining phrases are disambiguated using the approach mentioned earlier.

Can we improve mention detection with this approach?


- The link detection process starts by gathering all n-grams in the document, and retaining those whose probability exceeds a very low threshold. *Is it the best method?*
- All the remaining phrases are disambiguated using the approach mentioned earlier.
- This results in a set of associations between terms in the document and the Wikipedia articles that describe them.

Can we improve mention detection with this approach?

- The link detection process starts by gathering all n-grams in the document, and retaining those whose probability exceeds a very low threshold. *Is it the best method?*
- All the remaining phrases are disambiguated using the approach mentioned earlier.
- This results in a set of associations between terms in the document and the Wikipedia articles that describe them.

Can you use this to learn – which concepts should be linked?

Example



The Learning Problem: Which topics should be linked?

- The automatically identified Wikipedia articles provide training instances for a classifier.

The Learning Problem: Which topics should be linked?

- The automatically identified Wikipedia articles provide training instances for a classifier.
- Positive examples are the articles that were manually linked to, while negative ones are those that were not.

The Learning Problem: Which topics should be linked?

- The automatically identified Wikipedia articles provide training instances for a classifier.
- Positive examples are the articles that were manually linked to, while negative ones are those that were not.
- Features of these articles – and the places where they were mentioned – are used to inform the classifier about which topics should and should not be linked.

What are the features?

- **Link Probability:** Average as well as maximum of link probability of the link locations – (e.g. Hillary Clinton and Clinton)
- **Relatedness:** Topics which relate to the central thread of the document are more likely to be linked
- **Disambiguation Confidence:** The confidence score of the classifier for disambiguation
- **Generality:** Defined as the minimum depth at which it is located in Wikipedia's category tree. More useful for the readers to provide links for specific topics.
- **Location and Spread:** Where are these mentioned? First occurrence, last occurrence and the spread.

- Mihalcea, Rada, and Andras Csomai. “Wikify!: linking documents to encyclopedic knowledge.” Proceedings of the sixteenth ACM conference on information and knowledge management. ACM, 2007.
- Milne, David, and Ian H. Witten. “Learning to link with wikipedia.” Proceedings of the 17th ACM conference on Information and knowledge management. ACM, 2008.