

1.

Which of the following is/are not correct?

Doubly circular linked list contains only one node, if _____.

- i. next part of first node contains address of last node
- ii. next part of first node contains address of first node
- iii. prev part of last node contains null value
- iv. prev part of last node contains address of first node

- A. i, iv
- B. iii
- C. i
- D. ii

Answer: B

2.

If a doubly circular linked list contains nodes 112, 221, 454, 455, 554, 545, 121 and a pointer p points to node 545, then what would p -> next -> next -> prev fetch?

- A. 121
- B. 545
- C. 554
- D. 454

Answer: A

3.

What is the time complexity to count the number of nodes in a doubly circular linked list?

- A. $O(n)$
- B. $O(1)$
- C. $O(2n)$
- D. $O(\log n)$

Answer: A

4.

A singly circular linked list with a single node. List is having head and tail pointers.

What is the correct code to add a new node with data `7` at beginning?

- A. `new_node->next = head;`
`head->next = new_node;`
`head = new_node;`
- B. `new_node->next = NULL;`
`head = new_node;`
- C. `head = new_node;`
`tail->next = head;`
- D. `new_node->next = head;`
`tail->next = new_node;`
`head = new_node;`

Answer: D

5.

What would the prev pointer of the head node in a doubly circular linked list point to?

- A. NULL**
- B. address of itself**
- C. address of second last node**
- D. address of last node**

Answer: D

6.

Which type of linked list is often used to implement a Round Robin scheduling algorithm in operating systems?

- A. Singly Linked List**
- B. Self-Organizing List**
- C. Circular Linked List**
- D. Doubly Linked List**

Answer: C