

1.

What is the time complexity to add a node at the first position in the singly circular Linked List if the list is not empty?

- A. $O(1)$
- B. $O(n)$
- C. $O(\log n)$
- D. None of the above

Answer : B

2.

Select the correct option to attach a new node in an empty circular linked list.

`struct node *new_node=(struct node*)malloc(sizeof(struct node));`

- I. `head = new_node;`
`new_node->next = NULL;`
- II. `head = new_node;`
`new_node->next = head;`
- III. `head = new_node;`
- IV. `head = new_node;`
`new_node->next = new_node;`

- A. Only I
- B. Only II
- C. Only III
- D. Both I and III
- E. Both II and IV

Answer : E

3.

Select the correct option to print the node data in the Circular linked list.

- A. **struct** node *trav = head;
do
{
 printf("%d ",trav->data);
 trav = trav->next;
}**while**(trav->next != head);
- B. **struct** node *trav = head;
do
{
 printf("%d ",trav->data);
 trav = trav->next;
}**while**(trav != head);
- C. **struct** node *trav = head;
do
{
 printf("%d ",trav->data);
 trav = trav->next;
}**while**(trav->next != **NULL**);
- D. **struct** node *trav = head;
do
{
 printf("%d ",trav->data);
 trav = trav->next;
}**while**(trav-> != **NULL**);

Answer : B

4.

What will be the output of the following code if the circular linked list contains 3 nodes ?

```
struct Node* tail = head;  
while (tail->next != head)  
{  
    tail = tail->next;  
}  
printf("%d", tail->data)
```

- A. Prints the first nodes data
- B. Prints the last nodes data
- C. Prints all the nodes data
- D. Infinite Loop

Answer : B

5.

Which of the following Linked List is the most efficient in terms of time ?

- A. singly Liner Linked List
- B. Singly Circular Linked List
- C. Doubly Linear Linked List
- D. Doubly Circular Linked List

Answer : D