

1.

What will be the output of the following C code?

```
#include <stdio.h>
int main(void)
{
    int n1 = 10;
    printf("%d", printf("%s%d", "Hello", n1));
    return 0;
}
```

- A. Hello5
- B. Hello107
- C. 5Hello
- D. Compilation error

Answer: B

2.

What will be the output of the following C code?

```
#include <stdio.h>
int main(void)
{
    printf("10\\2 = %d", 10\\2);
    return 0;
}
```

- A. 5
- B. 10\\2 = 5
- C. Compilation error
- D. 10\\2 = 10

Answer: C

3.

What are tokens in C?

- A. Only Input/output operators
- B. Only Constants and strings
- C. Smallest individual units in a program
- D. Only keywords and identifiers

Answer: C

4.

What will be the output of the following C code?

```
#include<stdio.h>
int main(void)
{
    int a,b;
    printf("%d ",printf("%d ",scanf("%d%d",&a,&b)));
    return 0;
}
```

//Note [Consider a=20 and b=10]

- A. 2 2
- B. 2 1
- C. 20 10
- D. 1 1

Answer: A

5.

What is the purpose of %*d in scanf()?

- A. Read and store an int**
- B. Read but ignore an int input from storage**
- C. Store input into pointer**
- D. Print int as pointer**

Answer: B