

1.

```
#include <stdio.h>
int main(void)
{
    int a = 0, b = 6;
    if (a > 0 || b / a)
        printf("Yes");
    else
        printf("No");
    return 0;
}
```

- A. Yes if b divisible by a
- B. No if b divisible
- C. Always Yes
- D. Runtime error

Answer: D

2.

```
#include <stdio.h>
int main(void)
{
    int x = 1;
    printf("%d", x && x-- ? x : x + 2);
    return 0;
}
```

- A. 1
- B. 0
- C. 2
- D. 3

Answer: B

3.

```
#include <stdio.h>
int main(void)
{
    int x;
    if (x = printf("Hello"))
        printf(" world");
    if (x >= 1)
        printf("Shifted non-zero");
    else
        printf("Zero");
    printf("and now x is %d",x);
    return 0;
}
```

- A. Hello worldShifted non-zero and now x is 2
- B. Hello worldZero and now x is 5
- C. HelloZero and now x is 2
- D. worldShifted non-zero and now x is 10

Answer: A

4.

Which of the following is **TRUE** about nested conditional operators in C?

- A. Parentheses are required **for** every nested ternary expression
- B. Compiler throws error **for** nested ternary expressions
- C. Nested ternary expressions work without parentheses but may reduce readability
- D. Nested ternary expressions are not supported in standard C

Answer: C

5.

```
#include <stdio.h>
int main(void)
{
    int a = 5, b = 10, c = 15;
    int result = (a > b) ? ((b > c) ? b : c) : a;
    printf("%d", result);
    return 0;
}
```

- A. 5
- B. 10
- C. 15
- D. Compile error

Answer: A

6.

What is the output of the following code?

```
int a = 0;
int b = 2;
int c = 4;
int result = a ? b : c == 4 ? b : c;
printf("%d", result);
```

- A. 0
- B. 2
- C. 4
- D. Compile error

Answer: B