

1.

Which symbol is used to declare a pointer?

- A. &
- B. #
- C. *
- D. @

Answer: C

2. `#include <stdio.h>`
`void change(int * p)`
`{`
`*p += 5;`
`p = NULL;`
`return;`
`}`
`int main(void)`
`{`
`int a = 3;`
`int *ptr = &a;`
`change(ptr);`
`printf("%d", a);`
`return 0;`
`}`

- A. 3
- B. 8
- C. 0
- D. compiler error

Answer: B

3.

```
#include <stdio.h>
void square(int *const p)
{
    int temp = *p, k=temp;
    *p = temp++ * k;
    return;
}
int main(void)
{
    int x = 4;
    square(&x);
    printf("%d", x);
    return 0;
}
```

- A. 20
- B. 8
- C. 16
- D. Compile time error

Answer: C

4.

```
#include <stdio.h>
int main(void)
{
    int a = 1, b = 2;
    int *p = &a, *q = &b;
    p = q;
    *p = 10;
    printf("%d %d", a, b);
    return 0;
}
```

- A. 10 10
- B. 1 10
- C. 10 2
- D. 1 2

Answer: B

5. If ptr is a pointer to **float**, what is the result of ptr + 1?
- A. Address + 1 byte
 - B. Address + 2 bytes
 - C. Address + 4 bytes (on 32-bit)
 - D. Address + sizeof(int)

Answer: C

6. **#include <stdio.h>**
int main(void)
{
 int a = 10;
 int *ptr = &a;
 int c = ++*ptr, ++*ptr, ++*ptr;
 ;
 printf("%d", a);
 return 0;
}
- A. 10
 - B. compiler error
 - C. 11
 - D. 13

Answer: B