

1.

Below function will **return** which value?

```
int my_strcmp(char *s1, char *s2)
{
    while (*s1 && (*s1 == *s2))
    {
        s1++; s2++;
    }
    return *s1 - *s2;
}
```

- A. Always 0
- B. Returns 1 or -1
- C. Same as strcmp()
- D. Returns length difference

Answer: C

2.

Find the output of the below code:

```
#include<stdio.h>
int main(void)
{
    char str[] = "abcd";
    printf("%c", *(str + *(str + 2) - 97));
    return 0;
}
```

- A. a
- B. b
- C. c
- D. d

Answer: C

3.

Find the output of the below code:

```
#include <stdio.h>
#include <string.h>
int main(void)
{
    char a[10] = "sun";
    char b[10] = "sun";
    char *x = a, *y = b;
    if (strcmp(a, b))
        x++;
    else
        y++;
    y[-1] = '0';
    strcat(x, strcpy(y, "east"));
    printf("%s", x);
}
```

- A. sunFeast
- B. suFeast
- C. Compile Error
- D. sunfeast

Answer: A

4.

Find the output of the below code:

```
#include <stdio.h>
int main(void)
{
    char str[] = "abcde";
    printf("%c", *(&str[3] + 1));
    return 0;
}
```

- A. c
- B. d
- C. e
- D. Compile error

Answer: C

5.

Find the output of the below code:

```
#include<string.h>
#include<stdio.h>
char * demo(char *s);
int main(void)
{
    char *s = "xyz";
    printf("%s", demo(s));
    return 0;
}
char * demo(char *s)
{
    return (s + strlen(s));
}
```

- A, xyz
- B, x
- C, z
- D, No Output

Answer: D