



SCHEDULE OF FOOTINGS (SBC - 400KN/M²)

FOOTING TYPE	NOS	LENGTHXBREADTH	D	REINFORCEMENT
F1	02	1100X1400	400	12 d1a @ 125mm c/c Bothwys
F2	08	1400X1700	500	12 d1a @ 150mm c/c Bothwys
F3	04	1400X1800	600	12 d1a @ 100mm c/c Bothwys
F4	04	1500X1900	600	16 d1a @ 150mm c/c Bothwys

NOTE :

1. ALL DIMENSIONS ARE IN METERS, UNLESS OTHERWISE NOTIFIED ON DRAWING.

2. GRADE OF CONCRETE: COVER

> COLUMN : M25 40 MM
> BEAMS : M25 25 MM
> SLAB : M25 20 MM

3. GRADE OF STEEL : Fe415

4. DRAWINGS SHOULD NOT BE SCALED. ONLY WRITTEN DIMENSIONS ARE TO BE FOLLOWED.

5. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL DRAWINGS.

6. ALL DIMENSIONS SHOULD BE VERIFIED WITH ARCHITECTURAL DRAWINGS.

7. ANY DISCREPANCY SHOULD BE NOTIFIED TO THE ARCHITECT BEFORE COMMENCEMENT OF WORK.

8. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING ANY WORK OR SHOP DRAWING.

Consultant :

PROJECT:

TITLE :

CENTER LINE LAYOUT.

CLIENT :

Drawn : S.K	Dealt : P.K.K	Checked : P.K.K
Drawing No. : TWD/ITDA/So/ STR-2	Scale : N.T.S	Date : 01-10-2013