

Settings / Developer Settings

UP-PST settings / Backstage-Local-GitHub-Integration

- General
- Permissions & events
- Install App
- App managers
- Advanced
- Optional features

Public page

About

Owned by: @UP-PST

App ID: 354409

Client ID: lv1.9b4087ff9340b132

Revoke all user tokens

GitHub Apps can use OAuth credentials to identify users. Learn more about identifying users by reading our [integration developer documentation](#).

Client secrets

Generate a new client secret

Client secret

*****cff009ff

Added yesterday by sachinkumaranumula

Last used within the last week

You cannot delete the only client secret.
Generate a new client secret first.

Delete

Basic information

GitHub App name *

Backstage-Local-GitHub-Integration

The name of your GitHub App.

Write

Preview

Markdown supported

GitHub App for Backstage

Homepage URL *

http://localhost:3000/

The full URL to your GitHub App's website.

Identifying and authorizing users

Add Callback URL

The full URL to redirect to after a user authorizes an installation.

Callback URL

http://localhost:7007/api/auth/github/handler/frame

Delete

☐ Request user authorization (OAuth) during installation

Requests that the installing user grants access to their identity during installation of your App

Read our [Identifying and authorizing users for GitHub Apps documentation](#) for more information.

☐ Enable Device Flow

Allow this GitHub App to authorize users via the Device Flow.

Read the [Device Flow documentation](#) for more information.

Post installation

Setup URL (optional)

Users will be redirected to this URL after installing your GitHub App to complete additional setup.

☐ Redirect on update

Redirect users to the 'Setup URL' after installations are updated (E.g. repositories added/removed).

Webhook

☐ **Active**

We will deliver event details when this hook is triggered.

Webhook URL

https://smee.io/AZDGpPvapZr8jV9cB2x

Events will POST to this URL. Read our [webhook documentation](#) for more information.

Webhook secret (optional)

If you've lost or forgotten this secret, you can change it, but be aware that any integrations using this secret will need to be updated. — [Change Secret](#)

Read our [webhook secret documentation](#) for more information.

SSL verification

 By default, we verify SSL certificates when delivering payloads.

☒ **Enable SSL verification** ☐ **Disable** (not recommended)

Save changes

Cancel

Display information

Drag & drop

Upload a logo...

You can also drag and drop a picture from your computer.

Private keys

Generate a private key

You need a private key to sign access token requests. [Learn more about private keys.](#)



Private

Private key

SHA256: e6jDTyBak2WfAqC1bH+RXJAsBT4znsAa/oP6bIOoNDU=

Added 5 days ago by thewhitepeacock

Delete

IP allow list

Enter the IP addresses of your GitHub App to allow organizations with [IP allow lists](#) to selectively inherit the App's IP allow list when installed. [Learn more.](#)

There are no IP addresses on the allow list yet.

IP address or range in CIDR

Short description of IP addi

+ Add

Check IP address

Enter an IP address to check whether it is permitted by enabled entries on the IP allow list.