Sr.No.	Program Name	Date	Remarks
1.	To perform the program of Linear search.		
2.	To perform the program of Binary search.		
3.	To perform the program of sorting of an array using Insertion Sort.		
4.	To perform the program of sorting of an array using Quick sort .		
5.	To perform the program of sorting of an array using Merge sort.		
6 (A).	To perform the program of Fibonacci series using dynamic programming (DP) method.		
6 (B).	To perform the program of Fibonacci series without using dynamic programming (DP) method.		
7.	Write a program for the implementation of Activity selection problem using Greedy Approach.		
8.	Write a program to solve travelling salesman problem.		
9.	C program to implement Longest Common Sub- Sequence.		
10.	Write a program to implement MST of given undirected graph using Prim's algorithm.		
11.	Write a program to implement MST of given undirected graph using Kruskal's algorithm.		
12.	From a given vertex in a weighted connected graph,find shortest paths to other vertices using Dijkistra's algorithm.		
13.	Implement Bellman-Ford Algorithm to find Shortest Path from a source.		
14	Implement All Pairs Shortest Paths Problem Using Floyd's-Warshall Algorithm.		

# **Program – 06 (B)**

<u>AIM</u>: To perform the program of Fibonacci series using dynamic programming (DP) method.

<u>Description</u>: In this series, the next number is the sum of previous two numbers. By using DP method, all the values are calculated once and stored in a table. So, whenever these values are required for calculation, they can be fetched from the table which results in the lesser cost of the program.

```
#include<stdio.h>
#include<conio.h>
int main(int argc, char const *argv[])
  int a[10], n, j;
  // clrscr();
  printf("\n\t\tFibonacci Series using DP method\n\n");
  printf("Enter the limit:\n");
  scanf("%d", &n);
  a[0] = 0;
  a[1] = 1;
  for(int i = 2; i \le n; i++)
     a[i] = a[i-1]+a[i-2];
  printf("\nThe Fibonacci Series:\n");
  for(int i = 0; i < n; i++)
     printf("%d\n", a[i]);
```

	Manu kumar Pal(8520123)
}	
return 0;	
}	

```
Fibonacci Series using DP method

Enter the limit:
7

The Fibonacci Series:
0
1
2
3
5
8
```

# **Program – 06 (A)**

<u>AIM</u>: To perform the program of Fibonacci series without using dynamic programming(DP) method.

**<u>Description</u>**: In this series, the next number is the sum of previous two numbers. Without using DP method, the values can be calculated every time at each and every stage of calculation.

```
#include<stdio.h>
#include<conio.h>
int main(int argc, char const *argv[])
  int a[10], n, j;
  // clrscr();
  printf("\n\t\tFibonacci Series without using DP method\n\n");
  printf("Enter the limit:\n");
  scanf("%d", &n);
  printf("\nThe Fibonacci Series:\n");
  for(int i = 0; i < n; i++)
     printf("%d\n", fin(i));
  return 0;
int fin(int n)
  if(n==0)
     return 0;
```

```
Manu kumar Pal(8520123)

}
else if(n==1)
{
    return 1;
}
else
{
    return (fin(n-1)+fin(n-2));
}
```



# <u>AIM</u>: Write a program for the implementation of Activity selection problem using Greedy Approach.

<u>Description:</u> The activity selection problem is a mathematical optimization problem. Our first illustration is the problem of scheduling a resource among several challenge activities. We find a greedy algorithm provides a well designed and simple method for selecting a maximum- size set of manually compatible activities.

Suppose  $S = \{1, 2, ..., n\}$  is the set of n proposed activities. The activities share resources which can be used by only one activity at a time, e.g., Tennis Court, Lecture Hall, etc. Each Activity "i" has **start time**  $s_i$  and a **finish time**  $f_i$ , where  $s_i \le f_i$ . If selected activity "i" take place meanwhile the half-open time interval  $[s_i, f_i)$ . Activities i and j are **compatible** if the intervals  $(s_i, f_i)$  and  $[s_i, f_i)$  do not overlap (i.e. i and j are compatible if  $s_i \ge f_i$  or  $s_i \ge f_i$ ). The activity-selection problem chosen the maximum-size set of mutually consistent activities.

```
#include<stdio.h>
#include<conio.h>

int s[100], f[100], n, i, j;

void printMaxActivities()
{
    printf("Following activities are selected\n");
    i = 0;
    printf("%d\t", i+1);
    for(j = 1; j < n; j++)
    {
}</pre>
```

```
Manu kumar Pal(8520123)
```

```
if(s[j] \ge f[i])
       printf("%d\t", j+1);
       i = j;
int main(int argc, char const *argv[])
  printf("Enter number of activities\n");
  scanf("%d", &n);
  printf("Enter starting time activities\n");
  for(int i = 0; i < n; i++)
   {
     scanf("%d", &s[i]);
  printf("Enter finishing time activities\n");
  for(int i = 0; i < n; i++)
     scanf("%d", &f[i]);
  printMaxActivities();
  return 0;
```

Enter number of activities
11
Enter starting time activities
1 3 0 5 3 5 6 8 8 2 12
Enter finishing time activities
4 5 6 7 9 9 10 11 12 13 14 16
Following activities are selected
1 4 8 11

## AIM: Write a program to solve travelling salesman problem.

**Description:** The traveling salesman problems abide by a salesman and a set of cities. The salesman has to visit every one of the cities starting from a certain one (e.g., the hometown) and to return to the same city. The challenge of the problem is that the traveling salesman needs to minimize the total length of the trip.

Suppose the cities are  $x_1 x_2..... x_n$  where cost  $c_{ij}$  denotes the cost of travelling from city  $x_i$  to  $x_j$ . The travelling salesperson problem is to find a route starting and ending at  $x_1$  that will take in all cities with the minimum cost.

```
#include<stdio.h>
int ary[10][10],completed[10],n,cost=0;
void takeInput()
{
  int i,j;
  printf("Enter the number of villages: ");
  scanf("%d",&n);
  printf("\nEnter the Cost Matrix\n");
  for(i=0;i < n;i++)
  {
    printf("\nEnter Elements of Row: %d\n",i+1);
    for( j=0;j < n;j++)
    scanf("%d",&ary[i][j]);
  completed[i]=0;
}</pre>
```

```
Manu kumar Pal(8520123)
```

```
printf("\n\nThe cost list is:");
for( i=0; i < n; i++)
printf("\n");
for(j=0; j < n; j++)
printf("\t%d",ary[i][j]);
void mincost(int city)
int i,ncity;
completed[city]=1;
printf("%d--->",city+1);
ncity=least(city);
if(ncity==999)
ncity=0;
printf("%d",ncity+1);
cost+=ary[city][ncity];
return;
mincost(ncity);
int least(int c)
int i,nc=999;
```

```
int min=999,kmin;
for(i=0; i < n; i++)
if((ary[c][i]!=0)\&\&(completed[i]==0))
if(ary[c][i]+ary[i][c] \le min)
min=ary[i][0]+ary[c][i];
kmin=ary[c][i];
nc=i;
if(min!=999)
cost+=kmin;
return nc;
int main()
takeInput();
printf("\n\nThe Path is:\n");
mincost(0); //passing 0 because starting vertex
printf("\n\nMinimum cost is %d\n ",cost);
return 0;}
```

```
Enter the number of villages: 4
Enter the Cost Matrix
Enter Elements of Row: 1
4
1
3
Enter Elements of Row: 2
0
2
1
Enter Elements of Row: 3
1
2
0
5
Enter Elements of Row: 4
1
The cost list is:
       0 4 1 3
4 0 2 1
1 2 0 5
3 1 5 0
The Path is:
1--->3--->2--->4--->1
Minimum cost is 7
```

## **AIM**: C program to implement Longest Common Sub-Sequence.

**Description:** Here longest means that the subsequence should be the biggest one. The common means that some of the characters are common between the two strings. The subsequence means that some of the characters are taken from the string that is written in increasing order to form a subsequence.

```
#include<stdio.h>
#include<conio.h>
char b[10][10];
void lcs(int m,int n,char x[],char y[]);
void printles(char b[][10],char x[],int i,int j);
void main()
      int m,n,i,j;
      char x[10],y[10],t[10][10];
      // clrscr();
      printf("\n\t\t\t LONGEST COMMON SUB-SEQUENCE\n\n");
      printf("Enter the no. of elements in sequence 1:\n");
      scanf("%d",&m);
      printf("\nEnter the no. of elements in sequence 2:\n");
      scanf("%d",&n);
      printf("\nEnter the elements of the sequence 1:\n");
      for(i=1;i \le m;i++)
             scanf("%s",&x[i]);
```

```
Manu kumar Pal(8520123)
```

```
printf("\nEnter the elements of the sequence 2:\n");
      for(j=1;j \le n;j++)
             scanf("%s",&y[j]);
      lcs(m,n,x,y);
      printf("\nThe common elements are:\n");
      printlcs(b,x,m,n);
      getch();
void lcs(int m,int n,char x[],char y[])
      int c[10][10],i,j;
      for(i=1;i<=m;i++)
             c[i][0]=0;
      for(j=0;j<=n;j++)
             c[0][j]=0;
      for(i=1;i<=m;i++)
             for(j=1;j \le n;j++)
```

```
Manu kumar Pal(8520123)
```

```
if(x[i]==y[j])
                           c[i][j]=c[i-1][j-1]+1;
                           b[i][j]='a';
                    else if(c[i-1][j]>=c[i][j-1])
                           c[i][j]=c[i-1][j];
                           b[i][j]='b';
                    else
                           c[i][j]=c[i][j-1];
                           b[i][j]='c';
      printf("\nThe Total number of LCS elements are:\n");
      printf("\%d\n",c[m][n]);
void printles(char b[][10],char x[],int i,int j)
      if(i==0 && j==0)
             return;
      if(b[i][j]=='a')
```

```
Manu kumar Pal(8520123)

{
    printles(b,x,i-1,j-1);
    printf("%c\t",x[i]);
}
else if(b[i][j]=='b')
{
    printles(b,x,i-1,j);
}
else
{
    printles(b,x,i,j-1);
```

```
Enter the no. of elements in sequence 1:
4

Enter the no. of elements in sequence 2:
3

Enter the elements of the sequence 1:
a b c a

Enter the elements of the sequence 2:
a b c

The Total number of LCS elements are:
3

The common elements are:
a b c
```

## Program – 11

<u>AIM</u>: Write a program to implement MST of given undirected graph using Kruskal's algorithm.

<u>Description</u>: Kruskal's algorithm is a <u>minimum-spanning-tree</u> <u>algorithm</u> which finds an edge of the least possible weight that connects any two trees in the forest. It is a <u>greedy algorithm</u> in <u>graph</u> theory as it finds a <u>minimum spanning tree</u> for a <u>connected weighted graph</u> adding increasing cost arcs at each step. This means it finds a subset of the <u>edges</u> that forms a tree that includes every <u>vertex</u>, where the total weight of all the edges in the tree is minimized. If the graph is not connected, then it finds a minimum spanning forest (a minimum spanning tree for each <u>connected component</u>).

```
#include <stdio.h>
#include <limits.h>
#include <stdlib.h>

char vertex[10];
int weight[10][10], size, set_index[10], min, i, j, u, v, k, range = 1, temp;

void build_graph()
{
    printf("Enter The Number of Vertices");
    scanf("%d", &size);
    printf("Enter %d Vertices of Graph \n", size);
    for (i = 0; i < size; i++)
    {
        fflush(stdin);
        scanf("%c", &vertex[i]);
    }
}</pre>
```

```
Manu kumar Pal(8520123)
```

```
set_index[i] = i;
  printf("Enter the Weighted matrix For the Graph:\n");
  for (i = 0; i < size; i++)
     for (j = 0; j < size; j++)
       scanf("%d", &weight[i][j]);
void kruskal()
  for (k = 0; k < size; k++)
     min = INT_MAX;
     for (i = 0; i < size; i++)
       for (j = 0; j < size; j++)
          if (weight[i][j] < min && weight[i][j] >= range && set index[i]!=
set_index[j])
            min = weight[i][j];
            u = i;
             v = j;
```

```
Manu kumar Pal(8520123)
```

```
}
    range = min;
    if (set_index[u] != set_index[v])
       temp = set index[v];
       for (i = 0; i < size; i++)
       {
         if(set\_index[i] == temp)
            set index[i] = set index[u];
       printf("\%c--\%c = \%d\n", vertex[u], vertex[v], weight[u][v]);
int main()
  build graph();
  printf("\nThe Nodes Which Form the minimum spanning tree are : \n\n Node
Weight Of Node\n");
  kruskal();
  return 0;
```

```
Enter The Number of Vertices9
Enter 9 Vertices of Graph
b
d
g
Enter the Weighted matrix For the Graph:
040000080
4080000110
000704002
0070914000
0009010000
00414100200
000002016
8 11 0 0 0 0 1 0 7
002000670
The Nodes Which Form the minimum spanning tree are :
Node Weight Of Node
g--h = 1
c--i = 2
f--g = 2
a--b = 4
c--f=4
a--h = 8
d--e = 9
```

<u>AIM</u>: Write a program to implement MST of given undirected graph using Prim's algorithm.

<u>Description</u>: Prim's (also known as Jarník's) algorithm is a <u>greedy algorithm</u> that finds a <u>minimum spanning tree</u> for a <u>weighted undirected graph</u>. This means it finds a subset of the <u>edges</u> that forms a <u>tree</u> that includes every <u>vertex</u>, where the total weight of all the <u>edges</u> in the tree is minimized. The algorithm operates by building this tree one vertex at a time, from an arbitrary starting vertex, at each step adding the cheapest possible connection from the tree to another vertex.

```
#include<stdio.h>
#include<conio.h>
#includelimits.h>
#include<stdlib.h>
char vertex[10];
int weight[10][10],key[10],size,visited[10],parent[10],min,min index,i,j,u;
void build graph()
      printf("enter number of vertices\n");
      scanf("%d",&size);
      printf("enter %d vertices of graph\n",size);
      for(i=0;i\leq size;i++)
             fflush(stdin);
             scanf("%c",&vertex[i]);
      printf("enter weighted matrix for the graph:\n");
```

```
Manu kumar Pal(8520123)
```

```
for(i=0;i<size;i++)
            for(j=0;j<size;j++)
                  scanf("%d",&weight[i][j]);
int extract_min()
      min=INT MAX;
      for(i=0;i<size;i++)
            if(!visited[i]&&key[i]<min)</pre>
min=key[i];
                  min_index=i;
      return min_index;
void prims()
      for(i=0;i<size;i++)
            key[i]=INT_MAX;
```

```
Manu kumar Pal(8520123)
```

```
visited[i]=0;
            parent[i]=NULL;
      key[0]=0;
      for(j=0;j\leq size;j++)
            u=extract min();
            visited[u]=1;
            printf("%c-%c =
%d\n",vertex[parent[u]],vertex[u],weight[parent[u]][u]);
            for(i=0;i<size;i++)
                   if(!visited[i] && weight[u][i]!=0)
                         if(key[i]>weight[u][i])
                               key[i]=weight[u][i];
                               parent[i]=u;
void main()
      build graph();
      printf("the nodes which form the minimum spanning tree are:\n\nnode
weight of node\n");
```

		Manu kumar Pal(8520123)
	prims();	
	getch();	
}	gettin(),	
,		

```
enter number of vertices
enter 5 vertices of graph
enter weighted matrix for the graph: 0 0 0 1 0
2 0 1 2 1
0 1 2 2 0
3 0 0 1 0
2 0 1 0 0
the nodes which form the minimum spanning tree are:
node weight of node
1-1
1-o
            1
1-o
1-o
            1
1-o
[Program finished]
```

## Program – 14

# <u>AIM</u>: Implement All-Pairs Shortest Paths Problem using Floyd's-Warshall Algorithm.

**<u>Description</u>**: The <u>Floyd Warshall Algorithm</u> is for solving the All Pairs Shortest Path problem. The problem is to find shortest distances between every pair of vertices in a given edge weighted directed Graph.

```
#include<stdio.h>
#define V 4
#define INF 99999
void printSolution(int dist[][V]);
void floydWarshall (int graph[][V])
  int dist[V][V], i, j, k;
  for (i = 0; i < V; i++)
     for (j = 0; j < V; j++)
       dist[i][j] = graph[i][j];
  for (k = 0; k < V; k++)
          for (i = 0; i < V; i++)
       for (j = 0; j < V; j++)
          if (dist[i][k] + dist[k][i] < dist[i][i])
             dist[i][j] = dist[i][k] + dist[k][j];
  printSolution(dist);
void printSolution(int dist[][V])
  printf ("The following matrix shows the shortest distances"
        " between every pair of vertices \n");
  for (int i = 0; i < V; i++)
     for (int i = 0; i < V; i++)
```

Manu kumar Pal(8520123)

```
{
    if (dist[i][j] == INF)
        printf("%7s", "INF");
    else
        printf ("%7d", dist[i][j]);
    }
    printf("\n");
}

int main()
{
    int graph[V][V] = { {0, 5, INF, 10},
        {INF, 0, 3, INF},
        {INF, INF, 0, 1},
        {INF, INF, 1NF, 0}
        };

    floydWarshall(graph);
    return 0;
}
```

m

```
Enter the end vertices of edgel with its weight
20
 Enter the end vertices of edge2 with its weight
3
4 40
 Enter the end vertices of edge3 with its weight
3
15
 Enter the end vertices of edge4 with its weight
80
 Enter the end vertices of edge5 with its weight
3
10
Matrix of input data:
1999 20 10
999
                              999
         999
999
999
                    15
                              999
999
                    999
                              40
999
         999
                   999
                              999
 Transitive closure:
                             50
55
          20
                   10
                   15
999
         0
         999
                              40
999
                    0
999
         999
                   999
                              0
 The shortest paths are:
<1,2>=20
<1,3>=10
<1,4>=50
 <2,1>=999
<2,1>=999
<2,3>=15
<2,4>=55
<3,1>=999
<3,2>=999
 <3,4>=40
<4,1>=999
<4,2>=999
<4,3>=999[student@localhost S]$ clear
```

<u>AIM</u>: From a given vertex in a weighted connected graph, find shortest paths to other vertices using Dijkistra's algorithm.

**Description:** Dijkstra's algorithm is very similar to <u>Prim's algorithm for minimum spanning tree</u>. Like Prim's MST, we generate a *SPT (shortest path tree)* with a given source as a root. We maintain two sets, one set contains vertices included in the shortest-path tree, other set includes vertices not yet included in the shortest-path tree. At every step of the algorithm, we find a vertex that is in the other set (set of not yet included) and has a minimum distance from the source.

```
#include <iostream>
using namespace std;
#include inits.h>
#define V 9
int minDistance(int dist[], bool sptSet[])
  int min = INT MAX, min index;
  for (int v = 0; v < V; v++)
     if(sptSet[v] == false \&\& dist[v] \le min)
       min = dist[v], min index = v;
  return min index;
void printSolution(int dist[])
  cout <<"Vertex \t Distance from Source" << endl;
  for (int i = 0; i < V; i++)
     cout << i << " \t << dist[i] << endl;
void dijkstra(int graph[V][V], int src)
  int dist[V]; // The output array. dist[i] will hold the shortest
  bool sptSet[V];
  for (int i = 0; i < V; i++)
     dist[i] = INT MAX, sptSet[i] = false;
  dist[src] = 0;
  for (int count = 0; count < V - 1; count++) {
     int u = minDistance(dist, sptSet);
```

```
sptSet[u] = true;
     for (int v = 0; v < V; v++)
        if (!sptSet[v] && graph[u][v] && dist[u] != INT MAX
           && dist[u] + graph[u][v] < dist[v])
           dist[v] = dist[u] + graph[u][v];
  printSolution(dist);
int main()
  int graph[V][V] = { \{0, 4, 0, 0, 0, 0, 0, 8, 0\},\
                 \{4, 0, 8, 0, 0, 0, 0, 11, 0\},\
                 \{0, 8, 0, 7, 0, 4, 0, 0, 2\},\
                 \{0, 0, 7, 0, 9, 14, 0, 0, 0\},\
                 \{0, 0, 0, 9, 0, 10, 0, 0, 0\},\
                 \{0, 0, 4, 14, 10, 0, 2, 0, 0\},\
                 \{0, 0, 0, 0, 0, 2, 0, 1, 6\},\
                 \{8, 11, 0, 0, 0, 0, 1, 0, 7\},\
                 \{0, 0, 2, 0, 0, 0, 6, 7, 0\}\};
  dijkstra(graph, 0); return 0;
```

Vertex	Distance	from	Source

0 0

1 4

2 12

3 19

4 21

5 11

6 9

7 8

8 14

# <u>AIM</u>: Implement Bellman-Ford Algorithm to find Shortest Path from a source.

**Description:** The **Bellman–Ford algorithm** is an <u>algorithm</u> that computes <u>shortest paths</u> from a single source <u>vertex</u> to all of the other vertices in a <u>weighted digraph</u>. It is slower than <u>Dijkstra's algorithm</u> for the same problem, but more versatile, as it is capable of handling graphs in which some of the edge weights are negative numbers. The algorithm was first proposed by Alfonso Shimbel (1955), but is instead named after <u>Richard Bellman</u> and <u>Lester Ford Jr.</u>, who published it in <u>1958</u> and <u>1956</u>, respectively. Ledward F. Moore also published a variation of the algorithm in <u>1959</u>, and for this reason it is also sometimes called the **Bellman–Ford** 

```
#include <iostream>
#include <vector>
#include <iomanip>
#include <climits>
using namespace std;
struct Edge {
   int source, dest, weight;
};
void printPath(vector<int> const &parent, int vertex)
{
   if (vertex < 0) {
      return;
   }
}</pre>
```

```
printPath(parent, parent[vertex]);
  cout << vertex << " ";
void bellmanFord(vector<Edge> const &edges, int source, int N)
  vector<int> distance (N, INT MAX);
  distance[source] = 0;
  vector<int> parent (N, -1);
  int u, v, w, k = N;
  while (--k)
    for (Edge edge: edges)
       u = edge.source;
       v = edge.dest;
       w = edge.weight;
       if (distance[u] != INT MAX && distance[u] + w < distance[v])
         distance[v] = distance[u] + w;
         parent[v] = u;
  for (Edge edge: edges)
```

```
u = edge.source;
     v = edge.dest;
     w = edge.weight;
     if (distance[u] != INT MAX && distance[u] + w < distance[v])
        cout << "Negative-weight cycle is found!!";</pre>
        return;
  for (int i = 0; i < N; i++)
     cout << "The distance of vertex " << i << " from the source is "
        << setw(2) << distance[i] << ". Its path is [ ";
     printPath(parent, i); cout << "]" << endl;</pre>
int main()
  vector<Edge> edges =
     // `(x, y, w)` \longrightarrow edge from `x` to `y` having weight `w`
     \{0, 1, -1\}, \{0, 2, 4\}, \{1, 2, 3\}, \{1, 3, 2\},\
     {1, 4, 2}, {3, 2, 5}, {3, 1, 1}, {4, 3, -3}
```

```
Manu kumar Pal(8520123)
```

```
};
int N = 5;
int source = 0;
bellmanFord(edges, source, N);
return 0;
}
```

The distance of vertex 0 from the source is 0. Its path is [0]
The distance of vertex 1 from the source is -1. Its path is [01]
The distance of vertex 2 from the source is 2. Its path is [01]

The distance of vertex 2 from the source is 2. Its path is [ 0 1 2 ]

The distance of vertex 3 from the source is -2. Its path is [ 0 1 4 3 ]

The distance of vertex 4 from the source is 1. Its path is [ 0 1 4 ]

# **AIM:** Linear Search

**Description:** Linear search is a sequential searching algorithm where we start from one end and check every element of the list until the desired element is found. It is the simplest searching algorithm.

```
#include <stdio.h>
int search(int arr[], int n, int x)
  int i;
  for (i = 0; i < n; i++)
     if (arr[i] == x)
        return i;
  return -1;
int main(void)
  int arr[] = \{2, 3, 4, 10, 40\};
  int x = 10;
  int n = sizeof(arr) / sizeof(arr[0]);
  int result = search(arr, n, x);
  (result == -1)
 ? printf("Element is not present in array")
   : printf("Element is present at index %d", result);
return 0;
```

	Manu kumar Pal(8520123)
<b>OUTPUT</b> :	
Element is present at index 3	

## **PROGRAM-05**

# **AIM**: Binary Search

**Description:** Binary Search is a searching algorithm for finding an element's position in a sorted array. In this approach, the element is always searched in the middle of a portion of an array.

```
#include <stdio.h>
int binarySearch(int arr[], int I, int r, int x)
{
  if (r >= I) {
     int mid = I + (r - I) / 2;
     if (arr[mid] == x)
       return mid;
     if (arr[mid] > x)
       return binarySearch(arr, I, mid - 1, x);
     return binarySearch(arr, mid + 1, r, x);
  }
  return -1;
int main(void)
  int arr[] = \{ 2, 3, 4, 10, 40 \};
  int n = sizeof(arr) / sizeof(arr[0]);
  int x = 10;
  int result = binarySearch(arr, 0, n - 1, x);
```

```
Manu kumar Pal(8520123)
  (result == -1)
    ? printf("Element is not present in array")
    : printf("Element is present at index %d", result);
  return 0;
}
```

	Manu kumar Pal(8520123)
OUTPUT:	
Element is present at index 3	