

```

1 // @ts-nocheck
2
3 // MIT License
4
5 // Copyright (c) 2021 Pine Wu
6
7
8 // Permission is hereby granted, free of charge, to any person obtaining a copy
9 // of this software and associated documentation files (the "Software"), to deal
10 // in the Software without restriction, including without limitation the rights
11 // to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
12 // copies of the Software, and to permit persons to whom the Software is
13 // furnished to do so, subject to the following conditions:
14
15 // The above copyright notice and this permission notice shall be included in all
16 // copies or substantial portions of the Software.
17
18 // THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
19 // IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
20 // FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
21 // AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
22 // LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM
23 // OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
24 // SOFTWARE.
25
26 // @filename: renderer.ts
27 // source: https://github.com/shikijs/shiki/blob/ca5a6c60a255fb390776ada849e01e
28 // 4a916fc/packages/shiki/src/renderer.ts
29
30 import { FontStyle } from './stackElementMetadata'
31 import { IThemedToken } from './themedTokenizer'
32
33 export interface HtmlRendererOptions {
34   langId?: string
35   fg?: string
36   bg?: string
37 }
38
39 export function renderToHtml(
40   lines: IThemedToken[][],
41   options: HtmlRendererOptions = {}
42 ) {
43   const bg = options.bg || '#fff'
44
45   let html = ''
46
47   html += `

```
${options.langId}</div>`
50 }
51 html += `>`
52
53 lines.forEach((l: IThemedToken[]) => {
54 html += `

```


```

```

63     }
64     html += ``
67     })
68     html += `</span>\n`
69     })
70     html = html.replace(/\n*$/, '') // Get rid of final new lines
71     html += `</code></pre>`
72
73     return html
74 }
75
76 const htmlEscapes = {
77     '&': '&amp;',
78     '<': '&lt;',
79     '>': '&gt;',
80     '"': '&quot;',
81     "'": '&#39;',
82 }
83
84 function escapeHtml(html: string) {
85     return html.replace(/[&<>"']/g, (chr) => htmlEscapes[chr])
86 }
87
88 // @filename: highlighter.ts
89 // source: https://github.com/shikijs/shiki/blob/ca5a6c60a255fb390776ada849e01
4a916fc/packages/shiki/src/highlighter.ts
90 import type {
91     Highlighter,
92     HighlighterOptions,
93     ILanguageRegistration,
94     IShikiTheme,
95     IThemeRegistration,
96     StringLiteralUnion,
97 } from './types'
98 import { Resolver } from './resolver'
99 import { tokenizeWithTheme } from './themedTokenizer'
100 import { renderToHtml } from './renderer'
101
102 import { getOnigasm } from './loader'
103 import { Lang, languages as BUNDLED_LANGUAGES } from './languages'
104 import { Registry } from './registry'
105 import { Theme } from './themes'
106
107 function resolveLang(lang: ILanguageRegistration | Lang) {
108     return typeof lang === 'string'
109         ? BUNDLED_LANGUAGES.find((l) => l.id === lang || l.aliases?.includes(lang
110 ))
111         : lang
112 }
113
114 function resolveOptions(options: HighlighterOptions) {
115     let _languages: ILanguageRegistration[] = BUNDLED_LANGUAGES
116     let _themes: IThemeRegistration[] = options.themes || []
117
118     if (options.langs?.length) {
119         _languages = options.langs.map(resolveLang)
120     }
121     if (options.theme) {
122         _themes.unshift(options.theme)
123     }
124     if (!_themes.length) {
125         _themes = ['nord']
126     }
127
128     return { _languages, _themes }
129 }

```

```

130 export async function getHighlighter(
131     options: HighlighterOptions
132 ): Promise<Highlighter> {
133     const { _languages, _themes } = resolveOptions(options)
134     const _resolver = new Resolver(getOnigasm(), 'onigasm')
135     const _registry = new Registry(_resolver)
136
137     if (options.paths?.themes) {
138         _registry.themesPath = options.paths.themes
139     }
140
141     if (options.paths?.languages) {
142         _resolver.languagesPath = options.paths.languages
143     }
144
145     const themes = await _registry.loadThemes(_themes)
146     const _defaultTheme = themes[0]
147     let _currentTheme: IShikiTheme | undefined
148     await _registry.loadLanguages(_languages)
149
150     /**
151      * Shiki was designed for VS Code, so CSS variables are not currently supported
152      * See: https://github.com/shikijs/shiki/pull/212#issuecomment-906924986
153      *
154      * Instead, we work around this by using valid hex color codes as lookups in the
155      * final "repair" step which translates those codes to the correct CSS variables.
156      */
157     const COLOR_REPLACEMENTS: Record<string, string> = {
158         '#000001': 'var(--shiki-color-text)',
159         '#000002': 'var(--shiki-color-background)',
160         '#000004': 'var(--shiki-token-constant)',
161         '#000005': 'var(--shiki-token-string)',
162         '#000006': 'var(--shiki-token-comment)',
163         '#000007': 'var(--shiki-token-keyword)',
164         '#000008': 'var(--shiki-token-parameter)',
165         '#000009': 'var(--shiki-token-function)',
166         '#000010': 'var(--shiki-token-string-expression)',
167         '#000011': 'var(--shiki-token-punctuation)',
168         '#000012': 'var(--shiki-token-link)',
169     }
170
171     function fixCssVariablesTheme(theme: IShikiTheme, colorMap: string[]) {
172         theme.bg = COLOR_REPLACEMENTS[theme.bg] || theme.bg
173         theme.fg = COLOR_REPLACEMENTS[theme.fg] || theme.fg
174         colorMap.forEach((val, i) => {
175             colorMap[i] = COLOR_REPLACEMENTS[val] || val
176         })
177     }
178
179     function getTheme(theme?: IThemeRegistration) {
180         const _theme = theme ? _registry.getTheme(theme) : _defaultTheme
181         if (!_theme) {
182             throw Error(`No theme registration for ${theme}`)
183         }
184         if (!_currentTheme || _currentTheme.name !== _theme.name) {
185             _registry.setTheme(_theme)
186             _currentTheme = _theme
187         }
188         const _colorMap = _registry.getColorMap()
189         if (_theme.name === 'css-variables') {
190             fixCssVariablesTheme(_theme, _colorMap)
191         }
192         return { _theme, _colorMap }
193     }
194
195     function getGrammar(lang: string) {

```

```

196 const _grammer = _registry.getGrammer(lang)
197 if (!_grammer) {
198     throw Error(`No language registration for ${lang}`)
199 }
200 return { _grammer }
201 }
202
203 function codeToThemedTokens(
204     code: string,
205     lang = 'text',
206     theme?: StringLiteralUnion<Theme>,
207     options = { includeExplanation: true }
208 ) {
209     if (isPlaintext(lang)) {
210         return [{ content: code }]
211     }
212     const { _grammer } = getGrammer(lang)
213     const { _theme, _colorMap } = getTheme(theme)
214     return tokenizeWithTheme(_theme, _colorMap, code, _grammer, options)
215 }
216
217 function codeToHtml(
218     code: string,
219     lang = 'text',
220     theme?: StringLiteralUnion<Theme>
221 ) {
222     const tokens = codeToThemedTokens(code, lang, theme, {
223         includeExplanation: false,
224     })
225     const { _theme } = getTheme(theme)
226     return renderToHtml(tokens, {
227         fg: _theme.fg,
228         bg: _theme.bg,
229     })
230 }
231
232 async function loadTheme(theme: IShikiTheme | Theme) {
233     await _registry.loadTheme(theme)
234 }
235
236 async function loadLanguage(lang: ILanguageRegistration | Lang) {
237     const _lang = resolveLang(lang)
238     _resolver.addLanguage(_lang)
239     await _registry.loadLanguage(_lang)
240 }
241
242 function getLoadedThemes() {
243     return _registry.getLoadedThemes()
244 }
245
246 function getLoadedLanguages() {
247     return _registry.getLoadedLanguages()
248 }
249
250 function getBackgroundColor(theme?: StringLiteralUnion<Theme>) {
251     const { _theme } = getTheme(theme)
252     return _theme.bg
253 }
254
255 function getForegroundColor(theme?: StringLiteralUnion<Theme>) {
256     const { _theme } = getTheme(theme)
257     return _theme.fg
258 }
259
260 return {
261     codeToThemedTokens,
262     codeToHtml,
263     getTheme: (theme: IThemeRegistration) => {
264         return getTheme(theme)._theme
265     },

```

```
266     loadTheme,  
267     loadLanguage,  
268     getBackgroundColor,  
269     getForegroundColor,  
270     getLoadedThemes,  
271     getLoadedLanguages,  
272 }  
273 }  
274  
275 function isPlaintext(lang: string | null | undefined) {  
276     return !lang || ['plaintext', 'txt', 'text'].includes(lang)  
277 }  
278
```