B2B INTELLICA- AN AI-DRIVEN PRIVACY-PRESERVING BUSINESS INTELLIGENCE FRAMEWORK FOR MANUFACTURING USING DIFFERENTIAL PRIVACY AND ZERO-KNOWLEDGE AUTHENTICATION

Vithana V A S

(IT22282286)

BSc (Hons) in Information Technology

Specializing in Information Technology

Department of Information Technology

Sri Lanka Institute of Information Technology

Sri Lanka

April 26, 2026

B2B INTELLICA- AN AI-DRIVEN PRIVACY-PRESERVING BUSINESS INTELLIGENCE FRAMEWORK FOR MANUFACTURING USING DIFFERENTIAL PRIVACY AND ZERO-KNOWLEDGE AUTHENTICATION

Vithana V A S

(IT22282286)

(Final documentation in partial fulfilment of the requirement for the Degree of Bachelor of Science Special (honors) In Information Technology Specializing in Information Technology)

BSc (Hons) in Information Technology

Specializing in Information Technology

Department of Information Technology

Sri Lanka Institute of Information Technology

Sri Lanka

April 26, 2026

DECLARATION OF THE CANDIDATE AND SUPERVISOR

I declare that this is my own work and this dissertation does not incorporate without acknowledgment any material previously submitted for a degree or diploma in any other university or Institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgment is made in the text.

Name	Student ID	Signature
V.A.S Vithana	IT22282286	

The above candidate is carrying out research for the undergraduate Dissertation under my supervision.

Supervisor	Affiliation	Signature	Date
Ms. Samanthi Siriwardana	York St John University, London, UK		26.04.2026
Ms. Ishara Weerathunga	Dept. of Information Technology, SLIIT		26.04.2026
Ms. Lokesha Weerasinghe	Dept. of Information Technology, SLIIT		26.04.2026

ABSTRACT

This study presents a novel local-first Federated Business Intelligence (BI) framework, B2B Intellica, designed specifically for manufacturing environments, addressing critical privacy and security challenges inherent in collaborative analytics. The system enables multiple manufacturing organizations to share intelligence and derive actionable insights without ever exposing raw data beyond their own boundaries. Key innovations include: (1) the integration of Differential Privacy (DP) into association rule mining to mathematically protect analytical outputs before cross-organizational sharing; (2) the implementation of a Zero-Knowledge Proof (ZKP)-based authentication mechanism for secure, credential-free identity verification; and (3) a federated analytics framework facilitating privacy-preserving collaboration through a local-first architecture. Additionally, time-series forecasting models (Prophet and ARIMA) and privacy-aware KPI validation were incorporated to support decision-ready analytics. The experimental results, evaluated on a real-world FMCG manufacturing sales dataset comprising 2,044,757 transactional records across 14 regional nodes, demonstrate a favourable privacy-utility trade-off, robust security against common attacks, and system performance suitable for real-time manufacturing operations. The system achieves up to 92% analytical accuracy at $\varepsilon = 1.0$ while maintaining an authentication latency below 50 ms, confirming practical viability at industrial scale. This work directly addresses the research gap identified in Section 1.2 by being the first system to unify local-first architecture, DP-protected association rule mining, ZKP authentication, federated analytics, and privacy-aware forecasting into a single production-ready platform — evaluated on real Sri Lankan FMCG manufacturing data with formally proven privacy guarantees.

Keywords : Differential Privacy; Zero-Knowledge Proof; Manufacturing Intelligence; Association Rule Mining; Privacy-Preserving Analytics

ACKNOWLEDGEMENT

Several people played important roles in accomplishing this research. First, I would like to express my deepest appreciation and heartfelt gratitude to my supervisors Ms. Samanthi Siriwardana (York St John University, London), Ms. Ishara Weerathunga, and Ms. Lokesha Weerasinghe (Department of Information Technology, SLIIT), who provided unwavering guidance, continuous support, and insightful direction throughout the entire research journey. Their expertise in privacy-preserving systems, machine learning, and software engineering was invaluable in shaping both the theoretical foundations and practical implementation of this work.

I also wish to thank Sri Lanka Institute of Information Technology for providing the resources, infrastructure, and academic environment that made this research possible. The academic staff of the Department of Information Technology have been a constant source of encouragement and intellectual inspiration.

Special appreciation is extended to the organizations that provided access to the real-world FMCG manufacturing sales dataset used in the experimental evaluation of this system. Their willingness to contribute anonymized operational data across 14 regional nodes was essential to demonstrating the practical viability of the proposed framework at industrial scale.

Finally, I wish to express my deepest gratitude to my family for their unconditional love, patience, and moral support throughout my four years of study. Their encouragement was the foundation upon which this work was built.

TABLE OF CONTENTS

DECLARATION OF THE CANDIDATE AND SUPERVISOR----------3
ABSTRACT ----------4
ACKNOWLEDGEMENT----------5
TABLE OF CONTENTS----------6
LIST OF FIGURES ----------8
LIST OF TABLES---------- 10
LIST OF ABBREVIATIONS---------- 11
1. INTRODUCTION----------3
1.2 Research Gap ----------8
1.3 Research Problem ----------9
1.4 Research Objectives ---------- 10
1.4.1 Main Objective ---------- 10
1.4.2 Specific Objectives ---------- 11
2. METHODOLOGY ---------- 12
2.1 Understanding the Key Pillars of the Research Domain ---------- 12
2.1.1 Differential Privacy---------- 12
2.1.2 Zero-Knowledge Proofs ---------- 12
2.1.3 Association Rule Mining with Privacy ---------- 13
2.1.4 Federated Analytics Framework---------- 14
2.1.5 Time-Series Forecasting ---------- 14
2.2 Approach and System Architecture ---------- 15
2.2.1 Methodology of the Approach ---------- 15
2.2.2 Data Collection---------- 16
2.2.3 System Design Decisions---------- 16
2.4 High-Level Architecture Diagram---------- 17
2.5 Project Requirements that have been Achieved ---------- 18
2.5.1 Functional Requirements ---------- 18
2.5.2 Non-Functional Requirements ---------- 19
2.5.3 Other Requirements ---------- 20
2.6 Consideration of Aspects of the System ---------- 20
2.6.1 Social Aspects ---------- 20
2.6.2 Security Aspects ---------- 21
2.6.3 Ethical Aspects ---------- 21
2.6.4 Limitations ---------- 21
2.7 Commercialization Aspects of the Product ---------- 22
2.7.1 Target Audience---------- 22
2.7.2 Market Space ---------- 22
2.7.3 Revenue Earning ---------- 23

2.8 Testing and Implementation ---------- 23
2.8.1 System Interface — Landing Page ---------- 23
2.8.2 Workspace Registration — ZKP Keypair Generation ---------- 24
2.8.3 Private Key Recovery — OTP Flow ---------- 25
2.8.4 ZKP Login — Three-Step Authentication Protocol ---------- 27
2.8.5 Post-Login Welcome Dashboard ---------- 28
2.8.6 Common Collaboration Hub — Federated Industry Benchmarks ---------- 29
2.8.7 Company Overview Dashboard ---------- 30
2.8.8 Data Upload Interface ---------- 31
2.8.9 Training and Forecasting — Automatic Model Selection ---------- 31
2.8.10 Forecast Results — Prophet vs Naive Baseline ---------- 32
2.8.11 Combo Engine — Association Rule Mining Results ---------- 33
2.8.12 Bundle Details — Detailed Analytics with Business Recommendation ---------- 33
2.8.13 Share with Differential Privacy ---------- 34
2.8.14 Cross-Organisation Bundle Sharing ---------- 35
2.8.15 Code Implementation — Zero-Knowledge Proof Authentication ---------- 35
2.8.16 Code Implementation — Differential Privacy (Gaussian Mechanism) ---------- 36
2.8.17 Code Implementation — Association Rule Mining ---------- 38
2.8.18 Code Implementation — Time-Series Forecasting ---------- 39
2.8.19 Code Implementation — Privacy Budget Tracking and Composition ---------- 39
2.8.20 Code Implementation — Federated Weighted Averaging and Quality Scoring ---------- 39
2.8.21 Code Implementation — A/B Testing and KPI Validation (T-Test with Cohen's d) ---------- 41
2.8.22 Testing ---------- 41
2.9 Tools and Technologies ---------- 43
3. RESULTS AND DISCUSSION ---------- 44
3.1 Results ---------- 44
3.1.1 Privacy-Utility Trade-off Results ---------- 45
3.1.3 System Performance Results ---------- 46
3.1.4 Forecasting Model Accuracy Results ---------- 47
3.2 Research Findings and Discussion ---------- 48
3.2.1 Mapping of Research Objectives to Achieved Outcomes ---------- 48
3.2.2 Discussion of Key Findings ---------- 49
3.2.3 Comparison with Existing Approaches ---------- 50
3.2.4 Threat Model and Security Analysis Summary ---------- 51
4. CONCLUSION ---------- 52
4.1 Summary of Contributions ---------- 52
4.2 Limitations ---------- 53
4.3 Future Work ---------- 54
5. REFERENCES ---------- 56

6. APPENDICES ---------- 59

LIST OF FIGURES

Figure 2.1.2: ZKP Three-Step Challenge-Response Authentication Protocol 13
Figure 2.1.3: Privacy-Preserving Association Rule Mining Workflow 14
Figure 2.2.1: Methodology of the Approach — Privacy-Preserving Local-First Analytics Pipeline 15
Figure 2.4.1: High-Level Architecture of B2B Intellica showing local-first nodes and federated coordination layer 18
Figure 2.8.1: B2B Intellica Landing Page showing core value proposition and key performance metrics 24
Figure 2.8.2: Workspace registration interface — ZKP keypair generated on sign-up; private key shown once only 25
Figure 2.8.3: Private key recovery — initial OTP request screen 25
Figure 2.8.4: Private key recovery — OTP verification screen with registration number display 26
Figure 2.8.5: Password recovery OTP email received by user — B2B Intellica branded delivery 26
Figure 2.8.6: New private key generated — immediate download confirmation screen 26
Figure 2.8.7: Downloaded private key file contents — 256-bit hexadecimal key with security instructions 27
Figure 2.8.8: ZKP login — Step 1: email lookup and registration number retrieval 28
Figure 2.8.9: ZKP login — Step 2: challenge nonce display and private key entry modal (key never transmitted) 28
Figure 2.8.10: Post-login welcome dashboard with company workspace and federated system capabilities 29
Figure 2.8.11: Common Collaboration Hub — privacy-preserved industry benchmarks from federated analytics 30
Figure 2.8.12: Company overview dashboard with monthly trend and Sri Lanka regional performance map 31
Figure 2.8.13: Data upload interface — 45,146 records successfully processed to local Apache Parquet storage 31
Figure 2.8.14: Training and Forecasting — automatic model selection with Prophet recommended at 92% confidence 32
Figure 2.8.15: Forecast results — Prophet (MAE 0.882, MAPE 5.46%) vs Naive Baseline (MAPE 18.93%) 32
Figure 2.8.16: Combo Engine results — 50 association rules discovered from 9,000 local transaction baskets 33
Figure 2.8.17: Bundle details popup — BABY VENIVAL → BABY 4IN1 with detailed analytics and AI recommendation 34
Figure 2.8.18: Share with Differential Privacy modal — real-time ε = 1.0 noise preview on bundle metrics 34
Figure 2.8.19: Share bundle modal — cross-organisation sharing with tenant isolation by registration number 35

Figure 2.8.20: Code snippet — ZKP keypair generation using Python secrets module.....36
Figure 2.8.21: Code snippet — ZKP challenge generation and proof verification (Steps 2 and 3) 36
Figure 2.8.22: Code snippet — Gaussian mechanism for (ε, δ)-differential privacy with gradient clipping 36
Figure 2.8.22a: Code snippet — Global sensitivity Δf computation for support, confidence, and lift metrics 37
Figure 2.8.22a: Code snippet — Gaussian σ calibration formula; lower ε yields larger σ and stronger privacy 37
Figure 2.8.22c: Code snippet — Per-rule Gaussian noise applied to support, confidence, and lift before sharing.....38
Figure 2.8.23: Code snippet — Privacy-preserving ARM using Apriori/FP-Growth on local Parquet data.....38
Figure 2.8.24: Code snippet — Prophet and ARIMA(1,1,1) forecasting with MAE and MAPE evaluation.....39
Figure 2.8.25: Code snippet — Privacy budget tracking with basic composition theorem; warning at 80%, blocking at 100% 39
Figure 2.8.26: Code snippet — Federated weighted averaging with quality scoring (W_global = Σ(q_i × W_i) / Σq_i) 40
Figure 2.8.26a: Code snippet — Local model upload: clip → DP noise → quality score → submit (raw data never transmitted) 40
Figure 2.8.26b: Code snippet — Server-side FedAvg: collect DP updates → weighted average → persist global model 41
Figure 2.8.27: Code snippet — A/B testing with two-sample T-test and Cohen's d effect size for KPI validation 41
Figure 3.1.1: Privacy–Utility Trade-off (Analytical Accuracy vs. Epsilon).....45
Figure 3.1.2: Prophet vs. ARIMA vs. Exponential Smoothing — Comparative MAPE performance and visual bar comparison (lower MAPE = better accuracy).....51
Figure 6.1: Plagiarism Report 59

LIST OF TABLES

Table 1.2.1 - Comparison with Existing Systems and Identification of Research Gap 8
Table 1.2.2:Privacy-Preserving Federated BI vs. Prior Systems 9
Table 2.2.1 - Summary of Methodology — Five-Stage Pipeline 16
Table 2.5.1: Functional Requirements Achieved 18
Table 2.5.2: Non-Functional Requirements 19
Table 2.8.1: Privacy Budget (Epsilon) Interpretation 23
Table 2.8.2: Dataset Distribution Across 14 Federated Nodes (with per-node record ranges and volume categories) 42
Table 2.8.3: Unit and Integration Test Results Summary 42
Table 2.8.4: Security Assessment — ZKP Authentication Attack Resistance 43
Table 2.9.1: Tools and Technologies Used in B2B Intellica 43
Table 3.1.1: Privacy-Utility Trade-off Results (Full Dataset, 14-Node Federated Environment) 45
Table 3.1.2: ZKP vs Traditional Password Authentication — Feature Comparison 46
Table 3.1.3: System Performance — Key Operations Response Times 47
Table 3.1.4: Forecasting Model Accuracy Summary 47
Table 3.2.1: Mapping of Research Objectives to Achieved Outcomes 48
Table 3.2.2: Comparison of Proposed System with Existing Approaches 50
Table 3.2.3: Threat Model and Security Analysis Summary 51

LIST OF ABBREVIATIONS

Abbreviation	Expansion
BI	Business Intelligence
DP	Differential Privacy
ZKP	Zero-Knowledge Proof
FMCG	Fast-Moving Consumer Goods
KPI	Key Performance Indicator
ML	Machine Learning
ARM	Association Rule Mining
FP-Growth	FP-Growth (Frequent Pattern Growth)
ARIMA	Autoregressive Integrated Moving Average
API	Application Programming Interface
JWT	JSON Web Token
OTP	One-Time Password
REST	Representational State Transfer
OLAP	Online Analytical Processing
MAE	Mean Absolute Error
MAPE	Mean Absolute Percentage Error
ε (epsilon)	Privacy Budget Parameter in Differential Privacy
δ (delta)	Failure Probability in (ε, δ)-Differential Privacy
Δf	Global Sensitivity of a Query Function
SHA-256	Secure Hash Algorithm — 256-bit
CRDT	Conflict-free Replicated Data Type (Local-first concept)
FedAvg	Federated Averaging Algorithm
FIDO2	Fast Identity Online 2 (Credential-free authentication standard)
IoT	Internet of Things
SLIIT	Sri Lanka Institute of Information Technology
GDPR	General Data Protection Regulation
SKU	Stock Keeping Unit

1. INTRODUCTION

Business Intelligence (BI) systems have become indispensable in manufacturing, enabling organizations to transform vast amounts of operational data into actionable insights that enhance efficiency and decision-making [1] [2]. These systems support process optimization, predictive maintenance, supply chain management, and quality control, thereby driving competitive advantages [3] [4]. However, traditional centralized BI approaches face significant challenges including data silos that limit comprehensive analysis, latency issues due to centralized data aggregation, and heightened risks of data breaches caused by storing sensitive information in a single location. In manufacturing, where operational data often includes proprietary process details and competitive metrics, safeguarding data privacy and security is paramount to prevent intellectual property losses and ensure regulatory compliance [3] [4].

This study addresses the challenge of enabling collaborative BI across multiple manufacturing organizations without exposing raw data outside their respective boundaries. The core research question is: How can organizations share intelligence and collaboratively derive meaningful insights while preserving the confidentiality of their underlying data? Key challenges include maintaining stringent data privacy, implementing secure and privacy-preserving authentication, generating meaningful analytics under privacy constraints, and ensuring that the system remains usable and practical for manufacturing stakeholders.

This research introduces B2B Intellica — a novel local-first Federated Business Intelligence framework in which raw data never leave organizational boundaries. Unlike existing BI systems that rely on centralized data collection or isolated privacy techniques, the proposed system integrates Differential Privacy into association rule mining, implements Zero-Knowledge Proof authentication for secure access, and combines these with forecasting, KPI validation, and dashboard-driven decision support. This unified approach transforms privacy-preserving analytics into actionable business intelligence, representing a practical and scalable solution for Sri Lankan manufacturing environments and beyond.

The system was implemented and evaluated on a real-world FMCG manufacturing sales dataset comprising 2,044,757 transactional records across 14 regional sales nodes in Sri Lanka, achieving up to 92% analytical accuracy at $\varepsilon = 1.0$ differential privacy budget, with authentication latency below 50 ms — confirming practical viability at industrial scale.

1.1 Background and Literature Survey

This section reviews the key bodies of literature underpinning B2B Intellica. For each major research pillar, the state of the art is summarized and critically evaluated to identify the specific gaps that motivate the proposed system. The review covers: federated learning and federated analytics; differential privacy; association rule mining with privacy; zero-knowledge proofs; business intelligence in manufacturing; and local-first architecture.

Federated Learning and Federated Analytics

Federated learning, introduced by McMahan et al. [5], is a distributed machine learning paradigm that enables multiple participants to collaboratively train models without sharing raw data. Each participant trains a local model on its data and shares only model updates, which are aggregated centrally or decentrally [6] [7]. Yang et al. [8] formally defined federated machine learning and explored its applications across heterogeneous settings. Li et al. [9] identified key challenges including communication efficiency, statistical heterogeneity, and privacy guarantees during aggregation. Kairouz et al. [6] provided a comprehensive survey of advances and open problems in federated learning, noting that privacy guarantees during aggregation remain insufficiently addressed. Bonawitz et al. [7] proposed scalable system designs for federated learning at production scale. In BI contexts, Kairouz et al. [10] introduced the concept of federated analytics — applying federated principles to statistical analysis without sharing raw data. Boobalan et al. [11] surveyed the fusion of federated learning and industrial IoT, while Li et al. [12] examined the gap between theoretical promise and practical deployment. Rani et al. [13] provided a multifaceted survey on privacy preservation in federated learning, highlighting that most current implementations lack strong authentication mechanisms.

Critical evaluation: *None of the federated learning studies reviewed integrates BI analytics, association rule mining, or ZKP-based authentication. These works address model training, not collaborative decision-support analytics. This gap directly motivates the federated analytics component of B2B Intellica.*

Differential Privacy

Differential Privacy (DP), introduced by Dwork [14], provides a mathematical framework for quantifying and limiting the risk of disclosing individual data points through analytical outputs. Formally, a

mechanism M satisfies ε-differential privacy if: $Pr[M(D_1) \in S] \leq e^{\varepsilon} \times Pr[M(D_2) \in S]$ for all neighbouring datasets D_1, D_2. Dwork and Roth [15] established the algorithmic foundations of differential privacy, providing rigorous proofs of the Laplace and Gaussian mechanisms. McSherry and Talwar [16] developed the Laplace mechanism for mechanism design, while Dwork et al. [17] formalized the calibration of noise to query sensitivity. Xiao et al. [18] applied DP to wavelet transforms for complex data analysis. Lee and Clifton [19] addressed the critical practical question of choosing appropriate epsilon values for real-world deployments. Lee et al. [20] applied privacy-preserving techniques to neural networks in smart manufacturing. Cummings et al. [21] reviewed the current state of DP deployment, noting persistent challenges in balancing utility and privacy in industrial settings. Demelius et al. [22] provided a systematic survey of DP in deep learning. Pan et al. [23] reviewed DP applications across neural network architectures. Subramanian [24] demonstrated that differential privacy can enable precise analytics without privacy loss.

Critical evaluation: *While DP has been extensively studied for query outputs and model parameters, no prior work applies DP directly to association rule metrics (support, confidence, lift) in a federated BI setting with user-configurable epsilon. The existing literature applies DP in isolation — not as part of an integrated BI platform with authentication and forecasting.*

Association Rule Mining with Privacy

Association Rule Mining (ARM) identifies interesting correlations within datasets. Agrawal and Srikant [25] introduced the seminal Apriori algorithm for mining frequent itemsets. Han et al. [26] proposed FP-Growth as a more computationally efficient alternative. Evfimievski et al. [27] studied privacy-preserving ARM using randomisation. Rizvi and Haritsa [28] addressed privacy maintenance in association rule mining. Agrawal and Aggarwal [29] formalized privacy-preserving data mining algorithms. Clifton et al. [30] developed tools for privacy-preserving distributed data mining. Chen et al. [31] proposed privacy-preserving federated mining of frequent itemsets for collaborative settings, while Wu et al. [32] developed a framework for IoT using federated learning. Zehtabchi et al. [33] proposed homomorphic encryption for secure ARM, and Wu and Hao [34] applied this to cloud databases. Hewage et al. [35] provided a systematic literature review of privacy-preserving data mining techniques. Yang et al. [18] proposed federated machine learning with model IP protection.

Critical evaluation: *Chen et al.* [31] *and Wu et al.* [32] *represent the closest prior work to B2B Intellica's*

ARM component. However, neither integrates ZKP authentication, interactive dashboards, or time-series forecasting. Zehtabchi et al. [33] *and Wu and Hao* [34] *use homomorphic encryption which, while theoretically stronger, is computationally prohibitive at the dataset scale (2M+ records) addressed in this research. The DP-based approach in B2B Intellica provides a computationally feasible alternative with tunable privacy-utility trade-offs.*

Zero-Knowledge Proofs

Zero-Knowledge Proofs (ZKPs), introduced by Goldwasser, Micali, and Rackoff [36], are cryptographic protocols allowing a prover to demonstrate knowledge of a secret without revealing the secret itself. Damgård [37] developed the Sigma-protocol framework forming the basis of practical ZKP implementations. Schnorr [38] introduced efficient identification protocols for smart cards. Chen et al. [39] surveyed ZKP applications for IoT authentication. Ahmad et al. [40] proposed blockchain-based multi-factor authentication using ZKP for smart city applications. Würsching et al. [41] evaluated FIDO2 platform authentication as an alternative credential-free method. Gharib et al. [42] combined blockchain and ZKP for mutual authentication in IoT networks. The security analysis of ZKP systems confirms resistance to impersonation, replay, and man-in-the-middle attacks — advantages over traditional password-based methods that fundamentally expose credentials through transmission and storage.

Critical evaluation: *All reviewed ZKP implementations address authentication in isolation — none integrates ZKP as the authentication layer of a BI system. Furthermore, existing implementations such as Ahmad et al.* [40] *and Gharib et al.* [42] *rely on blockchain infrastructure, which introduces latency and infrastructure complexity unsuitable for the sub-50 ms manufacturing BI requirement. B2B Intellica's hash-based ZKP implementation achieves the same security properties with significantly lower overhead.*

Business Intelligence in Manufacturing

Manufacturing has increasingly adopted BI systems to enhance operational visibility and decision-making [1] [2]. Chen et al. [1] established the foundational framework linking big data analytics to business impact. Yeoh and Koronios [2] identified critical success factors for BI implementations. Lee et al. [3] proposed a cyber-physical systems architecture for Industry 4.0. Zheng et al. [4] developed smart manufacturing conceptual frameworks. Jan et al. [43] provided a systematic review of AI for Industry 4.0, identifying privacy as a key unsolved challenge. Xu et al. [14] reviewed deep learning challenges in smart

manufacturing. Kashpruk et al. [44] reviewed time-series prediction methods for Industry 4.0, while Fatima and Rahimi [45] reviewed forecasting algorithms for industrial systems. Hellmeier et al. [46] studied data sovereignty requirements in enterprise practice. Fugkeaw et al. [47] addressed secure OLAP for encrypted cloud data warehouses, and Cuzzocrea [48] studied privacy-preserving OLAP against large query workloads. Zanasi et al. [49] proposed a microservice framework for DP-based protection in industrial IoT.

Critical evaluation: *Existing manufacturing BI literature identifies privacy as a critical challenge* [3] [4] [43] *but proposes no unified solution. Zanasi et al.* [49] *is the closest work to B2B Intellica in addressing DP for industrial IoT, but targets sensor data rather than transactional sales analytics, and does not include authentication or federated coordination. Fugkeaw et al.* [47] *and Cuzzocrea* [48] *address privacy-preserving OLAP but require centralised encrypted databases rather than the local-first architecture employed in this research.*

Local-First Architecture

Kleppmann et al. [15] introduced the concept of local-first software, advocating for data storage and processing to occur locally within organizational boundaries, with synchronization of sanitized summaries rather than raw data. Haas et al. [50] developed a programming model for verifiably safe local-first software. This architectural philosophy directly aligns with the privacy requirements of manufacturing BI, where raw transactional data contains sensitive competitive information that must not leave the organization. Hellmeier et al. [46] documented practical requirements and challenges of implementing data sovereignty in enterprise settings. Zanasi et al. [49] demonstrated the feasibility of privacy-preserving local processing at industrial scale.

Synthesis of Literature: *The literature across all five pillars reveals a consistent and significant gap: privacy techniques, authentication mechanisms, and federated architectures have been studied extensively but applied independently. No existing system unifies differential privacy applied to association rule mining, ZKP authentication, federated analytics coordination, and time-series forecasting in a single local-first BI framework evaluated at real industrial scale. B2B Intellica is designed to fill precisely this gap.*

1.2 Research Gap

As demonstrated by the synthesis of literature above, and confirmed by the critical evaluations of each research pillar, no existing system combines all five capabilities required for privacy-preserving collaborative manufacturing BI: (1) a local-first architecture that keeps raw data within organizational boundaries; (2) Differential Privacy applied directly to association rule mining outputs; (3) Zero-Knowledge Proof-based authentication that eliminates credential transmission; (4) federated analytics aggregation without centralized raw data; and (5) privacy-aware time-series forecasting with decision-support dashboards. As shown in Table 1.2.1, each existing system addresses at most two or three of these requirements, leaving a clear and unaddressed research gap.

Table 1.2.1 - Comparison with Existing Systems and Identification of Research Gap

Reference	**Key Features**	**Technology Used**	**Limitation**
Traditional BI [1] [2]	Centralized analytics, dashboards, reporting	SQL/OLAP, centralized DB	No local-first architecture; no privacy-utility trade-off control; raw data must be centralized; high breach risk
Federated Learning [8] [5] [9] [6] [7]	Distributed model training, no raw data shared	FedAvg, model aggregation	No local-first BI; no ZKP auth; no ARM or forecasting; no privacy-utility trade-off interface
DP-Only Systems [14] [15] [17]	Noise injection to protect query outputs	Laplace/Gaussian mechanism	No local-first architecture; no privacy-utility trade-off control; no ZKP authentication; no federated BI
Privacy-Preserving ARM [31] [32]	Federated mining of association rules	Federated + DP	No local-first architecture; no privacy-utility trade-off UI; no ZKP auth; no forecasting dashboard
Homomorphic ARM [33] [34]	Cryptographically secure ARM	Homomorphic encryption	No local-first architecture; computationally infeasible at 2M+ scale; no privacy-utility trade-off control
ZKP Auth [39] [40] [42]	Credential-free identity verification	Sigma-protocol, blockchain	Standalone auth only; no local-first BI; no privacy-utility trade-off; blockchain latency >500 ms
Local-First Software [15][50]	Data locality, data sovereignty architecture	CRDTs, local storage	No analytics; no differential privacy; no privacy-utility trade-off; no ZKP authentication
Industrial IoT	DP for sensor data in	Microservice +	Sensor data only; no local-first

Reference	Key Features	Technology Used	Limitation
DP [49]	industrial IoT	DP	transactional BI; no privacy-utility trade-off UI; no ZKP auth
B2B Intellica (Proposed)	**Unified local-first federated BI: DP + ZKP + ARM + forecasting + dashboard**	**FastAPI, React, MLxtend, Prophet, ARIMA**	**First fully integrated system — evaluated on 2,044,757 real records, 14 nodes**

Table 1.2.2:Privacy-Preserving Federated BI vs. Prior Systems

Feature	**Traditional BI**[1][2]	**Federated Learning**[5][6][7][8][9]	**DP-Only Systems**[14][15][17]	**Privacy ARM**[31][32]	**Homomorphic Encrypt.**[33][34]	**Proposed System**
Local-first raw data architecture	✗	✗	✗	✗	✗	✓
DP applied to analytical outputs	✗	✗	✓	✓	✗	✓
ZKP credential-free authentication	✗	✗	✗	✗	✗	✓
Federated BI analytics aggregation	✗	✗	✗	✗	✗	✓
Privacy-utility trade-off control (ε UI)	✗	✗	✗	✗	✗	✓
Time-series forecasting with privacy guarantees	✗	✗	✗	✗	✗	✓
Interactive BI dashboard	✗	✗	✗	✗	✗	✓
Sri Lankan FMCG deployment & validation	✗	✗	✗	✗	✗	✓

1.3 Research Problem

The problem of enabling collaborative business intelligence across multiple manufacturing organizations while preserving the confidentiality of raw data represents a critical unsolved challenge in the field of privacy-preserving analytics. In Sri Lanka's manufacturing sector, particularly in the FMCG industry,

companies operate across multiple regional nodes and supply chains. While there is an increasing need for cross-organizational intelligence — such as understanding product bundle patterns, regional demand trends, and competitive benchmarks — the sensitive and competitive nature of transactional data makes sharing raw records with centralized systems unacceptable.

Traditional BI systems require all raw data to be aggregated into a centralized server, creating single points of failure, regulatory compliance risks, and intellectual property exposure. Federated learning approaches address data locality but do not provide the full BI capabilities manufacturing stakeholders require — association rule mining, forecasting, KPI validation, and interactive dashboards. Furthermore, most existing privacy-preserving systems rely on password-based authentication, remaining vulnerable to credential theft, replay attacks, and man-in-the-middle attacks. The absence of a unified solution forces manufacturing organizations to choose between sharing raw data (compromising confidentiality) or working in complete isolation (forgoing the cross-organizational intelligence that drives competitive advantage).

B2B Intellica was designed to eliminate this false dichotomy by providing: (1) strict data locality through local-first Apache Parquet storage; (2) mathematically provable privacy guarantees through Differential Privacy on analytical outputs; (3) credential-free authentication through Zero-Knowledge Proofs; (4) cross-organizational intelligence sharing through federated analytics; and (5) decision-ready insights through interactive, multilingual dashboards.

1.4 Research Objectives

1.4.1 Main Objective

The primary objective of this research was to design, implement, and evaluate a novel local-first Federated Business Intelligence framework for manufacturing environments that enables multiple organizations to collaborate on analytics and intelligence sharing without exposing raw transactional data beyond their own boundaries, while providing mathematically provable privacy guarantees and cryptographically secure authentication.

1.4.2 Specific Objectives

To design and implement a local-first architecture in which all raw transactional data remain within each organization's local storage, with only sanitized, privacy-protected analytical outputs being shared across organizational boundaries.

To integrate Differential Privacy (Gaussian mechanism) into association rule mining — protecting support, confidence, and lift metrics before cross-organizational sharing, with a configurable privacy budget (epsilon) to support user-defined privacy-utility trade-offs.

To develop a Zero-Knowledge Proof-based authentication mechanism enabling users to prove their identity without transmitting or storing passwords on the server, providing provable resistance against impersonation, replay, and man-in-the-middle attacks.

To implement a federated analytics framework that aggregates only privacy-preserved model outputs from multiple participating organizations, enabling collaborative intelligence without centralized raw data storage.

To incorporate time-series forecasting models (Prophet and ARIMA) and A/B testing-based KPI validation within the privacy-preserving framework to deliver decision-ready insights for manufacturing operations.

To evaluate the complete system on a real-world FMCG dataset of 2,044,757 records across 14 federated nodes, measuring privacy-utility trade-offs, authentication security, system performance, and forecasting accuracy at industrial scale.

2. METHODOLOGY

2.1 Understanding the Key Pillars of the Research Domain

B2B Intellica relies on five key technical pillars: Differential Privacy, Zero-Knowledge Proofs, Association Rule Mining, Federated Analytics, and Time-Series Forecasting. Each is described below with its theoretical foundation, mathematical formalization where applicable, and specific role in the proposed system.

2.1.1 Differential Privacy

Differential Privacy (DP) provides a mathematical guarantee that the inclusion or exclusion of any single individual's data will not significantly affect the output of an analytical query. Formally, a randomised mechanism M satisfies ε-differential privacy if, for all datasets D_1 and D_2 differing in exactly one record, and for all subsets of outputs S:

$$Pr[M(D_1) \in S] \leq e^{\varepsilon} \times Pr[M(D_2) \in S]$$

The Laplace mechanism achieves ε-DP by adding noise drawn from Laplace(0, Δf/ε), where Δf is the global sensitivity of the query function f, defined as $\Delta f = \max|f(D_1) - f(D_2)|$. The Gaussian mechanism provides (ε, δ)-DP by adding noise from $N(0, \sigma^2)$ where $\sigma = \Delta f \times \sqrt{(2 \ln(1.25/\delta))} / \varepsilon$. In B2B Intellica, the Gaussian mechanism is applied to model weights and analytical metrics before federated sharing. A lower epsilon value provides stronger privacy at the cost of analytical accuracy; a higher epsilon reduces noise but weakens privacy protection. The system supports user-configurable epsilon values of 0.1, 0.5, 1.0, and 2.0, evaluated experimentally to characterise the privacy-utility trade-off.

Cumulative privacy budget tracking is implemented using the basic composition theorem: if k mechanisms are applied with budgets $\varepsilon_1, \varepsilon_2, ..., \varepsilon_k$, the total privacy cost is $\varepsilon_total = \Sigma\varepsilon_i$. The system tracks this cumulative budget per tenant across all sharing operations, issuing warnings at 80% of the maximum recommended budget (10.0) and blocking further queries at 100%.

2.1.2 Zero-Knowledge Proofs

A Zero-Knowledge Proof (ZKP) is a cryptographic protocol in which a prover demonstrates knowledge

of a secret without revealing the secret itself. The protocol must satisfy three properties: (1) Completeness — an honest prover with the correct secret always convinces the verifier; (2) Soundness — a prover without the secret cannot convince the verifier except with negligible probability; (3) Zero-knowledge — the verifier learns nothing about the secret beyond the fact that the prover possesses it. In B2B Intellica, the ZKP uses a challenge-response protocol: the server generates a 128-bit random nonce as a challenge; the client computes proof = SHA-256(challenge ‖ public_key)[:32] using the private key locally; the server verifies the proof by independently recomputing the expected hash against the stored public key. Since the private key is never transmitted, the server verifies identity without ever receiving or storing the secret credential (Figure 2.1.2).



Figure 2.1.2: ZKP Three-Step Challenge-Response Authentication Protocol

2.1.3 Association Rule Mining with Privacy

Association Rule Mining (ARM) discovers relationships of the form $\{A\} \rightarrow \{B\}$ with associated metrics: support = $P(A \cup B)$, confidence = $P(B|A) = P(A \cup B)/P(A)$, and lift = $P(A \cup B)/(P(A) \times P(B))$. Two algorithms are used: Apriori [20], which generates candidate itemsets iteratively with level-wise pruning, and FP-Growth [21], which uses a compressed prefix tree structure for more efficient mining without candidate generation. Differential privacy is applied to these metrics by adding Laplace or Gaussian noise calibrated to their sensitivities before any cross-organisational sharing occurs (Figure 2.1.3).



Figure 2.1.3: Privacy-Preserving Association Rule Mining Workflow

2.1.4 Federated Analytics Framework

Federated analytics [10] enables cross-organisational insights through aggregation of privacy-preserved local results. In B2B Intellica, each organisation performs all primary analytics locally. Only noised model outputs are transmitted to the coordination layer. Aggregation uses Weighted FedAvg, where each participant's contribution is weighted by a data quality score q_i computed as $q_i = (\min(samples_i/1000, 1) + \min(time_periods_i/24, 1)) / 2$. Weighted averaging was chosen over simple averaging because it proportionally increases the influence of higher-quality data contributions, improving the accuracy of the global model. The aggregated global weights $W_{global} = \Sigma(q_i \times W_i) / \Sigma q_i$ are then made available to all participants as the global federated model.

2.1.5 Time-Series Forecasting

Two complementary forecasting models are implemented. Prophet [51] decomposes time series as $y(t) = trend(t) + seasonality(t) + holidays(t) + \varepsilon(t)$, using a piecewise linear or logistic trend model with Fourier series seasonality. Prophet is particularly effective for FMCG data with annual seasonality patterns and irregular events. ARIMA(1,1,1) [29] [52] models the time series as: $\Delta Y_t = \varphi_1 \Delta Y_{t-1} + \varepsilon_t + \theta_1 \varepsilon_{t-}$

1}, where Δ denotes first differencing (d=1), φ_1 is the AR(1) coefficient, and θ_1 is the MA(1) coefficient. Forecasting accuracy is measured using MAE = $(1/n)\Sigma|y_t - \hat{y}_t|$ and MAPE = $(1/n)\Sigma|(y_t - \hat{y}_t)/y_t| \times 100\%$.

2.2 Approach and System Architecture

2.2.1 Methodology of the Approach

The following table illustrates the five-stage methodology followed in implementing B2B Intellica (Figure 2.2.1): data collection and local storage; privacy-preserving analytics; ZKP-secured federated participation; cross-organisational intelligence aggregation; and decision-ready insights through interactive dashboards.



Figure 2.2.1: Methodology of the Approach — Privacy-Preserving Local-First Analytics Pipeline

Table 2.2.1 - Summary of Methodology — Five-Stage Pipeline

Stage	**Component**	**Methods/ Algorithms**	**Expected Outcome**
1. Local Data Collection	Apache Parquet Storage	CSV/Excel ingestion → Parquet conversion	Raw data never leaves organizational boundary; local-first enforced
2. Privacy Analytics	Differential Privacy + ARM	Gaussian mechanism, Apriori, FP-Growth	DP-protected association rules ready for sharing
3. Authentication	ZKP Challenge-Response	SHA-256(challenge ‖ public_key), Sigma-protocol	Credential-free secure login; < 50 ms latency
4. Federated Aggregation	Weighted FedAvg Coordination	Gaussian DP on model weights; quality-weighted averaging	Global model from noised outputs; no raw data transmitted
5. Decision Support	Forecasting + KPI Validation	Prophet, ARIMA, T-test, Cohen's d	Decision-ready forecasts; validated KPIs; interactive dashboards

2.2.2 Data Collection

The primary dataset is a real-world FMCG manufacturing sales dataset comprising 2,044,757 transactional records across 14 regional sales nodes in Sri Lanka, 30 product brands, and 438 unique SKUs. All customer identifiers were anonymized prior to use (e.g., dealer codes replaced with anonymous identifiers such as DebCode: RE024263). The dataset exhibits a highly right-skewed sales quantity distribution, reflecting realistic FMCG transactional complexity. Data is stored in Apache Parquet format within each node's local environment, enabling column-efficient storage and fast analytical retrieval.

Key dataset columns include: DebCode (anonymized dealer code), Year, Month, Brand, Product Name, Region, and Net_Sales_Qty. These columns support both association rule mining (on Brand co-occurrences grouped by DebCode/Year/Month as transaction baskets) and time-series forecasting (on Net_Sales_Qty aggregated monthly).

2.2.3 System Design Decisions

Several key design decisions shaped the implementation of B2B Intellica:

- Local-first storage (Apache Parquet): Keeps all raw files on the local file system, preventing any raw data from being accessible through network connections — even to the coordination layer.
- Weighted FedAvg over simple averaging: The data quality score accounts for both sample count and temporal coverage, ensuring that participants with richer, longer-term datasets have proportionally greater influence on the global model. This directly addresses the statistical heterogeneity challenge identified by Li et al. [9].
- Basic composition for epsilon tracking: Chosen for its computational simplicity and interpretability for non-technical manufacturing users. Advanced composition (Rényi DP) would provide tighter bounds and is identified as future work.
- Hash-based ZKP over blockchain ZKP [40] [42]: Eliminates blockchain infrastructure overhead, achieving < 50 ms authentication latency compared to 500+ ms typical of blockchain-based approaches.
- FastAPI (async) backend: Supports 14 concurrent federated nodes without request blocking, essential for real-time manufacturing operations.
- MLxtend for ARM: Provides production-ready Apriori and FP-Growth with pandas DataFrame integration, enabling basket analysis on locally stored Parquet data without data transmission.

2.4 High-Level Architecture Diagram

The high-level architecture of B2B Intellica adopts a three-layer local-first federated design (Figure 2.4.1). The bottom layer (Data Layer) consists of individual organisational nodes, each with its own local Apache Parquet data store, FastAPI analytics engine, ZKP authentication module, DP noise injection module, MLxtend ARM engine, and Prophet/ARIMA forecasting module. The middle layer (Coordination Layer) is a lightweight aggregation server that receives only privacy-protected model outputs — noised association rule metrics, differentially private model weights, and aggregated KPIs — and computes the global federated model. The top layer (Collaboration Layer) is the React-based interactive dashboard accessible to authenticated users from any participating organization, presenting privacy-preserved industry benchmarks, forecasts, and bundle insights.

The data flow is strictly enforced: raw transactional data flows only horizontally within the bottom layer (i.e., within each organization's own servers). Privacy-protected analytical outputs flow vertically upward

to the coordination and collaboration layers. This architecture guarantees that even a complete compromise of the coordination server would not expose any raw transactional data.



Figure 2.4.1: High-Level Architecture of B2B Intellica showing local-first nodes and federated coordination layer

2.5 Project Requirements that have been Achieved

2.5.1 Functional Requirements

Table 2.5.1: Functional Requirements Achieved

#	**Requirement**	**Status**
FR1	Tenant registration with auto-generated ZKP keypair and unique registration number	Achieved
FR2	ZKP challenge-response login without transmitting passwords or secret keys	Achieved
FR3	Private key recovery via OTP email verification with new keypair generation	Achieved
FR4	Local-first data upload (CSV/Excel) converted to Apache Parquet format	Achieved
FR5	Association rule mining using Apriori and FP-Growth on locally stored data	Achieved
FR6	Differential Privacy noise injection on ARM metrics before	Achieved

#	Requirement	Status
	cross-org sharing	
FR7	Time-series forecasting using Prophet, ARIMA, and Exponential Smoothing	Achieved
FR8	Automatic selection of best forecasting model based on dataset characteristics	Achieved
FR9	Federated local model training with configurable DP budget (epsilon, delta)	Achieved
FR10	Cross-organisation bundle sharing with DP-protected metrics and epsilon slider	Achieved
FR11	Common Collaboration Hub with privacy-preserved industry benchmarks	Achieved
FR12	Interactive overview dashboard with Sri Lanka geographic sales map	Achieved
FR13	A/B testing with T-test and Cohen's d for KPI validation	Achieved
FR14	Cumulative privacy budget tracking with warnings at 80% threshold	Achieved
FR15	Multilingual support — English, Sinhala, Tamil	Achieved

2.5.2 Non-Functional Requirements

Table 2.5.2: Non-Functional Requirements

Requirement	Target	Achieved
Authentication Latency	< 200 ms	< 50 ms (ZKP full 3-step flow)
Association Rule Generation	< 10 seconds	~2 seconds (9,000 transactions, Apriori)
Forecast Generation	< 10 seconds	~3 seconds (Prophet, 6-period)
Analytical Accuracy (ε = 1.0)	> 85%	92% — confirmed on 2M+ records
Data Sovereignty	Raw data never leaves organisation	Achieved — local Parquet only; server stores metadata
Replay Attack Resistance	Strong (per threat model)	Achieved — challenge deleted post-use; 5-min expiry
Scalability	14+ concurrent nodes	Tested on 14 federated nodes

Requirement	Target	Achieved
Usability	Accessible without IT expertise	React UI with guided 2-step workflows
Offline Analytics	No internet for local analytics	Achieved — fully local-first processing

2.5.3 Other Requirements

Each organisational node requires Python 3.10+, Node.js 18+, and at least 4 GB RAM for concurrent federated processing. MongoDB Atlas access is required for metadata storage only — no raw data is transmitted to the cloud database. The system operates without internet access for local analytics; only the federated coordination layer requires network connectivity.

2.6 Consideration of Aspects of the System

2.6.1 Social Aspects

B2B Intellica addresses a real and pressing social need in Sri Lanka's manufacturing sector: the ability for smaller manufacturing companies to access cross-organisational intelligence previously available only to large corporations with centralised data infrastructure. By enabling privacy-preserving collaboration, B2B Intellica levels the analytical playing field — allowing any manufacturer, regardless of size, to benefit from federated market insights without compromising the confidentiality of proprietary data. The multilingual interface (English, Sinhala, Tamil) ensures accessibility across Sri Lanka's diverse manufacturing workforce. This directly contributes to the competitiveness of Sri Lanka's FMCG export sector by enabling data-driven decision-making without the data sovereignty compromises required by existing solutions.

From a regulatory standpoint, Sri Lanka’s Personal Data Protection Act (PDPA) No. 9 of 2022 [52] introduces binding obligations for organisations that collect and process personal data, including lawful processing, purpose limitation, data minimisation, and accountability. B2B Intellica operationalises PDPA compliance architecturally: raw data never leaves the originating organisation’s local infrastructure (data localisation), analytical outputs are mathematically anonymised before any sharing (data minimisation), and access is restricted to cryptographically verified participants (accountability). This makes B2B Intellica not merely a research prototype but a regulatory compliance tool with direct practical relevance to Sri Lankan FMCG manufacturers operating under this emerging data protection framework.

2.6.2 Security Aspects

Security is a foundational design principle of B2B Intellica. The ZKP authentication mechanism ensures that no password or secret credential is ever transmitted over the network or stored on the server. The private key is provided to the user only once at registration and is never recoverable from the server. Challenge tokens are single-use (deleted immediately after successful verification) and expire after five minutes, providing robust protection against replay attacks. Raw data is stored exclusively in local Apache Parquet files within each organisation's own infrastructure. The MongoDB server stores only metadata — tenant names, public keys, challenge tokens — never raw transactional data. Differential privacy mathematically bounds the information leakage from analytical outputs even if an adversary intercepts federated communications. The threat model assumes an honest-but-curious server that may attempt to infer credentials from authentication traffic, and an external adversary capable of intercepting and replaying authentication messages — both of which are addressed by the ZKP design.

2.6.3 Ethical Aspects

The research was conducted in full compliance with data protection principles. The real-world FMCG dataset was fully anonymised prior to use — all customer and dealer identifiers were replaced with anonymous codes (DebCode: RE024263, etc.). No personal or identifying information is stored, processed, or exposed at any stage of the system. The differential privacy mechanism provides a mathematical guarantee that no individual's data can be inferred from shared analytical outputs. The system is designed to support, not replace, human business judgement — association rule results and AI-generated recommendations are presented as decision aids, with final decisions remaining with human analysts. The ZKP authentication ensures that system administrators cannot access user credentials even with full database access. Additionally, the system’s design is fully aligned with the Sri Lanka Personal Data Protection Act (PDPA) No. 9 of 2022 [52], which mandates lawful processing, purpose limitation, and data minimisation — all of which are satisfied architecturally by the local-first, differential-privacy-enforced framework.

2.6.4 Limitations

- The ZKP implementation uses a SHA-256-based challenge-response simulation rather than a fully formalised elliptic curve Sigma-protocol, which would provide stronger formal security proofs.

- Basic composition is used for epsilon budget tracking; advanced composition theorems or zero-concentrated DP (zCDP) would provide tighter privacy bounds for high-frequency query scenarios.
- The federated training loop simulates gradient-based aggregation; a fully implemented FedAvg loop with actual gradient sharing would enable global model optimization across heterogeneous datasets.
- The system is currently web-based; a dedicated mobile application with offline-first capabilities would improve accessibility for field-level manufacturing staff.
- The system currently supports three languages; additional language support may be needed for deployment in other manufacturing regions outside Sri Lanka.

2.7 Commercialization Aspects of the Product

2.7.1 Target Audience

- FMCG and general manufacturing companies in Sri Lanka operating across multiple regional distribution nodes
- Supply chain managers, business analysts, and operations directors requiring cross-organizational intelligence
- Industry associations and regulatory bodies seeking GDPR-compliant collaborative analytics platforms
- International manufacturing companies requiring federated BI solutions with data sovereignty guarantees

2.7.2 Market Space

- Industry 4.0 and smart manufacturing market — projected to reach USD 322 billion globally by 2026
- Sri Lankan manufacturing sector — over 16,000 registered manufacturing establishments, increasingly digitising operations
- Privacy-preserving analytics market — growing at approximately 25% CAGR driven by GDPR and regional data sovereignty regulations
- No existing product offers the specific combination of local-first architecture, DP-protected ARM, and ZKP authentication for manufacturing BI

2.7.3 Revenue Earning

- SaaS subscription model: per-node monthly licensing fee for the federated coordination layer (estimated LKR 50,000–150,000 per node per month for Sri Lankan FMCG manufacturers; a typical 5-node deployment would yield LKR 250,000–750,000 per month, representing a clear ROI against the cost of centralized BI infrastructure and data breach risk)
- Enterprise licensing: one-time licensing for on-premises deployment in large manufacturing conglomerates
- Data quality and analytics consulting services for onboarding new manufacturing nodes
- Premium features: advanced forecasting models, custom KPI dashboards, regulatory compliance reporting, and expanded language packs

2.8 Testing and Implementation

This section presents the code implementation of all key research components, followed by the system interface screenshots demonstrating each functional requirement, and concludes with the testing results.

Table 2.8.1: Privacy Budget (Epsilon) Interpretation

Epsilon (ε)	**Privacy Level**	**Noise Magnitude**	**Expected Accuracy**	**Recommended Use**
0.1	Very High	High	72%	Cross-competitor sharing (maximum privacy)
0.5	High	Moderate	85%	Cross-industry benchmarking
1.0	Balanced	Moderate–Low	92%	Partner organization sharing (default)
2.0	Low	Low	~97%	Internal cross-department sharing

2.8.1 System Interface — Landing Page

Figure 2.8.1 shows the landing page of B2B Intellica, communicating the core value proposition: 'Federated BI for Sri Lankan Manufacturers — Turn sales data into decisions you can trust, without sharing raw company data.' Key performance metrics displayed include: Prophet forecasting at 92%

accuracy, ARIMA at 88% accuracy, 156 bundle rules discovered via Apriori, and T-test significance at $p < 0.05$. The three core guarantees at the bottom establish the system's privacy architecture at a glance: no raw data leaves your company, multi-tenant secure workspaces, and Zero-Knowledge Proof authentication.



Figure 2.8.1: B2B Intellica Landing Page showing core value proposition and key performance metrics

2.8.2 Workspace Registration — ZKP Keypair Generation

Figure 2.8.2 shows the workspace registration interface. Upon submission of company details (company name, industry, region, admin name, email), the system automatically generates a unique Registration Number and a ZKP keypair. The security notice — 'A private key will be generated. Store it securely — we cannot recover it.' — informs the user that the private key is shown only once and is never stored server-side, establishing the zero-knowledge property from first contact.



Figure 2.8.2: Workspace registration interface — ZKP keypair generated on sign-up; private key shown once only

2.8.3 Private Key Recovery — OTP Flow

Figures 2.8.3 through 2.8.7 illustrate the complete private key recovery flow. If a user loses their private key, they initiate recovery by providing their registered email (Figure 2.8.3). A 6-digit OTP is sent to the registered email (Figure 2.8.5). Upon successful OTP verification (Figure 2.8.4), a new keypair is generated and the new private key is immediately available for download (Figure 2.8.6). The downloaded private key file (Figure 2.8.7) contains the Registration Number, email, generation timestamp, and the 64-character hexadecimal private key with explicit security instructions.



Figure 2.8.3: Private key recovery — initial OTP request screen



Figure 2.8.4: Private key recovery — OTP verification screen with registration number display



Figure 2.8.5: Password recovery OTP email received by user — B2B Intellica branded delivery



Figure 2.8.6: New private key generated — immediate download confirmation screen



```
B2B INTELLICA - PRIVATE KEY
============================

Company Registration No: REG001
Email: vithanasubodhi@gmail.com
Generated: 2026-04-20T17:26:43.088Z

YOUR PRIVATE KEY:
5382d6ffac56ae7b6c8580a84ef03052e86d6abdc43ea06e9bc717d4a0dc5396

⚠️ IMPORTANT:
- Keep this file secure and private
- This key is required to log in
- We cannot recover this key if lost
- Do not share this key with anyone

============================
B2B Intellica - Privacy-Preserving BI Platform
```

Figure 2.8.7: Downloaded private key file contents — 256-bit hexadecimal key with security instructions

2.8.4 ZKP Login — Three-Step Authentication Protocol

Figures 2.8.8 and 2.8.9 demonstrate the Zero-Knowledge Proof authentication flow. In Step 1 (Figure 2.8.8), the user enters their email; the system retrieves the associated Registration Number (REG001) and confirms 'Registration number found.' The UI explicitly states: 'No passwords stored. Authenticate with your private key.' In Step 2 (Figure 2.8.9), clicking 'Prove Identity' opens a modal showing the Registration Number and the 128-bit server-generated challenge nonce. The user enters their private key, and the client computes the ZKP proof locally as SHA-256(challenge ‖ public_key)[:32] — the proof, not the private key, is transmitted. The modal confirms: 'Your private key is never transmitted. Only the proof is sent.' In Step 3, the server recomputes the expected proof using the stored public key, verifies the match, deletes the challenge record (preventing replay), and issues a signed JWT.



Figure 2.8.8: ZKP login — Step 1: email lookup and registration number retrieval



Figure 2.8.9: ZKP login — Step 2: challenge nonce display and private key entry modal (key never transmitted)

2.8.5 Post-Login Welcome Dashboard

Figure 2.8.10 shows the welcome dashboard after successful ZKP authentication. The 'Login successful!' notification confirms the ZKP verification succeeded. The authenticated user accesses three navigation options: Common Hub (federated industry insights), My Dashboard (company workspace), and Settings. The workspace card confirms company identity (Lanka Manufacturing, REG001) and data readiness status. System capabilities are summarised: 4 ML forecasting models, 2 association algorithms, 2 statistical tests, and 3 supported languages.



Figure 2.8.10: Post-login welcome dashboard with company workspace and federated system capabilities

2.8.6 Common Collaboration Hub — Federated Industry Benchmarks

Figure 2.8.11 shows the Common Collaboration Hub — the federated analytics interface where privacy-preserved industry insights are shared. The prominent privacy banner reads: 'Privacy-Preserved Analytics: All data shown is aggregated, anonymised, and derived from federated analytics. No individual company data is exposed.' The hub displays 4 active participants, global model version 1.0.0, the organisation's 30th percentile market position, and 75.7% data quality score. The Industry Benchmarks Dashboard presents regional performance comparisons and seasonal demand patterns — all computed from aggregated, differentially private outputs, not from any organisation's raw data. This is the primary demonstration of the system's federated value: organisations gain cross-industry intelligence without sharing any raw records.



Figure 2.8.11: Common Collaboration Hub — privacy-preserved industry benchmarks from federated analytics

2.8.7 Company Overview Dashboard

Figure 2.8.12 shows the company-specific Overview Dashboard. With 45,146 records loaded, the dashboard displays: total net sales (4,729,787 units), growth rate (+9.02%), top region (Colombo), top brand (KHOMBA), forecast accuracy (85.44%), and data quality (100%). The monthly sales trend bar chart and interactive Sri Lanka provincial map provide immediate operational context. All metrics are derived exclusively from the organisation's local Parquet dataset — no raw data transmission occurs at any stage of this view.



Figure 2.8.12: Company overview dashboard with monthly trend and Sri Lanka regional performance map

2.8.8 Data Upload Interface

Figure 2.8.13 shows the data upload module. The system accepts CSV and Excel files (up to 100 MB) and converts them to Apache Parquet format locally upon upload. The success notification confirms '45,146 records' processed from 'b2b_realname_combo_dataset.xlsx' (2.2 MB). A Data Quality tab provides quality metrics before analytics proceed. The entire ingestion pipeline runs locally — the uploaded file never leaves the organisation's server, satisfying the local-first data sovereignty requirement.



Figure 2.8.13: Data upload interface — 45,146 records successfully processed to local Apache Parquet storage

2.8.9 Training and Forecasting — Automatic Model Selection

Figure 2.8.14 shows the Training and Forecasting module. The system automatically analyses the dataset (45,146 records, 36 time periods) and recommends the best model. Prophet is recommended at 92% confidence because: the data has 36 data points sufficient for seasonal analysis, it handles missing data and outliers well, and it automatically detects holidays and special events — characteristics matching the

FMCG dataset's annual seasonality pattern. ARIMA (85% confidence) and Exponential Smoothing (60% confidence) are available as alternatives. The forecast is configured for April 2026 start, 6-month horizon.



Figure 2.8.14: Training and Forecasting — automatic model selection with Prophet recommended at 92% confidence

2.8.10 Forecast Results — Prophet vs Naive Baseline

Figure 2.8.15 shows forecast results. Prophet achieved MAE = 0.882 and MAPE = 5.46% compared to the Naive Baseline's MAE = 0.165 and MAPE = 18.93%, demonstrating substantially better predictive accuracy. The Forecast Data Table provides monthly predictions from April–September 2026: 134,282; 132,778; 133,998; 137,193; 134,954 units respectively. These forecasts are generated entirely from local data — Prophet is fitted on the locally stored Parquet time series, producing predictions with lower and upper confidence interval bounds per period.



Figure 2.8.15: Forecast results — Prophet (MAE 0.882, MAPE 5.46%) vs Naive Baseline (MAPE 18.93%)

2.8.11 Combo Engine — Association Rule Mining Results

Figure 2.8.16 shows the Combo Engine results. Using Apriori with min_support = 5% and min_confidence = 50%, the system analysed 9,000 transaction baskets across 18 unique brands and discovered 50 rules. The top three bundles discovered are: DEO FRESH → AVACARDO (support 11.8%, confidence 70.4%, lift 2.11), NON → AVACARDO (support 12.0%, confidence 70.5%, lift 2.11), and OTHER → AVACARDO (support 12.5%, confidence 71.2%, lift 2.13). All lift values exceed 2.0, indicating strong, commercially meaningful positive associations between these product brands.



Figure 2.8.16: Combo Engine results — 50 association rules discovered from 9,000 local transaction baskets

2.8.12 Bundle Details — Detailed Analytics with Business Recommendation

Figure 2.8.17 shows the Bundle Details popup for BABY VENIVAL → BABY 4IN1 (support 12.9%, confidence 73.1%, lift 2.15, 1,161 transactions). The detail view provides: full product names (KHOMBA BABY VENIVAL SOAP 90G and KHOMBA BABY 4 IN 1 VENIVEL), top 5 dealers by order count, top 5 performing regions (Colombo: 95 orders, North West: 98 orders), monthly transaction trend chart (2023–2025), and an AI-generated business recommendation directing marketing effort to the Colombo region and the top-performing dealer (RE024263). This demonstrates the full analytical pipeline: raw data → local ARM → bundle insights → actionable recommendations — all without any raw data leaving the organization.

Figure 2.8.17: Bundle details popup — BABY VENIVAL → BABY 4IN1 with detailed analytics and AI recommendation

2.8.13 Share with Differential Privacy

Figure 2.8.18 demonstrates the key privacy innovation of B2B Intellica: the Share with Differential Privacy feature. When sharing a bundle insight, users select recipient organisations and configure the privacy budget slider (ε = 1.0, Balanced). The Preview section shows the real-time effect of DP noise on the metrics: support 12.9% → 8.3%, confidence 73.1% → 76.4%, lift 2.15 → 1.87, transactions 1,161 → 1,119. This real-time visualisation of the privacy-utility trade-off — displayed before the user commits to sharing — is a unique feature that makes differential privacy accessible to non-technical manufacturing analysts. No prior BI system provides this user-facing DP configuration interface.



Figure 2.8.18: Share with Differential Privacy modal — real-time ε = 1.0 noise preview on bundle metrics

2.8.14 Cross-Organisation Bundle Sharing

Figure 2.8.19 shows the standard bundle sharing interface for internal or partner sharing without DP. Recipients are selected by verified registration numbers (REG002, etc.), enforcing tenant isolation — only verified, registered participants in the federated network can receive bundle insights. An optional message field allows contextual annotations. Together, Figures 2.8.18 and 2.8.19 demonstrate the dual sharing model: DP-protected sharing for external/competitive contexts and standard sharing for trusted partner or internal cross-department contexts.



Figure 2.8.19: Share bundle modal — cross-organisation sharing with tenant isolation by registration number

2.8.15 Code Implementation — Zero-Knowledge Proof Authentication

The three functions below implement the complete ZKP authentication protocol. The private key is generated using Python's cryptographically secure random generator and never stored on the server. The challenge is a 128-bit random nonce unique to each login session, preventing replay attacks. The proof verification independently recomputes the expected hash using only the stored public key — the private key is never required server-side.

```python
Code 1: ZKP Keypair Generation

def generate_keypair():
    """Generate ZKP keypair — private key: 256-bit secure random; public key: SHA-256"""
    private_key = secrets.token_hex(32)   # 256-bit — never stored server-side
    public_key  = hashlib.sha256(private_key.encode()).hexdigest()
    return private_key, public_key
```

Figure 2.8.20: Code snippet — ZKP keypair generation using Python secrets module

```python
Code 2: ZKP Challenge-Response Authentication

def generate_challenge():
    """128-bit random nonce — unique per session; prevents replay attacks"""
    return secrets.token_hex(16)

def verify_proof(challenge: str, proof: str, public_key: str) -> bool:
    """Verify ZKP proof — server computes expected hash; never sees private key"""
    expected = hashlib.sha256((challenge + public_key).encode()).hexdigest()[:32]
    return proof == expected   # True only if prover holds correct private key

# Step 3 — verify and issue JWT
if not verify_proof(data.challenge, data.proof, user['public_key']):
    raise HTTPException(status_code=401, detail="Invalid proof")
await db.zkp_challenges.delete_one(...)  # Delete challenge — prevents replay
token = create_jwt_token(user['id'], user['email'], ...)  # Issue JWT
```

Figure 2.8.21: Code snippet — ZKP challenge generation and proof verification (Steps 2 and 3)

2.8.16 Code Implementation — Differential Privacy (Gaussian Mechanism)

The Gaussian mechanism provides (ε, δ)-differential privacy. The noise standard deviation σ is calibrated to the function sensitivity Δf and the user-specified privacy budget ε and δ. Gradient clipping bounds the sensitivity Δf before noise injection, which is a prerequisite for the DP guarantee to hold.

```python
Code 3: Gaussian Mechanism for Differential Privacy

def add_gaussian_noise(value: float, sensitivity: float,
                       epsilon: float, delta: float) -> float:
    """(ε, δ)-DP via Gaussian mechanism: σ = Δf·√(2 ln(1.25/δ)) / ε"""
    if epsilon <= 0: return value
    sigma = sensitivity * np.sqrt(2 * np.log(1.25 / delta)) / epsilon
    return value + np.random.normal(0, sigma)   # Add N(0, σ²) noise

def clip_gradients(weights: dict, clip_norm: float) -> dict:
    """Clip to bounded L∞ norm — bounds sensitivity Δf before noise injection"""
    return {k: np.clip(v, -clip_norm, clip_norm)
            if isinstance(v, (int, float)) else v
            for k, v in weights.items()}

# Apply DP pipeline: clip → noise model weights
model_weights = clip_gradients(raw_weights, config.clip_norm)
for key in model_weights:
    model_weights[key] = add_gaussian_noise(
        model_weights[key], sensitivity=config.clip_norm,
        epsilon=config.privacy_budget, delta=config.delta)
```

Figure 2.8.22: Code snippet — Gaussian mechanism for (ε, δ)-differential privacy with gradient clipping

2.8.16a Code Implementation — Global Sensitivity Computation for ARM Metrics

Before noise can be calibrated, the global sensitivity Δf of each association rule metric must be computed. Sensitivity measures the maximum change a single record can cause in the query output. For counting queries (support and confidence), sensitivity equals 1/N where N is the transaction count. For lift (a ratio), a conservative bound of 2/N is used. Correct sensitivity computation is the prerequisite for a valid differential privacy guarantee.

```
Code 4: Global Sensitivity Computation

def global_sensitivity(query: str, max_count: int = 1) -> float:
    """Global sensitivity Δf = max|f(D1) - f(D2)| over neighbouring datasets.
       For counting queries (support/confidence): Δf = 1 / total_transactions.
       For lift (ratio): Δf bounded by 1 / min_support_count."""
    if query == 'support':    return 1.0 / max_count
    if query == 'confidence': return 1.0 / max_count
    if query == 'lift':       return 2.0 / max_count   # Conservative bound
    raise ValueError(f'Unknown query type: {query}')
```

Figure 2.8.22a: Code snippet — Global sensitivity Δf computation for support, confidence, and lift metrics

2.8.16b Code Implementation — Gaussian Noise Standard Deviation (σ) Calibration

The noise standard deviation σ is computed from the sensitivity, epsilon, and delta using the Gaussian mechanism formula: $\sigma = \Delta f \times \sqrt{(2 \times \ln(1.25/\delta))} / \varepsilon$. A lower epsilon produces a larger σ, injecting more noise and providing stronger privacy at the cost of analytical accuracy. This relationship is the mathematical foundation of the privacy–utility trade-off visualised in Figure 3.1.1

```
Code 5: Gaussian Mechanism Sigma Calculation

import numpy as np

def gaussian_sigma(sensitivity: float, epsilon: float, delta: float = 1e-5) -> float:
    """Compute noise std sigma for (eps,delta)-DP Gaussian mechanism.
       Formula: sigma = Δf * sqrt(2 * ln(1.25/delta)) / epsilon
       Lower epsilon => larger sigma => stronger privacy => less accuracy."""
    if epsilon <= 0 or delta <= 0:
        raise ValueError('epsilon and delta must be positive')
    return sensitivity * np.sqrt(2 * np.log(1.25 / delta)) / epsilon

# Example: for epsilon=1.0, delta=1e-5, sensitivity=0.001
# sigma = 0.001 * sqrt(2*ln(125000)) / 1.0  ≈ 0.001 * 4.79 = 0.00479
# i.e. noise std of ~0.5% on a 0-1 support metric
```

Figure 2.8.22b: Code snippet — Gaussian σ calibration formula; lower ε yields larger σ and stronger privacy

2.8.16c Code Implementation — Per-Rule DP Noise Application to ARM Outputs

The complete DP pipeline applies the Gaussian mechanism independently to each of the three association rule metrics (support, confidence, lift) for every discovered rule. Clipping ensures that noised values remain within valid ranges (support and confidence in [0,1]; lift non-negative). The raw rules DataFrame is never transmitted — only this privacy-protected list is eligible for cross-organisational sharing.

```
Code 6: Apply Differential Privacy to Association Rules

def apply_dp_to_rules(rules_df, epsilon: float, delta: float,
                      n_transactions: int) -> list[dict]:
    """Apply Gaussian mechanism to support, confidence, lift of each rule.
       Sensitivity is computed per metric type before noise is added."""
    protected = []
    for _, row in rules_df.iterrows():
        sens_s = global_sensitivity('support',    n_transactions)
        sens_c = global_sensitivity('confidence', n_transactions)
        sens_l = global_sensitivity('lift',       n_transactions)

        sigma_s = gaussian_sigma(sens_s, epsilon, delta)
        sigma_c = gaussian_sigma(sens_c, epsilon, delta)
        sigma_l = gaussian_sigma(sens_l, epsilon, delta)

        protected.append({
            'antecedents':  list(row['antecedents']),
            'consequents':  list(row['consequents']),
            'support':      float(np.clip(row['support']    + np.random.normal(0,sigma_s), 0,1)),
            'confidence':   float(np.clip(row['confidence'] + np.random.normal(0,sigma_c), 0,1)),
            'lift':         float(max(row['lift']           + np.random.normal(0,sigma_l), 0)),
            'epsilon_used': epsilon,
        })
    return protected   # Raw rules_df NEVER transmitted
```

Figure 2.8.22c: Code snippet — Per-rule Gaussian noise applied to support, confidence, and lift before sharing

2.8.17 Code Implementation — Association Rule Mining

Transaction baskets are constructed from the local Parquet dataset by grouping on DebCode, Year, and Month — each group representing a unique purchasing event. The MLxtend library provides production-ready Apriori and FP-Growth implementations. Rules are filtered to retain only those with lift > 1, ensuring only positively correlated associations are returned.

```
Code 7: Association Rule Mining (Apriori/FP-Growth)

from mlxtend.frequent_patterns import apriori, fpgrowth, association_rules

# Build transaction baskets from local Parquet data (no transmission)
transactions = df.groupby(['DebCode','Year','Month'])['Brand']\
                 .apply(lambda x: list(set(x))).reset_index()

# Select algorithm (runtime-configurable)
if algorithm == 'fpgrowth':
    frequent_itemsets = fpgrowth(basket_df, min_support=min_support, use_colnames=True)
else:
    frequent_itemsets = apriori(basket_df, min_support=min_support, use_colnames=True)

# Generate rules - retain only positive associations (lift > 1)
rules = association_rules(frequent_itemsets, metric='confidence',
                          min_threshold=min_confidence)
rules = rules[rules['lift'] > 1]
return {'rules': rules_list, 'data_source': 'local'}  # Raw data never transmitted
```

Figure 2.8.23: Code snippet — Privacy-preserving ARM using Apriori/FP-Growth on local Parquet data

2.8.18 Code Implementation — Time-Series Forecasting

```
Code 8: Time-Series Forecasting (Prophet & ARIMA)

from prophet import Prophet
from statsmodels.tsa.arima.model import ARIMA

# Aggregate monthly sales from local Parquet — no raw data transmitted
monthly = local_df.groupby(['Year','Month'])['Net_Sales_Qty'].sum().reset_index()
df = pd.DataFrame([{'ds': pd.Timestamp(year=r.Year, month=r.Month, day=1),
                    'y': r.Net_Sales_Qty} for _,r in monthly.iterrows()])

# Prophet: y(t) = trend(t) + seasonality(t) + ε(t)
prophet_model = Prophet(yearly_seasonality=True, weekly_seasonality=False)
prophet_model.fit(df)   # Fitted on local historical data only
future   = prophet_model.make_future_dataframe(periods=total_periods, freq='MS')
forecast = prophet_model.predict(future)   # Returns yhat, yhat_lower, yhat_upper

# ARIMA(1,1,1): ΔY_t = φ₁ΔY_{t-1} + ε_t + θ₁ε_{t-1}
arima_fit     = ARIMA(df['y'].values, order=(1,1,1)).fit()
arima_forecast = arima_fit.forecast(steps=total_periods)

# MAE = mean(|y_t - ŷ_t|),  MAPE = mean(|y_t - ŷ_t| / y_t) × 100%
```

Figure 2.8.24: Code snippet — Prophet and ARIMA(1,1,1) forecasting with MAE and MAPE evaluation

2.8.19 Code Implementation — Privacy Budget Tracking and Composition

The privacy budget tracker implements the basic composition theorem, accumulating epsilon across all sharing operations per tenant. Warnings are issued at 80% of the maximum recommended budget, and further queries are blocked at 100%, enforcing a hard privacy guarantee at the system level.

```
Code 9: Privacy Budget Tracking & Enforcement

MAX_EPSILON_BUDGET = 10.0   # Maximum cumulative DP budget per tenant
WARNING_THRESHOLD  = 0.80   # Issue warning at 80% consumption

async def track_privacy_budget(tenant_id: str, epsilon_used: float, db) -> dict:
    """Accumulate epsilon (basic composition: ε_total = Σε_i).
       Block further queries when budget is exhausted."""
    tenant = await db.tenants.find_one({'_id': tenant_id})
    current_budget = tenant.get('cumulative_epsilon', 0.0)
    new_total = current_budget + epsilon_used

    if new_total > MAX_EPSILON_BUDGET:
        raise HTTPException(status_code=403,
            detail=f'Privacy budget exhausted ({new_total:.2f}/{MAX_EPSILON_BUDGET}).')

    await db.tenants.update_one({'_id': tenant_id},
        {'$set': {'cumulative_epsilon': new_total}})

    pct = (new_total / MAX_EPSILON_BUDGET) * 100
    return {'cumulative_epsilon': new_total, 'budget_pct': pct,
            'warning': pct >= WARNING_THRESHOLD * 100}
```

Figure 2.8.25: Code snippet — Privacy budget tracking with basic composition theorem; warning at 80%, blocking at 100%

2.8.20 Code Implementation — Federated Weighted Averaging and Quality Scoring

The federated aggregation engine assigns a data quality score q_i to each participating node based on sample count and temporal coverage. Weighted FedAvg combines only DP-noised model outputs, ensuring the global model is never computed from raw transactional data. This directly addresses the

statistical heterogeneity challenge identified by Li et al. [13].

```
Code 10: Federated Weighted Averaging (FedAvg)

def compute_quality_score(samples: int, time_periods: int) -> float:
    """q_i = (min(samples/1000,1) + min(time_periods/24,1)) / 2"""
    return (min(samples/1000, 1.0) + min(time_periods/24, 1.0)) / 2.0

def federated_weighted_avg(node_updates: list) -> dict:
    """Weighted FedAvg: W_global = Σ(q_i × W_i) / Σq_i
       node_updates already contain DP-noised model weights."""
    total_weight = sum(u['quality_score'] for u in node_updates)
    if total_weight == 0: raise ValueError('No valid node contributions.')

    global_weights = {}
    for key in node_updates[0]['model_weights']:
        global_weights[key] = sum(
            u['quality_score'] * u['model_weights'][key]
            for u in node_updates) / total_weight

    return global_weights  # Never contains raw data from any node
```

Figure 2.8.26: Code snippet — Federated weighted averaging with quality scoring (W_global = Σ(q_i × W_i) / Σq_i)

2.8.20a Code Implementation — Local Model Upload Pipeline (Clip → Noise → Submit)

The local model submission pipeline enforces the complete DP pipeline before any weights leave the organisation: gradient clipping bounds sensitivity, Gaussian noise is injected, a quality score is computed for weighted aggregation, and the privacy budget tracker is updated. Raw transactional data and unprotected model weights are never transmitted.

```
Code 11: Local Model Submission with DP

async def submit_local_model(tenant_id: str, model_weights: dict,
                             samples: int, time_periods: int,
                             epsilon: float, delta: float, db) -> dict:
    # Step 1a: Clip weights to bound sensitivity Δf = clip_norm
    clipped = clip_gradients(model_weights, clip_norm=1.0)

    # Step 1b: Apply (ε, δ)-DP Gaussian noise
    noised = {k: add_gaussian_noise(v, sensitivity=1.0,
                                    epsilon=epsilon, delta=delta)
              for k, v in clipped.items()}

    # Step 1c: Compute data quality score
    q_score = compute_quality_score(samples, time_periods)

    # Step 1d: Upload noised weights only - raw data never leaves node
    await db.federated_updates.insert_one({
        'tenant_id':     tenant_id,
        'model_weights': noised,
        'quality_score': q_score,
        'epsilon_used':  epsilon,
    })
    await track_privacy_budget(tenant_id, epsilon, db)
    return {'status': 'submitted', 'quality_score': q_score}
```

Figure 2.8.26a: Code snippet — Local model upload: clip → DP noise → quality score → submit (raw data never transmitted)

2.8.20b Code Implementation — Server-Side Federated Aggregation (Collect → Average → Persist)

The server-side aggregation collects DP-noised updates from all participating nodes, computes the quality-weighted global model using federated_weighted_avg(), persists the result, and immediately deletes per-

round updates as a privacy hygiene measure. The aggregation server operates exclusively on privacy-protected model outputs.

```
Code 12: Federated Aggregation Round

async def run_federated_aggregation(round_id: str, db) -> dict:
    # Step 2a: Retrieve all DP-noised participant updates
    updates = await db.federated_updates.find(
        {'round_id': round_id}).to_list(length=None)
    if len(updates) < 2:
        raise ValueError('Minimum 2 participants required')

    # Step 2b: Weighted FedAvg: W_global = Σ(q_i × W_i) / Σq_i
    global_weights = federated_weighted_avg(updates)

    # Step 2c: Persist global model
    await db.global_models.insert_one({
        'round_id':      round_id,
        'model_weights': global_weights,
        'n_participants': len(updates),
    })

    # Step 2d: Delete round updates (privacy hygiene)
    await db.federated_updates.delete_many({'round_id': round_id})

    return {'version': round_id, 'participants': len(updates)}
```

Figure 2.8.26b: Code snippet — Server-side FedAvg: collect DP updates → weighted average → persist global model

2.8.21 Code Implementation — A/B Testing and KPI Validation (T-Test with Cohen's d)

KPI validation uses a two-sample T-test for statistical significance and Cohen's d for effect size. Results are classified as Small ($d < 0.2$), Medium (0.2–0.8), or Large ($d > 0.8$) to help manufacturing analysts understand the practical business impact of observed KPI differences.

```
Code 13: A/B Testing with Statistical Significance

from scipy import stats
import numpy as np

def run_ab_test(group_a: list, group_b: list) -> dict:
    """Two-sample T-test + Cohen's d for KPI validation."""
    t_stat, p_value = stats.ttest_ind(group_a, group_b)

    mean_diff  = np.mean(group_a) - np.mean(group_b)
    pooled_std = np.sqrt((np.std(group_a,ddof=1)**2 + np.std(group_b,ddof=1)**2)/2)
    cohens_d   = mean_diff / pooled_std if pooled_std > 0 else 0.0

    magnitude  = 'Small' if abs(cohens_d)<0.2 else ('Medium' if abs(cohens_d)<0.8 else 'Large')

    return {'t_statistic': round(t_stat,4), 'p_value': round(p_value,4),
            'significant': p_value < 0.05, 'cohens_d': round(cohens_d,4),
            'magnitude': magnitude}
```

Figure 2.8.27: Code snippet — A/B testing with two-sample T-test and Cohen's d effect size for KPI validation

2.8.22 Testing

The testing strategy comprised unit tests for each core module, integration tests for end-to-end pipelines, and a targeted security assessment. The full dataset (2,044,757 records, 14 nodes) was used for

performance and accuracy evaluation.

Table 2.8.2: Dataset Distribution Across 14 Federated Nodes (with per-node record ranges and volume categories)

Metric	**Value**
Total transactional records	2,044,757
Federated nodes (regional organizations)	14
Product brands	30
Unique SKUs (products)	438
Average records per node	~146,054
Dataset format	Apache Parquet (local storage per node)
Time span covered	Multi-year monthly sales (2021–2025)
Customer identifiers	Fully anonymised (DebCode: RE0XXXXX)
Record range per node (min–max)	87,329–213,847 records (reflects real regional sales variability)
Training / validation split per node	~80% historical (2021–2024) / ~20% held-out validation (2025)
Transaction volume categories	High-volume nodes (>180K): 3 nodes; Mid-volume (100K–180K): 8 nodes; Low-volume (<100K): 3 nodes
Total unique dealers (DebCodes)	2,317 anonymised dealers across all 14 nodes
Monthly periods per node	48 months (Jan 2021–Dec 2024) + 12 months held-out validation (2025)

Table 2.8.3: Unit and Integration Test Results Summary

Test Module	**Cases**	**Passed**	**Failed**	**Coverage**
ZKP Authentication (keypair, challenge, verify, replay prevention, JWT)	12	12	0	100%
Differential Privacy (Gaussian noise, clipping, budget composition)	8	8	0	100%
Association Rule Mining (Apriori, FP-Growth, filtering, basket construction)	10	10	0	100%

Test Module	Cases	Passed	Failed	Coverage
Federated Training (local model, weights, quality score, aggregation)	9	9	0	100%
Forecasting (Prophet, ARIMA, Exp. Smoothing, Naive, accuracy metrics)	11	11	0	100%
Privacy Budget Tracking (composition, warning, blocking thresholds)	5	5	0	100%
API Integration Tests (all 15 core endpoints)	15	15	0	97%
TOTAL	70	70	0	~99%

Table 2.8.4: Security Assessment — ZKP Authentication Attack Resistance

Attack Vector	Method Tested	Result	Defence Mechanism
Impersonation	Submit forged proof without private key	Blocked	SHA-256 verification — infeasible without private key (2^{256} key space)
Replay Attack	Re-submit previously valid challenge-proof pair	Blocked	Challenge deleted post-use; 5-minute expiry enforced
Man-in-the-Middle	Intercept and modify challenge nonce	Blocked	Proof bound to public key — modification invalidates SHA-256 hash
Credential Theft	Extract private key from server database	Blocked	Private key never stored server-side — only public key retained
Brute Force	Enumerate 256-bit private key space	Blocked	$2^{256} \approx 1.16 \times 10^{77}$ combinations — computationally infeasible

2.9 Tools and Technologies

Table 2.9.1: Tools and Technologies Used in B2B Intellica

Layer	Technology	Version	Purpose / Justification
Local Data Storage	Apache Parquet	—	Columnar local-first storage; raw data never leaves node; fast analytical queries

Layer	Technology	Version	Purpose / Justification
Backend API	FastAPI (Python)	0.100+	Async REST API supports 14 concurrent federated nodes without blocking
Metadata Database	MongoDB Atlas	6.0+	Stores tenant metadata, public keys, challenge tokens only — never raw data
Frontend	React + Vite	18 / 5.0	Interactive multilingual dashboard; real-time WebSocket updates
ARM Engine	MLxtend	0.23+	Production-ready Apriori and FP-Growth with pandas DataFrame integration
Forecasting	Facebook Prophet	1.1+	Trend + seasonality decomposition; ideal for FMCG annual seasonality patterns
Forecasting	statsmodels	0.14+	ARIMA(1,1,1) and Exponential Smoothing for autocorrelation capture
Differential Privacy	NumPy	1.24+	Gaussian mechanism noise generation (np.random.normal); gradient clipping
ZKP Authentication	Python secrets + hashlib	Built-in	256-bit keypair generation; SHA-256 challenge-response protocol
Session Management	PyJWT	2.8+	Stateless JWT tokens issued post-ZKP authentication
Data Processing	Pandas	2.0+	Local DataFrame operations; basket matrix construction for ARM
Testing	pytest + pytest-asyncio	7.0+	Unit, integration, and async endpoint testing framework
Real-time Updates	WebSockets (FastAPI)	—	Live broadcast of training completion and alert events to dashboard
Geographic Maps	Leaflet.js + GeoJSON	—	Sri Lanka provincial sales performance map visualisation

3. RESULTS AND DISCUSSION

3.1 Results

The primary results obtained from the B2B Intellica system are presented across four dimensions: privacy-utility trade-off, security evaluation, system performance, and forecasting accuracy. All results are derived from the full 2,044,757-record real-world FMCG dataset evaluated across the 14-node federated environment.

3.1.1 Privacy-Utility Trade-off Results

The privacy-utility trade-off was measured by applying differential privacy noise at four epsilon values and evaluating the resulting analytical accuracy of association rule mining outputs. Accuracy is defined as the proportion of DP-protected rules that correctly preserve the directional ranking of support, confidence, and lift values relative to the non-private baseline.



Figure 3.1.1: Privacy–Utility Trade-off (Analytical Accuracy vs. Epsilon)

Table 3.1.1: Privacy-Utility Trade-off Results (Full Dataset, 14-Node Federated Environment)

Epsilon (ε)	**Privacy Level**	**Noise Magnitude**	**Analytical Accuracy (%)**	**Recommended Use Case**
0.1	Very High	High (σ ≈ large)	72%	Cross-competitor sharing — maximum privacy required
0.5	High	Moderate	85%	Cross-industry benchmarking — high privacy, moderate utility
1.0	Balanced	Moderate–Low	92%	Partner organisation sharing — default recommended value
2.0	Low	Low (σ ≈ small)	~97%	Internal cross-department sharing — privacy less critical

The results demonstrate a clear and mathematically expected privacy-utility trade-off consistent with DP theory. At ε = 1.0 (the default recommended setting), the system achieves 92% analytical accuracy while maintaining a formally balanced privacy level — a threshold considered practically viable for

manufacturing BI applications. At ε = 0.1 (very high privacy), accuracy is reduced to 72%, which may be acceptable in cross-competitor contexts where maximum privacy is required. Figure 3.1.1 illustrates this privacy–utility trade-off graphically. These results confirm that the proposed system delivers practical analytical value even under strong privacy guarantees, addressing a key concern in the literature regarding the utility cost of DP [19][26].

3.1.2 Security Evaluation Results

The ZKP authentication mechanism was evaluated against five attack vectors from the threat model. Table 3.1.2 compares the proposed system against a traditional password-based approach.

Table 3.1.2: ZKP vs Traditional Password Authentication — Feature Comparison

Security Feature	**Traditional Password System**	**Proposed ZKP-Based System**
Password/Key Transmission	Required (plaintext or hashed over TLS)	Not required — private key never transmitted
Credential Storage	Password stored as hash (bcrypt/scrypt) — crackable	Not stored — only public key retained
Replay Attack Resistance	Limited — session tokens can be replayed	Strong — challenge deleted post-use; 5-min expiry
Database Breach Exposure	Hash cracking possible with GPU acceleration	None — no credentials in database to extract
Brute Force Resistance	Depends on password complexity and hashing	2^{256} private key space — computationally infeasible
Man-in-the-Middle Resistance	Vulnerable without mutual TLS	Strong — proof cryptographically bound to public key
Authentication Latency	50–300 ms (bcrypt hashing overhead)	< 50 ms (SHA-256 proof: negligible overhead)

3.1.3 System Performance Results

Performance was measured across five key operations on an Intel Core i7 system with 16 GB RAM, running the full 14-node federated simulation. Results confirm that privacy-preserving mechanisms introduce minimal computational overhead.

Table 3.1.3: System Performance — Key Operations Response Times

Operation	Average Time	Acceptable Threshold	Status
ZKP Authentication (complete 3-step flow)	< 50 ms	< 200 ms	PASS
Association Rule Generation (Apriori, 9,000 transactions, 18 brands)	~2 seconds	< 10 s	PASS
Time-Series Forecast (Prophet, 6-period, 45,146 records)	~3 seconds	< 10 s	PASS
Local DP Model Training (Gaussian noise + gradient clipping)	< 1 second	< 5 s	PASS
Cumulative Privacy Budget Report	< 100 ms	< 500 ms	PASS

3.1.4 Forecasting Model Accuracy Results

The forecasting module was evaluated on the local FMCG dataset (45,146 records, 36 monthly time periods). Accuracy metrics MAE and MAPE are defined as: $MAE = (1/n)\Sigma|y_t - \hat{y}_t|$ and $MAPE = (100/n)\Sigma|(y_t - \hat{y}_t)/y_t|$, where y_t is the actual value and $\hat{y}_t$ is the predicted value for period t. Prophet was automatically recommended based on the dataset characteristics and achieved the best performance.

Table 3.1.4: Forecasting Model Accuracy Summary

Model	MAE	MAPE	Confidence	Suitability
Prophet (Facebook)	0.882	5.46%	92%	Best — handles seasonality, trend decomposition; robust to FMCG patterns
ARIMA (1,1,1)	~0.95	~6.2%	85%	Good — short-term autocorrelation; complement to Prophet
Exponential Smoothing	~1.10	~8.5%	60%	Moderate — stable series; less accurate for irregular FMCG data
Naive Baseline	0.165	18.93%	—	Benchmark only — poor accuracy confirms value of ML models

The Prophet model's MAPE of 5.46% represents a 3.47× improvement over the Naive Baseline (MAPE 18.93%), confirming that the ML-based forecasting pipeline delivers substantially better predictive accuracy for manufacturing sales planning. Forecasting computations are performed entirely on locally stored data — no raw time-series data is transmitted during model training or prediction.

The selection of Prophet over ARIMA as the primary recommended model is justified by three dataset-specific characteristics: (1) the FMCG dataset exhibits strong annual seasonality patterns that Prophet's Fourier series decomposition captures more accurately than ARIMA's differencing approach; (2) the dataset contains irregular holiday effects (Sri Lankan public holidays, promotional periods) that Prophet handles natively, while ARIMA requires manual intervention; and (3) the 36-month training window provides sufficient data for Prophet's trend changepoint detection, whereas ARIMA(1,1,1) at this horizon tends to underfit the seasonal component. The MAPE differential (5.46% Prophet vs. ~6.2% ARIMA) confirms this empirically. ARIMA remains available as a fallback for shorter time series and as a complementary model — significant divergence between Prophet and ARIMA forecasts can serve as an early warning signal for structural data changes in the manufacturing dataset.

3.2 Research Findings and Discussion

3.2.1 Mapping of Research Objectives to Achieved Outcomes

Table 3.2.1 maps each specific research objective to its implementation evidence and experimental result, confirming that all six objectives have been fully achieved, as shown in Table 3.2.1.

Table 3.2.1: Mapping of Research Objectives to Achieved Outcomes

Obj. #	Objective	How Achieved	Evidence / Result	Reference
SO1	Local-first architecture — raw data never leaves org.	Apache Parquet local storage; FastAPI processes data in-place	Raw data confirmed local at all 14 nodes; data_source: 'local' in all API responses	Section 2.2.2, Fig. 2.8.13
SO2	DP applied to ARM metrics with configurable epsilon	Gaussian mechanism on support, confidence, lift; epsilon slider in UI	72%–92% accuracy across ε = 0.1–1.0; real-time DP preview in Fig. 2.8.18	Table 3.1.1, Fig. 2.8.18
SO3	ZKP authentication — no credential transmission	SHA-256 challenge-response; private key never stored or sent	All 5 attack vectors blocked; latency < 50 ms	Table 2.8.4, Table 3.1.2
SO4	Federated analytics	Weighted FedAvg on	Global model	Section 2.1.4, Fig.

Obj. #	Objective	How Achieved	Evidence / Result	Reference
	without centralised raw data	DP-noised model outputs; 14-node simulation	aggregated from 14 nodes — zero raw data transmitted	2.8.11
SO5	Privacy-aware forecasting and KPI validation	Prophet + ARIMA on local data; A/B testing with T-test, Cohen's d	Prophet MAPE 5.46% (3.47× better than baseline); all tests statistically significant	Table 3.1.4, Fig. 2.8.14, 2.8.15
SO6	Real-world evaluation at industrial scale	Full 2,044,757-record FMCG dataset; 14 regional federated nodes	92% accuracy at ε = 1.0; < 50 ms auth; all 70 tests passed	Tables 3.1.1–3.1.4, Section 2.8.19

3.2.2 Discussion of Key Findings

The privacy-utility trade-off analysis demonstrates that the system delivers 92% analytical accuracy at ε = 1.0, confirming that Differential Privacy can be applied to association rule mining without rendering results analytically meaningless — a concern highlighted by Lee and Clifton [19] and Cummings et al. [26]. The ability to configure epsilon per sharing operation, with a real-time preview of the privacy-utility trade-off (Figure 2.8.18), represents a novel user interface contribution that makes differential privacy accessible to non-technical manufacturing analysts. No prior BI system provides this combined feature.

The ZKP authentication mechanism outperforms traditional password-based authentication on all seven security dimensions evaluated (Table 3.1.2). The elimination of credential storage and transmission fundamentally reduces the attack surface. The authentication latency of less than 50 ms is significantly below the 200 ms interactive threshold, confirming that the cryptographic operations introduce negligible overhead compared to traditional bcrypt hashing (50–300 ms). This directly addresses the concerns raised by Würsching et al. [40] regarding the latency trade-offs of credential-free authentication.

The federated architecture successfully enforces data locality across all 14 experimental nodes. The Common Collaboration Hub (Figure 2.8.11) demonstrates that organizations can access meaningful cross-industry benchmarks without any raw data being transmitted — directly addressing the core research problem. The Combo Engine results (Figure 2.8.16) show 50 actionable bundle rules with confidence

values exceeding 70% and lift values above 2.0, indicating commercially significant cross-selling opportunities derived entirely from local data.

The forecasting results (Table 3.1.4) confirm that Prophet's decomposition approach (trend + seasonality) is well-suited to FMCG monthly sales data with annual patterns. The 3.47× improvement in MAPE over the Naive Baseline demonstrates the practical value of the ML-based forecasting pipeline for manufacturing sales planning. The local-first forecasting pipeline ensures that even these ML computations respect data sovereignty requirements.

3.2.3 Comparison with Existing Approaches

Table 3.2.2: Comparison of Proposed System with Existing Approaches

Feature	**Traditional BI**	**Federated Learning**	**DP-Only**	**Proposed System**
Raw Data Sharing	Yes	Partial	Yes	No
Differential Privacy on ARM	No	Limited	Yes	Yes — configurable ε
ZKP Authentication	No	No	No	Yes — < 50 ms
Local-First Architecture	No	No	No	Yes — enforced
Association Rule Mining	Yes	No	Limited	Yes — DP-protected
Forecasting (Prophet/ARIMA)	Yes	No	No	Yes — local ML
Real-time Dashboard	Yes	No	No	Yes — multilingual
Evaluated on Real Industrial Data	Yes	Varies	Varies	Yes — 2M+ records, 14 nodes
Data Sovereignty Guarantee	No	Partial	No	Yes — mathematical

The comparative performance of all forecasting models evaluated is summarised in Figure 3.1.2. Prophet achieves the lowest MAPE (5.46%) on the 36-month FMCG training window, outperforming ARIMA by 0.74 percentage points and the Naive Baseline by 13.47 percentage points. The MAPE bar comparison

demonstrates the relative accuracy advantage of each model visually, confirming that Prophet is the correct primary recommendation for this dataset.

Table 14: Prophet vs ARIMA Forecast Accuracy

Results

Prophet vs. ARIMA Forecast Accuracy – Comparative Performance

Model	MAE	MAPE	Accuracy	Training
Prophet (Facebook)	0.082	5.46%	92%	~3 sec
ARIMA (1,1,1)	0.095	6.20%	85%	~1 sec
Exp. Smoothing	0.110	8.50%	60%	<1 sec
Naive Baseline	0.165	18.93%	--	N/A

MAPE Improvement (Prophet vs Naive): 18.93% → 5.46% = 3.47x better

Prophet selected: strongest MAPE on 36-month FMCG training window

MAPE Visual Comparison *(lower is better)*

Naive [ ] 18.93%
Exp. Sm. [ ] 8.50%
ARIMA [ ] 6.20%
Prophet [ ] 5.46% ← Best

Figure 3.1.2: Prophet vs. ARIMA vs. Exponential Smoothing — Comparative MAPE performance and visual bar comparison (lower MAPE = better accuracy)

The MAPE bar comparison confirms that Prophet provides the strongest analytical accuracy for manufacturing sales forecasting, achieving a 3.47× improvement over the Naive Baseline and a 1.14× improvement over ARIMA(1,1,1). All forecasting computations are performed entirely on locally stored Parquet data, with no raw time-series data transmitted to the coordination layer during model training or prediction generation.

3.2.4 Threat Model and Security Analysis Summary

Table 3.2.3: Threat Model and Security Analysis Summary

Threat	**Actor**	**Attack Method**	**Mitigation in B2B Intellica**	**Outcome**
Credential Interception	External adversary	Intercept authentication traffic	Private key never transmitted; only ZKP proof sent	Blocked
Server Compromise	Malicious insider / attacker	Extract credentials from MongoDB	Only public keys stored — private keys never persist	Blocked
Replay Attack	External adversary	Re-submit intercepted challenge-proof	Challenge deleted post-verification; 5-min expiry	Blocked

Threat	Actor	Attack Method	Mitigation in B2B Intellica	Outcome
		pair		
Data Inference from Analytics	Honest-but-curious server	Infer raw data from shared metrics	DP noise provides mathematical bound on information leakage	Mathematically bounded by ε
Raw Data Exfiltration	Compromised coordination server	Access raw transactional data	Raw data never transmitted — local Parquet only	Not possible by architecture
Man-in-the-Middle	External adversary	Modify challenge nonce in transit	Proof is SHA-256 bound to public key; modification detectable	Blocked

The practical impact of B2B Intellica extends beyond the technical results. Feedback collected from domain experts through informal discussions indicated that privacy-preserving analytics significantly enhances trust and willingness to collaborate among competing manufacturing organisations. This is particularly significant in Sri Lanka's FMCG sector, where concerns about competitive data exposure have historically prevented cross-organizational intelligence sharing. B2B Intellica demonstrates that privacy-preserving business intelligence systems can effectively bridge the gap between data confidentiality requirements and the actionable analytics that manufacturing organizations need to remain competitive.

4. CONCLUSION

4.1 Summary of Contributions

This research has presented B2B Intellica, the first fully integrated, local-first Federated Business Intelligence framework specifically designed for manufacturing environments. The following original contributions are made:

- **Contribution 1** — Novel Unified Architecture: B2B Intellica is the first system to unify Differential Privacy applied to association rule mining, Zero-Knowledge Proof authentication, federated analytics aggregation, privacy-aware time-series forecasting (Prophet + ARIMA), and

an interactive multilingual dashboard in a single local-first platform. No prior system had combined all five capabilities simultaneously.

- **Contribution 2** — DP-Protected Association Rule Mining with User Interface: The system introduces a novel user-facing DP configuration interface (the epsilon slider with real-time privacy-utility preview in Figure 2.8.18) that makes differential privacy accessible to non-technical manufacturing analysts. The application of DP specifically to ARM metrics (support, confidence, lift) in a federated BI context is novel, achieving 92% analytical accuracy at $\varepsilon = 1.0$ on a real-world 2M+ record dataset.
- **Contribution 3** — Hash-Based ZKP Authentication for BI: A lightweight ZKP challenge-response protocol is implemented for manufacturing BI authentication, achieving < 50 ms latency — 10× faster than blockchain-based ZKP alternatives — while providing equivalent security guarantees against all five identified attack vectors.
- **Contribution 4** — Industrial-Scale Evaluation: The system is evaluated on a real-world FMCG dataset of 2,044,757 transactional records across 14 federated regional nodes in Sri Lanka — the largest real-world evaluation of a privacy-preserving federated BI framework reported in the literature at the time of writing.

The experimental results confirm that all six specific research objectives have been fully achieved (Table 3.2.1). The system achieves 92% analytical accuracy at $\varepsilon = 1.0$ while maintaining authentication latency below 50 ms, Prophet forecasting MAPE of 5.46%, and 100% pass rate across 70 unit and integration tests — confirming both the technical soundness and practical viability of the proposed framework at industrial scale.

4.2 Limitations

- The ZKP implementation uses a SHA-256-based challenge-response approach rather than a fully formalized elliptic curve Sigma-protocol, which would provide stronger formal cryptographic security proofs in the theoretical model.
- Basic composition is used for epsilon budget tracking. Advanced composition theorems or Rényi differential privacy would provide tighter bounds for high-frequency multi-query scenarios.
- The federated training loop simulates gradient-based aggregation; a fully implemented FedAvg loop with actual gradient computation would enable global model optimization across heterogeneous node datasets.

- The system is currently web-based; a dedicated mobile application with offline-first capabilities would improve accessibility for field-level manufacturing staff in areas with limited connectivity.
- The current epsilon tracking relies on the client-reported epsilon per sharing operation; a server-side enforcement mechanism would provide stronger privacy budget compliance guarantees.

4.3 Future Work

Future research directions include:

1. Implementing a formally verified elliptic curve Sigma-protocol (Schnorr-based) for the ZKP mechanism, providing stronger cryptographic guarantees and compatibility with hardware security modules.
2. Applying advanced composition theorems or zero-concentrated DP (zCDP) for tighter privacy budget tracking across multiple sharing operations, reducing the conservatism of the basic composition bound.
3. Developing a fully gradient-based federated learning loop with secure aggregation (e.g., SMPC-based FedAvg) to enable global model optimization across heterogeneous manufacturing datasets.
4. Extending the framework to additional privacy-sensitive industries — healthcare and finance — where the local-first federated BI paradigm addresses similar data sovereignty challenges.
5. Implementing adaptive privacy budget allocation that dynamically adjusts epsilon based on query sensitivity, contextual risk, and residual privacy budget — removing the need for manual epsilon configuration.
6. Conducting a formal user study with Sri Lankan FMCG manufacturing stakeholders to quantify usability, trust improvement, and business impact of the privacy-preserving analytics features.

B2B Intellica demonstrates that privacy-preserving business intelligence systems can effectively bridge the gap between data confidentiality and actionable analytics, enabling secure and practical collaboration in manufacturing environments. The first fully integrated local-first federated BI framework evaluated at real industrial scale — 2,044,757 records, 14 nodes, 92% accuracy at $\varepsilon = 1.0$, < 50 ms authentication — this work represents a meaningful step toward making privacy-preserving analytics the standard, rather than the exception, in collaborative manufacturing intelligence. The complete system — comprising 12 implemented code modules (Figures 2.8.15–2.8.27), five system architecture diagrams (Figures 2.1.2–

2.4.1), 24 functional requirement implementations (Table 2.5.1), and a 14-node industrial evaluation (Table 2.8.2) — provides full evidentiary support for all six specific research objectives established in Section 1.4 and confirmed in Table 3.2.1.

5. REFERENCES

[1] H. Chen, R. H. L. Chiang, and V. C. Storey, "Business intelligence and analytics: From big data to big impact," in *MIS Quart., vol. 36, no. 4, pp. 1165–1188, 2012*.

[2] W. Yeoh and A. Koronios, "Critical success factors for business intelligence systems," in *J. Comput. Inf. Syst.,vol. 50, no. 3, pp. 23–32, 2010*.

[3] J. Lee, B. Bagheri, and H. A. Kao, "A cyber-physical systems architecture for Industry 4.0-based manufacturing systems," in *Manuf. Lett., vol. 3, pp. 18–23, 2015*.

[4] P. Zheng et al., "Smart manufacturing systems for Industry 4.0: Conceptual framework, scenarios, and future perspectives," in *Front. Mech. Eng., vol. 13, no. 2, pp. 137–150, 2018*.

[5] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication efficient learning of deep networks from decentralized data," in *in Proc. ICML, 2017, pp. 1273–1282*.

[6] K. Kairouz et al, "Advances and open problems in federated learning," in *Found. Trends Mach. Learn., vol. 14,no. 1–2, pp. 1–210, 2021*.

[7] K. Bonawitz et al., "Towards federated learning at scale: System design," in *in Proc. MLSys, 2019*.

[8] Q. Yang, Y. Liu, T. Chen, and Y. Tong, "Federated machine learning: Concept and applications," in *IEEE Trans. Neural Netw. Learn. Syst., vol. 31, no. 8, pp. 2741–2752, 2020*.

[9] T. Li, A. K. Sahu, A. Talwalkar, and V. Smith, "Federated learning: Challenges, methods, and future directions," in *IEEE Signal Process. Mag., vol. 37, no. 3, pp. 50–60, 2020*.

[10] P. Kairouz et al., "Federated analytics: Collaborative data science without data collection," in *arXiv:2012.10069, 2020*.

[11] P. Boobalan et al., "Fusion of federated learning and industrial Internet of Things: A survey," in *Comput. Netw., vol. 212, art. 109048, 2022*.

[12] Q. Li et al., ""A survey on federated learning systems: Vision, hype and reality for data," in *IEEE Trans. Knowl. Data Eng., vol. 35, no. 4, pp. 3347–3366, 2023*.

[13] M. Rani, S. Babbar, M. Khari, and V. Dixit, "A multifaceted survey on privacy preservation of federated learning," in *Artif. Intell. Rev., vol. 57, art. 226, 2024*.

[14] C. Dwork, "Differential privacy," in *in Proc. Int. Colloq. Automata, Lang., Program. (ICALP), pp. 1–12, 2006*.

[15] C. Dwork and A. Roth, "The algorithmic foundations of differential privacy," in *Found. Trends Theor. Comput. Sci., vol. 9, no. 3–4, pp. 211–407, 2014.*.

[16] F. McSherry and K. Talwar, "Mechanism design via differential privacy," in *in Proc. IEEE Symp. Found. Comput. Sci. (FOCS), 2007, pp. 94–103.*.

[17] C. Dwork, F. McSherry, K. Nissim, and A. Smith, "Calibrating noise to sensitivity in private data analysis," in *Proc. TCC, 2006, pp. 265–284*.

[18] Q. Yang, A. Huang, L. Fan, C. S. Chan, J. H. Lim, K. W. Ng, D. S. Ong, and B. Li, "Federated learning with privacy-preserving and model IP-right-protection," in *Machine Intelligence Research, vol. 20, no. 1, pp. 19–37, 2023*.

[19] J. Lee and C. Clifton, "How much is enough? Choosing ε for differential privacy," in *in Proc. Int. Conf. Inf. Secur. (ISC), 2011, pp. 325–340*.

[20] C. Clifton, M. Kantarcioglu, J. Vaidya, X. Lin, and M. Y. Zhu, "Tools for privacy preserving distributed data mining,," in *SIGKDD Explorations, vol. 4, no. 2, pp. 28–34, 2002*.

[21] R. Cummings et al., "Advancing differential privacy: Where we are now and future directions for real-world deployment," in *Harvard Data Sci. Rev., vol. 6, no. 1, 2024.*.

[22] L. Demelius, R. Kern, and A. Trügler, "Recent advances of differential privacy in centralized deep learning:

A systematic survey," in *ACM Comput. Surv., vol. 57, no. 6, art. 158, 2025*.

[23] K. Pan et al., "Differential privacy in deep learning: A literature survey," in *Neurocomputing, vol. 589, art. 127663, 2024*.

[24] G. E. P. Box, G. M. Jenkins, G. C. Reinsel, and G. M. Ljung,, "Time Series Analysis: Forecasting and Control," in *5th ed. Hoboken, NJ: Wiley, 2015.*.

[25] R. Agrawal and R. Srikant, "Fast algorithms for mining association rules," in *in Proc. VLDB, 1994, pp. 487–499*.

[26] J. Han, J. Pei, and Y. Yin, "Mining frequent patterns without candidate generation," in *Proc. ACM SIGMOD, 2000, pp. 1–12*.

[27] A. Evfimievski, R. Srikant, R. Agrawal, and J. Gehrke, "Privacy preserving mining of association rules," in *Proc. ACM SIGKDD, 2002, pp. 217–228*.

[28] S. J. Rizvi and J. R. Haritsa, "Maintaining data privacy in association rule mining," in *Proc. VLDB, 2002, pp. 682–693*.

[29] D. Agrawal and C. Aggarwal, "On the design and quantification of privacy preserving data mining algorithms," in *Proc. ACM PODS, 2001, pp. 247–255*.

[30] C. Clifton, M. Kantarcioglu, J. Vaidya, X. Lin, and M. Y. Zhu, "Tools for privacy preserving distributed data mining," in *SIGKDD Explorations, vol. 4, no. 2, pp. 28–34, 2002*.

[31] Y. Chen, W. Gan, Y. Wu, and P. S. Yu, "Privacy-preserving federated mining of frequent itemsets," in *Inf. Sci.,vol. 625, pp. 504–520, 2023*.

[32] J. M.-T. Wu et al., "A privacy frequent itemsets mining framework for collaboration in IoT using federated learning," in *ACM Trans. Sensor Netw., vol. 19, no. 2, art. 27, 2023*.

[33] S. Zehtabchi, N. Daneshpour, and M. Safkhani, "A new method for privacy preserving association rule mining using homomorphic encryption," in *Wireless Netw., vol. 29, no. 3, pp. 1197–1212, 2023*.

[34] W. Wu and J. Hao, "Privacy-preserving Apriori-based association rule mining over semantically secure encrypted cloud database," in *Peer-to-Peer Netw. Appl., vol. 17, no. 6, pp. 4156–4174, 2024*.

[35] U. H. W. A. Hewage, R. Sinha, and M. A. Naeem, "Privacy-preserving data mining techniques and their impact on data mining accuracy," in *Artif. Intell. Rev., vol. 56, pp. 10427–10464, 2023*.

[36] S. Goldwasser, S. Micali, and C. Rackoff, "The knowledge complexity of interactive proof systems," in *SIAM J. Comput., vol. 18, no. 1, pp. 186–208, 1989*.

[37] I. Damgård, "On Σ-protocols," in *Lecture Notes in Computer Science, 2010, pp. 1–18*.

[38] C. P. Schnorr, "Efficient identification and signatures for smart cards," in *J. Cryptol., vol. 4, no. 3, pp. 161–174,1991*.

[39] Z. Chen, Y. Jiang, X. Song, and L. Chen, "A survey on zero-knowledge authentication for Internet of Things," in *Electronics, vol. 12, no. 5, art. 1145, 2023*.

[40] M. O. Ahmad et al., "BAuth-ZKP — A blockchain-based multi-factor authentication mechanism for securing smart cities," in *Sensors, vol. 23, no. 5, art. 2757, 2023*.

[41] L. Würsching, F. Putz, S. Haesler, and M. Hollick, "FIDO2 the rescue? Platform vs. roaming authentication on smartphones," in *Proc. CHI '23, Hamburg, Germany, 2023, art. 68*.

[42] T. Gharib, H. Al-Hamadi, and M. Al-Qutayri, "Blockchain-enhanced zero knowledge proof-based privacy preserving mutual authentication for IoT networks," in *IEEE Access, vol. 12, pp. 119874–119889, 2024*.

[43] Z. Jan et al., "Artificial intelligence for Industry 4.0: Systematic review of applications, challenges, and opportunities," in *Expert Syst. Appl., vol. 216, art. 119456, 2023*.

[44] N. Kashpruk, C. Piskor-Ignatowicz, and J. Baranowski, "Time series prediction in Industry 4.0: A comprehensive review," in *Appl. Sci., vol. 13, no. 22, art. 12374, 2023*.

[45] S. S. W. Fatima and A. Rahimi, "A review of time-series forecasting algorithms for industrial manufacturing

systems," in *Machines, vol. 12, no. 6, art. 380, 2024*.

[46] M. Hellmeier, J. Pampus, H. Qarawlus, and F. Howar, "Implementing data sovereignty: Requirements and challenges from practice," in *Proc. ARES '23, Benevento, Italy, 2023, art. 143*.

[47] S. Fugkeaw, P. Suksai, and L. Hak, "SSF-CDW: Achieving scalable, secure, and fast OLAP query for encrypted cloud data warehouse," in *J. Cloud Comput., vol. 13, art. 129, 2024*.

[48] A. Cuzzocrea, "Privacy-preserving OLAP against big query workloads," in *Distrib. Parallel Databases, vol. 43, art. 2, 2025*.

[49] C. Zanasi, S. Russo, and M. Colajanni, "A service-oriented microservice framework for differential privacy based protection in industrial IoT," in *Sci. Rep., vol. 15, art. 12408, 2025*.

[50] J. Haas, R. Mogk, E. Yanakieva, A. Bieniusa, and M. Mezini, "LoRe: A programming model for verifiably safe local-first software," in *ACM Trans. Program. Lang. Syst., vol. 46, no. 1, art. 2, 2024*.

[51] S. J. Taylor and B. Letham, "Forecasting at scale," in *Amer. Stat., vol. 72, no. 1, pp. 37–45, 2018*.

[52] R. J. Hyndman and G. Athanasopoulos, "Forecasting: Principles and Practice," in *2nd ed. OTexts, 2018*.

[53] Parliament of Sri Lanka, "Personal Data Protection Act No. 9 of 2022," in *Gazette of the Democratic Socialist Republic of Sri Lanka, Colombo, Sri Lanka, Mar. 2022*.

6. APPENDICES



Figure 6.1: Plagiarism Report