

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)
Artificial Intelligence Application Development
Module 1
Practical –III

Roll no. : T018	Name : Sachin Ramesh Mehta
Class : TYIT	Batch : 1
Date of assignment : 18/07/2026	Date of assignment : 18/07/2026

Problem Solving by Searching (Informed Search)

1. Given an initial configuration of the 8-puzzle and a goal configuration, write a Python program to find the solution using Greedy Best-First Search with the Manhattan Distance heuristic.

Code :-

```
import heapq
def print_state(state):
    for i in range(0, 9, 3):
        print(state[i], state[i+1], state[i+2])
    print()
def heuristic(state, goal):
    distance = 0
    for num in range(1, 9):
        current = state.index(num)
        target = goal.index(num)
        x1, y1 = current // 3, current % 3
        x2, y2 = target // 3, target % 3
        distance += abs(x1 - x2) + abs(y1 - y2)
    return distance
def get_neighbors(state):
    neighbors = []
    blank = state.index(0)
    moves = [-3, 3, -1, 1]
    for move in moves:
        new = blank + move
        if new >= 0 and new < 9:
            if blank % 3 == 0 and move == -1:
                continue
            if blank % 3 == 2 and move == 1:
                continue
            temp = list(state)
            temp[blank], temp[new] = temp[new], temp[blank]
            neighbors.append(tuple(temp))
    return neighbors
def greedy(initial, goal):
    queue = []
```

```

heapq.heappush(
    queue,
    (heuristic(initial, goal), initial, [])
)
visited = set()
while queue:
    h, state, path = heapq.heappop(queue)
    if state == goal:
        return path + [state]
    if state not in visited:
        visited.add(state)
        for next_state in get_neighbors(state):
            heapq.heappush(
                queue,
                (heuristic(next_state, goal),
                 next_state,
                 path + [state])
            )
    return None
initial = (
    1, 2, 3,
    4, 0, 6,
    7, 5, 8
)
goal = (
    1, 2, 3,
    4, 5, 6,
    7, 8, 0
)
print("Initial State:")
print_state(initial)
print("Goal State:")
print_state(goal)
solution = greedy(initial, goal)
print("Solution:")
for step, state in enumerate(solution):
    print("Step", step)
    print_state(state)
print("Sachin Ramesh Mehta")

```

Output :-

Initial State:

```

1 2 3
4 0 6
7 5 8

```

Goal State:

```

1 2 3
4 5 6
7 8 0

```

Solution:

```

Step 0
1 2 3
4 0 6
7 5 8

```

Step 1

```

1 2 3
4 5 6
7 0 8

```

Step 2

```

1 2 3
4 5 6
7 8 0

```

Sachin Ramesh Mehta

2. Given an initial configuration of the 8-puzzle and a goal configuration, write a Python program to find the shortest path using A* search with the Manhattan Distance heuristic.

Code :-

```
import heapq
def print_state(state):
    for i in range(0, 9, 3):
        print(state[i], state[i+1], state[i+2])
    print()
def heuristic(state, goal):
    distance = 0
    for num in range(1, 9):
        current = state.index(num)
        target = goal.index(num)
        x1, y1 = current // 3, current % 3
        x2, y2 = target // 3, target % 3
        distance += abs(x1-x2) + abs(y1-y2)
    return distance
def get_neighbors(state):
    neighbors = []
    blank = state.index(0)
    moves = [-3, 3, -1, 1]
    for move in moves:
        new = blank + move
        if new >= 0 and new < 9:
            if blank % 3 == 0 and move == -1:
                continue
            if blank % 3 == 2 and move == 1:
                continue
            temp = list(state)
            temp[blank], temp[new] = temp[new], temp[blank]
            neighbors.append(tuple(temp))
    return neighbors
def astar(initial, goal):
    queue = []
    heapq.heappush(queue, (heuristic(initial, goal), 0, initial, []))
    visited = set()
    while queue:
        f, g, state, path = heapq.heappop(queue)
        if state == goal:
            return path + [state]
        if state not in visited:
            visited.add(state)
            for next_state in get_neighbors(state):
                new_g = g + 1
                new_f = new_g + heuristic(next_state, goal)
                heapq.heappush(
                    queue,
                    (new_f, new_g, next_state, path + [state])
                )
    return None
initial = (1,2,3,
          4,0,6,
```

```

        7,5,8)
goal = (1,2,3,
        4,5,6,
        7,8,0)
print("Initial State:")
print_state(initial)
print("Goal State:")
print_state(goal)
solution = astar(initial, goal)
print("Shortest Path using A* Search:")
step = 1
for state in solution[1:]:
    print("Step", step)
    print_state(state)
    step += 1
print("Goal reached successfully.")
print("Total number of moves:", len(solution)-1)
print("Sachin Ramesh Mehta")

```

Output :-

Initial State:

```

1 2 3
4 0 6
7 5 8

```

Goal State:

```

1 2 3
4 5 6
7 8 0

```

Shortest Path using A* Search:

```

Step 1
1 2 3
4 5 6
7 0 8

```

Step 2

```

1 2 3
4 5 6
7 8 0

```

Goal reached successfully.

Total number of moves: 2

Sachin Ramesh Mehta

3. Given a weighted graph representing cities and distances between them, write a Python program to find the shortest path from Arad to Bucharest using A* search with a heuristic function (straight-line distance to destination).

Code :-

```

import heapq
graph = {
    'Arad': [('Zerind',75), ('Sibiu',140), ('Timisoara',118)],
    'Zerind': [('Arad',75), ('Oradea',71)],
    'Oradea': [('Zerind',71), ('Sibiu',151)],
    'Sibiu': [('Arad',140), ('Oradea',151), ('Fagaras',99), ('Rimnicu Vilcea',80)],
    'Timisoara': [('Arad',118), ('Lugoj',111)],
    'Lugoj': [('Timisoara',111), ('Mehadia',70)],
    'Mehadia': [('Lugoj',70), ('Drobeta',75)],
    'Drobeta': [('Mehadia',75), ('Craiova',120)],
    'Craiova': [('Drobeta',120), ('Rimnicu Vilcea',146), ('Pitesti',138)],
    'Rimnicu Vilcea': [('Sibiu',80), ('Craiova',146), ('Pitesti',97)],
    'Fagaras': [('Sibiu',99), ('Bucharest',211)],

```

```

    'Pitesti': [('Rimnicu Vilcea',97), ('Craiova',138), ('Bucharest',101)],
    'Bucharest': []
}
heuristic = {
    'Arad': 366,
    'Zerind': 374,
    'Oradea': 380,
    'Sibiu': 253,
    'Timisoara': 329,
    'Lugoj': 244,
    'Mehadia': 241,
    'Drobeta': 242,
    'Craiova': 160,
    'Rimnicu Vilcea': 193,
    'Fagaras': 176,
    'Pitesti': 100,
    'Bucharest': 0
}

def astar(start, goal):
    queue = []
    # queue contains: f_cost, g_cost, city, path
    heapq.heappush(queue, (heuristic[start], 0, start, [start]))
    visited = set()
    while queue:
        f_cost, g_cost, city, path = heapq.heappop(queue)
        if city == goal:
            return g_cost, path
        if city not in visited:
            visited.add(city)
            for neighbor, distance in graph[city]:
                new_g = g_cost + distance
                new_f = new_g + heuristic[neighbor]
                heapq.heappush(queue, (new_f, new_g, neighbor, path + [neighbor]))
    return None, []
cost, path = astar('Arad', 'Bucharest')
print("Shortest path using A* Search:")
print("Path:", " -> ".join(path))
print("Total Cost:", cost)
print("Sachin Ramesh Mehta")

```

Output :-

```

Shortest path using A* Search:
Path: Arad -> Sibiu -> Rimnicu Vilcea -> Pitesti -> Bucharest
Total Cost: 418
Sachin Ramesh Mehta

```