

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)
Enterprise Java

Practical – V

Roll No.: T018	Name: Sachin Ramesh Mehta
Class: TYIT	Batch: 1
Date of Assignment: 01/08/2026	Date/Time of Submission: 01/08/2026

5. Implement the following JSP JSTL and EL Applications.

a. Create an html page with fields, eno, name, age, designation, salary. Now on submit this data to a JSP page which will update the employee table of database with matching eno.

Code:

Index.html:

```
<!DOCTYPE html>
<html>
<head>
  <title>Employee Update</title>
</head>
<body>
<h2>Employee Update Form</h2>
<form action="update.jsp" method="post">
  Employee No:
  <input type="text" name="eno"><br><br>
  Name:
  <input type="text" name="name"><br><br>
  Age:
  <input type="text" name="age"><br><br>
  Designation:
  <input type="text" name="designation"><br><br>
  Salary:
  <input type="text" name="salary"><br><br>
  <input type="submit" value="Update Employee">
</form>
</body>
</html>
```

Update.jsp:

```
<%@page import="java.sql.*"%>
<%
String eno = request.getParameter("eno");
String name = request.getParameter("name");
String age = request.getParameter("age");
String designation = request.getParameter("designation");
String salary = request.getParameter("salary");
try
{
  Class.forName("com.mysql.jdbc.Driver");
```

```
Connection con = DriverManager.getConnection(
    "jdbc:mysql://localhost:3306/employee_db",
    "root",
    "IT");
PreparedStatement ps = con.prepareStatement(
    "UPDATE employee SET name=?, age=?, designation=?, salary=? WHERE eno=?");
ps.setString(1, name);
ps.setInt(2, Integer.parseInt(age));
ps.setString(3, designation);
ps.setDouble(4, Double.parseDouble(salary));
ps.setInt(5, Integer.parseInt(en));
int i = ps.executeUpdate();
if(i>0)
    out.println("<h2>Employee Updated Successfully</h2>");
else
    out.println("<h2>Employee Number Not Found</h2>");

con.close();
}
catch(Exception e)
{
    out.println(e);
}
}%>
```

Output:

Employee Update Form

Employee No:

Name:

Age:

Designation:

Salary:

Employee Updated Successfully

```
mysql> SELECT * FROM employee;
+-----+-----+-----+-----+-----+
| eno | name  | age | designation | salary |
+-----+-----+-----+-----+-----+
| 101 | Rahul | 25  | Developer   | 35000  |
| 102 | Sachin | 22  | Manager     | 50000  |
| 103 | Amit  | 30  | Tester      | 40000  |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from employee;
+-----+-----+-----+-----+-----+
| eno | name  | age | designation | salary |
+-----+-----+-----+-----+-----+
| 101 | Sachin | 20  | New Manager | 60000  |
| 102 | Sachin | 22  | Manager     | 50000  |
| 103 | Amit  | 30  | Tester      | 40000  |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

b. Create a JSP page to demonstrate the use of Expression language.**Code:****index.html:**

```
<!DOCTYPE html>
<html>
<body>
<h2>Home Page</h2>
<a href="language.jsp">Open JSP EL Example</a>
</body>
</html>
```

Expressions.jsp:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<title>Expression Language Demo</title>
</head>
<body>
<h2>JSP Expression Language Example</h2>
<p>Addition: ${12+2}</p>
<p>Multiplication: ${5*4}</p>
<p>Division: ${20/5}</p>
<p>Comparison: ${10>5}</p>
<p>Logical Operation: ${true && false}</p>
</body>
</html>
```

Output:**Home Page**[Click here](#)**JSP Expression Language Example**

Addition: 14

Multiplication: 20

Division: 4.0

Comparison: true

Logical Operation: false

c. Create a JSP application to demonstrate the use of JSTL.**Code:****index.html:**

```
<!DOCTYPE html>
<html>
<body>
<h2>Home Page</h2>
<a href="language.jsp">Open JSP EL Example</a>
</body>
</html>
```

Expressions.jsp:

```
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Core Tag Example</title>
</head>
<body>
<c:forEach var = "j" begin="5" end="15">
Item <c:out value = "${j}" /><p>
</c:forEach>
</body>
</html>
```

Output:

```
Item 5
Item 6
Item 7
Item 8
Item 9
Item 10
Item 11
Item 12
Item 13
Item 14
Item 15
```