



Discrete Structures

Lecture 11: Sets and Set Operations

based on slides by Jan Stelovsky

based on slides by Dr. Baek and Dr. Still

Originals by Dr. M. P. Frank and Dr. J.L. Gross

Provided by McGraw-Hill

Muhammad Adeel Zahid

Department of Computer Science
Government College University
Faisalabad



Set Identities

- Identity: $A \cup \emptyset = A = A \cap U$
- Domination: $A \cup U = U, A \cap \emptyset = \emptyset$
- Idempotent: $A \cup A = A, A \cap A = A$
- Double complement: $(A^c)^c = A$
- Commutative: $A \cup B = B \cup A, A \cap B = B \cap A$
- Associative:
 - $A \cup (B \cup C) = (A \cup B) \cup C,$
 - $A \cap (B \cap C) = (A \cap B) \cap C$
- Distributive:
 - $A \cap (B \cup C) = (A \cap B) \cup (A \cap C),$
 - $A \cup (B \cap C) = (A \cup B) \cap (A \cup C)$
- Absorption: $A \cup (A \cap B) = A, A \cap (A \cup B) = A$
- Complement: $A \cup A^c = U, A \cap A^c = \emptyset$



De Morgan's Law for Sets

- Exactly analogous to (and provable from) DeMorgan's Law for propositions
 - $(A \cup B)^c = A^c \cap B^c$
 - $(A \cap B)^c = A^c \cup B^c$



Proving Set Identities

- To prove statements about sets, of the form $E1 = E2$ (where the E s are set expressions), here are three useful techniques:
 - 1. Prove $E1 \subseteq E2$ and $E2 \subseteq E1$ separately.
 - 2. Use set builder notation & logical equivalences.
 - 3. Use a membership table.
 - 4. Use a Venn diagrams



Method 1: Mutual Subsets

- Example: Show $A \cap (B \cup C) = (A \cap B) \cup (A \cap C)$
- Part 1: Show $A \cap (B \cup C) \subseteq (A \cap B) \cup (A \cap C)$
- Assume $x \in A \cap (B \cup C)$, & show $x \in (A \cap B) \cup (A \cap C)$
- We know that $x \in A$, and either $x \in B$ or $x \in C$
 - Case 1: $x \in A \wedge x \in B$. Then $x \in A \cap B$,
 - so $x \in (A \cap B) \cup (A \cap C)$
 - Case 2: $x \in A \wedge x \in C$. Then $x \in A \cap C$,
 - so $x \in (A \cap B) \cup (A \cap C)$
- Therefore, $x \in (A \cap B) \cup (A \cap C)$
- Therefore, $A \cap (B \cup C) \subseteq (A \cap B) \cup (A \cap C)$



Method 1: Mutual Subsets

- Part 2: Show $(A \cap B) \cup (A \cap C) \subseteq A \cap (B \cup C)$
- Let's assume that $x \in (A \cap B) \cup (A \cap C)$
- $x \in (A \cap B)$ or $x \in (A \cap C)$ By definition of union
- $(x \in A \text{ and } x \in B)$ or $(x \in A \text{ and } x \in C)$ By def of intersection
- We can see that, $x \in A$ and $(x \in B \text{ or } x \in C)$
- And $x \in A$ and $x \in (B \cup C)$ By def of union
- Finally, $x \in A \cap (B \cup C)$ By def of intersection
- Consequently, $(A \cap B) \cup (A \cap C) \subseteq A \cap (B \cup C)$ is proved



Method 2: Set Builder Notation and Logical Equivalence

- Show that $(A \cap B)^c = A^c \cup B^c$
- $(A \cap B)^c = \{x | x \notin A \cap B\}$ definition of complement
- $= \{x | \neg (x \in A \cap B)\}$ definition of does not belong
- $= \{x | \neg (x \in A \wedge x \in B)\}$ definition of intersection
- $= \{x | \neg x \in A \vee \neg x \in B\}$ De Morgan's Law (logic)
- $= \{x | x \notin A \vee x \notin B\}$ Definition of does not belong
- $= \{x | x \in A^c \vee x \in B^c\}$ Definition of Complement
- $= \{x | x \in A^c \cup B^c\}$ Definition of Union
- $= A^c \cup B^c$ By set builder Notation



Method 3: Membership Tables

- Analog to truth tables in propositional logic
- Columns for different set expressions
- Rows for all combinations of memberships in constituent sets
- Use “1” to indicate membership in the derived set, “0” for non-membership.
- Prove equivalence with identical columns



Membership Table Example

- Prove that $(A \cup B) - B = A - B$

A	B	$A \cup B$	$(A \cup B) - B$	$A - B$
1	1	1	0	0
1	0	1	1	1
0	1	1	0	0
0	0	0	0	0



Membership Table Exercise


- Prove $(A \cup B) - C = (A - C) \cup (B - C)$

A	B	C	$A \cup B$	$(A \cup B) - C$	$A - C$	$B - C$	$(A - C) \cup (B - C)$
1	1	1	1	0	0	0	0
1	1	0	1	1	1	1	1
1	0	1	1	0	0	0	0
1	0	0	1	1	1	0	1
0	1	1	1	0	0	0	0
0	1	0	1	1	0	1	1
0	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0



Method 4: Venn Diagrams

- Prove $(A \cup B) - C = (A - C) \cup (B - C)$





Generalized Unions and Intersections

- Since union & intersection are
 - Commutative and
 - Associative,
- we can extend them from operating on pairs of sets A and B to operating on sequences of sets A_1, \dots, A_n , or even on sets of sets, $X = \{A \mid P(A)\}$



Generalized Union

- Binary union operator: $A \cup B$
- n-ary union: $A_1 \cup A_2 \cup \dots \cup A_n = ((\dots ((A_1 \cup A_2) \cup \dots) \cup A_n)$
 - (grouping & order is irrelevant)
- “Big U” notation: $\bigcup_{i=1}^n A_i$
- More generally, union of the sets A_i for $i \in I$: $\bigcup_{i \in I} A_i$
- For infinite number of sets: $\bigcup_{i=1}^{\infty} A_i$



Generalized Union Example

- Let $A_i = \{i, i + 1, i + 2, \dots\}$. Then,
- $\bigcup_{i=1}^n A_i = A_1 \cup A_2 \cup A_3 \cup \dots \cup A_n$
- $= \{1, 2, 3, \dots\} \cup \{2, 3, 4, \dots\} \cup \dots \cup \{n, n + 1, n + 2, \dots\}$
- $= \{1, 2, 3, \dots\} = \mathbb{Z}^+$
- Let $A_i = \{1, 2, 3, \dots, i\}$ Then
- $\bigcup_{i=1}^{\infty} A_i = A_1 \cup A_2 \cup A_3 \cup \dots$
- $= \{1\} \cup \{1, 2\} \cup \{1, 2, 3\} \cup \dots$
- $= \{1, 2, 3, \dots\} = \mathbb{Z}^+$



Generalized Intersection

- Binary intersection operator: $A \cap B$
- n-ary intersection: $A_1 \cap A_2 \cap \cdots \cap A_n = ((\dots ((A_1 \cap A_2) \cap \cdots) \cap A_n)$
 - (grouping & order is irrelevant)
- “Big arch” notation: $\bigcap_{i=1}^n A_i$
- More generally, intersection of the sets A_i for $i \in I$: $\bigcap_{i \in I} A_i$
- For infinite number of sets: $\bigcap_{i=1}^{\infty} A_i$



Generalized Intersection Example

- Let $A_i = \{i, i + 1, i + 2, \dots\}$. Then,
- $\bigcap_{i=1}^n A_i = A_1 \cap A_2 \cap \dots \cap A_n$
- $= \{1, 2, 3, \dots\} \cap \{2, 3, 4, \dots\} \cap \dots \cap \{n, n + 1, n + 2, \dots\}$
- $= \{n, n + 1, n + 2, \dots\}$
- Let $A_i = \{1, 2, 3, \dots, i\}$ Then
- $\bigcap_{i=1}^n A_i = A_1 \cap A_2 \cap \dots$
- $= \{1\} \cap \{1, 2\} \cap \{1, 2, 3\} \cap \dots$
- $= \{1\}$



Bit String Representation of Sets

- A frequent theme of this course are methods of representing one discrete structure using another discrete structure of a different type
- For an enumerable universal set U with ordering x_1, x_2, x_3, \dots , we can represent a finite set $S \subseteq U$ as the finite bit string $B = b_1 b_2 \dots b_n$ where $b_i = 1$ if $x_i \in S$ and $b_i = 0$ if $x_i \notin S$
- $U = N, S = \{2, 3, 5, 7, 11\}, B = 0011 0101 0001$
- In this representation, the set operators, union, intersection and complement are implemented directly by bitwise OR, AND, NOT respectively



Examples of Sets as Bit Strings

- Let $U = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 10\}$, and the ordering of elements of U has the elements in increasing order, then
- $S_1 = \{1, 2, 3, 4, 5\} \Rightarrow B_1 = 11\ 1110\ 0000$
- $S_2 = \{1, 3, 5, 7, 9\} \Rightarrow B_2 = 10\ 1010\ 1010$
- $S_1 \cup S_2 = \{1, 2, 3, 4, 5, 7, 9\} \Rightarrow \text{bit string} = 11\ 1110\ 1010 = B_1 \vee B_2$
- $S_1 \cap S_2 = \{1, 3, 5\} \Rightarrow \text{bit string} = 10\ 1010\ 0000 = B_1 \wedge B_2$
- $S_1^c = \{6, 7, 8, 9, 10\} \Rightarrow \text{bit string} = 00\ 0001\ 1111 = \neg B_1$