



Select a spec

default



Transaction Microservice API^{1.0}

[Base URL: localhost:8084/]

<http://localhost:8084/v2/api-docs>

API for Transaction Microservice

[Terms of service](#)

[Fatih Zukorlic - Website](#)

[Send email to Fatih Zukorlic](#)

[API License](#)

Product Controller

Product Controller

**POST****/products/add** Add a new product

This service method is used to add a new product to the transaction database.

Parameters

Try it out**Name****Description****product** * required

product

*(body)***Example Value** | Model

```
{
  "arhived": true,
  "id": 0,
  "name": "string",
  "price": 0
}
```

Parameter content type

application/json



Responses

Response content type

/



Code

Description

200

OK

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

Transaction Controller

Transaction Controller



GET

/{id}/active Get active transaction

This service method is used to get active transaction to the system for user with {id}.

Parameters

Try it out

Name

Description

id * required

id

integer(\$int64)

(path)

Responses

Response content type

/



Code

Description

200

OK

Example Value | Model

{ }

401

Unauthorized

403

Forbidden

404

Not Found

PUT

/{id}/close Close transaction

This service method is used to close transaction.

Parameters

Try it out

Name

Description

id * required

id

integer(\$int64)
(path)

Responses

Response content type

/



Code

Description

Code	Description
200	<div>OK</div>
	<div>Example Value Model</div> <div>{ }</div>
201	<div>Created</div>
401	<div>Unauthorized</div>
403	<div>Forbidden</div>
404	<div>Not Found</div>

GET

/{id}/closed

Get closed transaction

This service method is used to get closed transaction to the system for user with {id}.

Parameters

Try it out

Name	Description
<div><div>id * required</div><div>integer(\$int64)</div><div>(path)</div></div>	id

Responses

Response content type

/

▼

Code	Description
------	-------------

Code	Description
200	<div>OK</div>
	<div>Example Value Model</div> <div>{ }</div>
401	<div>Unauthorized</div>
403	<div>Forbidden</div>
404	<div>Not Found</div>

POST

/add Add a new transaction

This service method is used to add a new transaction to the system.

Parameters

Try it out

Name	Description
allErrors[0].arguments	
array[object]	
(query)	
allErrors[0].code	
string	
(query)	
allErrors[0].codes	
array[string]	
(query)	

Name	Description
------	-------------

allErrors[0].defaultMessage	
-----------------------------	--

string	
--------	--

(query)	
---------	--

allErrors[0].objectName	
-------------------------	--

string	
--------	--

(query)	
---------	--

errorCount	
------------	--

integer(\$int32)	
------------------	--

(query)	
---------	--

fieldError.arguments	
----------------------	--

array[object]	
---------------	--

(query)	
---------	--

fieldError.bindingFailure	
---------------------------	--

boolean	
---------	--

(query)	
---------	--

fieldError.code	
-----------------	--

string	
--------	--

(query)	
---------	--

fieldError.codes	
------------------	--

array[string]	
---------------	--

(query)	
---------	--

fieldError.defaultMessage	
---------------------------	--

string	
--------	--

(query)	
---------	--

fieldError.field	
------------------	--

string	
--------	--

(query)	
---------	--

fieldError.objectName	
-----------------------	--

string	
--------	--

(query)	
---------	--

fieldError.rejectedValue	
--------------------------	--

object	
--------	--

(query)	
---------	--

Name	Description
------	-------------

fieldErrorCount

integer(\$int32)
(query)

fieldErrors[0].arguments

array[object]
(query)

fieldErrors[0].bindingFailure

boolean
(query)

fieldErrors[0].code

string
(query)

fieldErrors[0].codes

array[string]
(query)

fieldErrors[0].defaultMessage

string
(query)

fieldErrors[0].field

string
(query)

fieldErrors[0].objectName

string
(query)

fieldErrors[0].rejectedValue

object
(query)

globalError.arguments

array[object]
(query)

globalError.code

string
(query)

Name	Description
------	-------------

globalError.codes

array[string]

(query)

globalError.defaultMessage

string

(query)

globalError.objectName

string

(query)

globalErrorCount

integer(\$int32)

(query)

globalErrors[0].arguments

array[object]

(query)

globalErrors[0].code

string

(query)

globalErrors[0].codes

array[string]

(query)

globalErrors[0].defaultMessage

string

(query)

globalErrors[0].objectName

string

(query)

nestedPath

string

(query)

objectName

string

(query)

Name

requestBody * required
(body)

Description

requestBody

Example Value | Model

```
{  
  "buyer": 0,  
  "owner": 0,  
  "product": 0  
}
```

Parameter content type

application/json

▼

Responses

Response content type

/

▼

Code

Description

200

OK

Example Value | Model

```
{}
```

201

Created

401

Unauthorized

403

Forbidden

404

Not Found

user-controller User Controller

**DELETE**`/users/{email} deleteUser`

Parameters

[Try it out](#)

Name

Description

email * required

email

string

(path)

Responses

Response content type

/



Code

Description

200

OK

204

No Content

401

Unauthorized

403

*Forbidden***POST**`/users/add addUser`

Parameters

[Try it out](#)

Name

Description

Name

Description

user * required*(body)*

USER

Example Value | Model

```
{
  "email": "string",
  "firstName": "string",
  "id": 0,
  "lastName": "string"
}
```

Parameter content type

application/json



Responses

Response content type

/



Code

Description

200

OK

201

Created

401

Unauthorized

403

Forbidden

404

Not Found



Models

Product ▾ {

```
  arhived      boolean
  id           integer($int64)
  name         string
  price        number($double)
}
```

TransactionForm ▾ {

```
  buyer      integer($int64)
  owner       integer($int64)
  product     integer($int64)
}
```

User ▾ {

```
  email      string
  firstName  string
  id         integer($int64)
  lastName   string
}
```