

CSE 431/531: Algorithm Analysis and Design (Fall 2024)

Divide-and-Conquer

Lecturer: Kelin Luo

*Department of Computer Science and Engineering
University at Buffalo*

Outline

- 1 Divide-and-Conquer
- 2 Counting Inversions
- 3 Quicksort and Selection
 - Quicksort
 - Lower Bound for Comparison-Based Sorting Algorithms
 - Selection Problem
- 4 Polynomial Multiplication
- 5 Solving Recurrences
- 6 Computing n -th Fibonacci Number
- 7 Other Classic Algorithms using Divide-and-Conquer

Running Time for Merge-Sort Using Recurrence

- $T(n)$ = running time for sorting n numbers, then

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + O(n) & \text{if } n \geq 2 \end{cases}$$

Running Time for Merge-Sort Using Recurrence

- $T(n)$ = running time for sorting n numbers, then

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + O(n) & \text{if } n \geq 2 \end{cases}$$

- With some tolerance of informality:

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ 2T(n/2) + O(n) & \text{if } n \geq 2 \end{cases}$$

Running Time for Merge-Sort Using Recurrence

- $T(n)$ = running time for sorting n numbers, then

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + O(n) & \text{if } n \geq 2 \end{cases}$$

- With some tolerance of informality:

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ 2T(n/2) + O(n) & \text{if } n \geq 2 \end{cases}$$

- Even simpler: $T(n) = 2T(n/2) + O(n)$. (Implicit assumption: $T(n) = O(1)$ if n is at most some constant.)

Running Time for Merge-Sort Using Recurrence

- $T(n)$ = running time for sorting n numbers, then

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + O(n) & \text{if } n \geq 2 \end{cases}$$

- With some tolerance of informality:

$$T(n) = \begin{cases} O(1) & \text{if } n = 1 \\ 2T(n/2) + O(n) & \text{if } n \geq 2 \end{cases}$$

- Even simpler: $T(n) = 2T(n/2) + O(n)$. (Implicit assumption: $T(n) = O(1)$ if n is at most some constant.)
- Solving this recurrence, we have $T(n) = O(n \lg n)$ (we shall show how later)

Outline

- 1 Divide-and-Conquer
- 2 Counting Inversions
- 3 Quicksort and Selection
 - Quicksort
 - Lower Bound for Comparison-Based Sorting Algorithms
 - Selection Problem
- 4 Polynomial Multiplication
- 5 Solving Recurrences
- 6 Computing n -th Fibonacci Number
- 7 Other Classic Algorithms using Divide-and-Conquer

Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Counting Inversions

Input: a sequence A of n numbers

Output: number of inversions in A

Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Counting Inversions

Input: a sequence A of n numbers

Output: number of inversions in A

Example:

10

8

15

9

12

Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Counting Inversions

Input: a sequence A of n numbers

Output: number of inversions in A

Example:

10	8	15	9	12
8	9	10	12	15


Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Counting Inversions

Input: a sequence A of n numbers

Output: number of inversions in A

Example:




Def. Given an array A of n integers, an inversion in A is a pair (i, j) of indices such that $i < j$ and $A[i] > A[j]$.

Counting Inversions

Input: a sequence A of n numbers

Output: number of inversions in A

Example:




- 4 inversions (for convenience, using numbers, not indices):
 $(10, 8)$, $(10, 9)$, $(15, 9)$, $(15, 12)$

Naive Algorithm for Counting Inversions

count-inversions(A, n)

```
1:  $c \leftarrow 0$ 
2: for every  $i \leftarrow 1$  to  $n - 1$  do
3:   for every  $j \leftarrow i + 1$  to  $n$  do
4:     if  $A[i] > A[j]$  then  $c \leftarrow c + 1$ 
5: return  $c$ 
```

Divide-and-Conquer




- $p = \lfloor n/2 \rfloor, B = A[1..p], C = A[p+1..n]$
- $$\#invs(A) = \#invs(B) + \#invs(C) + m$$
$$m = |\{(i, j) : B[i] > C[j]\}|$$

Q: How fast can we compute m , via trivial algorithm?

A: $O(n^2)$

- Can not improve the $O(n^2)$ time for counting inversions.

Divide-and-Conquer



- $p = \lfloor n/2 \rfloor, B = A[1..p], C = A[p+1..n]$
- $$\#invs(A) = \#invs(B) + \#invs(C) + m$$
$$m = |\{(i, j) : B[i] > C[j]\}|$$

Lemma If both B and C are sorted, then we can compute m in $O(n)$ time!

Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:

B :

3	8	12	20	32	48
---	---	----	----	----	----


 total = 0

C :

5	7	9	25	29
---	---	---	----	----



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0

+2



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:






+0

+2






Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2 +3 +3




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2 +3 +3




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2 +3 +3




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2 +3 +3




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:





+0 +2 +3 +3




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:






+0 +2 +3 +3






Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:




Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:



Counting Inversions between B and C

Count pairs i, j such that $B[i] > C[j]$:



Count Inversions between B and C

- Procedure that merges B and C and counts inversions between B and C at the same time

merge-and-count(B, C, n_1, n_2)

```
1:  $count \leftarrow 0$ ;  
2:  $A \leftarrow$  array of size  $n_1 + n_2$ ;  $i \leftarrow 1$ ;  $j \leftarrow 1$   
3: while  $i \leq n_1$  or  $j \leq n_2$  do  
4:   if  $j > n_2$  or ( $i \leq n_1$  and  $B[i] \leq C[j]$ ) then  
5:      $A[i + j - 1] \leftarrow B[i]$ ;  $i \leftarrow i + 1$   
6:      $count \leftarrow count + (j - 1)$   
7:   else  
8:      $A[i + j - 1] \leftarrow C[j]$ ;  $j \leftarrow j + 1$   
9: return ( $A, count$ )
```

Sort and Count Inversions in A

- A procedure that returns the sorted array of A and counts the number of inversions in A :

sort-and-count(A, n)

```
1: if  $n = 1$  then  
2:   return ( $A, 0$ )  
3: else  
4:    $(B, m_1) \leftarrow \text{sort-and-count}(A[1..\lfloor n/2 \rfloor], \lfloor n/2 \rfloor)$   
5:    $(C, m_2) \leftarrow \text{sort-and-count}(A[\lfloor n/2 \rfloor + 1..n], \lceil n/2 \rceil)$   
6:    $(A, m_3) \leftarrow \text{merge-and-count}(B, C, \lfloor n/2 \rfloor, \lceil n/2 \rceil)$   
7:   return ( $A, m_1 + m_2 + m_3$ )
```

Sort and Count Inversions in A

- A procedure that returns the sorted array of A and counts the number of inversions in A :

sort-and-count(A, n)

1: **if** $n = 1$ **then**

2: **return** $(A, 0)$

3: **else**

4: $(B, m_1) \leftarrow \text{sort-and-count}(A[1..\lfloor n/2 \rfloor], \lfloor n/2 \rfloor)$

5: $(C, m_2) \leftarrow \text{sort-and-count}(A[\lfloor n/2 \rfloor + 1..n], \lceil n/2 \rceil)$

6: $(A, m_3) \leftarrow \text{merge-and-count}(B, C, \lfloor n/2 \rfloor, \lceil n/2 \rceil)$

7: **return** $(A, m_1 + m_2 + m_3)$

- Divide: trivial

- Conquer: 4, 5

- Combine: 6, 7

sort-and-count(A, n)

```
1: if  $n = 1$  then  
2:   return ( $A, 0$ )  
3: else  
4:    $(B, m_1) \leftarrow \text{sort-and-count}(A[1..\lfloor n/2 \rfloor], \lfloor n/2 \rfloor)$   
5:    $(C, m_2) \leftarrow \text{sort-and-count}(A[\lfloor n/2 \rfloor + 1..n], \lceil n/2 \rceil)$   
6:    $(A, m_3) \leftarrow \text{merge-and-count}(B, C, \lfloor n/2 \rfloor, \lceil n/2 \rceil)$   
7:   return ( $A, m_1 + m_2 + m_3$ )
```

- Recurrence for the running time: $T(n) = 2T(n/2) + O(n)$

sort-and-count(A, n)

```
1: if  $n = 1$  then  
2:   return ( $A, 0$ )  
3: else  
4:    $(B, m_1) \leftarrow \text{sort-and-count}(A[1..\lfloor n/2 \rfloor], \lfloor n/2 \rfloor)$   
5:    $(C, m_2) \leftarrow \text{sort-and-count}(A[\lfloor n/2 \rfloor + 1..n], \lceil n/2 \rceil)$   
6:    $(A, m_3) \leftarrow \text{merge-and-count}(B, C, \lfloor n/2 \rfloor, \lceil n/2 \rceil)$   
7:   return ( $A, m_1 + m_2 + m_3$ )
```

- Recurrence for the running time: $T(n) = 2T(n/2) + O(n)$
- Running time = $O(n \lg n)$

Outline

- 1 Divide-and-Conquer
- 2 Counting Inversions
- 3 Quicksort and Selection
 - Quicksort
 - Lower Bound for Comparison-Based Sorting Algorithms
 - Selection Problem
- 4 Polynomial Multiplication
- 5 Solving Recurrences
- 6 Computing n -th Fibonacci Number
- 7 Other Classic Algorithms using Divide-and-Conquer

Outline

- 1 Divide-and-Conquer
- 2 Counting Inversions
- 3 Quicksort and Selection
 - Quicksort
 - Lower Bound for Comparison-Based Sorting Algorithms
 - Selection Problem
- 4 Polynomial Multiplication
- 5 Solving Recurrences
- 6 Computing n -th Fibonacci Number
- 7 Other Classic Algorithms using Divide-and-Conquer

Quicksort vs Merge-Sort

	Merge Sort	Quicksort
Divide	Trivial	Separate small and big numbers
Conquer	Recurse	Recurse
Combine	Merge 2 sorted arrays	Trivial

Quicksort Example

Assumption We can choose median of an array of size n in $O(n)$ time.

29	82	75	64	38	45	94	69	25	76	15	92	37	17	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Quicksort Example

Assumption We can choose median of an array of size n in $O(n)$ time.

29	82	75	64	38	45	94	69	25	76	15	92	37	17	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Quicksort Example

Assumption We can choose median of an array of size n in $O(n)$ time.

29	82	75	64	38	45	94	69	25	76	15	92	37	17	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

29	38	45	25	15	37	17	64	82	75	94	92	69	76	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Quicksort Example

Assumption We can choose median of an array of size n in $O(n)$ time.

29	82	75	64	38	45	94	69	25	76	15	92	37	17	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

29	38	45	25	15	37	17	64	82	75	94	92	69	76	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Quicksort Example

Assumption We can choose median of an array of size n in $O(n)$ time.

29	82	75	64	38	45	94	69	25	76	15	92	37	17	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

29	38	45	25	15	37	17	64	82	75	94	92	69	76	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

25	15	17	29	38	45	37	64	82	75	94	92	69	76	85
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Quicksort

quicksort(A, n)

- 1: **if** $n \leq 1$ **then return** A
- 2: $x \leftarrow$ lower median of A
- 3: $A_L \leftarrow$ array of elements in A that are less than x $\backslash\backslash$ Divide
- 4: $A_R \leftarrow$ array of elements in A that are greater than x $\backslash\backslash$ Divide
- 5: $B_L \leftarrow$ quicksort(A_L , length of A_L) $\backslash\backslash$ Conquer
- 6: $B_R \leftarrow$ quicksort(A_R , length of A_R) $\backslash\backslash$ Conquer
- 7: $t \leftarrow$ number of times x appear A
- 8: **return** concatenation of B_L , t copies of x , and B_R

Quicksort

quicksort(A, n)

- 1: **if** $n \leq 1$ **then return** A
- 2: $x \leftarrow$ lower median of A
- 3: $A_L \leftarrow$ array of elements in A that are less than x $\backslash\backslash$ Divide
- 4: $A_R \leftarrow$ array of elements in A that are greater than x $\backslash\backslash$ Divide
- 5: $B_L \leftarrow$ quicksort(A_L , length of A_L) $\backslash\backslash$ Conquer
- 6: $B_R \leftarrow$ quicksort(A_R , length of A_R) $\backslash\backslash$ Conquer
- 7: $t \leftarrow$ number of times x appear A
- 8: **return** concatenation of B_L , t copies of x , and B_R

- Recurrence $T(n) \leq 2T(n/2) + O(n)$

Quicksort

quicksort(A, n)

- 1: **if** $n \leq 1$ **then return** A
- 2: $x \leftarrow$ lower median of A
- 3: $A_L \leftarrow$ array of elements in A that are less than x $\backslash\backslash$ Divide
- 4: $A_R \leftarrow$ array of elements in A that are greater than x $\backslash\backslash$ Divide
- 5: $B_L \leftarrow$ quicksort(A_L , length of A_L) $\backslash\backslash$ Conquer
- 6: $B_R \leftarrow$ quicksort(A_R , length of A_R) $\backslash\backslash$ Conquer
- 7: $t \leftarrow$ number of times x appear A
- 8: **return** concatenation of B_L , t copies of x , and B_R

- Recurrence $T(n) \leq 2T(n/2) + O(n)$
- Running time = $O(n \lg n)$

Assumption We can choose median of an array of size n in $O(n)$ time.

Q: How to remove this assumption?

Assumption We can choose median of an array of size n in $O(n)$ time.

Q: How to remove this assumption?

A:

- 1 There is an algorithm to find median in $O(n)$ time, using divide-and-conquer (we shall not talk about it; it is complicated and not practical)

Assumption We can choose median of an array of size n in $O(n)$ time.

Q: How to remove this assumption?

A:

- 1 There is an algorithm to find median in $O(n)$ time, using divide-and-conquer (we shall not talk about it; it is complicated and not practical)
- 2 Choose a **pivot randomly** and pretend it is the median (it is practical)

Quicksort Using A Random Pivot

quicksort(A, n)

- 1: **if** $n \leq 1$ **then return** A
- 2: $x \leftarrow$ a random element of A (x is called a **pivot**)
- 3: $A_L \leftarrow$ array of elements in A that are less than x $\backslash\backslash$ Divide
- 4: $A_R \leftarrow$ array of elements in A that are greater than x $\backslash\backslash$ Divide
- 5: $B_L \leftarrow$ quicksort(A_L , length of A_L) $\backslash\backslash$ Conquer
- 6: $B_R \leftarrow$ quicksort(A_R , length of A_R) $\backslash\backslash$ Conquer
- 7: $t \leftarrow$ number of times x appear A
- 8: **return** concatenation of B_L , t copies of x , and B_R

Randomized Algorithm Model

Assumption There is a procedure to produce a random real number in $[0, 1]$.

Q: Can computers really produce random numbers?

Randomized Algorithm Model

Assumption There is a procedure to produce a random real number in $[0, 1]$.

Q: Can computers really produce random numbers?

A: No! The execution of a computer programs is deterministic!

Randomized Algorithm Model

Assumption There is a procedure to produce a random real number in $[0, 1]$.

Q: Can computers really produce random numbers?

A: No! The execution of a computer programs is deterministic!

- In practice: use **pseudo-random-generator**, a deterministic algorithm returning numbers that “look like” random

Randomized Algorithm Model

Assumption There is a procedure to produce a random real number in $[0, 1]$.

Q: Can computers really produce random numbers?

A: No! The execution of a computer programs is deterministic!

- In practice: use **pseudo-random-generator**, a deterministic algorithm returning numbers that “look like” random
- In theory: assume they can.

Quicksort Using A Random Pivot

quicksort(A, n)

- 1: **if** $n \leq 1$ **then return** A
- 2: $x \leftarrow$ a random element of A (x is called a **pivot**)
- 3: $A_L \leftarrow$ array of elements in A that are less than x $\backslash\backslash$ Divide
- 4: $A_R \leftarrow$ array of elements in A that are greater than x $\backslash\backslash$ Divide
- 5: $B_L \leftarrow$ quicksort(A_L , length of A_L) $\backslash\backslash$ Conquer
- 6: $B_R \leftarrow$ quicksort(A_R , length of A_R) $\backslash\backslash$ Conquer
- 7: $t \leftarrow$ number of times x appear A
- 8: **return** concatenation of B_L , t copies of x , and B_R

Lemma The **expected** running time of the algorithm is $O(n \lg n)$.

Quicksort Can Be Implemented as an “In-Place” Sorting Algorithm

- In-Place Sorting Algorithm: an algorithm that only uses “small” **extra** space.