

CSE 431/531: Algorithm Analysis and Design (Fall 2024)

Greedy Algorithms


Lecturer: Kelin Luo


*Department of Computer Science and Engineering
University at Buffalo*

Outline

- 1 Data Compression and Huffman Code
- 2 Summary
- 3 Summary of Studies until Mid Term I


Properties of Encoding Tree





Properties of Encoding Tree

- Rooted binary tree




Properties of Encoding Tree

- Rooted binary tree
- Left edges labelled 0 and right edges labelled 1




- 3/20



Properties of Encoding Tree

- Rooted binary tree
- Left edges labelled 0 and right edges labelled 1
- A leaf corresponds to a code for some letter
- If coding scheme is not wasteful: a non-leaf has exactly two children



Properties of Encoding Tree

- Rooted binary tree
- Left edges labelled 0 and right edges labelled 1
- A leaf corresponds to a code for some letter
- If coding scheme is not wasteful: a non-leaf has exactly two children


Best Prefix Codes

Input: frequencies of letters in a message


Output: prefix coding scheme with the shortest encoding for the message

example


letters	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	
frequencies	18	3	4	6	10	



scheme 1




scheme 2




scheme 3

example


letters	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	
frequencies	18	3	4	6	10	
scheme 1 length	2	3	3	2	2	total = 89
scheme 2 length	1	3	3	3	3	total = 87
scheme 3 length	1	4	4	3	2	total = 84



scheme 1



scheme 2



scheme 3

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

Q: What types of decisions should we make?

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

Q: What types of decisions should we make?

- Can we directly give a code for some letter?

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

Q: What types of decisions should we make?

- Can we directly give a code for some letter?
- Hard to design a strategy; residual problem is complicated.

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

Q: What types of decisions should we make?

- Can we directly give a code for some letter?
- Hard to design a strategy; residual problem is complicated.
- Can we partition the letters into left and right sub-trees?

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)

Q: What types of decisions should we make?

- Can we directly give a code for some letter?
- Hard to design a strategy; residual problem is complicated.
- Can we partition the letters into left and right sub-trees?
- Not clear how to design the greedy algorithm

- Example Input: (a : 18, b : 3, c : 4, d : 6, e : 10)


Q: What types of decisions should we make?

- Can we directly give a code for some letter?
- Hard to design a strategy; residual problem is complicated.
- Can we partition the letters into left and right sub-trees?
- Not clear how to design the greedy algorithm

A: We can choose two letters and make them brothers in the tree.


Which Two Letters Can Be Safely Put Together As Brothers?

- Focus on the “structure” of the optimum encoding tree




Which Two Letters Can Be Safely Put Together As Brothers?

- Focus on the “structure” of the optimum encoding tree
- There are two deepest leaves that are brothers




Which Two Letters Can Be Safely Put Together As Brothers?

- Focus on the “structure” of the optimum encoding tree
- There are two deepest leaves that are brothers



Which Two Letters Can Be Safely Put Together As Brothers?

- Focus on the “structure” of the optimum encoding tree
- There are two deepest leaves that are brothers



Lemma It is safe to make the two least frequent letters brothers.

Lemma There is an optimum encoding tree, where the two least frequent letters are brothers.

Lemma There is an optimum encoding tree, where the two least frequent letters are brothers.

- So we can irrevocably decide to make the two least frequent letters brothers.

Lemma There is an optimum encoding tree, where the two least frequent letters are brothers.

- So we can irrevocably decide to make the two least frequent letters brothers.

Q: Is the residual problem another instance of the best prefix codes problem?


Lemma There is an optimum encoding tree, where the two least frequent letters are brothers.

- So we can irrevocably decide to make the two least frequent letters brothers.

Q: Is the residual problem another instance of the best prefix codes problem?


A: Yes, though it is not immediate to see why.

- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.




$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x_1}
 \end{aligned}$$

- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.



$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x_1}
 \end{aligned}$$


- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.



$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x_1}
 \end{aligned}$$

Def: $f_{x'} = f_{x_1} + f_{x_2}$


- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.



$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x'} \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x'} (d_{x'} + 1)
 \end{aligned}$$

Def: $f_{x'} = f_{x_1} + f_{x_2}$


- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.



Def: $f_{x'} = f_{x_1} + f_{x_2}$

$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x_1} \\
 = & \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x'} (d_{x'} + 1) \\
 = & \sum_{x \in S \setminus \{x_1, x_2\} \cup \{x'\}} f_x d_x + f_{x'}
 \end{aligned}$$

- f_x : the frequency of the letter x in the support.
- x_1 and x_2 : the two letters we decided to put together.
- d_x the depth of letter x in our output encoding tree.



$$\begin{aligned}
 & \sum_{x \in S} f_x d_x \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x_1} d_{x_1} + f_{x_2} d_{x_2} \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + (f_{x_1} + f_{x_2}) d_{x_1} \\
 &= \sum_{x \in S \setminus \{x_1, x_2\}} f_x d_x + f_{x'} (d_{x'} + 1) \\
 &= \sum_{x \in S \setminus \{x_1, x_2\} \cup \{x'\}} f_x d_x + f_{x'}
 \end{aligned}$$

Def: $f_{x'} = f_{x_1} + f_{x_2}$

In order to minimize

$$\sum_{x \in S} f_x d_x,$$

we need to minimize

$$\sum_{x \in S \setminus \{x_1, x_2\} \cup \{x'\}} f_x d_x,$$

subject to that d is the depth function for an encoding tree of $S \setminus \{x_1, x_2\}$.

- This is exactly the best prefix codes problem, with letters $S \setminus \{x_1, x_2\} \cup \{x'\}$ and frequency vector f !

Example

$(A)^{27}$ $(B)^{15}$ $(C)^{11}$ $(D)^9$ $(E)^8$ $(F)^5$


Example

A 27

B 15

C 11



D 9




Example

A 27


B 15




Example




Example




Example



Example



Example



A : 00
B : 10
C : 010
D : 011
E : 110
F : 111

Def. The codes given the greedy algorithm is called the **Huffman codes**.

Def. The codes given the greedy algorithm is called the **Huffman codes**.

Huffman(S, f)

- 1: **while** $|S| > 1$ **do**
- 2: let x_1, x_2 be the two letters with the smallest f values
- 3: introduce a new letter x' and let $f_{x'} = f_{x_1} + f_{x_2}$
- 4: let x_1 and x_2 be the two children of x'
- 5: $S \leftarrow S \setminus \{x_1, x_2\} \cup \{x'\}$
- 6: **return** the tree constructed

Algorithm using Priority Queue

Huffman(S, f)

- 1: $Q \leftarrow \text{build-priority-queue}(S)$
- 2: **while** $Q.\text{size} > 1$ **do**
- 3: $x_1 \leftarrow Q.\text{extract-min}()$
- 4: $x_2 \leftarrow Q.\text{extract-min}()$
- 5: introduce a new letter x' and let $f_{x'} = f_{x_1} + f_{x_2}$
- 6: let x_1 and x_2 be the two children of x'
- 7: $Q.\text{insert}(x', f_{x'})$
- 8: **return** the tree constructed

Outline

- 1 Data Compression and Huffman Code
- 2 Summary
- 3 Summary of Studies until Mid Term I

Summary for Greedy Algorithms

Greedy Algorithm

- Build up the solutions in steps
- At each step, make an **irrevocable** decision using a “reasonable” strategy

Summary for Greedy Algorithms

Greedy Algorithm

- Build up the solutions in steps
- At each step, make an **irrevocable** decision using a “reasonable” strategy
- Interval scheduling problem: schedule the job j^* with the earliest deadline

Summary for Greedy Algorithms

Greedy Algorithm

- Build up the solutions in steps
- At each step, make an **irrevocable** decision using a “reasonable” strategy
- Interval scheduling problem: schedule the job j^* with the earliest deadline
- Offline Caching: evict the page that is used furthest in the future

Summary for Greedy Algorithms

Greedy Algorithm

- Build up the solutions in steps
- At each step, make an **irrevocable** decision using a “reasonable” strategy
- Interval scheduling problem: schedule the job j^* with the earliest deadline
- Offline Caching: evict the page that is used furthest in the future
- Huffman codes: make the two least frequent letters brothers

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- Safety: Prove that the reasonable strategy is “safe” (key)
- Self-reduce: Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- **Safety:** Prove that the reasonable strategy is “safe” (key)
- **Self-reduce:** Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)

Def. A strategy is “safe” if there is always an optimum solution that “agrees with” the decision made according to the strategy.

Proving a Strategy is Safe

- Take an arbitrary optimum solution S

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done
- So assume S does not agree with decision

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done
- So assume S does not agree with decision
- Change S slightly to another optimum solution S' that agrees with the decision

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done
- So assume S does not agree with decision
- Change S slightly to another optimum solution S' that agrees with the decision
 - Interval scheduling problem: exchange j^* with the first job in an optimal solution

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done
- So assume S does not agree with decision
- Change S slightly to another optimum solution S' that agrees with the decision
 - Interval scheduling problem: exchange j^* with the first job in an optimal solution
 - Offline caching: a complicated “copying” algorithm

Proving a Strategy is Safe

- Take an arbitrary optimum solution S
- If S agrees with the decision made according to the strategy, done
- So assume S does not agree with decision
- Change S slightly to another optimum solution S' that agrees with the decision
 - Interval scheduling problem: exchange j^* with the first job in an optimal solution
 - Offline caching: a complicated “copying” algorithm
 - Huffman codes: move the two least frequent letters to the deepest leaves.

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- Safety: Prove that the reasonable strategy is “safe” (key)
- Self-reduce: Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- Safety: Prove that the reasonable strategy is “safe” (key)
- Self-reduce: Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)
- Interval scheduling problem: remove j^* and the jobs it conflicts with

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- Safety: Prove that the reasonable strategy is “safe” (key)
- Self-reduce: Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)
- Interval scheduling problem: remove j^* and the jobs it conflicts with
- Offline caching: trivial

Summary for Greedy Algorithms

Analysis of Greedy Algorithm

- Safety: Prove that the reasonable strategy is “safe” (key)
- Self-reduce: Show that the remaining task after applying the strategy is to solve a (many) smaller instance(s) of the same problem (usually easy)
- Interval scheduling problem: remove j^* and the jobs it conflicts with
- Offline caching: trivial
- Huffman codes: merge two letters into one

Outline

- 1 Data Compression and Huffman Code
- 2 Summary
- 3 Summary of Studies until Mid Term I

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph
 - Two representations: adjacency matrix, linked lists

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph
 - Two representations: adjacency matrix, linked lists
 - Path, cycle, tree, directed acyclic graph, bipartite graph

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph
 - Two representations: adjacency matrix, linked lists
 - Path, cycle, tree, directed acyclic graph, bipartite graph
 - Connectivity problem: BFS and DFS algorithm

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph
 - Two representations: adjacency matrix, linked lists
 - Path, cycle, tree, directed acyclic graph, bipartite graph
 - Connectivity problem: BFS and DFS algorithm
 - Testing Bipartiteness problem: test-bipartiteness-BFS or test-bipartiteness-DFS algorithm

Important notations/algorithms

- Introduction:
 - Asymptotic analysis: O , Ω , Θ , compare the orders
 - Polynomial time (efficient algorithm), exponential time
- Graph Basics:
 - Undirected graph, directed graph
 - Two representations: adjacency matrix, linked lists
 - Path, cycle, tree, directed acyclic graph, bipartite graph
 - Connectivity problem: BFS and DFS algorithm
 - Testing Bipartiteness problem: test-bipartiteness-BFS or test-bipartiteness-DFS algorithm
 - Topological Ordering problem: topological-sort algorithm (Queue or Stack)

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem
 - Interval Partitioning problem

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem
 - Interval Partitioning problem
 - Offline Caching problem

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem
 - Interval Partitioning problem
 - Offline Caching problem
 - Priority Queue: heap

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem
 - Interval Partitioning problem
 - Offline Caching problem
 - Priority Queue: heap
 - Huffman Code problem

Important notations/algorithms

- Greedy algorithms: safety strategy+self reduce
 - Box Packing problem
 - Interval Scheduling problem
 - Interval Partitioning problem
 - Offline Caching problem
 - Priority Queue: heap
 - Huffman Code problem
 - Exercise problems (Lecture: Monday, 30th September)