

Introduction to Machine Learning

Spectral Clustering

Mingchen Gao

Computer Science & Engineering
State University of New York at Buffalo
Buffalo, NY, USA
mgao8@buffalo.edu
Slides Adapted from Varun Chandola



University at Buffalo
Department of Computer Science
and Engineering
School of Engineering and Applied Sciences



Spectral Clustering

Graph Laplacian

Spectral Clustering Algorithm

Spectral Clustering

- ▶ An alternate approach to clustering
- ▶ Let the data be a set of N points

$$\mathbf{X} = \mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N$$

- ▶ Let \mathbf{S} be a $N \times N$ **similarity matrix**

$$S_{ij} = \text{sim}(\mathbf{x}_i, \mathbf{x}_j)$$

- ▶ $\text{sim}(\cdot, \cdot)$ is a similarity function
- ▶ Construct a weighted undirected graph from \mathbf{S} with adjacency matrix, \mathbf{W}

$$W_{ij} = \begin{cases} \text{sim}(\mathbf{x}_i, \mathbf{x}_j) & \text{if } \mathbf{x}_i \text{ is nearest neighbor of } \mathbf{x}_j \\ 0 & \text{otherwise} \end{cases}$$

- ▶ Can use more than 1 nearest neighbors to construct the graph

Spectral Clustering as a Graph Min-cut Problem

- ▶ Clustering \mathbf{X} into K clusters is equivalent to finding K cuts in the graph \mathbf{W}
 - ▶ A_1, A_2, \dots, A_K
- ▶ Possible objective function

$$\text{cut}(A_1, A_2, \dots, A_K) \triangleq \frac{1}{2} \sum_{k=1}^K W(A_k, \bar{A}_k)$$

- ▶ where \bar{A}_k denotes the nodes in the graph which are **not in** A_k and

$$W(A, B) \triangleq \sum_{i \in A, j \in B} W_{ij}$$

Straight min-cut results in trivial solution

Normalized Min-cut Problem

$$\text{normcut}(A_1, A_2, \dots, A_K) \triangleq \frac{1}{2} \sum_{k=1}^K \frac{W(A_k, \bar{A}_k)}{\text{vol}(A_k)}$$

where $\text{vol}(A) \triangleq \sum_{i \in A} d_i$, d_i is the weighted degree of the node i

NP Hard Problem

- ▶ Equivalent to solving a 0-1 knapsack problem
- ▶ Find N binary vectors, \mathbf{c}_i of length K such that $c_{ik} = 1$ only if point i belongs to cluster k
- ▶ If we relax constraints to allow c_{ik} to be real-valued, the problem becomes an eigenvector problem
 - ▶ Hence the name: **spectral clustering**

The Graph Laplacian

$$\mathbf{L} \triangleq \mathbf{D} - \mathbf{W}$$

- ▶ \mathbf{D} is a diagonal matrix with degree of corresponding node as the diagonal value

Properties of Laplacian Matrix

1. Each row sums to 0
2. $\mathbf{1}$ is an eigen vector with eigen value equal to 0
3. Symmetric and positive semi-definite
4. Has N non-negative real-valued eigenvalues
5. If the graph (\mathbf{W}) has K connected components, then \mathbf{L} has K eigenvectors spanned by $\mathbf{1}_{\mathbf{A}_1}, \dots, \mathbf{1}_{\mathbf{A}_K}$ with 0 eigenvalue.

Spectral Clustering Algorithm

Observation

- ▶ In practice, \mathbf{W} might not have K exactly isolated connected components
- ▶ By *perturbation theory*, the smallest eigenvectors of \mathbf{L} will be close to the ideal indicator functions

Algorithm

- ▶ Compute first (smallest) K eigen vectors of \mathbf{L}
- ▶ Let \mathbf{U} be the $N \times K$ matrix with eigenvectors as the columns
- ▶ Perform kMeans clustering on the rows of \mathbf{U}

Murphy Book Chapter 21.5