

CSE 431/531: Algorithm Analysis and Design (Fall 2024)

# Testing Bipartiteness and Topological Ordering

Lecturer: Kelin Luo

*Department of Computer Science and Engineering*  
*University at Buffalo*

# Outline


1 Testing Bipartiteness

2 Topological Ordering

- Applications: Word Ladder

# Bipartite Graph


**Def.** An undirected graph  $G = (V, E)$  is a **bipartite graph** if there is a partition of  $V$  into two sets  $L$  and  $R$  such that for every edge  $(u, v) \in E$ , either  $u \in L, v \in R$  or  $v \in L, u \in R$ .



# Bipartite Graph

**Def.** An undirected graph  $G = (V, E)$  is a **bipartite graph** if there is a partition of  $V$  into two sets  $L$  and  $R$  such that for every edge  $(u, v) \in E$ , either  $u \in L, v \in R$  or  $v \in L, u \in R$ .

**Obs.** Bipartite graph may contain cycles.




# Bipartite Graph

**Def.** An undirected graph  $G = (V, E)$  is a **bipartite graph** if there is a partition of  $V$  into two sets  $L$  and  $R$  such that for every edge  $(u, v) \in E$ , either  $u \in L, v \in R$  or  $v \in L, u \in R$ .

**Obs.** Bipartite graph may contain cycles.

**Obs.** If a graph is a tree, then it is also a bipartite graph.



# BFS and DFS

**Obs.** BFS and DFS naturally induce a tree.

# BFS and DFS

**Obs.** BFS and DFS naturally induce a tree.

**Obs.** If  $G$  is a tree, then BFS tree = DFS tree.

# BFS and DFS

**Obs.** BFS and DFS naturally induce a tree.

**Obs.** If  $G$  is a tree, then BFS tree = DFS tree.

**Obs.** If BFS tree = DFS tree, then  $G$  is a tree.



**Obs.** If BFS tree = DFS tree, then  $G$  is a tree.

- True: simple, undirected graph, starting at the same vertex
- Not True: starting at different vertices or an directed graph

# Outline

1 Testing Bipartiteness

2 Topological Ordering


- Applications: Word Ladder

## Topological Ordering Problem

**Input:** a directed acyclic graph (DAG)  $G = (V, E)$

**Output:** 1-to-1 function  $\pi : V \rightarrow \{1, 2, 3 \dots, n\}$ , so that

- if  $(u, v) \in E$  then  $\pi(u) < \pi(v)$




## Topological Ordering Problem

**Input:** a directed acyclic graph (DAG)  $G = (V, E)$


**Output:** 1-to-1 function  $\pi : V \rightarrow \{1, 2, 3 \dots, n\}$ , so that

- if  $(u, v) \in E$  then  $\pi(u) < \pi(v)$




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.



# Topological Ordering


- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.






# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.



# Topological Ordering


- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.






# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.




# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.



# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.



# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.

## topological-sort( $G$ )

```
1:  $i \leftarrow 0$ 
2: for  $V \neq \emptyset$  do
3:    $v \leftarrow$  vertex in  $V$  without incoming edges
4:    $i \leftarrow i + 1$ ,  $\pi(v) \leftarrow i$  and  $V \leftarrow V \setminus \{v\}$ 
5:   while  $V \neq \emptyset$  do
6:     for every  $u \in V$  such that  $(v, u) \in E$  do
7:        $E \leftarrow E \setminus \{(v, u)\}$ 
```

- Running time =  $O(n + m)$



# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.

# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.

**Q:** How to make the algorithm as efficient as possible?

# Topological Ordering

- Algorithm: each time take a vertex without incoming edges, then remove the vertex and all its outgoing edges.

**Q:** How to make the algorithm as efficient as possible?

**A:**

- Use linked-lists of outgoing edges
- Maintain the in-degree  $d_v$  of vertices
- Maintain a queue (or stack) of vertices  $v$  with  $d_v = 0$

## topological-sort( $G$ )



```
1: let  $d_v \leftarrow 0$  for every  $v \in V$ 
2: for every  $v \in V$  do
3:   for every  $u$  such that  $(v, u) \in E$  do
4:      $d_u \leftarrow d_u + 1$ 
5:  $S \leftarrow \{v : d_v = 0\}, i \leftarrow 0$ 
6: while  $S \neq \emptyset$  do
7:    $v \leftarrow$  arbitrary vertex in  $S, S \leftarrow S \setminus \{v\}$ 
8:    $i \leftarrow i + 1, \pi(v) \leftarrow i$ 
9:   for every  $u$  such that  $(v, u) \in E$  do
10:     $d_u \leftarrow d_u - 1$ 
11:    if  $d_u = 0$  then add  $u$  to  $S$ 
```

- $S$  can be represented using a queue or a stack
- Running time =  $O(n + m)$

# $S$ as a Queue or a Stack



DS	Queue	Stack
Initialization	$head \leftarrow 1, tail \leftarrow 0$	$top \leftarrow 0$
Non-Empty?	$head \leq tail$	$top > 0$
Add( $v$ )	$tail \leftarrow tail + 1$ $S[tail] \leftarrow v$	$top \leftarrow top + 1$ $S[top] \leftarrow v$
Retrieve $v$	$v \leftarrow S[head]$ $head \leftarrow head + 1$	$v \leftarrow S[top]$ $top \leftarrow top - 1$

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	1	1	1	2	1	3

# Example



	a	b	c	d	e	f	g
degree	0	1	1	1	2	1	3



# Example



	a	b	c	d	e	f	g
degree	0	0	0	1	2	1	3





# Example





	a	b	c	d	e	f	g
degree	0	0	0	1	2	1	3

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	1	2	1	3

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	1	1	1	3

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	1	1	1	3

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	1	0	3

# Example





	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	1	0	3

# Example



	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	1	0	3



# Example



	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	2





# Example




	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	2

# Example




	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	2

# Example




	$a$	$b$	$c$	$d$	$e$	$f$	$g$
degree	0	0	0	0	0	0	1

# Example



	$a$	$b$	$c$	$d$	$e$	$f$	$g$
degree	0	0	0	0	0	0	1


# Example



⑨

	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	0


# Example



⑨

	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	0

# Example



⑨

	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>
degree	0	0	0	0	0	0	0

# Outline

1 Testing Bipartiteness

2 Topological Ordering

- Applications: Word Ladder



**Def.** Word: A string formed by letters.

**Def.** Adjacency words: Word  $A$  and  $B$  are adjacent if they differ in exactly one letter.

e.g. *word* and *work*; *tell* and *tall*; *askbe* and *askee*.

**Def.** Word Ladder: Players start with one word, and in a series of steps, change or transform that word into another word.

**Def.** Word Ladder: Players start with one word, and in a series of steps, change or transform that word into another word.

- The objective is to make the change in the smallest number of steps, with each step involving changing a **single letter** of the word to create a new valid word.

## Word Ladder Problem

**Input:** Two words  $S$  and  $T$ , a list of words  $A = \{W_1, W_2, \dots, W_k\}$ .


**Output:** “The smallest word ladder” if we can change  $S$  to  $T$  by moving between adjacency words in  $A \cup \{S, T\}$ ;  
Otherwise, “No word ladder”.

Example:


- $S = \text{“a e f g h”}$ ,  $T = \text{“d l m i h”}$
- $W_1 = \text{“a e f i h”}$ ,  $W_2 = \text{“a e m g h”}$ ,  $W_3 = \text{“d l f i h”}$   
 $W_4 = \text{“s e f i h”}$ ,  $W_5 = \text{“a d f g h”}$ ,  $W_6 = \text{“d e m i h”}$   
 $W_7 = \text{“d e f i h”}$ ,  $W_8 = \text{“d e m g h”}$ ,  $W_9 = \text{“s e m i h”}$

Example:

- $S = \text{"a e f g h"} , T = \text{"d l m i h"}$
- $W_1 = \text{"a e f i h"} , W_2 = \text{"a e m g h"} , W_3 = \text{"d l f i h"}$   
 $W_4 = \text{"s e f i h"} , W_5 = \text{"a d f g h"} , W_6 = \text{"d e m i h"}$   
 $W_7 = \text{"d e f i h"} , W_8 = \text{"d e m g h"} , W_9 = \text{"s e m i h"}$



- Each vertex corresponds to a word.
- Two vertices are adjacent if the corresponding words are adjacent.



- Each vertex corresponds to a word.
- Two vertices are adjacent if the corresponding words are adjacent.
- Hints: Given vertex  $v$ , check its nearest neighbor.