

Introduction to Machine Learning

General Note About Linear Classifiers

Mingchen Gao

Computer Science & Engineering
State University of New York at Buffalo
Buffalo, NY, USA
mgao8@buffalo.edu
Slides adapted from Varun Chandola



University at Buffalo
Department of Computer Science
and Engineering
School of Engineering and Applied Sciences



Linear Classifiers and Loss Function

Regularizers

Approximate Regularization

Loss Function for Linear Classification

- ▶ Linear binary classification can be written as a general optimization problem:

$$\min_{\mathbf{w}, b} L(\mathbf{w}, b) = \min_{\mathbf{w}, b} \sum_{n=1}^N \mathbb{I}(y_n(\mathbf{w}^\top \mathbf{x}_n + b) < 0) + \lambda R(\mathbf{w}, b)$$

- ▶ \mathbb{I} is an **indicator function** (1 if $(.)$ is negative, 0 otherwise)
- ▶ Objective function = **Loss function** + λ **Regularizer**
- ▶ Objective function wants to **fit training data well** and **have simpler solution**

0-1 Loss is Hard to Optimize

- ▶ Combinatorial optimization problem
- ▶ NP-hard
- ▶ No polynomial time algorithm
- ▶ Loss function is non-smooth, non-convex
- ▶ Small changes in \mathbf{w}, b can change the loss by lot

Approximations to 0-1 Loss

- ▶ Different linear classifiers use different approximations to 0-1 loss
 - ▶ Also known as *surrogate loss functions*

Approximations to 0-1 Loss

- ▶ Different linear classifiers use different approximations to 0-1 loss
 - ▶ Also known as *surrogate loss functions*

Support Vector Machines

- ▶ **Hinge Loss**

Approximations to 0-1 Loss

- ▶ Different linear classifiers use different approximations to 0-1 loss
 - ▶ Also known as *surrogate loss functions*

Support Vector Machines

- ▶ **Hinge Loss**

Squared Loss

- ▶ **Squared Loss**

Approximations to 0-1 Loss

- ▶ Different linear classifiers use different approximations to 0-1 loss
 - ▶ Also known as *surrogate loss functions*

Support Vector Machines

- ▶ **Hinge Loss**

Squared Loss


- ▶ **Squared Loss**

Logistic Regression

- ▶ **Log Loss**

Plot of Loss Functions

- ▶ black, indicator loss
- ▶ green, squared loss
- ▶ red, log loss
- ▶ blue, hinge loss



Role of Regularizers

- ▶ Recall the optimization problem for linear classification

$$\min_{\mathbf{w}, b} L(\mathbf{w}, b) = \min_{\mathbf{w}, b} \sum_{n=1}^N \mathbb{I}(y_n(\mathbf{w}^\top \mathbf{x}_n + b) < 0) + \lambda R(\mathbf{w}, b)$$

- ▶ What is the role of the regularizer term?

Role of Regularizers

- ▶ Recall the optimization problem for linear classification

$$\min_{\mathbf{w}, b} L(\mathbf{w}, b) = \min_{\mathbf{w}, b} \sum_{n=1}^N \mathbb{I}(y_n(\mathbf{w}^\top \mathbf{x}_n + b) < 0) + \lambda R(\mathbf{w}, b)$$

- ▶ What is the role of the regularizer term?
 - ▶ Ensure simplicity
- ▶ Ideally we want most entries of \mathbf{w} to be zero
- ▶ Why?
- ▶ Desired minimization

$$R(\mathbf{w}, b) = \sum_{d=1}^D \mathbb{I}(w_d \neq 0)$$

- ▶ NP Hard

Approximate Regularization

- ▶ **Norm based regularization**

- ▶ l_2 squared norm

$$\|\mathbf{w}\|_2^2 = \sum_{d=1}^D w_d^2$$

- ▶ l_1 norm

$$\|\mathbf{w}\|_1 = \sum_{d=1}^D |w_d|$$

- ▶ l_p norm

$$\|\mathbf{w}\|_p = \left(\sum_{d=1}^D w_d^p \right)^{1/p}$$

- ▶ Norm becomes non-convex for $p < 1$
 - ▶ l_1 norm gives best results
 - ▶ l_2 norm is easiest to deal with