

CSE 431/531: Algorithm Analysis and Design (Fall 2024)

Graph Algorithms

Lecturer: Kelin Luo

*Department of Computer Science and Engineering
University at Buffalo*

Outline

- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

Outline

- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

Outline

- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

Outline


- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

Assumption Assume all edge weights are different.

Lemma (u, v) is in MST, if and only if there exists a **cut** $(U, V \setminus U)$, such that (u, v) is the lightest edge between U and $V \setminus U$.

Assumption Assume all edge weights are different.


Lemma (u, v) is in MST, if and only if there exists a **cut** $(U, V \setminus U)$, such that (u, v) is the lightest edge between U and $V \setminus U$.



- (c, f) is in MST because of cut $(\{a, b, c, i\}, V \setminus \{a, b, c, i\})$

Assumption Assume all edge weights are different.

Lemma (u, v) is in MST, if and only if there exists a **cut** $(U, V \setminus U)$, such that (u, v) is the lightest edge between U and $V \setminus U$.



- (c, f) is in MST because of cut $(\{a, b, c, i\}, V \setminus \{a, b, c, i\})$
- (i, g) is not in MST because no such cut exists

“Evidence” for $e \in \text{MST}$ or $e \notin \text{MST}$

Assumption Assume all edge weights are different.

- $e \in \text{MST} \leftrightarrow$ there is a cut in which e is the lightest edge
- $e \notin \text{MST} \leftrightarrow$ there is a cycle in which e is the heaviest edge

“Evidence” for $e \in \text{MST}$ or $e \notin \text{MST}$

Assumption Assume all edge weights are different.

- $e \in \text{MST} \leftrightarrow$ there is a cut in which e is the lightest edge
- $e \notin \text{MST} \leftrightarrow$ there is a cycle in which e is the heaviest edge

Exactly one of the following is true:

- There is a cut in which e is the lightest edge
- There is a cycle in which e is the heaviest edge

“Evidence” for $e \in \text{MST}$ or $e \notin \text{MST}$

Assumption Assume all edge weights are different.

- $e \in \text{MST} \leftrightarrow$ there is a cut in which e is the lightest edge
- $e \notin \text{MST} \leftrightarrow$ there is a cycle in which e is the heaviest edge

Exactly one of the following is true:

- There is a cut in which e is the lightest edge
- There is a cycle in which e is the heaviest edge

Thus, the minimum spanning tree is unique with assumption.

Outline

- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

algorithm	graph	weights	SS?	running time
Simple DP	DAG	\mathbb{R}	SS	$O(n + m)$
Dijkstra	U/D	$\mathbb{R}_{\geq 0}$	SS	$O(n \log n + m)$
Bellman-Ford	U/D	\mathbb{R}	SS	$O(nm)$
Floyd-Warshall	U/D	\mathbb{R}	AP	$O(n^3)$

- DAG = directed acyclic graph U = undirected D = directed
- SS = single source AP = all pairs

s - t Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s, t \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$


Output: shortest path from s to t

s - t Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s, t \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest path from s to t




s - t Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s, t \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest path from s to t



Single Source Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest paths from s to all other vertices $v \in V$

Single Source Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest paths from s to all other vertices $v \in V$

Reason for Considering Single Source Shortest Paths Problem

- We do not know how to solve s - t shortest path problem more efficiently than solving single source shortest path problem

Single Source Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest paths from s to **all other vertices** $v \in V$

Reason for Considering Single Source Shortest Paths Problem

- We do not know how to solve s - t shortest path problem more efficiently than solving single source shortest path problem
- Shortest paths in directed graphs is more general than in undirected graphs: we can replace every undirected edge with two anti-parallel edges of the same weight

Single Source Shortest Paths

Input: (directed or undirected) graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest paths from s to **all other vertices** $v \in V$

Reason for Considering Single Source Shortest Paths Problem

- We do not know how to solve s - t shortest path problem more efficiently than solving single source shortest path problem
- Shortest paths in directed graphs is more general than in undirected graphs: we can replace every undirected edge with two anti-parallel edges of the same weight

Single Source Shortest Paths

Input: **directed** graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: shortest paths from s to **all other vertices** $v \in V$

Reason for Considering Single Source Shortest Paths Problem

- We do not know how to solve s - t shortest path problem more efficiently than solving single source shortest path problem
- Shortest paths in directed graphs is more general than in undirected graphs: we can replace every undirected edge with two anti-parallel edges of the same weight

Single Source Shortest Paths

Input: directed graph $G = (V, E)$, $s \in V$

$$w : E \rightarrow \mathbb{R}_{\geq 0}$$

Output: $\pi[v], v \in V \setminus s$: the parent of v in shortest path tree

$d[v], v \in V \setminus s$: the length of shortest path from s to v


Q: How to compute shortest paths from s when all edges have weight 1?

Q: How to compute shortest paths from s when all edges have weight 1?

A: Breadth first search (BFS) from source s


Q: How to compute shortest paths from s when all edges have weight 1?

A: Breadth first search (BFS) from source s




Q: How to compute shortest paths from s when all edges have weight 1?

A: Breadth first search (BFS) from source s




Q: How to compute shortest paths from s when all edges have weight 1?

A: Breadth first search (BFS) from source s




Q: How to compute shortest paths from s when all edges have weight 1?

A: Breadth first search (BFS) from source s



Q: How to compute shortest paths from s when all edges have weight 1?



A: Breadth first search (BFS) from source s



Assumption Weights $w(u, v)$ are integers (w.l.o.g.).



Assumption Weights $w(u, v)$ are integers (w.l.o.g).

- An edge of weight $w(u, v)$ is equivalent to a path of $w(u, v)$ unit-weight edges



Assumption Weights $w(u, v)$ are integers (w.l.o.g.).

- An edge of weight $w(u, v)$ is equivalent to a path of $w(u, v)$ unit-weight edges





Shortest Path Algorithm by Running BFS

- 1: replace (u, v) of length $w(u, v)$ with a path of $w(u, v)$ unit-weight edges, for every $(u, v) \in E$
- 2: run BFS
- 3: $\pi[v] \leftarrow$ vertex from which v is visited
- 4: $d[v] \leftarrow$ index of the level containing v

Assumption Weights $w(u, v)$ are integers (w.l.o.g.).

- An edge of weight $w(u, v)$ is equivalent to a path of $w(u, v)$ unit-weight edges





Shortest Path Algorithm by Running BFS

- 1: replace (u, v) of length $w(u, v)$ with a path of $w(u, v)$ unit-weight edges, for every $(u, v) \in E$
- 2: run BFS
- 3: $\pi[v] \leftarrow$ vertex from which v is visited
- 4: $d[v] \leftarrow$ index of the level containing v

- Problem: $w(u, v)$ may be too large!

Assumption Weights $w(u, v)$ are integers (w.l.o.g).

- An edge of weight $w(u, v)$ is equivalent to a path of $w(u, v)$ unit-weight edges



Shortest Path Algorithm by Running BFS


- 1: replace (u, v) of length $w(u, v)$ with a path of $w(u, v)$ unit-weight edges, for every $(u, v) \in E$
- 2: run BFS **virtually**
- 3: $\pi[v] \leftarrow$ vertex from which v is visited
- 4: $d[v] \leftarrow$ index of the level containing v

- Problem: $w(u, v)$ may be too large!


Shortest Path Algorithm by Running BFS Virtually

- 1: $S \leftarrow \{s\}, d(s) \leftarrow 0$
- 2: **while** $|S| \leq n$ **do**
- 3: find a $v \notin S$ that minimizes $\min_{u \in S: (u,v) \in E} \{d[u] + w(u, v)\}$
- 4: $S \leftarrow S \cup \{v\}$
- 5: $d[v] \leftarrow \min_{u \in S: (u,v) \in E} \{d[u] + w(u, v)\}$

Virtual BFS: Example




Virtual BFS: Example




Time 0

Virtual BFS: Example




Time 2

Virtual BFS: Example




Time 4

Virtual BFS: Example




Time 7

Virtual BFS: Example



Time 9

Virtual BFS: Example



Time 10

Outline

- 1 Minimum Spanning Tree
 - Kruskal's Algorithm
 - Reverse-Kruskal's Algorithm
 - Prim's Algorithm
- 2 Single Source Shortest Paths
 - Dijkstra's Algorithm
- 3 Shortest Paths in Graphs with Negative Weights
- 4 All-Pair Shortest Paths and Floyd-Warshall

Dijkstra's Algorithm

Dijkstra(G, w, s)

```
1:  $S \leftarrow \emptyset, d(s) \leftarrow 0$  and  $d[v] \leftarrow \infty$  for every  $v \in V \setminus \{s\}$ 
2: while  $S \neq V$  do
3:    $u \leftarrow$  vertex in  $V \setminus S$  with the minimum  $d[u]$ 
4:   add  $u$  to  $S$ 
5:   for each  $v \in V \setminus S$  such that  $(u, v) \in E$  do
6:     if  $d[u] + w(u, v) < d[v]$  then
7:        $d[v] \leftarrow d[u] + w(u, v)$ 
8:        $\pi[v] \leftarrow u$ 
9: return  $(d, \pi)$ 
```

Dijkstra's Algorithm

Dijkstra(G, w, s)

```
1:  $S \leftarrow \emptyset, d(s) \leftarrow 0$  and  $d[v] \leftarrow \infty$  for every  $v \in V \setminus \{s\}$ 
2: while  $S \neq V$  do
3:    $u \leftarrow$  vertex in  $V \setminus S$  with the minimum  $d[u]$ 
4:   add  $u$  to  $S$ 
5:   for each  $v \in V \setminus S$  such that  $(u, v) \in E$  do
6:     if  $d[u] + w(u, v) < d[v]$  then
7:        $d[v] \leftarrow d[u] + w(u, v)$ 
8:        $\pi[v] \leftarrow u$ 
9: return  $(d, \pi)$ 
```

- Running time = $O(n^2)$

