

CSE 431/531: Algorithm Analysis and Design (Fall 2024)

# Graph Algorithms

Lecturer: Kelin Luo

*Department of Computer Science and Engineering  
University at Buffalo*

# Outline

- 1 Minimum Spanning Tree
  - Kruskal's Algorithm
  - Reverse-Kruskal's Algorithm
  - Prim's Algorithm
- 2 Single Source Shortest Paths
- 3 All-Pair Shortest Paths and Floyd-Warshall

# Outline

- 1 Minimum Spanning Tree
  - Kruskal's Algorithm
  - Reverse-Kruskal's Algorithm
  - Prim's Algorithm
- 2 Single Source Shortest Paths
- 3 All-Pair Shortest Paths and Floyd-Warshall

# Outline

- 1 Minimum Spanning Tree
  - Kruskal's Algorithm
  - Reverse-Kruskal's Algorithm
  - Prim's Algorithm
- 2 Single Source Shortest Paths
- 3 All-Pair Shortest Paths and Floyd-Warshall

# Outline

## 1 Minimum Spanning Tree

- Kruskal's Algorithm
- Reverse-Kruskal's Algorithm
- Prim's Algorithm

## 2 Single Source Shortest Paths

## 3 All-Pair Shortest Paths and Floyd-Warshall

# Outline

- 1 Minimum Spanning Tree
  - Kruskal's Algorithm
  - Reverse-Kruskal's Algorithm
  - Prim's Algorithm
- 2 Single Source Shortest Paths
- 3 All-Pair Shortest Paths and Floyd-Warshall

## dynamic-programming( $G, w, s$ )

- 1:  $f^0[s] \leftarrow 0$  and  $f^0[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$
- 2: **for**  $\ell \leftarrow 1$  to  $n - 1$  **do**
- 3:     copy  $f^{\ell-1} \rightarrow f^\ell$
- 4:     **for** each  $(u, v) \in E$  **do**
- 5:         **if**  $f^{\ell-1}[u] + w(u, v) < f^\ell[v]$  **then**
- 6:              $f^\ell[v] \leftarrow f^{\ell-1}[u] + w(u, v)$
- 7: **return**  $(f^{n-1}[v])_{v \in V}$

## dynamic-programming( $G, w, s$ )

```
1:  $f^0[s] \leftarrow 0$  and  $f^0[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   copy  $f^{\ell-1} \rightarrow f^\ell$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f^{\ell-1}[u] + w(u, v) < f^\ell[v]$  then
6:        $f^\ell[v] \leftarrow f^{\ell-1}[u] + w(u, v)$ 
7: return  $(f^{n-1}[v])_{v \in V}$ 
```

**Obs.** Assuming there are no negative cycles, then a shortest path contains at most  $n - 1$  edges



## dynamic-programming( $G, w, s$ )

```
1:  $f^0[s] \leftarrow 0$  and  $f^0[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   copy  $f^{\ell-1} \rightarrow f^\ell$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f^{\ell-1}[u] + w(u, v) < f^\ell[v]$  then
6:        $f^\ell[v] \leftarrow f^{\ell-1}[u] + w(u, v)$ 
7: return  $(f^{n-1}[v])_{v \in V}$ 
```

**Obs.** Assuming there are no negative cycles, then a shortest path contains at most  $n - 1$  edges

## Proof.

If there is a path containing at least  $n$  edges, then it contains a cycle. Removing the cycle gives a path with the same or smaller length.  $\square$

# Dynamic Programming with Better Space Usage

## dynamic-programming( $G, w, s$ )

```
1:  $f^{\text{old}}[s] \leftarrow 0$  and  $f^{\text{old}}[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   copy  $f^{\text{old}} \rightarrow f^{\text{new}}$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f^{\text{old}}[u] + w(u, v) < f^{\text{new}}[v]$  then
6:        $f^{\text{new}}[v] \leftarrow f^{\text{old}}[u] + w(u, v)$ 
7:   copy  $f^{\text{new}} \rightarrow f^{\text{old}}$ 
8: return  $f^{\text{old}}$ 
```

- $f^\ell$  only depends on  $f^{\ell-1}$ : only need 2 vectors

# Dynamic Programming with Better Space Usage

## dynamic-programming( $G, w, s$ )

```
1:  $f^{\text{old}}[s] \leftarrow 0$  and  $f^{\text{old}}[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   copy  $f^{\text{old}} \rightarrow f^{\text{new}}$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f^{\text{old}}[u] + w(u, v) < f^{\text{new}}[v]$  then
6:        $f^{\text{new}}[v] \leftarrow f^{\text{old}}[u] + w(u, v)$ 
7:   copy  $f^{\text{new}} \rightarrow f^{\text{old}}$ 
8: return  $f^{\text{old}}$ 
```

- $f^\ell$  only depends on  $f^{\ell-1}$ : only need 2 vectors
- only need 1 vector!

# Dynamic Programming with Better Space Usage

## dynamic-programming( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   copy  $f \rightarrow f$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f[u] + w(u, v) < f[v]$  then
6:        $f[v] \leftarrow f[u] + w(u, v)$ 
7:   copy  $f \rightarrow f$ 
8: return  $f$ 
```

- $f^\ell$  only depends on  $f^{\ell-1}$ : only need 2 vectors
- only need 1 vector!

# Dynamic Programming with Better Space Usage

## dynamic-programming( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- $f^\ell$  only depends on  $f^{\ell-1}$ : only need 2 vectors
- only need 1 vector!

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- $f^\ell$  only depends on  $f^{\ell-1}$ : only need 2 vectors
- only need 1 vector!

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- Issue: when we compute  $f[u] + w(u, v)$ ,  $f[u]$  may be changed since the end of last iteration

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- Issue: when we compute  $f[u] + w(u, v)$ ,  $f[u]$  may be changed since the end of last iteration
- This is OK: it can only “accelerate” the process!



# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- Issue: when we compute  $f[u] + w(u, v)$ ,  $f[u]$  may be changed since the end of last iteration
- This is OK: it can only “accelerate” the process!
- After iteration  $\ell$ ,  $f[v]$  is **at most** the length of the shortest path from  $s$  to  $v$  that uses at most  $\ell$  edges

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n - 1$  do
3:   for each  $(u, v) \in E$  do
4:     if  $f[u] + w(u, v) < f[v]$  then
5:        $f[v] \leftarrow f[u] + w(u, v)$ 
6: return  $f$ 
```

- Issue: when we compute  $f[u] + w(u, v)$ ,  $f[u]$  may be changed since the end of last iteration
- This is OK: it can only “accelerate” the process!
- After iteration  $\ell$ ,  $f[v]$  is **at most** the length of the shortest path from  $s$  to  $v$  that uses at most  $\ell$  edges
- $f[v]$  is always the length of **some path** from  $s$  to  $v$

# Bellman-Ford Algorithm

- After iteration  $\ell$ :


$$\begin{aligned} & \text{length of shortest } s\text{-}v \text{ path} \\ & \leq f[v] \\ & \leq \text{length of shortest } s\text{-}v \text{ path using at most } \ell \text{ edges} \end{aligned}$$

- Assuming there are no negative cycles:

$$\begin{aligned} & \text{length of shortest } s\text{-}v \text{ path} \\ & = \text{length of shortest } s\text{-}v \text{ path using at most } n - 1 \text{ edges} \end{aligned}$$


- So, assuming there are no negative cycles, after iteration  $n - 1$ :

$$f[v] = \text{length of shortest } s\text{-}v \text{ path}$$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	$\infty$	$\infty$	$\infty$	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	$\infty$	$\infty$	$\infty$	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	$\infty$	$\infty$	$\infty$



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$


vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	$\infty$	$\infty$	$\infty$



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$


vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	$\infty$	$\infty$






- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	$\infty$	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	$\infty$	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	2	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	2	$\infty$




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	2	4




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	2	4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$


vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	6	7	2	4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	2	4






- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	<i>s</i>	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
<i>f</i>	0	2	7	2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	<i>s</i>	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
<i>f</i>	0	2	7	2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	<i>s</i>	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
<i>f</i>	0	2	7	2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	<i>s</i>	<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
<i>f</i>	0	2	7	-2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4

- end of iteration 1: 0, 2, 7, 2, 4




- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4

- end of iteration 1: 0, 2, 7, 2, 4






- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4


- end of iteration 1: 0, 2, 7, 2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4


- end of iteration 1: 0, 2, 7, 2, 4
- end of iteration 2: 0, 2, 7, -2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4

- end of iteration 1: 0, 2, 7, 2, 4
- end of iteration 2: 0, 2, 7, -2, 4
- end of iteration 3: 0, 2, 7, -2, 4



- order in which we consider edges:  
 $(s, a)$ ,  $(s, b)$ ,  $(a, b)$ ,  $(a, c)$ ,  $(b, d)$ ,  
 $(c, d)$ ,  $(d, a)$

vertices	$s$	$a$	$b$	$c$	$d$
$f$	0	2	7	-2	4

- end of iteration 1: 0, 2, 7, 2, 4
- end of iteration 2: 0, 2, 7, -2, 4
- end of iteration 3: 0, 2, 7, -2, 4
- Algorithm terminates in 3 iterations, instead of 4.

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

- 1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$
- 2: **for**  $\ell \leftarrow 1$  to  $n$  **do**
- 3:      $updated \leftarrow \text{false}$
- 4:     **for each**  $(u, v) \in E$  **do**
- 5:         **if**  $f[u] + w(u, v) < f[v]$  **then**
- 6:              $f[v] \leftarrow f[u] + w(u, v)$
- 7:              $updated \leftarrow \text{true}$
- 8:     **if not**  $updated$ , then return  $f$
- 9: output “negative cycle exists”

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n$  do
3:    $updated \leftarrow \text{false}$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f[u] + w(u, v) < f[v]$  then
6:        $f[v] \leftarrow f[u] + w(u, v)$ ,  $\pi[v] \leftarrow u$ 
7:        $updated \leftarrow \text{true}$ 
8:   if not  $updated$ , then return  $f$ 
9: output “negative cycle exists”
```

- $\pi[v]$ : the parent of  $v$  in the shortest path tree

# Bellman-Ford Algorithm

## Bellman-Ford( $G, w, s$ )

```
1:  $f[s] \leftarrow 0$  and  $f[v] \leftarrow \infty$  for any  $v \in V \setminus \{s\}$ 
2: for  $\ell \leftarrow 1$  to  $n$  do
3:    $updated \leftarrow \text{false}$ 
4:   for each  $(u, v) \in E$  do
5:     if  $f[u] + w(u, v) < f[v]$  then
6:        $f[v] \leftarrow f[u] + w(u, v)$ ,  $\pi[v] \leftarrow u$ 
7:        $updated \leftarrow \text{true}$ 
8:   if not  $updated$ , then return  $f$ 
9: output “negative cycle exists”
```

- $\pi[v]$ : the parent of  $v$  in the shortest path tree
- Running time =  $O(nm)$

# Outline

- 1 Minimum Spanning Tree
  - Kruskal's Algorithm
  - Reverse-Kruskal's Algorithm
  - Prim's Algorithm
- 2 Single Source Shortest Paths
- 3 All-Pair Shortest Paths and Floyd-Warshall



# All-Pair Shortest Paths

## All Pair Shortest Paths

**Input:** directed graph  $G = (V, E)$ ,  
 $w : E \rightarrow \mathbb{R}$  (can be negative)

**Output:** shortest path from  $u$  to  $v$  for **every**  $u, v \in V$

# All-Pair Shortest Paths

## All Pair Shortest Paths

**Input:** directed graph  $G = (V, E)$ ,  
 $w : E \rightarrow \mathbb{R}$  (can be negative)

**Output:** shortest path from  $u$  to  $v$  for **every**  $u, v \in V$

- 1: **for** every starting point  $s \in V$  **do**
- 2:     run Bellman-Ford( $G, w, s$ )

# All-Pair Shortest Paths

## All Pair Shortest Paths

**Input:** directed graph  $G = (V, E)$ ,  
 $w : E \rightarrow \mathbb{R}$  (can be negative)

**Output:** shortest path from  $u$  to  $v$  for **every**  $u, v \in V$

- 1: **for** every starting point  $s \in V$  **do**
- 2:     run Bellman-Ford( $G, w, s$ )

- Running time =  $O(n^2m)$

# Summary of Shortest Path Algorithms we learned

algorithm	graph	weights	SS?	running time
Simple DP	DAG	$\mathbb{R}$	SS	$O(n + m)$
Dijkstra	U/D	$\mathbb{R}_{\geq 0}$	SS	$O(n \log n + m)$
Bellman-Ford	U/D	$\mathbb{R}$	SS	$O(nm)$
Floyd-Warshall	U/D	$\mathbb{R}$	AP	$O(n^3)$

- DAG = directed acyclic graph    U = undirected    D = directed
- SS = single source    AP = all pairs

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- For now assume there are no negative cycles

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- For now assume there are no negative cycles

## Cells for Floyd-Warshall Algorithm



# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- For now assume there are no negative cycles

## Cells for Floyd-Warshall Algorithm

- First try:  $f[i, j]$  is length of shortest path from  $i$  to  $j$

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- For now assume there are no negative cycles

## Cells for Floyd-Warshall Algorithm

- First try:  $f[i, j]$  is length of shortest path from  $i$  to  $j$
- Issue: do not know in which order we compute  $f[i, j]$ 's

# Design a Dynamic Programming Algorithm

- It is convenient to assume  $V = \{1, 2, 3, \dots, n\}$
- For simplicity, extend the  $w$  values to non-edges:


$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- For now assume there are no negative cycles

## Cells for Floyd-Warshall Algorithm

- First try:  $f[i, j]$  is length of shortest path from  $i$  to  $j$
- Issue: do not know in which order we compute  $f[i, j]$ 's
- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

# Example for Definition of $f^k[i, j]$ 's



$$f^0[1, 4] = \infty$$

$$f^1[1, 4] = \infty$$

$$f^2[1, 4] = 140 \quad (1 \rightarrow 2 \rightarrow 4)$$

$$f^3[1, 4] = 90 \quad (1 \rightarrow 3 \rightarrow 2 \rightarrow 4)$$

$$f^4[1, 4] = 90 \quad (1 \rightarrow 3 \rightarrow 2 \rightarrow 4)$$

$$f^5[1, 4] = 60 \quad (1 \rightarrow 3 \rightarrow 5 \rightarrow 4)$$

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$f^k[i, j] = \begin{cases} & k = 0 \\ & k = 1, 2, \dots, n \end{cases}$$

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$f^k[i, j] = \begin{cases} w(i, j) & k = 0 \\ & k = 1, 2, \dots, n \end{cases}$$

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$f^k[i, j] = \begin{cases} w(i, j) & k = 0 \\ \min \left\{ \begin{array}{l} f^k[i, v] + w(v, j) \\ f^k[v, i] + w(i, v) \end{array} \right\} & k = 1, 2, \dots, n \end{cases}$$



$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$f^k[i, j] = \begin{cases} w(i, j) & k = 0 \\ \min \left\{ \begin{array}{l} f^{k-1}[i, j] \\ \min_{1 \leq l < k} \{ f^{k-1}[i, l] + w(l, j) \} \end{array} \right. & k = 1, 2, \dots, n \end{cases}$$

$$w(i, j) = \begin{cases} 0 & i = j \\ \text{weight of edge } (i, j) & i \neq j, (i, j) \in E \\ \infty & i \neq j, (i, j) \notin E \end{cases}$$

- $f^k[i, j]$ : length of shortest path from  $i$  to  $j$  that only uses vertices  $\{1, 2, 3, \dots, k\}$  as intermediate vertices

$$f^k[i, j] = \begin{cases} w(i, j) & k = 0 \\ \min \begin{cases} f^{k-1}[i, j] \\ f^{k-1}[i, k] + f^{k-1}[k, j] \end{cases} & k = 1, 2, \dots, n \end{cases}$$

## Floyd-Warshall( $G, w$ )

```
1:  $f^0 \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   copy  $f^{k-1} \rightarrow f^k$ 
4:   for  $i \leftarrow 1$  to  $n$  do
5:     for  $j \leftarrow 1$  to  $n$  do
6:       if  $f^{k-1}[i, k] + f^{k-1}[k, j] < f^k[i, j]$  then
7:          $f^k[i, j] \leftarrow f^{k-1}[i, k] + f^{k-1}[k, j]$ 
```

## Floyd-Warshall( $G, w$ )

```
1:  $f^{\text{old}} \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   copy  $f^{\text{old}} \rightarrow f^{\text{new}}$ 
4:   for  $i \leftarrow 1$  to  $n$  do
5:     for  $j \leftarrow 1$  to  $n$  do
6:       if  $f^{\text{old}}[i, k] + f^{\text{old}}[k, j] < f^{\text{new}}[i, j]$  then
7:          $f^{\text{new}}[i, j] \leftarrow f^{\text{old}}[i, k] + f^{\text{old}}[k, j]$ 
```

## Floyd-Warshall( $G, w$ )

```
1:  $f^{\text{old}} \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   copy  $f^{\text{old}} \rightarrow f^{\text{new}}$ 
4:   for  $i \leftarrow 1$  to  $n$  do
5:     for  $j \leftarrow 1$  to  $n$  do
6:       if  $f^{\text{old}}[i, k] + f^{\text{old}}[k, j] < f^{\text{new}}[i, j]$  then
7:          $f^{\text{new}}[i, j] \leftarrow f^{\text{old}}[i, k] + f^{\text{old}}[k, j]$ 
```

## Floyd-Warshall( $G, w$ )

```
1:  $f \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   copy  $f \rightarrow f$ 
4:   for  $i \leftarrow 1$  to  $n$  do
5:     for  $j \leftarrow 1$  to  $n$  do
6:       if  $f[i, k] + f[k, j] < f[i, j]$  then
7:          $f[i, j] \leftarrow f[i, k] + f[k, j]$ 
```

## Floyd-Warshall( $G, w$ )

```
1:  $f \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   for  $i \leftarrow 1$  to  $n$  do
4:     for  $j \leftarrow 1$  to  $n$  do
5:       if  $f[i, k] + f[k, j] < f[i, j]$  then
6:          $f[i, j] \leftarrow f[i, k] + f[k, j]$ 
```

## Floyd-Warshall( $G, w$ )

```
1:  $f \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   for  $i \leftarrow 1$  to  $n$  do
4:     for  $j \leftarrow 1$  to  $n$  do
5:       if  $f[i, k] + f[k, j] < f[i, j]$  then
6:          $f[i, j] \leftarrow f[i, k] + f[k, j]$ 
```

**Lemma** Assume there are no negative cycles in  $G$ . After iteration  $k$ , for  $i, j \in V$ ,  $f[i, j]$  is **exactly** the length of shortest path from  $i$  to  $j$  that only uses vertices in  $\{1, 2, 3, \dots, k\}$  as intermediate vertices.




## Floyd-Warshall( $G, w$ )

```
1:  $f \leftarrow w$ 
2: for  $k \leftarrow 1$  to  $n$  do
3:   for  $i \leftarrow 1$  to  $n$  do
4:     for  $j \leftarrow 1$  to  $n$  do
5:       if  $f[i, k] + f[k, j] < f[i, j]$  then
6:          $f[i, j] \leftarrow f[i, k] + f[k, j]$ 
```


**Lemma** Assume there are no negative cycles in  $G$ . After iteration  $k$ , for  $i, j \in V$ ,  $f[i, j]$  is **exactly** the length of shortest path from  $i$  to  $j$  that only uses vertices in  $\{1, 2, 3, \dots, k\}$  as intermediate vertices.

- Running time =  $O(n^3)$ .




	1	2	3	4	5
1	0	90	30	$\infty$	$\infty$
2	10	0	$\infty$	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0






	1	2	3	4	5
1	0	90	30	$\infty$	$\infty$
2	10	0	$\infty$	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 2, k = 1, j = 3$




	1	2	3	4	5
1	0	90	30	$\infty$	$\infty$
2	10	0	40	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 2, k = 1, j = 3$




	1	2	3	4	5
1	0	90	30	$\infty$	$\infty$
2	10	0	40	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 1, k = 2, j = 4$




	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 1, k = 2, j = 4$



	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	60	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0


- $i = 3, k = 2, j = 1,$



	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	20	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0


- $i = 3, k = 2, j = 1,$






	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	20	10	0	70	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 3, k = 2, j = 4$




	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	20	10	0	60	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 3, k = 2, j = 4$



	1	2	3	4	5
1	0	90	30	140	$\infty$
2	10	0	40	50	$\infty$
3	20	10	0	60	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 1, k = 3, j = 2$



	1	2	3	4	5
1	0	40	30	140	$\infty$
2	10	0	40	50	$\infty$
3	20	10	0	60	20
4	$\infty$	$\infty$	$\infty$	0	20
5	$\infty$	$\infty$	$\infty$	10	0

- $i = 1, k = 3, j = 2$