

Assignment 5

Due: 11:59pm May 3 (Sunday)

This assignment is done individually or by a group of 2 students (each group submits only 1 copy of the assignment)

Input/output format (including the function name and the number of arguments) – 5 points

1. [10 points] Write a Prolog predicate **maxodd(L,Res)** that computes the maximum integer that appears in the odd position of an integer list L and stores the result in Res. Assume that L contains at least 1 element.

E.g. `?-maxodd([1,5,3,4,2], Res).`

`Res = 3` //3 is the maximum number that appears in the odd position of the list `[1,5,3,4,2]`

2. [15 points] Define a Prolog predicate **deleteNList(N,L,Res)** that delete **every Nth** argument of a list : and store the results in Res.

E.g. `?- deleteNList(3, [2,3,4,5,6,7,8], Res).`

`Res = [2,3,5,6,8].`

`no`

3. [15 points] Write a Prolog predicate **replace_first(L, X, Y, Res)** that replaces the first occurrences of X in a list L with Y and stores the result in Res. IF L does not contain X, then return L.

e.g. `?- replace_first([2,1,3,1,4,1,5,1,6,1], 1, 6, Res).`

`Res = [2,6,3,1,4,1,5,1,6,1].`

4. [15 points] Write a Prolog program **position(X, L, Res)** that takes an integer X and an integer list L, returns a list of positions of X in L. The result is stored in Res.

e.g. `?- position(1, [1,3,1,2,5,1], Res).`

`Res = [1,3,6].`

`No`

5. [12 points] Given the following code in Java

```
public class A
{ public void p() { System.out.println("A.p");}
  public void q() { System.out.println("A.q");}
  public void r() { p(); q();}
}
```

```
class B extends A
{ public void p() { System.out.println("B.p");}
}
```

```
class C extends B
{ public void q() { System.out.println("C.q");}
  public void r() { q(); p();}
}
```

...

```
A a = new B();
```

```
a.r();
```

```
a = new C();
```

```
a.r();
```

What does the above program print?

6. [12 points] Question 10.20 Given the following code in C++:

```
class A{
public:
    virtual void p(){cout << "A.p"<< endl;}
    void q(){cout << "A.q" << endl;}
    virtual void r(){p(); q();}
};
class B: public A{
public:
    void p(){cout << "B.p" << endl;}
};
class C: public B{
public:
    void q(){cout << "C.q" << endl;}
    void r(){q(); p();}
};
...
A a; C c; a = c; a.r();
A* ap = new B; ap -> r();
A* ap1 = new C; ap1 -> r();
```

What does the above program print?

7. [16 points] Question 10.48

```
Class A
{ public:
    virtual void f();
    virtual void g();
private: int a;
};
class B: public A
{ public:
    void f();
    void h();
private: int b;
}
Class C: public B
{ public: void g();
  Private: int c;
}
```

Draw the VMT of each class and the layout of memory for a dynamically-allocated object of each class.

Instruction of Submission:

- Create a directory [userid]_5 (e.g. pyang_5), which contains
 - o Prolog program **assignment5.P**
 - o A .pdf file containing the name and email address of the group members, and solutions to Q5-Q7
- Tar the contents of this directory using the following command.
tar -cvf [directory_name].tar [directory_name]
E.g. tar -cvf pyang_5.tar pyang_5/
- Upload the tared file you created above to mycourses.

Academic Honesty:

All students should follow [Student Academic Honesty Code](http://watson.binghamton.edu/acadhonorcode.html) (<http://watson.binghamton.edu/acadhonorcode.html>). All forms of cheating will be treated with utmost seriousness. You may discuss the problems with other students, however, you must write your OWN codes and solutions. Discussing solutions to the problem is NOT acceptable. Copying an assignment from another student or allowing another student to copy your work may lead to an automatic **F** for this course. If you borrow small parts of code/text from Internet, you must acknowledge this in your submission. Also, you must clearly understand and be able to explain the material. Copying entire material or large parts of such material from the Internet will be considered academic dishonesty. Moss will be used to detect plagiarism in programming assignments. You need ensure that your code and documentation are protected and not accessible to other students. Use **chmod 700** command to change the permissions of your working directories before you start working on the assignments. If you have any questions about whether an act of collaboration may be treated as academic dishonesty, please consult the instructor before you collaborate.