

EXPERIMENT NO: 03 - Network Packet Sniffing and Credential Analysis

Using Wireshark

DATE:

1. AIM

To capture and analyze unencrypted network traffic using the Wireshark packet analyzer, isolate HTTP GET and POST request methods, and extract transmitted plain-text login credentials (username and password).

2. SOFTWARE / TOOLS REQUIRED

- **Operating System:** Windows 10/11 or Kali Linux
- **Packet Analyzer:** Wireshark v4.x (with Npcap driver installed)
- **Web Browser:** Google Chrome / Mozilla Firefox
- **Target Environment:** Acunetix Web Vulnerability Test Site
([http://testphp.vulnweb.com])(<http://testphp.vulnweb.com>)

3. DESCRIPTION

Network packet sniffing is the process of monitoring and capturing data packets passing through a network interface card (NIC). Wireshark utilizes packet capture drivers (Npcap/libpcap) to set the system's NIC into **promiscuous mode**, allowing it to capture all frames traversing the local network segment.

When web applications transmit data using unencrypted protocols such as **HTTP (Hypertext Transfer Protocol)** over TCP port 80, the payload remains in ASCII plain text:

- **HTTP GET Method:** Appends parameters to the URL string. While used primarily for retrieving data, it leaves information visible in server logs and browser histories.
- **HTTP POST Method:** Embeds data within the body of the request header (Content-Type: application/x-www-form-urlencoded). Although hidden from the URL bar, the payload remains completely legible to network sniffers if not protected by TLS/SSL encryption (**HTTPS**).

4. PROCEDURE

Step 1: Interface Initialization

1. Launch Wireshark.
2. Select the active **Wi-Fi** network interface to begin live traffic capture.




Figure 1: Wireshark Interface Capture Selection

Step 2: Generating Network Traffic

1. Open the target web page in a browser.
2. Enter the credential details (Username: 99240041226, Password: Sadhan) into the form fields and submit.

Username:

Password:

Figure 2: Submitting Credentials on Test Web Page

Step 3: Filtering Protocol Traffic

Apply the http filter in the display filter bar to filter out ambient TCP, UDP, and DNS background traffic and isolate application-layer HTTP traffic.




Figure 3: Applying Display Filter for HTTP Protocol

Step 4: Inspecting HTTP GET Requests

Enter the following filter to inspect GET requests:

`http.request.method == "GET"`

Observation: GET packets retrieve page components, but do not carry submitted form parameters in their payload.




Figure 4: Analysis of Captured HTTP GET Requests

Step 5: Extracting POST Payload and Credentials

Apply the POST filter to locate form submission requests:

`http.request.method == "POST"`

Select the packet containing `application/x-www-form-urlencoded`. In the **Packet Details** pane, expand the **HTML Form URL Encoded** tree to read the plain-text form variables.




Figure 5: Inspecting HTTP POST Packet Payload



Figure 6: Plain-text Credential Extraction from Form Fields

5. OBSERVATIONS

Extracted Form Parameters

Field Name	Captured Key	Extracted Value
Username	txtUsername	9240041226
Password	txtPassword	Sadhan

6. VERIFICATION OF SAVED LOGS & DIRECTORY STRUCTURE

The packet capture data (Captured_File.pcapng) and generated screen outputs have been archived in the repository.

7. PREVENTIVE COUNTERMEASURES

1. **Enforce HTTPS (TLS 1.3):** Encrypt all client-server communications so intercepted payloads appear as encrypted ciphertext.
2. **HTTP Strict Transport Security (HSTS):** Enforce browser-side HSTS policies to prevent downgrade attacks to plain HTTP.
3. **Network Isolation:** Implement VLANs and 802.1X port-based access controls to restrict unauthorized packet sniffing on local physical and wireless networks.

8. RUBRICS

Criteria & Marks Assigned	Mark Allotted	Mark Awarded
1. GitHub Activity & Submission Regularity	3	
2. Application of Forensic Tools & Practical Execution	3	
3. Documentation & Reporting	2	
4. Engagement, Problem-Solving & Team Collaboration	2	
Total	10	

9. RESULT

The network traffic was successfully captured and analyzed using Wireshark. Plain-text credentials (**Username:** 9240041226, **Password:** Sadhan) transmitted over HTTP were extracted from the POST request payload.