

After Call Webhook



MyOperator

This document describes webhook aftercall api for clients.

Overview

Webhooks are HTTP callbacks that receive notification messages for events. MyOperator uses webhooks to notify your application any time an call event happens in your account. For example, if a call has been received by your agent, you will receive a webhook during the call (incall webhook), and after the call has finished (aftercall webhook).

After call webhook is the feature of MyOperator which is used to share the call data at the end of every call through HTTP request.

Purpose

After call Webhook enables clients to do actions on the data at the end of every call. Webhook data can be used to do below things at client's end:

- Collect call data in datastore at client's end.
- Invoking custom integrations like adding a lead in the CRM.

The call log records all associated information related to given call. After each call, we send the same log via webhooks. How we send the log (in post body or GET params) depends on the type of webhook requested by client.

Components

A webhook is made up of components. Each component allows you to configure certain part of webhook. This gives you flexibility of configuration each part of webhook separately.

Target URL

Target URL allows you to configure your webhook listener URL. When you code your system, which will receive the data after each call, you give the url for that code in this input.

Example: `http://your-service-url.com/webhook.php`

Method

There are two type of methods supported by webhooks:

1. GET
2. POST

GET

GET Method, as name suggest, will send webhook using HTTP GET requests. This means, you will need to looks for `query parameters` in your GET requests for data. We use query parameters to send the data that you have set. Hence, the request looks something like this:

```
curl -X GET http://your-service-url.com/webhook.php?parameter1=<call log value>&parameter2=<another call log value>
```

To get the above data in your code (PHP sample):

```
// If you have set Query string parameters, you can still get them here too.  
$some_value = $_GET['parameter1'];
```

In above example, you can see that the `parameter1` and `parameter2` seem important. These parameters contains certain call log information. For example, `parameter1` may have caller's number, and `parameter2` might have call duration. To know how to configure these parameters in details, see [Query parameter](#) section.

POST

POST method sends a HTTP POST request to your webhook listener. This allows you to take additional decisions based on the call log. This is why we recommend you to use `POST` method.

We send the following data in `POST` format:

```
myoperator={  
  '_ai': '5f114f490dbe2437',  
  '_so': '1',  
  '_ci': '5cd40f6554442586',  
  '_cr': '9711636496',  
  '_cm': '',  
  '_cl': '+919711636496',  
  '_cy': '91',  
  '_se': 'DL, IN',  
  '_ts': 1594969967,  
  '_st': 1594969929,  
  '_ms': 1594969929000,  
  '_ss': 25929,  
  '_et': 1594969968,  
  '_dr': '00:00:39',  
  '_drm': 0.65,  
  '_ty': 1,  
  '_ev': 1,  
  '_fn': 'e673ba2e1747cb32960b19275f459c1869776c7b673901bb1f20ddd779117e93b148825cb28ce1d0.mp3',  
  '_fu':
```

```
'http:\\\\\\app.myoperator.co\\\\audio\\\\e673ba2e1747cb32960b19275f459c1869776c7b673901bb1f20ddd7
79117e93b148825cb28ce1d0',
'_ns': '0',
'_su': 1,
'_dn': 'sales',
'_di': '5cd40f6559784843',
'_pm': [{'ky': 'ui', 'vl': 'd5.1594969927.2496720'},
{'ky': 'is', 'vl': '0'},
{'ky': 'vt', 'vl': '2'},
{'ky': 'ic', 'vl': '1'},
{'ky': 'ia', 'vl': '0'},
{'ky': 'ib', 'vl': '1'}],
'_cn': [{'_tx': 'asdfg',
'_cd': '5f114f54741cc966',
'_ce': 1594969940,
'_id': '5cd40f6556f2f124',
'_na': 'Sumit',
'_em': 'sumit.arya@myoperator.co',
'_ex': '10',
'_ct': '8586848544',
'_nr': '+918586848544'}],
'_ld': [{'_rst': '2020-07-17 07:12:28',
'_ds': 'ANSWER',
'_did': '1161568087',
'_rr': [{'_id': '5cd40f6556f2f124',
'_na': 'Sumit',
'_em': 'sumit.arya@myoperator.co',
'_ex': '10',
'_ct': '8586848544',
'_nr': '+918586848544'}],
'_tt': [],
'_su': '1',
'_st': 1594969959,
'_et': 1594969968,
'_dr': '00:00:09',
'_ac': 'received'}],
'_an': 0,
'_bp': [{'_tm': [{'type': 'local', 'use': 1}],
'_ti': [{'type': 'local', 'use': 0}],
'_ta': [{'type': 'local', 'use': 0}],
'_tr': [{'type': 'local', 'use': 1}]}],
'_us': [{'ky': '5cd40f6556f2f124', 'vl': 'received'}],
'_tc': [{'ye': '5cd40f6556f2f124', 'yf': 9}],
'_ri': '',
'_ji': '',
'_ivid': '',
'_cri': ''}
```

we send the data in POST body inside `myoperator` key. A basic cURL request for it looks like this:

```
curl -X POST http://your-service-url.com/webhook.php -d myoperator=<call log>
```

NOTE - We send the data in JSON format. So, you should json decode the data on your side to ensure correctness of it. See the example below.

You can get the call log data from a POST webhook like this (PHP code sample):

```
$call_data = $_POST['myoperator'];  
/*  
The data is in this string format:  
{ "_ai": "xyz", "_ci": "123abc", ... }  
Hence you should decode it to array to get particular call data  
*/  
$call_data_array = json_decode($call_data, true);  
  
// get caller's number  
$caller_number = $call_data_array['_cr'];  
  
/*  
Remember, POST request doesn't mean you won't get query parameters.  
If you have set Query string parameters, you can still get them here too.  
*/  
  
$caller_number = $_GET['caller_number'];
```

Header

This component allows you to send any custom headers with the webhook request. Headers is a way to pass any key value pair from our side.

Suppose, in your code, you want to verify if the request is actually coming from our side, and not from someone outside or hackers, you can easily check this using headers.

You can set any secret token in this component, which we will append in the webhook request before sending it to your service. Once you receive a request from us, you can check if the header has the secret token. If it does, you can confirm we are the one sending the request.

Example:

Suppose, you set the header:

```
["my-super-secret-token: abc123def"]
```

Then we will send this cURL request to your webhook listener:

```
curl -X POST http://your-service-url.com/webhook.php -H 'my-super-secret-token: abc123def'
```

which you can check like this (PHP code sample):

```
$my_secret_header = $_SERVER['HTTP_my-super-secret-token'];

if( $my_secret_header == 'abc123def' ) {
    // Request come from MyOperator webhook
    echo "Good";
} else {
    // Request didn't come from MyOperator webhook
    echo "Bad";
}
```

Credentials

Sometimes, you may have a service which requires authentication. There are several types of possible authentications, such as, OAuth, Basic, API Key based etc.

However, we only support BASIC auth for now. If your service has BASIC Auth enabled, You can configure the username and password in this component. The format we use is

```
{"username": <your username>, "password": <password>}
```

For example, if my service has "admin" as username and "123456" as password, I will enter following in the panel:

```
{"username": "admin", "password": "123456"}
```

When we detect that you have configured your credentials, we will invoke the webhook with credentials.

```
curl -u admin:123456 http://your-service-url.com/webhook.php
```

Log Criteria

This component allows you to choose which type of data you want to receive from webhook. Sometimes, you want the call log (from panel), while sometimes, you want to receive mobile logs only. In this component, you can only pick one out of two.

If you want both the call logs and mobile logs, you can create two webhooks - one for call log and one for mobile logs.

Query string parameters

This section is the most important of all. In this component, you can pick which part of call log you are interested in receiving.

This component allows you to mention a name, and map it to a particular call record value you are interested in. Once you choose a name and map it to a value, we will send the webhook to you with that name in the query parameters.

For example, lets say you are interested in receiving the caller's number. You can choose the name to be "caller_number" (do not put spaces and url encodeable values in the name). From the dropdown, pick "Caller

number with country code". Once you save, we will send the webhook to your webhook listener like this:

```
curl -XGET http://your-service-url.com/webhook.php?caller_number=+919876543210
```

So, you can get the `caller_number` in your code (PHP code sample) like:

```
$caller_number = $_GET['caller_number'];  
echo $caller_number; //+919876543210
```

The dropdown, which you have selected the value from, are called query parameters fields. The description of each field is documented in the [Query parameter fields](#) section.

NOTE: If you have set the Method as `POST`, we will have sent the data like this:

```
curl -XPOST http://your-service-url.com/webhook.php?caller_number=+919876543210 -d myoperator=  
<call log>
```

Query parameter fields

Query parameters is a set of key value pairs. You configure which call log should be mapped to the key of your choosing. This section focus on explaining what each call log (from the dropdown) means, with an example.

Caller number with country code

This field gives the caller's mobile number, along with country code. For example: +919876543210

This field is same as `_cl` in Call log (the data that you receive in POST body)

Caller number without country code

This field gives the caller's mobile number, without country code. This basically means the raw call data we got in call records. For example: 9876543210

This field is same as `_cr` in Call log (the data that you receive in POST body)

Creation date of log (epoch)

This field gives you the time (in UNIX Epoch format), in UTC timezone, when the log was created. For example: 1577797873 (Tuesday, 31 December 2019 13:11:13)

Event of log

This gives you the type of call record. Possible values are:

- incoming
- outgoing

Status of log

This gives you the overall call status of record. Possible values are:

- Connected (call was picked by atleast one agent and for some non zero duration)
- Missed (call was dialed by never picked by any of the agents)
- Voicemail (call landed on voicemail)

UID

We use UID as a unique identifier for each call. Each call log has its own UID. It helps us trace the call and routes. An example UID looks like: s5.347638.78643857

This field is same as `_pm.ui` in Call log

Company ID

Company ID gives you the company in which call took place. It can help you get the company details and in which country the agent was in. It is alphanumeric in nature. Example: abc123.

This field is same as `_ci` in Call log

User's phone number

This gives you the agent's contact number who picked up the call(in incoming cases) or dialed the number (in outgoing cases). An agent represents a user within a company. Agent contact number contains 10 digits contact number, without country code. For example- 9876543210

This field is same as `_ld._rr._ct` in Call log

Department name

This field provides the name of department that the call went through. For example- Sales department.

This field is same as `_dn` in Call log

Recording file name

This field gives you the call recording file name. For example, 9bb6eab4c44519dsdkhj884d3d40b3995991d9.mp3

This field is same as `_fn` in Call log.

Recording URL

Use this field to download your call recording. This field gives you the link to the call recording. Note that, only logged in user is allowed to download recording. For example,
<http://app.myoperator.dev/audio/9bb6eab4c44519dsdkhj884d3d40b3995991d9>

This field is same as `_fu` in Call log.

Start time of call (epoch)

This gives out the call start time in UNIX Epoch format. For example, 1577085001 (which translates to Monday, 23 December 2019 07:10:01). To convert unix epoch to human date format, you can use <https://www.epochconverter.com/>

This field is same as `_st` in Call log.

End time of call (epoch)

This gives out the call end time in UNIX Epoch format. For example, 1577085001 (which translates to Monday, 23 December 2019 07:10:01). To convert unix epoch to human date format, you can use <https://www.epochconverter.com/>

This field is same as `_et` in Call log.

Log push timestamp (microseconds)

This field gives the exact time (in microseconds, unix epoch format) at which this call log was pushed via webhook to your webhook listener (url). Example: 1577971356261. To convert unix epoch to human date format, you can use <https://www.epochconverter.com/>

Unique caller id

Each call that we have in our system has a unique caller id attached to it. It helps us identifying the entire call record as well as other call related queries. This field gives the unique caller id (alphanumeric string). For example: 5e01684774c24532

This field is same as `_ai` in Call log.

Location

This field gives the location of caller present in the call log. We record the location in (State, Country) format. Country is a 2 digit short representation of country name ([ISO 3166 format](#)).

If we are unable to locate the state, we only record the country code. For example: "DL, IN" represents a caller location in New Delhi, India.

Whole log data

Use this option to get all the call data in the request. Explanation of each call log field is explained in the section: [Call log](#)

Status of log

This field gives you the entire call status. A call can have following statuses:

- Connected (A call was picked by atleast one agent)
- Missed (A call was picked by no agent)

- Voicemail (Call landed on voicemail)

Each status gives you a basic understanding of the whole call. We also give this status in integer format, when you select "Status of log(integer format)" option:

- 1 (Connected)
- 2 (missed)
- 3 (voicemail)

Additional status are also provided, if you chose the type of log to be sms.

- 4 (Success - sms sent successfully)
- 5 (Failed - sms sending failed)

Duration (hh:mm:ss)

This field gives the call duration in hh:mm:ss format. Example: 00:01:22 (represents 1min and 22 seconds call).

This field is same as `_dr` in Call log.

Formatted duration

This field gives the call duration in minutes. Example: 1.37 (represents 1min and 22 seconds call).

Department id

This field gives the department id of the department in the call. For example, if call landed on sales department, this will give you sales department id. Example: 5da80d5d1cb3c532

Custom

You can also set any type of custome key value pair to be included in the webhook request. Selecting this option will allow you to set a custom key to the name of your choosing.

Call Log

A call log is a hashmap (key-value pair) composed of several short field names with their values, related to call. The call log is in JSON format. We use short field name to save bandwidth and storage requirements. However, it may become difficult to understand the field meaning, hence this section explores the fields, with their meanings, as well as example value inside it.

Log Field name	Description	Example
<code>_an</code>	Is Anonymous User	1=yes, 0=no
<code>_ai</code>	Call log id (unique for each call)	abcdef123
<code>_cl</code>	Caller's number (formatted)	+919876543210
<code>_cr</code>	Caller's number (raw)	919876543210

Log Field name	Description	Example
_cm	Caller's contact name (if found)	My Contact
_cy	Caller's contact country code*	My Contact
_ev	Call event type (1=incoming/2=outgoing)	1= incoming, 2= outgoing
_fu	Call recording file link	http://myoperator.co/audio/abc
_fn	Call recording file name	abc.mp3
_ts	Log timestamp (unix epoch)	1572505408
_ms	Log timestamp (unix epoch) in milliseconds	1572505408000
_st	Call start time	1572505408
_et	Call end time	1572505438
_ss	diff b/w call end time and start time in seconds	31131
_ns	Notification Status	1 = clickocall, 2 = obd, 3 = webrtc
_se	call location*	RJ,IN
_su	Status of call	1 =connected, 2 =missed, 3 =voicemail
_so	Call source (IVR/Mobile)	1 =IVR, 2 =Mobile
_ci	Company id	abc123
_dr	Call duration (hh:mm:ss)	00:06:23
_drm	Call duration (in minutes)	6.38
_di	Department id	5c80e49e7d452564
_dn	Department name	sales
_ty	Call log type	1 =call, 2 =sms
_ri	Reference id (obd v2 calls)	abcdef123
_ji	Obd v2 job id	abcdef123 - obd v2 call, empty - otherwise
_ivid	Public IVR ID	abcdef123
_cri	Client reference id (obd v2 calls)	abcdef123 - obd v2 call, empty - otherwise
_ld._rst	Ring start time(In GMT)	2019-12-04 11:22:30
_ld._rr._na	Agent Name	Agent Sharma
_ld._rr._id	Agent id	abcdef123
_ld._rr._em	Agent email id	agent@example.com
_ld._rr._ct	Agent contact number	9876543210
_ld._rr._nr	Agent contact number with country code	+919876543210
_ld._su	Status of call	1= connected, 2= missed, 3=voicemail, 4=success
_ld._st	Call start time	1572424745
_ld._et	Call end time	1572424750

Log Field name	Description	Example
_ld._dr	Call duration	00:00:05
_ld._ds	Dial String	ANSWER/NOANSWER/CANCEL
_ld._did	Last Caller Id (used in callback)	abcdef123
_ld._ac	Call status	received/missed/transferred
_ld._tt._na	Transferred Agent Name	Agent Sharma
_ld._tt._id	Transferred Agent id	abcdef123
_ld._tt._em	Transferred Agent email id	agent@example.com
_ld._tt._ct	Transferred Agent contact number	9876543210
_ld._tt._nr	Transferred Agent contact number with country code	+919876543210
_pm._ky	ui = Call UID	s4.1572424727.994
_pm._ky	is = Is Call starred	0 = not starred, 1 = starred
_pm._ky	ic = Is Commented	1 = yes, 0 = no
_pm._ky	ia = Is archived log	1 = yes, 0 = no
_pm._ky	ib = Is Billable log	1 = yes, 0 = no
_pm._ky	vt = View Type	1 - personal, 2 - public/corporate

Need Help?

In case of any query please contact the support team at support@myoperator.co. Or generate a support ticket from [MyOperator Panel](#).

🕒 Revision #37

★ Created Tue, Dec 24, 2019 1:57 PM by [Ashutosh](#)

✎ Updated Thu, Jul 16, 2020 9:19 AM by [Ashutosh](#)